

Leading the way in Business Products, Services, and Solutions



State of North Carolina Term Contract 204D

Contract Number: ITS#400096

Contract Period: February 01, 2017 - January 31, 2020

with 2 one year renewals

Purchase, Lease, Supplies & Maintenance Konica Minolta

High Capacity Printer / Multifunction Device Equipment

www. Systel State Contracts. com





Black & White Multifunction Devices



Giving Shape to Ideas



Up to 22 ppm print/copy output to keep pace with rising demands

Color display with quick tablet-like interface

Touchscreen for simple control and 3rd-party software integration

Standard web browser to support web-based apps

Built-in Emperon® print system, universal printer drivers

Simitri® HD polymerized toner for high-resolution imaging

Standard 250 GB HDD for on-board document storage

Meets ISO 15408 and IEEE 2600.1 Security standards

Power-saving design with quick recovery from sleep mode

3,600-sheet maximum capacity, tab printing support, carbon-copy printing

Advanced authentication, secure print release, remote firmware updates

Options for booklet-making, stapling, hole punch and more

Downloadable apps to help you work faster and smarter

i-Options to add functions for working more efficiently

Low power consumption to cut costs

Mobile printing support (AirPrint, Google Cloud Print, NFC)

bizhub 227

MONOCHROME MID-VOLUME MULTIFUNCTION PRINTER







bizhub 227

As easy as a familiar tablet, the enhanced touch-and-swipe interface of the bizhub 227 helps make you more productive — with 22 ppm output in high-resolution B&W, scanning in color or B&W at up to 45 originals per minute, 3,600-sheet maximum paper capacity and economical, high-value performance.

System Overview

System Overview	
System memory	4 GB
System hard disk	250 GB
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Reversing automatic document feeder (optional)	Up to 100 originals / 5.5" x 8.5" to 11" x 17" / 50-128 gsm
Printable paper size	Scanning/Copying: up to 11" x 17" Printing: up to 11" x 17" Custom paper sizes
Printable paper weight	60-220 gsm
Paper input capacity	Standard: 1,100 sheets / Max.: 3,600 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 8.5" x 14" / 60-220 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 11" x 17" / 60-220 gsm
Tray 3 (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 60-220 gsm
Tray 4 (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 60-220 gsm
Large capacity tray PC-413 (optional)	2,500 sheets / 8.5" x 11" / 60-220 gsm
Manual bypass	100 sheets / 4" x 6" to 11" x 17" / custom paper sizes / 60-220 gsm
Automatic duplexing	5.5" x 8.5" to 11" x 17" / 60-220 gsm
Finishing modes	Offset, group, sort, punch, half-fold, tri-fold, booklet
Output capacity	Max. with finisher: 3,300 sheets Max. without finisher: 250 sheets
Stapling (optional)	Max.: 50 sheets or 48 sheets + 1 cover sheet (up to 209 gsm)
Stapling output capacity	Max.: 1,000 sheets
Tri-fold (optional)	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray)
Copy/print volume	Max.: 100,000 pages/month ¹
Toner lifetime	23,000 pages
Imaging unit lifetime	85,000 pages / 590,000 pages (Drum / Developer)
Power consumption	120 V / 50/60 Hz, less than 1.5 kW (system)
System dimensions	23.0" x 26.0" x 28.9" (W x D x H)
System weight	Approx. 124.6 lb

	-						-	
'n	nic	ar (С'n	20	ifi	ביי	Hin	ns

Copying process	Electrostatic laser copy, tandem
Toner system	Simitri® HD Polymerized Toner
Print speed (8.5" x 11")	Up to 22 ppm (Portrait)
Print speed (11" x 17")	Up to 14 ppm
Auto-duplex speed	Up to 22 ppm (Portrait)
(8.5" x 11")	
1st copy out time	5.3 sec.
Warm-up time	Approx. 15 sec. ²
Copy resolution	600 x 600 dpi
Gradations	256 gradations
Multi-copy	1-9,999
Original format	Up to 11" x 17"
Magnification	25-400% in 0.1% steps, auto zooming
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1

Printer Specifications

Print resolution	1,800 (equivalent) x 600 dpi
PDL	PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 ³ / 2012 ³ Macintosh OS X 10.2.8 or later UNIX / Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

Scanner Specifications

Scan speed	B&W / Color: up to 45 ipm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview

Fax Specifications

Fax	Super G3 (optional)				
Transmission	Analog, i-Fax, Color i-Fax, IP-Fax				
Resolution	Max.: 600 x 600 dpi (ultra-fine)				
Compression	MH, MR, MMR, JBIG				
Modem	Up to 33.6 Kbps				
Destinations	2,100 (single + group)				
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to Fmail/FTP/SMB. up to 400 job programs				

User Box Specifications

occ. Describence	
Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public
	Personal (with password or authentication)
	Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation
User box functionality	Reprint, combination, download, sending (Email/FTP/SMB and fax),
	copy box-to-box

System Features

ISO 15408 EAL
IEEE 2600.1
IP filtering and port blocking
SSL2, SSL3 and TSL1.0 network communication
IPsec support
IEEE 802.1x support
User authentication
Authentication log
Secure print
Hard disk overwrite (8 standard types)
Hard disk data encryption (AES 128)
Memory data auto deletion
Confidential fax reception
Print user data encryption
Copy protection (Copy Guard, Password Copy) optional
Up to 1,000 user accounts
Active Directory support
(user name + password + Email + SMB folder)
User function access definition
Optional Biometric authentication (finger vein scanner)
Optional ID card authentication (ID card reader)
PageScope Net Care Device Manager
PageScope Data Administrator
PageScope Box Operator
Print Status Notifier
Driver Packaging Utility
Log Management Utility

<sup>Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis.
This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs 2 Warm-up time may vary depending on the operating environment and usage
3 Supports x64 only</sup>

Components and Options	3
AU-102 Biometric	Finger vein scanner
authentication	
AU-205H Universal	Various ID card technologies
ID card reader	
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection, Bluetooth
DF-628	Reversing automatic document feeder, capacity 100 originals
Document feeder	
DK-513 Copier desk	Provides storage space for print media and other materials
FK-513 Fax board	Super G3 fax, digital fax functionality
FS-533 Staple finisher	50-sheet stapling, 500 sheets max. output (requires MK-602)
FS-534 Staple finisher	50-sheet stapling, 3,300 sheets max. output (requires RU-514)
FS-534 + SD-511	50-sheet staple finisher, 20-sheet booklet finisher,
Booklet finisher	3,300 sheets max. output (requires RU-514)
JS-506 Job separator	Separation for fax output, etc.
KH-102	To place USB keyboard
Keyboard holder	To place des hojsbard
KP-101 10-Key pad	For use instead of touchscreen
LK-102 v3	PDF/A, PDF encryption, digital signature
PDF enhancements	· - · · · , · - · · · · · / μ · · · · , · · · · · · · · · · · · · ·
LK-104 v3	Provides voice guidance functions
Voice guidance	J
LK-105 v4	Searchable PDF
OCR text recognition	
LK-106	Supports native barcode printing
Barcode fonts	
LK-107	Supports native Unicode printing
Unicode fonts	
LK-108	Supports native OCR A and B font printing
OCR A and B fonts	
LK-110 v2 Enhanced	Generates various file formats incl. DOCX, XLSX and combines
image support	LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
LK-111	Print data compression for reduced network impact
ThinPrint® Client	
LK-114 Universal	Supports server-less ubiquitous printing
print function	L
MK-602 Mount kit	Installation kit required for FS-533
MK-735 Mount kit	Installation kit for ID card reader
OC-514 Original cover	Cover instead of auto document feeder
PC-113	5.5" x 8.5" to 11" x 17", 500 sheets, 60-220 gsm
Universal tray (x1)	F FIL. 0 FILE 14II - 17II 0 - F00 -ht- 00 000
PC-213	5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 60-220 gsm
Universal tray (x2)	0.5" v 11" 0.500 abouto 60.000 gam
PC-413 Large capacity tray	8.5" x 11", 2,500 sheets, 60-220 gsm
PK-519 Punch kit	2/2 hala nunahing autopuitahing
for FS-533	2/3-hole punching, autoswitching
PK-520 Punch kit	2/3-hole punching, autoswitching
for FS-534	270 Holo pariothing, autoswitching
RU-514 Relay unit	Required for installation of FS-534
UK-212 Wireless LAN	Wireless LAN to network connector
WT-506 Working table	Authentication device placement
Nata Nat all antions may be sue	

Note: Not all options may be available at time of launch.



bizhub 360i

Black & White A3 multifunctional









CUSTOMER BENEFITS



Security

Secure network integration, data encryption, hard drive overwrite and advanced user authentication



Productivity

Reliability, high-speed scanning and printing, combined with powerful finishing functions



Sustainability

Numerous eco features reduce energy consumption and costs



Intuitive operability Operate the bizhub like a

smartphone or tablet with fully customized user interface



Application ecosystem Enhanced efficiency thanks

to Konica Minolta's extensive applications portfolio



Services

Efficient printer fleet management, including automatic consumables delivery, pro-active maintenance and remote setup

OPTIONS



PDF enhancements

OCR text recognition

Barcode fonts LK-106

Unicode fonts

OCR A and B fonts


Document converter pack

ThinPrint® client

Antivirus LK-116

FOIP IP Fax (T.38)





Mount kit MK-735



Document feeder DF-632 **Document feeder** DF-714 Original cover OC-511

Working table WT-506

10-Key pad KP-102

Security kit SC-509

Replacement SSD EM-908

Keyboard holder KH-102

4 MEDIA INPUT

Intelligent media sensor

1 x Universal tray PC-116

2 x Universal tray PC-216 Large capacity tray PC-416

Large capacity tray PC-417

Large Capacity tray LU-302

MEDIA OUTPUT

Job Separator

Inner Finisher FS-533

Staple finisher FS-539

Relay unit

Staple/booklet finisher FS-539SD

Relay unit RU-513

Punch kit

LEGEND

Mandatory option

Option

This option can only be installed with the respective option above it

FINISHING FUNCTIONALITIES































stapling

stapling

punching

punching

Duplex

Combined mixplex/ mixmedia

Half-fold

insertion

Tri-fold

Booklet

Offset sorting

printing

Stapling (offline)

DESCRIPTION

	 1 ^	R I	\sim	 ١ ١	 Α 7	CI I	10	^
E١								

2	
LK-102v3 PDF enhancements	PDF/A(1b), PDF encryption, digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A
LK-111 ThinPrint® client	Print data compression for reduced network impact
LK-116 Antivirus	Bitdefender® antivirus provides real time scanning of all
	incoming and outgoing data
LK-117 FOIP activation	Fax over IP networks (T.38), requires fax kit
CONNECTIVITY	
EIV COO LICE L'EL'S	HCD1 I I I'

EK-608 USB I/F kit	USB keyboard connection
MK-735 Mount kit	Installation kit for ID card reader
ID card reader	Various ID card technologies
AU-102 Biometric authentication	Finger vein scanner
FK-514 Fax board	Super G3 fax, digital fax functionality
EK-609 USB I/F kit	USB keyboard connection; Bluetooth
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode

OTHERS

DF-632 Document feeder	Reversing automatic document feeder, capacity 100 originals
DF-714 Document feeder	Dual scan automatic document feeder, capacity 100 originals

OTHERS

OC-511 Original Cover	Cover instead of ADF
WT-506 Working table	Authentication device placement
KP-102 10-Key pad	For use instead of touchscreen
SC-509 Security kit	Copy guard function
EM-908 Replacement SSD	1 TB SSD to increase storage space
KH-102 Keyboard holder	To place USB keyboard

MEDIA INPUT

IM-102 Intelligent media sensor	Auto detects paper weight and type
PC-116 1x Universal tray	500 sheets, 5.5" x 8.5" to 11" x 17", 52-256 gsm
PC-216 2x Universal tray	2x 500 sheets, 5.5" x 8.5" to 11" x 17", 52-256 gsm
PC-416 Large capacity tray	2,500 sheets, 8.5" x 11", 52-256 gsm
PC-417 Large capacity tray	1,500 + 1,000 sheets, 5.5" x 8.5" or 8.5" x 11" $/$ 52–256 g/m ²
LU-302 Large capacity tray	3,000 sheets, 8.5" x 11", 52-256 gsm
MK-730 Banner tray	Multipage banner feeding

MEDIA OUTPUT

FS-539 Staple finisher	50-sheet stapling; 3,200 sheets max. output
FS-539SD Booklet finisher	50-sheet stapling; 20 sheets booklet finisher;
	2,200 sheets max. output
PK-524 Punch kit for FS-539/SD	2/3-hole punching; auto switching
RU-513 Relay unit	For FS-539/SD installation
JS-506 Job separator	Separation of fax output; etc.
FS-533 Inner finisher	50-sheet stapling, 500 sheets max. output
PK-519 Punch kit for FS-533	2/3-hole punching, auto switching

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS System speed 8 5" v 11"

System speed 8.5" x 11"	Up to 36 ppm
System speed 11" x 17"	Up to 18 ppm
Autoduplex speed 8.5" x 11"	Up to 36 ppm
1st page out time 8.5" x 11"	4.6 sec.
Warm-up time	Approx. 12 sec. ¹
Imaging technology	Laser
Toner technology	Simitri® HD polymerized toner
Panel size/resolution	10.1" / 1024 x 600
System memory	8,192 MB (standard/max)
System hard drive	256 GB SSD (standard) / 1 TB SSD (optional)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11 b/g/n/ac (optional)
Network protocols	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP(S)
Automatic document feeder	Up to 100 originals; A6-A3; 35-163 gsm;
(optional)	RADF or Dual scan ADF available
ADF double feed detection	Standard (with dual scan ADF)
Printable paper size	A6-SRA3; banner paper max. 1,200 x 297 mm;
	customized paper sizes
Printable paper weight	52–300 g/m ²
Paper input capacity	1,150 sheets / 6,650 sheets (standard/max)
Paper tray input (standard)	1x 500 sheets; 3.5" x 8.5" to 11" x 17"; custom sizes; 52–256 gsm
	1x 500 sheets; 5.5" x 8.5" to 12" x 18"; custom sizes; 52–256 gsm
Paper tray input (optional)	2x 500 sheets; 5.5" x 8.5" to 11" x 17"; 52–256 gsm
	1x 2,500 sheets; 8.5" x 11"; custom sizes; 52-256 gsm
Large capacity tray (optional)	1x 3,000 sheets; 8.5" x 11"; custom sizes; 52–256 gsm
Manual bypass	150 sheets; 3.5" x 8.5" to 12" x 18"; Custom sizes; Banner;
	60-300 gsm
Finishing modes (optional)	Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold;
	Letter-fold; Booklet
Automatic duplexing	5.5" x 8.5" to 12" x 18"; 52–256 gsm

SYSTEM SPECIFICATIONS

Output capacity	Up to 250 sheets / up to 3,300 sheets (standard/max)
Stapling	Max. 50 sheets or 48 sheets + 2 cover sheets (up to 209 g/m²)
Stapling output capacity	Max. 100 sets
Tri-fold	Max. 3 sheets
Tri-fold capacity	Max. 30 sets; unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet (up to 209 g/m²)
Booklet output capacity	Max. 20 booklets; unlimited (without tray)
Duty cycle (monthly)	Rec. 33,000 pages; Max. ² 175,000 pages
Toner lifetime	Black up to 25,000 pages
Imaging unit lifetime	Black up to 245,000/1,000,000 pages (drum/developer)
Power consumption	110–120 V / 50/60 Hz; Less than 1.50 kW
System dimension (W x D x H)	24.2" x 27" x 31" (without options)
System weight	Approx. 187 lbs. (without options)

PRINTER SPECIFICATIONS

Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Page description language	PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
Operating systems	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64);
	Windows Server 2008 (32/64); Windows Server 2008 R2;
	Windows Server 2012; Windows Server 2012 R2; Windows Server
	2016; Windows Server 2019; Macintosh OS X 10.10 or later; Linux
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	Konica Minolta Print Service (Android);
	Konica Minolta Mobile Print (iOS/Android);
	AirPrint (iOS),Mopria (Android)
	optional: WiFi Direct

SCANNER SPECIFICATIONS

Scan speed	Up to 100 ipm in simplex (mono)
	Up to 200 ipm in duplex (mono)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);
	Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; Scan-
	to-DPWS; Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; Compact
	XPS; PPTX
	Optional: Searchable PDF; PDF/A 1a and 1b; Searchable DOCX/
	PPTX/XLSX
Scan destinations	2,000 destinations + 100 groups; LDAP support

COPIER SPECIFICATIONS

Copy resolution	600 x 600 dpi	
Gradation	256 gradations	
Multicopy	1–9,999	
Original format	Max. A3	
Magnification	25–400% in 0.1% steps; Auto-zooming	

FAX SPECIFCIATION

Fax standard	Super G3 (optional)	
Fax transmission	Analog; i-Fax; Color i-Fax; IP-Fax	
Fax resolution	Up to 600 x 600 dpi	
Fax compression	MH; MR; MMR; JBIG	
Fax modem	Up to 33.6 Kbps	
Fax destinations	2,000 single + 100 groups	

USER BOX SPECIFICATIONS

	· -
Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication);
	Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling

SYSTEM FEATURES

Security	ISO 15408 HCD-PP Common Criteria (in evalutation); IP filtering
	and port blocking; SSL3 and TLS1.0/1.1/1.2 network communica-
	tion; IPsec support; IEEE 802.1x support; User authentication;
	Authentication log; Secure print; Kerberos; Hard drive overwrite;
	Hard drive data encryption (AES 256); Confidential fax; Print user
	data encryption
	optional: Antivirus realtime scanning (Bitdefender®); Copy
	protection (Copy Guard, Password Copy)
Accounting	Up to 1,000 user accounts; Active Directory support (user name +
	password + e-mail + smb folder); User function access definition;
	Authentication by mobile device (Android)
	optional: Biometric authentication (finger vein scanner);
	ID card authentication (ID card reader);
	Authentication by mobile device (iOS)
Software	Net Care Device Manager; Data Administrator; Box Operator;
	Web Connection; Print Status Notifier; Driver Packaging Utility;
	Log Management Utility

¹ Warm-up time may vary depending on the operating environment and usage

- All specifications refer to letter-size paper of 80 gsm weight.
 The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a
 particular page size (6% coverage of letter).. The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.























For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2020 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo and bizhub are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com









² If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed













CUSTOMER BENEFITS



Security

Secure network integration, data encryption, hard drive overwrite and advanced user authentication



Productivity

Reliability, high-speed scanning and printing, combined with powerful finishing functions



Sustainability

Numerous eco features reduce energy consumption and costs



Intuitive operability Operate the bizhub like a

smartphone or tablet with fully customized user interface



Application ecosystem Enhanced efficiency thanks

to Konica Minolta's extensive applications portfolio



Services

Efficient printer fleet management, including automatic consumables delivery, pro-active maintenance and remote setup

OPTIONS



PDF enhancements

OCR text recognition

Barcode fonts LK-106

Unicode fonts

OCR A and B fonts


Document converter pack

ThinPrint® client

Antivirus LK-116

FOIP IP Fax (T.38)





3 OTHERS

Working table

10-Key pad Security kit

Replacement SSD

Keyboard holder KH-102

MEDIA INPUT

Intelligent media senso

1x Universal tray PC-116 2x Universal tray

Large capacity tray PC-417

Large capacity tray

Large capacity tray LU-207

Banner tray

5 MEDIA OUTPUT

Output tray OT-513

Attachment kit MK-607

Staple finisher FS-539

ınch kit for FS-539/SD

Staple finisher FS-540

Booklet finisher FS-540SD

Punch kit for FS-540/SD PK-526

OR)

Post inserter for FS-540/SD PI-507 Job separator for FS-540/SD OR

Z-fold unit for FS-540/SD

LEGEND

Mandatory option Option

This option can only be installed with the respective option above it

FINISHING FUNCTIONALITIES

































stapling

stapling

punching

punching

Duplex

Combined mixplex/ mixmedia

Half-fold

insertion

Tri-fold

Booklet

Offset sorting

printing

Stapling

DESCRIPTION

ENHANCED	FEATURES
-----------------	-----------------

LK-102v3 PDF enhancements	PDF/A(1b), PDF encryption, digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A
LK-111 ThinPrint® client	Print data compression for reduced network impact
LK-116 Antivirus	Bitdefender® antivirus provides real time scanning of all incom-
	ing and outgoing data
LK-117 FOIP activation	Fax over IP networks (T.38), requires fax kit

CONNECTIVITY

FK-514 Fax board	Super G3 fax, digital fax functionality
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection; Bluetooth
AU-102 Biometric authentication	Finger vein scanner
ID card reader	Various ID card technologies
MK-735 Mount kit	Installation kit for ID card reader

OTHERS

WT-506 Working table	Authentication device placement
KP-102 10-Key pad	For use instead of touchscreen
SC-509 Security kit	Copy guard function
EM-908 Replacement SSD	1 TB SSD to increase storage space
KH-102 Keyboard holder	To place USB keyboard

MEDIA INPUT

IM-102 Intelligent media sensor	Auto detects paper weight and type
PC-116 1x Universal tray	500 sheets, 5.5" x 8.5" – 11" x 17" / 52–256 g/m ²

MEDIA INPUT

PC-216 2x Universal tray	2x 500 sheets, 5.5" x 8.5" – 11" x 17" / 52–256 g/m ²²
PC-416 Large capacity tray	2,500 sheets, 8.5" x 11" / 52–256 g/m²
PC-417 Large capacity tray	$1,500 + 1,000$ sheets, 5.5 " x 8.5 " or 8.5 " x 11 " $/ 52 - 256$ g/m 2
LU-302 Large capacity tray	3,000 sheets, 8.5" x 11" / 52–256 g/m²
LU-207 Large capacity tray	2,500 sheets, 8.5" x 11" – 12" x 18" / 52–256 g/m ²
MK-730 Banner tray	Multipage banner feeding

Output tray used instead of finisher
Separation of fax output; etc.
50-sheet stapling, 500 sheets max. output
For FS-533 installation
2/3-hole punching, auto switching
50-sheet stapling; 3,200 sheets max. output
50-sheet stapling; 20 sheets booklet finisher;
2,200 sheets max. output
2/3-hole punching; auto switching
100 sheets stapling; 3,200 sheets max. output
100-sheet stapling; 20 sheets booklet finisher;
2,700 sheets max. output
2/3-hole punching; auto switching
For FS-539/SD or FS-540/SD installation
Separation of fax output; etc.
Cover insertion; post finishing
Z-fold for 11" x 17" prints

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS

System speed 8.5" x11"	Up to 45 ppm
System speed 11" x 17"	Up to 22 ppm
Autoduplex speed 8.5" x11"	Up to 45 ppm
1st page out time 8.5" x11"	3.8 sec.
Warm-up time	Approx. 15 sec. ¹
Imaging technology	Laser
Toner technology	Simitri® HD polymerized toner
Panel size/resolution	10.1" / 1024 x 600
System memory	8,192 MB (standard/max)
System hard drive	256 GB SSD (standard) / 1 TB SSD (optional)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11 b/g/n/ac (optional)
Network protocols	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP(S)
Automatic document feeder	Up to 300 originals; A6–A3; 35–210 g/m²; Dual scan ADF
ADF double feed detection	Standard
Printable paper size	3.5" x 5.5" – 12" x 18" / customized paper sizes /
	banner paper max. 47.2" x 11.7"
Printable paper weight	52-300 g/m ²
Paper input capacity	1,150 sheets / 6,650 sheets (standard/max)
Paper tray input (standard)	1 x 500 /3.5" x 5.8" – 11" x 17" / custom sizes / 52–256 g/m ²
	$1x500/5.5$ " x 8.5 " – 12 " x 18 " / custom sizes / 52 – $256g/m^2$
Paper tray input (optional)	1 x 500 / 5.5" x 8.5" – 11" x 17" / 52–256 g/m²
	2 x 500 / 5.5" x 8.5" - 11" x 17" / 52-256 g/m ²

 $2\,x\,500\,/\,5.5^{\prime\prime}\,x\,8.5^{\prime\prime}\,{-}\,11^{\prime\prime}\,x\,17^{\prime\prime}/\,52{-}256\,g/m^2$

1 x 2,500 / 8.5" x 11" /52-256 g/m²

1 x 1,500 + 1 x 1,000 sheets / 5.5" x 8.5" or 8.5" x 11" /

 $52-256 \text{ g/m}^2$

SYSTEM SPECIFICATIONS

Large capacity tray (optional)	1 x 3,000 / 8.5" x 11" / 52–256 g/m²
	1 x 2,500/8.5" x 11" – 12" x 18" / custom sizes /
	52-256 g/m ²
Manual bypass	150 sheets / 3.5" x 5.5" – 12" x 18" / custom sizes /
	banner / 60-300 g/m ²
Finishing modes (optional)	Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold;
	Letter-fold; Booklet; Post insertion; Z-fold
Automatic duplexing	4.1" x 5.5" – 12" x 18" / 52–256 g/m ²
Output capacity	Up to 250 sheets / up to 3,300 sheets (standard/max)
Stapling	Max. 100 sheets or 98 sheets + 2 cover sheets (up to 300 g/m^2)
Stapling output capacity	Max. 200 sets
Tri-fold	Max. 3 sheets
Tri-fold capacity	Max. 50 sets; unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet (up to 300 g/m^2)
Booklet output capacity	Max. 35 booklets; unlimited (without tray)
Duty cycle (monthly)	Rec. 40,000 pages; Max. ² 200,000 pages
Toner lifetime	Black up to 24,000 pages
Imaging unit lifetime	Black up to 240,000/1,000,000 pages (drum/developer)
Power consumption	110-120 V / 60 Hz, Less than 1.6 kW
System dimension (W x D x H)	24.2" x 27.1" x 37.8" (without options)
System weight	Approx. 220 lb (without options)

PRINTER SPECIFICATIONS

Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Page description language	PostScript 3 (CPSI 3016); PCL 6 (XL3.0); PCL 5c; XPS
Operating systems	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64);
	Windows Server 2008 (32/64); Windows Server 2008 R2;
	Windows Server 2012; Windows Server 2012 R2;
	Windows Server 2016; Windows Server 2019;
	Macintosh OS X 10.10 or later; Linux
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	Konica Minolta Print Service (Android);
	Konica Minolta Mobile Print (iOS/Android);
	AirPrint (iOS); Mopria (Android)
	optional: WiFi Direct

SCANNER SPECIFICATIONS

SCATTLER ST ECH TCATTO	113
Scan speed	Up to 140 ipm in simplex (mono)
	Up to 280 ipm in duplex (mono)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);
	Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV;
	Scan-to-DPWS; Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; PPTX
	optional: Searchable PDF; PDF/A 1a and 1b;
	Searchable DOCX/PPTX/XLSX
Scan destinations	2,000 destinations + 100 groups; LDAP support

COPIER SPECIFICATIONS

Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1–9,999
Original format	Max. 11" x 17"
Magnification	25–400% in 0.1% steps; Auto-zooming

FAX SPECIFCIATION

Fax standard	Super G3 (optional)
Fax transmission	Analog; i-Fax; Color i-Fax; IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,000 single + 100 groups

USER BOX SPECIFICATIONS

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication);
	Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling
SYSTEM FEATURES	
Security	ISO 15408 HCD-PP Common Criteria (in evalutation);
	IP filtering and port blocking; SSL3 and TLS1.0/1.1/1.2 network
	communication; IPsec support; IEEE 802.1x support;
	User authentication; Authentication log; Secure print; Kerberos;
	Hard drive overwrite; Hard drive data encryption (AES 256);
	Confidential fax; Print user data encryption
	optional: Antivirus realtime scanning (Bitdefender®);
	Copy protection (Copy Guard, Password Copy)
Accounting	Up to 1,000 user accounts; Active Directory support (user name +
	password + e-mail + smb folder); User function access definition;
	Authentication by mobile device (Android)
	optional: Biometric authentication (finger vein scanner);
	ID card authentication (ID card reader);
	Authentication by mobile device (iOS)
Software	Net Care Device Manager; Data Administrator; Box Operator;
	Web Connection; Print Status Notifier; Driver Packaging Utility;
	Log Management Utility

¹ Warm-up time may vary depending on the operating environment and usage

- All specifications refer to 8.5" x 11"-size paper of 80 g/m 2 quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of 8.5" x 11"). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.























For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2020 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com









² If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed



bizhub 550i

Black & White A3 multifunctional









CUSTOMER BENEFITS



Security

Secure network integration, data encryption, hard drive overwrite and advanced user authentication



Productivity

Reliability, high-speed scanning and printing, combined with powerful finishing functions



Sustainability

Numerous eco features reduce energy consumption and costs



Intuitive operability Operate the bizhub like a

smartphone or tablet with fully customized user interface



Application ecosystem Enhanced efficiency thanks

to Konica Minolta's extensive applications portfolio



Services

Efficient printer fleet management, including automatic consumables delivery, pro-active maintenance and remote setup

OPTIONS



PDF enhancements

OCR text recognition

Barcode fonts LK-106

Unicode fonts

OCR A and B fonts


Document converter pack

ThinPrint® client

Antivirus LK-116

FOIP IP Fax (T.38)





3 OTHERS

Working table

10-Key pad Security kit

Replacement SSD

Keyboard holder KH-102

MEDIA INPUT

1x Universal tray PC-116 2x Universal tray

Large capacity tray PC-417

Large capacity tray

Large capacity tray LU-207

Banner tray

5 MEDIA OUTPUT

Output tray OT-513

Attachment kit MK-607

Staple finisher FS-539

ınch kit for FS-539/SD

Staple finisher FS-540

Booklet finisher FS-540SD

Punch kit for FS-540/SD PK-526

OR)

Post inserter for FS-540/SD PI-507 Job separator for FS-540/SD OR

Z-fold unit for FS-540/SD

LEGEND

Option

Mandatory option

This option can only be installed with the respective option above it

FINISHING FUNCTIONALITIES



































stapling

stapling

punching

punching

Duplex

Combined mixplex/ mixmedia

Half-fold

insertion

Tri-fold

Booklet

Offset sorting

printing

Stapling

DESCRIPTION

ENHANCED FEATURES	
LK-102v3 PDF enhancements	PDF/A(1b), PDF encryption, digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A
LK-111 ThinPrint® client	Print data compression for reduced network impact
LK-116 Antivirus	Bitdefender® antivirus provides real time scanning of all
	incoming and outgoing data
LK-117 FOIP activation	Fax over IP networks (T.38), requires fax kit
CONNECTIVITY FK-514 Fax board	Super G3 fax, digital fax functionality
	Super G3 fax, digital fax functionality Wireless LAN and wireless LAN Access Point Mode
UK-221 Wireless LAN	
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection; Bluetooth
AU-102 Biometric authentication	Finger vein scanner
ID card reader	Various ID card technologies
MK-735 Mount kit	Installation kit for ID card reader
OTHERS	
	Authorization device placement
WT-506 Working table	Authentication device placement For use instead of touchscreen
KP-102 10-Key pad	Tot about total or to a on to
SC-509 Security kit	Copy guard function
EM-908 Replacement SSD	1 TB SSD to increase storage space
KH-102 Keyboard holder	To place USB keyboard

Auto detects paper weight and type

500 sheets, 5.5" x 8.5" – 11" x 17" / 52–256 g/m 2

PC-216 2x Universal tray	2x 500 sheets, 5.5" x 8.5" – 11" x 17" / 52–256 g/m ²
PC-416 Large capacity tray	2,500 sheets, 8.5" x 11" / 52–256 g/m ²
PC-417 Large capacity tray	1,500 + 1,000 sheets, 5.5" x 8.5" or 8.5" x 11" / 52-256 g/m ²
LU-302 Large capacity tray	3,000 sheets, 8.5" x 11" / 52–256 g/m²
LU-207 Large capacity tray	2,500 sheets, 8.5" x 11" – 12" x 18" / 52–256 g/m ²
MK-730 Banner tray	Multipage banner feeding
MEDIA OUTPUT	
OT-513 Output tray	Output tray used instead of finisher
JS-508 Job separator	Separation of fax output; etc.
FS-533 Inner finisher	50-sheet stapling, 500 sheets max. output
MK-607 Attachment kit	For FS-533 installation
PK-519 Punch kit for FS-533	2/3-hole punching, auto switching
FS-539 Staple finisher	50-sheet stapling; 3,200 sheets max. output
FS-539SD Booklet finisher	50-sheet stapling; 20 sheets booklet finisher;
	2,200 sheets max. output
PK-524 Punch kit for FS-539/SD	2/3-hole punching; auto switching
FS-540 Staple finisher	100 sheets stapling; 3,200 sheets max. output
FS-540SD Booklet finisher	100 sheets stapling; 20 sheets booklet finisher;
	2,700 sheets max. output
PK-526 Punch kit for FS-540/SD	2/3-hole punching; auto switching
RU-513 Relay unit	For FS-539/SD or FS-540/SD installation
JS-602 Job separator for FS-540/SD	Separation of fax output; etc.
PI-507 Post inserter for FS-540/SD	Cover insertion; post finishing
ZU-609 Z-fold unit for FS-540/SD	Z-fold for 11" x 17" prints

TECHNICAL SPECIFICATIONS

MEDIA INPUT

IM-102 Intelligent media sensor

PC-116 1x Universal tray

SYSTEM SPECIFICATIONS System speed 8.5" x11" Up to 55 ppm System speed 11" x 17" Up to 27 ppm Autoduplex speed 8.5" x 11" Up to 55 ppm 1st page out time 8.5" x 11" 3.3 sec. Warm-up time Approx. 14 sec.1 Imaging technology Toner technology Simitri® HD polymerized toner Panel size/resolution 10.1" / 1024 x 600 System memory 8,192 MB (standard/max) System hard drive 256 GB SSD (standard) / 1 TB SSD (optional) 10/100/1,000-Base-T Ethernet; Interface USB 2.0; Wi-Fi 802.11 b/g/n/ac (optional) Network protocols TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP(S) Automatic document feeder Up to 300 originals / 5.5" x 8.5" – 11" x 17" / $35-210~g/m^2$ / Dual scan ADF ADF double feed detection Standard Printable paper size 3.5" x 5.5" – 12" x 18" / customized paper sizes / banner paper max. 47.2" x 11.7" Printable paper weight $52-300 \text{ g/m}^2$ Paper input capacity 1,150 sheets / 6,650 sheets (standard/max) 1 x 500 /3.5" x 5.8" – 11" x 17" / custom sizes / 52–256 g/m² Paper tray input (standard) $1\,x\,500\,/\,5.5"\,x\,8.5"$ – $12"\,x\,18"\,/\,$ custom sizes $/\,52$ – $256\,g/m^2$ 1 x 500 / 5.5" x 8.5" - 11" x 17" / 52-256 g/m² Paper tray input (optional) $2 \times 500 / 5.5$ " x 8.5" – 11" x 17"/ 52– $256 \, g/m^2$ $1\,x\,2,500\,/\,8.5"\,x\,11"\,/52-256\,g/m^2$

52-256 g/m²

1 x 1,500 + 1 x 1,000 sheets / 5.5" x 8.5" or 8.5" x 11" /

Large capacity tray (optional)	1 x 3,000 / 8.5" x 11" / 52-256 g/m ²
	1 x 2,500/ 8.5" x 11" – 12" x 18" / custom sizes /
	52-256 g/m ²
Manual bypass	150 sheets / 3.5" x 5.5" – 12" x 18" / custom sizes /
	banner / 60-300 g/m ²
Finishing modes (optional)	Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold;
	Letter-fold; Booklet; Post insertion; Z-fold
Automatic duplexing	4.1" x 5.5" – 12" x 18" / 52–256 g/m ²
Output capacity	Up to 250 sheets / up to 3,300 sheets (standard/max)
Stapling	Max. 100 sheets or 98 sheets + 2 cover sheets (up to 300 g/m²)
Stapling output capacity	Max. 200 sets
Letter fold	Max. 3 sheets
Letter fold capacity	Max. 50 sets; unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet (up to 300 g/m²)
Booklet output capacity	Max. 35 booklets; unlimited (without tray)
Duty cycle (monthly)	Rec. 50,000 pages; Max. ² 200,000 pages
Toner lifetime	Black up to 24,000 pages
Imaging unit lifetime	Black up to 240,000/1,000,000 pages (drum/developer)
Power consumption	220-240 V / 50/60 Hz; Less than 2.00 kW
System dimension (W x D x H)	24.2" x 27.1" x 37.8" (without options)
System weight	Approx. 220 lb (without options)

SYSTEM SPECIFICATIONS

PRINTER SPECIFICATIONS

Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Page description language	PostScript 3 (CPSI 3016); PCL 6 (XL3.0); PCL 5c; XPS
Operating systems	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64);
	Windows Server 2008 (32/64); Windows Server 2008 R2;
	Windows Server 2012; Windows Server 2012 R2;
	Windows Server 2016; Windows Server 2019;
	Macintosh OS X 10.10 or later; Linux
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	Konica Minolta Print Service (Android);
	Konica Minolta Mobile Print (iOS/Android);
	AirPrint (iOS); Mopria (Android)
	optional: WiFi Direct

SCANNER SPECIFICATIONS

00/11/11/21/01/2011/0/11/0/	
Scan speed	Up to 140 ipm in simplex (mono)
	Up to 280 ipm in duplex (mono)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);
	Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV;
	Scan-to-DPWS; Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; PPTX
	optional: Searchable PDF; PDF/A 1a and 1b;
	Searchable DOCX/PPTX/XLSX
Scan destinations	2,000 destinations + 100 groups; LDAP support

COPIER SPECIFICATIONS

Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1–9,999
Original format	Max. 11" x 17"
Magnification	25–400% in 0.1% steps; Auto-zooming

FAX SPECIFCIATION

Fax standard	Super G3 (optional)
Fax transmission	Analog; i-Fax; Color i-Fax; IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,000 single + 100 groups

























For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

USER BOX SPECIFICATIONS

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication);
	Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling
SYSTEM FEATURES	
Security	ISO 15408 HCD-PP Common Criteria (in evalutation);
	IP filtering and port blocking; SSL3 and TLS1.0/1.1/1.2 network
	communication; IPsec support; IEEE 802.1x support;
	User authentication; Authentication log; Secure print; Kerberos;
	Hard drive overwrite; Hard drive data encryption (AES 256);
	Confidential fax; Print user data encryption
	optional: Antivirus realtime scanning (Bitdefender®);
	Copy protection (Copy Guard, Password Copy)
Accounting	Up to 1,000 user accounts; Active Directory support (user name +
	password + e-mail + smb folder); User function access definition;
	Authentication by mobile device (Android)
	optional: Biometric authentication (finger vein scanner);
	ID card authentication (ID card reader);
	Authentication by mobile device (iOS)
Software	Net Care Device Manager; Data Administrator; Box Operator;
	Web Connection; Print Status Notifier; Driver Packaging Utility;
	Log Management Utility

- All specifications refer to 8.5" x 11"-size paper of 80 g/m 2 quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
 The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a
- $particular\ page\ size\ (5\%\ coverage\ of\ 8.5''\ x\ 11'').\ The\ actual\ life\ of\ each\ consumable\ will\ vary\ depending\ on\ use\ and$ $other \ printing \ variables \ including \ page \ coverage, \ page \ size, \ media \ type, \ continuous \ or \ intermittent \ printing, \ ambient$ temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com









¹ Warm-up time may vary depending on the operating environment and usage

² If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed



TECHNOLOGY



MONOCHROME MID-VOLUME MULTIFUNCTION PRINTER

Up to 65 ppm print/copy output to keep pace with rising demands
Standard dual scanning handles up to 240 originals per minute
High capacity 300-sheet document feeder
Large 9" color display with quick tablet-like touchscreen interface
Scan-to-email and FTP, scan-to-me, scan-to-home convenience
Built-in Emperon® print system, universal printer drivers
Simitri® HD polymerized toner for high-resolution imaging
Standard 250 GB HDD for on-board document storage
Web browser with 4 GB of memory
ISO 15408 and IEEE 2600.1 security standards

Power-saving design with quick recovery from sleep mode
6,650-Sheet maximum capacity, tab printing support, carbon-copy printing
Advanced authentication, secure print release, remote firmware updates
Multiple bypass tray and detachable paper feed trays improve paper handling
Finishing options for 80-page booklet-making, up to 100-sheet stapling
Options for 2/3-hole punch, tri-fold, z-fold, post-insertion and more
Downloadable apps to help you work faster and smarter
Multiple i-Options to suit the needs of your workflow
EPEAT Gold-certified, low power consumption to cut costs
Mobile printing support (AirPrint, Google Cloud Print Classic, NFC)

bizhub 658e

MONOCHROME MID-VOLUME MULTIFUNCTION PRINTER

Combining 65 ppm B&W print/copy output with dual scanning at up to 240 opm, the bizhub 658e raises the bar in MFP power and productivity — with an enhanced touch-and-swipe interface and scalable options for specialized needs in business as well as legal, education, healthcare and other applications.

SYSTEM OVERVIEW

SYSTEM OVERVIEW	
System memory	4 GB
System hard disk	250 GB Standard
Interface	10-BASE-T / 100-BASE-TX / 1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB v2, LPD, IPP, SNMP, HTTP
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Dual scan document feeder	Up to 300 originals / 5.5" x 8.5" to 11" x 17" / 35-210 gsm
Printable paper size	Scanning/Copying: up to 11" x 17"
	Printing: up to 11" x 17" full bleed on 12" x 18" paper
	Custom paper sizes
Drintable nanar weight	Banner paper max.: 11.75" x 47.25"
Printable paper weight	52-300 gsm
Paper input capacity	Standard: 1,150 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
PC-115 paper feed cabinet (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
PC-215 2-way paper feed cabinet (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 52-256 gsm
Large capacity tray PC-415 (optional)	2,500 sheets / 8.5" x 11" / 52-256 gsm
Large capacity tray LU-207 (optional)	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm
Large capacity tray LU-302 (optional)	3,000 sheets / 8.5" x 11" / 52-256 gsm
Manual bypass	150 sheets / 4" x 6" to 12" x 18" /
	custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, sort, staple, punch, half-fold, z-fold, tri-fold, post-insertion, booklet
Output capacity	Max. with finisher: 3,300 sheets Max. without finisher: 250 sheets
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheets (up to 209 gsm)
Stapling output capacity	Max.: 1,000 sheets
Tri-fold (optional)	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray)
Copy/print volume	Max.: 300,000 pages/month ¹
Toner lifetime	26,000 pages
ioner medine	
Imaging unit lifetime	300,000 pages / 600,000 pages (Drum / Developer)
Imaging unit lifetime	300,000 pages / 600,000 pages (Drum / Developer) 120 V / 60 Hz, less than 1.59 kW (system)
	300,000 pages / 600,000 pages (Drum / Developer) 120 V / 60 Hz, less than 1.59 kW (system) 24.2" x 27" x 38" (W x D x H)

COPIER SPECIFICATIONS

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD Polymerized Toner
Print speed (8.5" x 11")	Up to 65 ppm (portrait)
Print speed (11" x 17")	Up to 33 ppm (portrait)
Autoduplex speed (8.5" x 11")	Up to 65 ppm (portrait)
1st copy out time	3 sec.
Warm-up time	Approx. 22 sec. ²
Copy resolution	600 x 600 dpi
Gradations	256 gradations
Multi-copy	1-9,999
Original format	Up to 11" x 17"
Magnification	25-400% in 0.1% steps, auto zooming
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1

PRINTER SPECIFICATION	DNS
Print resolution	1,800 (equivalent) x 600 dpi, 1,200 x 1,200 dpi
PDL	PCL6 (XL 3.0), PCL5e/c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32/x64): 7 / 8 / 10 Windows Server (x32/x64): 2008 / 2008 R2 ³ / 2012 ³ / 2016 ³ Macintosh OS X 10.8 or later Linux / Unix / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print.

SCANNER SPECIFICATIONS	
Scan speed	B&W / Color: up to 240 ipm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan- to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/ XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, real-time scan preview

FAX SPECIFICATIONS

Fax	Super G3 (optional)
Transmission	Analog, Internet fax, Color i-Fax, IP-Fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to Email/FTP/SMB, up to 400 job programs

USER BOX SPECIFICATIONS

Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public Personal (with password or authentication)
	Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt,
	fax polling, annotation
User box functionality	Reprint, combination, download, sending (Email/FTP/SMB and fax), copy box-to-box

SYSTEM FEATURES

Security	ISO 15408 FAL3 ³
security	IEEE 2600.13
	IP filtering and port blocking
	3 1 3
	SSL2, SSL3 and TSL1.0 network communication
	IPsec support
	IEEE 802.1x support
	FIPS 140-2
	User authentication
	Authentication log
	Secure print
	Hard disk overwrite (8 standard types)
	Hard disk data encryption (AES 128)
	Memory data auto deletion
	Confidential fax receipt
	Print user data encryption
	Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts
	Active Directory support
	(user name + password + Email + SMB folder)
	User function access definition
	Optional biometric authentication (finger vein scanner)
	Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager
	PageScope Data Administrator
	PageScope Box Operator
	PageScope Direct Print
	Print Status Notifier
	Driver Packaging Utility
	Log Management Utility

Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.

2 Warm-up time may vary depending on the operating environment and usage.

3 Supports x64 only.

4 Certification pending.

COMPONENTS AND OPTIONS

AU-102 Biometric	Finger vein scanner
authentication	6/39/1
AU-205H Universal	Various ID card technologies
ID card reader	
AU-211	Requires WT-506 Working Table
CAC/PIV solution*	
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection, Bluetooth
DK-510 Copier desk	Provides storage space for print media and other materials
FK-514 Fax board	Super G3 fax, digital fax functionality
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support
	(requires MK-742)
FS-536 Staple finisher	50-sheet stapling, 3,200 sheets max. output
FS-536SD	50-sheet staple finisher, 20-sheet booklet finisher,
Booklet finisher	2,500 sheets max. output
FS-537 Staple finisher	100-sheet stapling, 3,200 sheets max. output
FS-537SD	100-sheet stapling, 20-sheet booklet finisher,
Booklet finisher	2,500 sheets max. output
HD-524 Hard disk	Backup HDD
JS-602 Job separator	Separation for fax output, etc.
for FS-537	
Keyboard	External keyboard (requires KH-102)
KH-102 Keyboard holder	To place USB keyboard
KP-101 10-Key pad	For use instead of touchscreen
LK-102 v3	PDF/A, PDF encryption, digital signature
LK-104 v3	Provides voice guidance functions

COMPONENTS AND OPTIONS (CONTINUED)

ONS (CONTINUED)
Searchable PDF
Supports native barcode printing
Supports native Unicode printing
Supports native OCR A and B font printing
Generates various file formats incl. DOCX, XLSX and combines LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
ThinPrint® data compression for reduced network impact
2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm
10
3,000 sheets / 8.5" x 11" / 52-256 gsm
ş
Banner paper guide
Installation kit for ID card reader
Installation kit for FK-515 fax board
Output tray used instead of finisher
500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
2 x 500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
2 x 500 sheets / 8.5" x 11" / 52-256 gsm
Cover insertion, post finishing
2/3-hole punching, autoswitching
2/3-hole punching, autoswitching
Required for FS-537/FS-537SD and FS-536/FS-536SD
Copy Guard function (2x required)
Added stapling functionality kit
Added fax stamp capability kit
Wireless LAN to network connector
Wireless LAN to network connector

^{*} May not be available at time of launch.





PARTNERSHIP

Konica Minolta can help give shape to your ideas and partner with you to achieve your corporate objectives. Contact us to realize opportunities in:

INFORMATION MANAGEMENT	IT SERVICES	TECHNOLOGY
Enterprise Content Management (ECM)	Application Services	Office Multifunction Business Solutions
Document Management	Cloud Services	Commercial and Production Printers
Automated Workflow Solutions	IT Security	3D Printers
Business Process Automation	Managed IT Services	Wide Format Printers
Security and Compliance	IT Consulting & Projects	Laptops, Desktops and
Mobility	Business Consulting Services	Computer Hardware
eDiscovery Services		Servers and Networking Equipment
		Managed Print Services (MPS)
		Managed Enterprise Services





For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2017 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo and bizhub are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com









Giving Shape to Ideas

• • • •

High-speed print/copy output of 80 ppm in high-quality B&W Standard dual scanning handles up to 240 originals per minute High capacity 300-sheet document feeder INFO-Palette display for instant access to more information Large 9" color display with quick tablet-like interface Web browser ready with 4 GB memory Downloadable apps to improve your productivity Built-in Emperon® print system, universal printer drivers Simitri® HDE toner guarantees excellent print quality Scan to email and ftp, scan-to-me, scan-to-home convenience 6,650-Sheet capacity, tab printing support, carbon-copy printing Finishing options for 80-page booklet-making, up to 100-sheet stapling Options for 2/3-hole punch, tri-fold, z-fold, post-insertion and more Internal card reader and other advanced security options ISO 15408 and IEEE 2600.1 Security standards Optional voice guidance, PDF/A formatting Multiple i-Options to suit the needs of your workflow Low power consumption, eco-indicator to help cut costs **EPEAT Gold-certified** Mobile printing support (AirPrint, Google Cloud Print, NFC)

bizhub 808

MONOCHROME HIGH-VOLUME MULTIFUNCTION PRINTER

mfp





bizhub 808

With 80 ppm print/copy output in high-resolution B&W, standard dual scanning at up to 240 opm, multiple finishing options and enhanced touch-and-swipe interface, the bizhub 808 brings maximum productivity to high-volume document demands and in-house, on-demand printing applications.

System Overview

System Overview	
System memory	4 GB
System hard disk	250 GB
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0,
	Wi-Fi 802.11 b/g (opt.)
Network protocols	TCP/IP (IPv4/IPv6), NetBEUI, SMB, LPD, IPP, SNMP, HTTP
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Dual scan	Up to 300 originals / 5.5" x 8.5" to 11" x 17" / 35–210 gsm
document feeder	
Printable paper size	Scanning/Copying: up to 11" x 17"
	Printing: up to 11" x 17" full bleed on 12" x 18" paper
	Custom paper sizes
	Banner paper max.: 11.75" x 47.25"
Printable	52–300 gsm
paper weight	
Paper input capacity	Standard: 3,650 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 12" x 18" / 52–256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52–256 gsm
Tray 3	1,500 sheets / 8.5" x 11", 5.5" x 8.5", 4" x 6" / 52–256 gsm
Tray 4	1,000 sheets / 8.5" x 11", 5.5" x 8.5", 4" x 6" / 52–256 gsm
Large capacity tray	3,000 sheets / 8.5" x 11" / 52–256 gsm
LU-303 (optional)	
Large capacity tray	2,500 sheets / 8.5" x 11" to 12" x 18" / 52–256 gsm
LU-205 (optional)	
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes /
	52–300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52–256 gsm
Finishing modes	Offset, group, sort, staple, punch, post insertion,
Otmt annacitus	z-fold, half-fold, tri-fold, booklet
Output capacity	Max. with finisher: 3,200 sheets Max. without finisher: 250 sheets
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheets
Stapinig (optional)	(up to 209 gsm)
Stapling	Max.: 1000 sheets
output capacity	The state of the s
Tri-fold	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray), unlimited
Booklet	Max.: 20 sheets or 19 sheets + 1 cover sheet
	(up to 209 gsm)
Booklet output	Max.: 100 sheets (tray), unlimited
capacity	
Copy/print volume	Max.: 300,000 pages/month ¹
Toner lifetime	Black: 40,800 pages
Imaging unit lifetime	400,000 pages / 1,200,000 pages (Developer)
Power consumption	120 V / 50/60 Hz, less than 2.1 kW (system)
System dimensions	26.4" x 32.3" x 48.5" (W x D x H)
System weight	Approx. 441 lb.
,	

Printer Specifications

i illiter opcomouti	V110
Print resolution	1,800 x 600 dpi, 1,200 x 1,200 dpi
PDL	PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32/x64): Vista / 7 / 8
	Windows Server (x32/x64): 2008 / 2008 R2 / 2012 / 2012 R2
	Macintosh OS X 10.6 / 10.7 / 10.8 / 10.9 / 10.10
	UNIX / Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3 emulation
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex,
	"Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

Copier Specifications

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD ^E Polymerized Toner
Print speed	Up to 80 ppm (Portrait)
(8.5" x 11")	
Autoduplex speed	Up to 80 ppm (Portrait)
(8.5" x 11")	
1st copy out time	3.6 sec.
Warm-up time	Approx. 100 sec. ²
Copy resolution	600 x 600 dpi
Gradations	256 gradations
Multi-copy	1–9,999
Original format	Up to 11" x 17"
Magnification	25–400% in 0.1% steps, auto zooming
Copy functions	Chapter, cover and page insertion, proof copy (print
	and screen), adjustment test print, digital art functions,
	job setting memory, poster mode, image repeat,
	overlay, stamping, copy protection

Scanner Specifications

Scan speed	B&W / Color: up to 240 ipm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, real time scan preview

Fax Specifications

Fax	Super G3 (optional)	
Transmission	Analog, i-Fax, Color i-Fax, IP-fax	
Resolution	Max.: 600 x 600 dpi (ultra-fine)	
Compression	MH, MR, MMR, JBIG	
Modem	Up to 33.6 Kbps	
Destinations	2,100 (single + group)	
Functions	Polling, time shift, PC-fax, receipt to confidential box,	
	receipt to Email/FTP/SMB, up to 400 job programs	

User Box Specifications

Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public
	Personal (with password or authentication)
	Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling
User box functionality	Reprint, combination, download, sending
	(Email/FTP/SMB and fax), copy box-to-box

System Features

Security	ISO 15408 EAL3 ³	
•	IEEE 2600.13	
	IP filtering and port blocking	
	SSL2, SSL3 and TSL1.0 network communication	
	IPsec support	
	IEEE 802.1x support	
	User authentication	
	Authentication log	
	Secure print	
	Hard disk overwrite (8 standard types)	
	Hard disk data encryption (AES 256)	
	Hard disk mirroring (opt.)	
	Memory data auto deletion	
	Confidential fax receipt	
	Print user data encryption	
	Copy protection (Copy Guard, Password Copy) (opt.)	
Accounting	Up to 1,000 user accounts	
	Active Directory support	
	(user name + password + Email + SMB folder)	
	User function access definition	
	Optional Biometric authentication (finger vein scanner)	
	Optional ID card authentication (ID card reader)	
Software	PageScope Net Care Device Manager	
	PageScope Data Administrator	
	PageScope Box Operator	
	PageScope Direct Print	
	Print Status Notifier	
	Driver Packaging Utility	
	Log Management Utility	

¹ Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs

Components and Opti	
AU-102 Biometric	Finger vein scanner
authentication	
AU-205H Universal	Various ID card technologies
D card reader	
EK-610 USB I/F kit	USB keyboard connection
EK-611 USB I/F kit	USB keyboard connection, Bluetooth
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support
FK-516 Fax board	Super G3 fax, digital fax functionality
FS-536 Staple finisher	50-sheet stapling, 3,200 sheets max. output
FS-536SD	50-sheet staple finisher, 20-sheet booklet finisher,
Booklet finisher	2,200 sheets max. output
S-537 Staple finisher	100-sheet stapling, 3,200 sheets max. output
-S-537SD	100-sheet stapling, 20-sheet booklet finisher,
Booklet finisher	2,500 sheets max. output
HD-524 Hard	Back-up HDD
lisk mirroring	
S-602 Job	Separation for fax output, etc.
separator for FS-537	ocparation for tax output, etc.
Keyboard	External keyboard (requires KH-102)
(H-102	To place USB keyboard
Keyboard holder	to place our heybourd
(P-101 10-Key pad	For use instead of touchscreen
K-101 10-key pau K-102 v3	PDF/A, PDF encryption, digital signature
PDF enhancements	i Di / A, FDT Eliciyption, aigital signature
.K-104 v3	Provides voice guidance functions
/oice guidance	Provides voice guidance functions
.K-105 v3	Searchable PDF
	Searchable PDF
OCR text recognition K-106	Cupports native harrande printing
	Supports native barcode printing
Barcode fonts	Consideration Haire de autotion
.K-107	Supports native Unicode printing
Jnicode fonts	0. 1 1. 0004 100 1 11
.K-108	Supports native OCR A and B font printing
OCR A and B fonts	0
.K-110 Enhanced	Generates various file formats incl. DOCX, XLSX
mage support	and combines LK-102 (encrypted PDF) + LK-105
.K-111	(searchable PDF/OCR functionality)
'hinPrint [®] Client	Print data compression for reduced network impact
	0.5111111
.U-205	8.5" x 11" to 12" x 18", 2,500 sheets, 52–256 gsm
arge capacity tray	0.511 4411 2.000 1 1 52.250
.U-303	8.5" x 11", 3,000 sheets, 52–256 gsm
arge capacity tray	
MK-735 Mount kit	Installation kit for ID card reader
MK-742 Mount kit	Installation kit for FK-515 fax board
OT-508 Output tray	Output tray used instead of finisher
PI-507 Post inserter	Cover insertion, post finishing
or FS-537	0.01
K-520 Punch kit	2/3-hole punching, autoswitching
or FS-536	
PK-523 Punch kit	2/3-hole punching, autoswitching
or FS-537	
RU-515 Relay unit	Required for the FS-537/FS-537SD
	and FS-536/FS-536SD
C-508 Security kit	Copy Guard function (2x required)
	Wireless LAN to network connector
JK-212	Detects multi-feeding in the document feeder
JK-212 JK-501 Multi-feed	Detects multi-feeding in the document feeder
JK-212 JK-501 Multi-feed Jetection kit	
JK-212 JK-501 Multi-feed detection kit WT-506 Working table	Authentication device placement
JK-212 JK-501 Multi-feed Jetection kit WT-506 Working table WT-513 Working table ZU-609 Z-fold unit	

² Warm-up time may vary depending on the operating environment and usage

³ Certification pending



Color Multifunction Devices















CUSTOMER BENEFITS



Intuitive operability Operate the bizhub like a smartphone or tablet with fully customized user interface



Mobile connectivity Print anytime from anywhere with Konica Minolta's innovative mobile technologies



Security Secure network integration, data encryption, SSD overwrite, and advanced user authentication



Application ecosystem Enhanced efficiency thanks to Konica Minolta's extensive applications portfolio



Productivity Reliability, high-speed scanning and printing, combined with powerful finishing functions



Sustainability Efficient printer fleet management, including automatic consumables delivery, pro-active maintenance and remote setup

OPTIONS



OCR text recognition

Barcode fonts

Unicode fonts LK-107 OCR A and B fonts

Document converter pack LK-110v2

ThinPrint® client LK-111












above it





FINISHING FUNCTIONALITIES











Duplex

















punching

Three-hole punching

Combined mixplex/ mixmedia

Half-fold

insertion. report

Letter-fold

Booklet

Offset sorting

Banner printing

DESCRIPTIONS

ENHANCED FEATURES

LK-102v3 PDF enhancements	PDF/A (1b); PDF encryption; digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX; XLSX and PDF/A
LK-111 ThinPrint® Client	Print data compression for reduced network impact
LK-116 Antivirus	Bitdefender® Antivirus provides real time scanning
	of all input/output data

CONNECTIVITY

CONNECTIVITY	
FK-514 Fax board	Super G3 fax, digital fax functionality
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support
MK-742	Installation kit for FK-515
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection; Bluetooth
IC-420 Fiery controller	Professional color print controller
VI-516 Interface kit for IC-420	Fiery controller interface card
UK-115 Interface board for IC-420	Fiery controller interface board
AU-102 Biometric authentication	Finger vein scanner
AU-205H card reader	Various ID card technologies
MK-735 Mount kit	Installation kit for ID card reader

OTHERS

DF-632 Document feeder	Reversing automatic document feeder, capacity 100 originals
DF-714 Document feeder	Dualscan automatic document feeder, capacity 100 originals
OC-511 Original cover	Cover instead of ADF
WT-506 Working table	Authentication device placement
KP-102 10-Key pad	For use instead of touchscreen
SC-509 Security kit	Copy guard function (2 kits required for Dualscan ADF)
KH-102 Keyboard holder	To place USB keyboard
External Keyboard	Keyboard for alpha numeric data entry

MEDIA INPUT

PC-116 1 Universal tray	500 sheets, 5.5" x 8.5" to 11" x 17", 52-256 gsm
PC-216 2 Universal tray	2x 500 sheets, 5.5" x 8.5" to 11" x 17", 52-256 gsm
PC-416 Large capacity tray	2,500 sheets, 8.5" x 11", 52-256 gsm
LC-302 Large capacity tray	3,000 sheets, 8.5" x 11", 52-256 gsm
MK-730 Banner tray	Multipage banner feeding
DK-516 Copier desk	Provides storage space for print media and other materials

MEDIA OUTPUT

FS-533 Inner finisher	50-sheet stapling, 500 sheets max. output
PK-519 Punch kit for FS-533	2/3 hole punching, autoswitching
FS-536 Staple finisher	50-sheet stapling, 3,300 sheets max. output
FS-536SD Booklet finisher	50-sheet staple finisher; 20-sheet booklet finisher;
	2,300 sheets max. output
PK-520 Punch kit for FS-536(SD)	2/3 hole punching; autoswitching
RU-513 Relay unit	For FS-536(SD)/FS-537(SD) installation,
	(Max. 100 sheets output capacity)
JS-506 Job separator	Separation of fax output; etc.

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS

Panel size/resolution	10.1" / 1024 x 600
System memory (standard/max)	8 GB
Solid State Drive	256 GB (standard)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11 b/g/n (optional)
Network protocols	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP;
	HTTP(S); AppleTalk; Bonjour
Automatic document feeder (optional)	Up to 100 originals; A6-A3; 35-163 gsm;
	RADF or Dual scan ADF available
Paper input capacity (standard/max)	1,150 sheets / 6,650 sheets
Paper tray input (standard)	1x 500 sheets; 3.5" x 8.5" to 11" x 17"; custom sizes; 52–256 gsm
	1x 500 sheets; 5.5" x 8.5" to 12" x 18"; custom sizes; 52–256 gsm
Paper tray input (optional)	2x 500 sheets; 5.5" x 8.5" to 11" x 17"; 52–256 gsm
	1x 2,500 sheets; 8.5" x 11"; custom sizes; 52–256 gsm
Large capacity tray (optional)	1x 3,000 sheets; 8.5" x 11"; custom sizes; 52–256 gsm
Manual bypass	150 sheets; 3.5" x 8.5" to 12" x 18"; Custom sizes; Banner;
	60-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18"; 52–256 gsm
Finishing modes (optional)	Offset; Group; Sort; Staple; Punch; Half-fold; Letter-fold; Booklet
Output capacity (standard)	Max. 250 sheets
Output Capacity (optional)	Max. 3,300 sheets
Stapling	Max. 50 sheets or 48 sheets + 2 cover sheets (up to 209 gsm)
Letter fold	Max. 3 sheets
Letter fold capacity	Max. 30 sheets; unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max. 100 booklets; unlimited (without tray)
Copy/print volume (monthly)	Max. ¹ 175,000 pages
Toner lifetime	Black up to 28,000 pages
	CMY up to 28,000 pages

Imaging unit lifetime	Black up to 225,000/1,000,000 pages (drum/developer)
	CMY up to 105,000/1,000,000 pages (drum/developer)
Power consumption	110–120 V / 50/60 Hz; Less than 1.50 kW
System dimension (W x D x H)	24.2" x 27" x 31" (without options)
System weight	Approx. 187 lbs. (without options)

PRINTER SPECIFICATIONS (STANDARD)

Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Print Speed letter (mono/color)	Up to 36/36 ppm
Page description language	PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
Operating System	Windows 7 (32/64); Windows 8/8.1 (32/64); Windows 10 (32/64);
	Windows Server 2008 (32/64); Windows Server 2008 R2;
	Windows Server 2012; Windows Server 2012 R2;
	Windows Server 2016; Windows Server 2019;
	Macintosh OS X 10.10 or later; Unix; Linux; Citrix
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	AirPrint (iOS); Mopria (Android);
	Konica Minolta Mobile Print (iOS/Android/Windows 10 Mobile);
	Mobile Authentication and Pairing (iOS/Android)
	Optional: Google Cloud Print; WiFi Direct

PRINTER SPECIFICATIONS (OPTIONAL)

Print controller	Embedded Fiery IC-420
Controller CPU	AMD GX-424CC @ 2.4 GHz
Memory/HDD	2 GB / 500 GB
Page description language	Adobe PostScript 3 (CPSI 3020); PCL 6; PCL 5c

SCANNER SPECIFICATIONS Scan speed (mono/color) Up to 100/100 ipm in simplex Up to 200/200 ipm in duplex Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home); Scan modes Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; Scan-to-URL: TWAIN scan File formats JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; Compact XPS; PPTX Optional: Searchable PDF; PDF/A 1a and 1b; Searchable DOCX/PPTX/XLSX Scan destinations 2,100 (single + group); LDAP support

COPIER SPECIFICATIONS

COLIEK SLECILICATIONS	
Imaging technology	Laser
Toner technology	Simitri® HD polymerized toner
Copy/print speed letter (mono/color)	Up to 36/36 ppm
Copy/print speed 11"x17"	Up to 18/18 ppm
(mono/color)	
Autoduplex Speed letter (mono/color)	Up to 36/36 ppm
1st copy out time letter	4.6/6.1 sec.
Warm-up time	Approx. 12 sec. in mono; 13 sec. in color ²
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-9,999
Original format	3.5" x 8.5" to 11" x 17"; Custom sizes
Magnification	25–400% in 0.1% steps; Auto-zooming

FAX SPECIFICATIONS		
Fax standard	Super G3 (optional)	
Fax transmission	Analog; i-Fax; Color i-Fax; IP-Fax	
Fax resolution	Up to 600 x 600 dpi	
Fax compression	MH; MR; MMR; JBIG	
Fax modem	Up to 33.6 Kbps	
Fax destinations	2,100 (single + group)	

USER BOX SPECIFICATIONS

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication);
	Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling
SYSTEM FEATURES	
Security Functions (standard)	ISO 15408 HCD-PP Common Criteria (in evalutation); IP filtering
	and port blocking; SSL2; SSL3 and TLS1.0/1.1/1.2/1.3 network
	communication; IPsec support; IEEE 802.1x support;
	User authentication; Authentication log; Secure print; Kerberos;
	Solid state drive overwrite (8 standard types); SSD data
	encryption (AES 256); Memory data auto deletion; Confidential
	fax receipt; Print user data encryption
Security Functions (optional)	Antivirus realtime scanning (Bitdefender®);
	Copy protection (Copy Guard, Password Copy)
Accounting (standard)	Up to 1,000 user accounts; Active Directory support (user name +
	password + e-mail + smb folder); User function access definition
Accounting Functions (optional)	Biometric authentication (finger vein scanner);
	ID card authentication (ID card reader);
	Authentication by mobile device (Android/iOS)
Software	Net Care Device Manager; Data Administrator; Box Operator;
	Web Connection; Print Status Notifier; Driver Packaging Utility;
	Log Management Utility

¹ Maximum monthly copy/print volume supported under standard vendor supplied service. Defines the upper end of the expected customer volume for the device. Customers should consider multiple machines if average monthly volume approaches duty cycle on a continual basis.

- All specifications refer to letter-size paper of 80 gsm weight.
- The support and availability of the listed specifications and functionalities varies depending on operating
- systems, applications and network protocols as well as network and system configurations.

 The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (6% coverage of letter). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.

 Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

PARTNERSHIP.

Konica Minolta can help give shape to your ideas and partner with you to achieve your corporate objectives. Contact us to realize opportunities in:

INFORMATION MANAGEMENT	IT SERVICES	TECHNOLOGY
Enterprise Content Management (ECM)	Application Services	Office Multifunction Business Solutions
Document Management	Cloud Services	Commercial and Production Printers
Automated Workflow Solutions	IT Security	Industrial Printers
Business Process Automation	Managed IT Services	Wide Format Printers
Security and Compliance	IT Consulting & Projects	3D Printers
Mobility	Apple Managed Services	Scanners
eDiscovery Services	Managed Voice Services	Security Surveillance Systems
	Technology Implementation and Deployment	Laptops, Desktops and Computer Hardware
		Servers and Networking Equipment
		Managed Print Services (MPS)
		Managed Enterprise Services

For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com



























KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com









² Warm-up time may vary depending on the operating environment and usage.





Color A3 multifunctional





CUSTOMER BENEFITS



Intuitive operability

Operate the bizhub like a smartphone or tablet with fully customised user interface



Mobile connectivity

Print anytime from anywhere with Konica Minolta's innovative mobile technologies



Security

Secure network integration, data encryption, and advanced user authentication



Application ecosystem

Enhanced efficiency thanks to Konica Minolta's extensive applications portfolio



Productivity


Reliability, high-speed scanning and printing, combined with powerful finishing functions



Sustainability

Numerous eco features reduce energy consumption and costs

OPTIONS




Document converter pack LK-110v2

ThinPrint® client LK-111

Antivirus LK-116

IP fax (T.38 fax) LK-117











above it





Inner finisher FS-533 Attachment kit Punch kit for FS-533 PK-519 **Staple finisher** FS-539 Relay unit Punch kit for FS-539/SD

Staple finisher FS-540 Relay unit RU-513 Booklet finisher FS-540SD Punch kit for FS-540/SD PK-526 Post inserter for FS-540/SD PI-507

Job separator for FS-540/SD OR JS-602

Z-fold unit for FS-540/SD ZU-609

FINISHING FUNCTIONALITIES



































Banner printing

Corner stapling

Two-hole punching

Three-hole punching

Duplex

Combined mixplex/

Half-fold

Sheet insertion

Tri-fold

Booklet

Offset sorting

Z-fold

Corner stapling

DESCRIPTION

ENHANCED FEATURES	
LK-102v3 PDF enhancements	PDF/A(1b), PDF encryption, digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document	Generates various file formats including
file conversion	DOCX, XLSX and PDF/A
LK-111 ThinPrint client	Print data compression for reduced network impact
LK-116 Antivirus	Bitdefender® antivirus provides real time scanning of all incoming and outgoing data
LK-117 IP fax (T.38 fax)	Fax over IP networks (T.38), requires fax kit
CONNECTIVITY	
FK-514 Fax board	Super G3 fax, digital fax functionality
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection, Bluetooth
IC-420 Fiery controller	Professional color print controller
VI-516 Interface kit for IC-420	Fiery controller interface card
UK-115 Mount kit	Fiery controller mount kit
AU-102 Biometric authentication	Finger vein scanner
AU-205H ID card reader	Supports various ID card technologies
MK-735 Mount kit	Installation kit for ID card reader
OTHERS	
WT-506 Working table	Authentication device placement
KP-102 10-Key pad	For numeric entry instead of touchscreen
SC-509 Security kit	Copy guard function
EM-908 SSD	1 TB SSD to increase storage space
KH-102 Keyboard holder	To place USB keyboard
External keyboard	Keyboard for alpha numeric data entry

MEDIA INPUT	
PC-116 1x Universal tray	500 sheets / 5.5" x 8.5" - 11" x 17" / 52-256 g/m ²
PC-216 2x Universal tray	2x500 sheets / 5.5 " x 8.5 " – 11 " x 17 " / 52 – 256 g/m²
PC-416 Large capacity tray	2,500 sheets / 8.5" x 11" / 52–256 g/m²
PC-417 Large capacity tray	1,500 + 1,000 sheets / 5.5" x 8.5" or 8.5" x 11" /
	52-256 g/m ²
LU-302 Large capacity tray	$3,000 \text{sheets} / 8.5$ " x 11 " $/ 52 - 256 \text{g/m}^2$
LU-207 Large capacity tray	$2,500 \text{sheets} / 8.5 \text{" x } 11 \text{"} - 12 \text{" x } 18 \text{"} / 52 256 \text{g/m}^2$
MK-730 Banner tray	Multipage banner feeding
DK-516 Copier desk	Provides storage space for print media and
	other materials
MEDIA OUTPUT	
OT-513 Output tray	Output tray used instead of finisher
JS-508 Job separator	Separation of fax output; etc.
FS-533 Inner finisher	50-sheet stapling, 500 sheets max. output
MK-607 Attachment kit	For FS-533 installation
PK-519 Punch kit for FS-533	2/4 hole punching, auto switching
FS-539 Staple finisher	50-sheet stapling / 3,200 sheets max. output
FS-539SD Booklet finisher	50-sheet stapling / 20-sheet booklet finisher /
	2,200 sheets max. output
PK-524 Punch kit for FS-539/SD	2/3 hole punching, auto switching
	=, o note partorning, date officering
FS-540 Staple finisher	100-sheet stapling / 3,200 sheets max. output

FS-540SD Booklet finisher

RU-513 Relay unit

PK-526 Punch kit for FS-540/SD

JS-602 Job separator for FS-540/SD

PI-507 Post inserter for FS-540/SD

ZU-609 Z-fold unit for FS-540/SD

100-sheet stapling / 20-sheet booklet finisher /

2,700 sheets max. output

Separation of fax output, etc.

Cover insertion, post finishing

Z-fold for 11" x 17" prints

2/3 hole punching, auto switching
For FS-539/SD or FS-540/SD installation

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS

01012111012011101110110	
System speed 8.5" x11"	Up to 45/45 ppm (mono/color)
System speed 11" x 17"	Up to 22/22 ppm (mono/color)
Auto duplex speed 8.5" x 11"	Up to 45/45 ppm (mono/color)
1st page out time 8.5" x 11"	3.8/5.0 sec. (mono/color)
Warm-up time	Approx. 15/17 sec. (mono/color) ¹
Imaging technology	Laser
Toner technology	Simitri® HD polymerized toner
Panel size/resolution	10.1" / 1,024 x 600
System memory	8 GB (standard/max.)
System hard drive	256 GB SSD (standard) / 1 TB SSD (optional)
Interface	10/100/1,000-Base-T Ethernet, USB 2.0, Wi-Fi 802.11 b/g/n/ac (optional)
Network protocols	TCP/IP (IPv4 / IPv6) / SMB / LPD / IPP / SNMP / HTTP(S) / Bonjour
Automatic document feeder	Up to 300 originals / 5.5" x 8.5" – 11" x 17" / 35–210 g/m² / Dualscan ADF
ADF double feed detection	Standard
Printable paper size	3.5" x 5.5" – 12" x 18" / customized paper sizes / banner paper max.47.2" x 11.7"
Printable paper weight	52-300 g/m ²
Paper input capacity	1,150 sheets / 6,650 sheets (standard/max.)
Paper tray input (standard)	1 x 500 / 3.5" x 5.8" – 11" x 17" / custom sizes / 52–256 g/m ² 1 x 500 / 5.5" x 8.5" – 12" x 18" / custom sizes / 52–256 g/m ²
Paper tray input (optional)	1 x 500 / 5.5" x 8.5" – 11" x 17" / 52–256 g/m ² 2 x 500 / 5.5" x 8.5" – 11" x 17"/ 52–256 g/m ² 1 x 2,500 / 8.5" x 11" /52–256 g/m ² 1 x 1,500 + 1 x 1,000 sheets / 5.5" x 8.5" or 8.5" x 11" /

 $52-256 \, g/m^2$

Large capacity tray (optional)	1 x 3,000 / 8.5" x 11" / 52-256 g/m ²
	1 x 2,500/ 8.5" x 11" – 12" x 18" / custom sizes /
	52–256 g/m ²
Manual bypass	150 sheets / 3.5" x 5.5" – 12" x 18" / custom sizes /
	banner / 60–300 g/m²
Finishing modes (optional)	Offset, Group, Sort, Staple, Staple (offline), Punch,
	Half-fold, Letter-fold, Booklet, Post insertion, Z-fold
Automatic duplexing	4.1" x 5.5" – 12" x 18" / 52–256 g/m²
Output capacity	Up to 250 sheets / up to 3,300 sheets (standard/max.)
Stapling	Max. 100 sheets or 98 sheets + 2 cover sheets
	(up to 300 g/m²)
Stapling output capacity	Max. 200 sets
Letter fold	Max. 3 sheets
Letter fold capacity	Max. 50 sets, unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet
	(up to 300 g/m^2)
Booklet output capacity	Max. 35 booklets, unlimited (without tray)
Duty cycle (monthly)	Max. ² 200,000 pages
Toner lifetime	Black up to 28,000 pages
	CMY up to 28,000 pages
Imaging unit lifetime	Black up to 240,000/1,000,000 pages (drum/developer)
	CMY up to 165,000/1,000,000 pages (drum/developer)
Power consumption	110-120 V / 60 Hz, Less than 1.6 kW
System dimension (W x D x H)	24.2" x 27.1" x 37.8" (without options)
System weight	Approx. 220 lb (without options)

PRINTER SPECIFICATIONS

Print resolution	1,800 (equivalent) x 600 dpi, 1,200 x 1,200 dpi
Page description language	PCL 6 (XL3.0), PCL 5c, PostScript 3 (CPSI 3016), XPS
Operating systems	Windows 7 (32/64), Windows 8.1 (32/64), Windows 10 (32/64), Windows Server 2008 (32/64), Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Macintosh OS X 10.10 or later, Unix, Linux, Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3 Emulation Latin
Mobile printing	AirPrint (iOS), Mopria (Android), Konica Minolta Print Service (Android), Konica Minolta Mobile Print (iOS/Android) Optional: Google Cloud Print, Wi-Fi Direct

PRINTER SPECIFICATIONS (OPTIONAL)

Print controller	Embedded Fiery IC-420
Controller CPU	AMD GX-424CC @ 2.4 GHz
Memory/HDD	4 GB / 500 GB
Page description language	Adobe PostScript 3 (CPSI 3020), PCL 6, PCL 5c
Operating systems	Windows 7 (32/64), Windows 8.1 (32/64), Windows 10 (32/64), Windows Server 2008 (32/64), Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Macintosh OS X 10.10 or later, Linux

SCANNER SPECIFICATIONS

Scan speed	Up to 140/140 ipm in simplex (mono/color)
	Up to 280/280 ipm in duplex (mono/color)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me), Scan-to-SMB (Scan-to- Home), Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan- to-WebDAV, Scan-to-DPWS, Scan-to-URL, TWAIN scan
File formats	JPEG, TIFF, PDF, Compact PDF, Encrypted PDF, XPS, Compact XPS, PPTX Optional: Searchable PDF, PDF/A 1a and 1b, Searchable DOCX/PPTX/XLSX
Scan destinations	2,000 destinations + 100 groups, LDAP support

COPIER SPECIFICATIONS

600 x 600 dpi
256 gradations
1-9,999
Max. 11" x 17"
25-400% in 0.1% steps, Auto zoom

FAX SPECIFICATIONS

Fax standard	Super G3 (optional)
Fax transmission	Analog, i-Fax, Color i-Fax, IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH, MR, MMR, JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,000 single + 100 groups

USER BOX SPECIFICATIONS

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public, Personal (with password or authentication), Group (with authentication)
Type of system boxes	Secure print, Encrypted PDF print, Fax receipt, Fax polling

SYSTEM FEATURES	
Security	ISO 15408 HCD-PP Common Criteria (in evaluation), IP filtering and port blocking, SSL3 and TLS1.0/1.1/1.2 network communication, IPsec support, IEEE 802.1x support, User authentication, Authentication log, Secure print, Kerberos, Hard drive data encryption (AES 256), Confidential fax, Print user data encryption Optional: Antivirus scanning (Bitdefender*), Copy protection (Copy Guard, Password Copy)
Accounting	Up to 1,000 user accounts, Active Directory support (user name + password + e-mail + smb folder), User function access definition, Authentication by mobile device (Android) Optional: Biometric authentication (finger vein scanner) ID card authentication (ID card reader), Authentication by mobile device (iOS)
Software	Net Care Device Manager, Data Administrator, Box Operator, Web Connection, Print Status Notifier, Driver Packaging Utility, Log Management Utility

- $^{\rm 1}$ Warm-up time may vary depending on the operating environment and usage.
- ² Maximum monthly copy/print volume supported under standard vendor-supplied service defines the upper end of expected customer volume for the device. Customers should consider multiple machines if average $monthly\ volume\ approaches\ duty\ cycle\ on\ a\ continual\ basis.$
- All specifications refer to 8.5" x 11" paper of 80 g/m² weight.
- The support and availability of the listed specifications and functionalities vary depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of 8.5" x 11"). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.























For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC.




KONICA MINOLTA





CountOnKonicaMinolta.com





Color A3 multifunctional





CUSTOMER BENEFITS



Intuitive operability

Operate the bizhub like a smartphone or tablet with fully customised user interface



Mobile connectivity

Print anytime from anywhere with Konica Minolta's innovative mobile technologies



Security

Secure network integration, data encryption, and advanced user authentication



Application ecosystem

Enhanced efficiency thanks to Konica Minolta's extensive applications portfolio



Productivity


Reliability, high-speed scanning and printing, combined with powerful finishing functions



Sustainability


Numerous eco features reduce energy consumption and costs

OPTIONS



ThinPrint® client LK-111 Antivirus LK-116 **IP fax (T.38 fax)** LK-117








10-Key pad KP-102 Security kit


1 TB SSD EM-908

Keyboard holder

External keyboard

LEGEND Mandatory option Option This option can only be installed with the respective option above it





Inner finisher FS-533 Attachment kit MK-607 **Staple finisher** FS-539 Relay unit Booklet finisher Punch kit for FS-539/SD PK-524

Staple finisher FS-540 Relay unit Booklet finisher FS-540SD Punch kit for FS-540/SD PK-526 Post inserter for FS-540/SD Job separator for FS-540/SD

Z-fold unit for FS-540/SD

FINISHING FUNCTIONALITIES











Duplex























Corner stapling

Two-point stapling

Two-hole punching

Three-hole punching

Combined mixplex/

Half-fold

Sheet insertion

Tri-fold

Booklet

Offset sorting

Z-fold

Banner printing

DESCRIPTION

ENHANCED FEATURES	
IK-102v3 PDF enhancements	DDF/A/1h\ DDF energy tion digital signature
	PDF/A(1b), PDF encryption, digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document	Generates various file formats including
file conversion	DOCX, XLSX and PDF/A
LK-111 ThinPrint client	Print data compression for reduced network impact
LK-116 Antivirus	Bitdefender® antivirus provides real time scanning of all incoming and outgoing data
LK-117 IP fax (T.38 fax)	Fax over IP networks (T.38), requires fax kit
CONNECTIVITY	
FK-514 Fax board	Super G3 fax, digital fax functionality
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection, Bluetooth
IC-420 Fiery controller	Professional color print controller
VI-516 Interface kit for IC-420	Fiery controller interface card
AU-102 Biometric authentication	Finger vein scanner
AU-205H ID card reader	Supports various ID card technologies
MK-735 Mount kit	Installation kit for ID card reader
OTHERS	
WT-506 Working table	Authentication device placement
KP-102 10-Key pad	For numeric entry instead of touchscreen
SC-509 Security kit	Copy guard function
EM-908 SSD	1 TB SSD to increase storage space
KH-102 Keyboard holder	To place USB keyboard
External keyboard	Keyboard for alpha numeric data entry

MEDIA INPUT	
PC-116 1x Universal tray	500 sheets / 5.5" x 8.5" – 11" x 17" / 52–256 g/m²
PC-216 2x Universal tray	$2x500\text{sheets}/5.5$ " $x8.5$ " – 11 " $x17$ " $/52$ – 256g/m^2
PC-416 Large capacity tray	2,500 sheets / 8.5" x 11" / 52–256 g/m ²
PC-417 Large capacity tray	1,500 + 1,000 sheets / 5.5" x 8.5" or 8.5" x 11" / 52–256 g/m²
LU-302 Large capacity tray	$3,000 \text{sheets} / 8.5$ " x 11 " $/ 52$ – 256g/m^2
LU-207 Large capacity tray	2,500 sheets / 8.5" x 11" - 12" x 18" / 52-256 g/m ²
MK-730 Banner tray	Multipage banner feeding
DK-516 Copier desk	Provides storage space for print media and other materials
MEDIA OUTPUT	
OT-513 Output tray	Output tray used instead of finisher
JS-508 Job separator	Separation of fax output; etc.
FS-533 Inner finisher	50-sheet stapling, 500 sheets max. output
MK-607 Attachment kit	For FS-533 installation
PK-519 Punch kit for FS-533	2/4 hole punching, auto switching
FS-539 Staple finisher	50-sheet stapling / 3,200 sheets max. output
FS-539SD Booklet finisher	50-sheet stapling / 20-sheet booklet finisher / 2,200 sheets max. output
PK-524 Punch kit for FS-539/SD	2/3 hole punching, auto switching
FS-540 Staple finisher	100-sheet stapling / 3,200 sheets max. output
FS-540SD Booklet finisher	100-sheet stapling / 20-sheet booklet finisher / 2,700 sheets max. output
PK-526 Punch kit for FS-540/SD	2/3 hole punching, auto switching
RU-513 Relay unit	For FS-539/SD or FS-540/SD installation
JS-602 Job separator for FS-540/SD	Separation of fax output, etc.

Z-fold for 11" x 17" prints

PI-507 Post inserter for FS-540/SD Cover insertion, post finishing

ZU-609 Z-fold unit for FS-540/SD

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS

System speed 8.5" x11"	Up to 55/55 ppm (mono/color)
System speed 11" x 17"	Up to 27/27 ppm (mono/color)
Auto duplex speed 8.5" x 11"	Up to 55/55 ppm (mono/color)
1st page out time 8.5" x 11"	3.3/4.3 sec. (mono/color)
Warm-up time	Approx. 14/16 sec. (mono/color) ¹
Imaging technology	Laser
Toner technology	Simitri® HD polymerized toner
Panel size/resolution	10.1" / 1,024 x 600
System memory	8 GB (standard/max.)
System hard drive	256 GB SSD (standard) / 1 TB SSD (optional)
Interface	10/100/1,000-Base-T Ethernet, USB 2.0, Wi-Fi 802.11 b/g/n/ac (optional)
Network protocols	TCP/IP (IPv4 / IPv6) / SMB / LPD / IPP / SNMP / HTTP(S) / Bonjour
Automatic document feeder	Up to 300 originals / 5.5" x 8.5" – 11" x 17" / 35–210 g/m² / Dualscan ADF
ADF double feed detection	Standard
Printable paper size	3.5" x 5.5" – 12" x 18" / customized paper sizes / banner paper max. 47.2" x 11.7"
Printable paper weight	52-300 g/m ²
Paper input capacity	1,150 sheets / 6,650 sheets (standard/max.)
Paper tray input (standard)	1 x 500 / 3.5" x 5.8" – 11" x 17" / custom sizes / 52–256 g/m ² 1 x 500 / 5.5" x 8.5" – 12" x 18" / custom sizes / 52–256 g/m ²
Paper tray input (optional)	1 x 500 / 5.5" x 8.5" – 11" x 17" / 52–256 g/m ² 2 x 500 / 5.5" x 8.5" – 11" x 17"/52–256 g/m ² 1 x 2,500 / 8.5" x 11" /52–256 g/m ² 1 x 1,500 + 1 x 1,000 sheets / 5.5" x 8.5" or 8.5" x 11" /
	FO OFC / 3

 $52-256 \, g/m^2$

Large capacity tray (optional)	1 x 3,000 / 8.5" x 11" / 52-256 g/m ²
	1 x 2,500/ 8.5" x 11" - 12" x 18" / custom sizes /
	52-256 g/m ²
Manual bypass	150 sheets / 3.5" x 5.5" – 12" x 18" / custom sizes /
	banner / 60–300 g/m²
Finishing modes (optional)	Offset, Group, Sort, Staple, Staple (offline), Punch,
	Half-fold, Letter-fold, Booklet, Post insertion, Z-fold
Automatic duplexing	4.1" x 5.5" - 12" x 18" / 52-256 g/m ²
Output capacity	Up to 250 sheets / up to 3,300 sheets (standard/max.)
Stapling	Max. 100 sheets or 98 sheets + 2 cover sheets
	(up to 300 g/m^2)
Stapling output capacity	Max. 200 sets
Letter fold	Max. 3 sheets
Letter fold capacity	Max. 50 sets, unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet
	(up to 300 g/m^2)
Booklet output capacity	Max. 35 booklets, unlimited (without tray)
Duty cycle (monthly)	Max. ² 200,000 pages
Toner lifetime	Black up to 28,000 pages
	CMY up to 28,000 pages
Imaging unit lifetime	Black up to 240,000/1,000,000 pages (drum/developer)
	CMY up to 165,000/1,000,000 pages (drum/developer)
Power consumption	110-120 V / 60 Hz, Less than 1.6 kW
System dimension (W x D x H)	24.2" x 27.1" x 37.8" (without options)
System weight	Approx. 220 lb (without options)

PRINTER SPECIFICATIONS

Print resolution	1,800 (equivalent) x 600 dpi, 1,200 x 1,200 dpi
Page description language	PCL 6 (XL3.0), PCL 5c, PostScript 3 (CPSI 3016), XPS
Operating systems	Windows 7 (32/64), Windows 8.1 (32/64), Windows 10 (32/64), Windows Server 2008 (32/64), Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Macintosh OS X 10.10 or later, Unix, Linux, Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3 Emulation Latin
Mobile printing	AirPrint (iOS), Mopria (Android), Konica Minolta Print Service (Android), Konica Minolta Mobile Print (iOS/Android) Optional: Google Cloud Print, Wi-Fi Direct

PRINTER SPECIFICATIONS (OPTIONAL)

	,
Print controller	Embedded Fiery IC-420
Controller CPU	AMD GX-424CC @ 2.4 GHz
Memory/HDD	4 GB / 500 GB
Page description language	Adobe PostScript 3 (CPSI 3020), PCL 6, PCL 5c
Operating systems	Windows 7 (32/64), Windows 8.1 (32/64), Windows 10 (32/64), Windows Server 2008 (32/64), Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Macintosh OS X 10.10 or later, Linux

SCANNER SPECIFICATIONS

Scan speed	Up to 140/140 ipm in simplex (mono/color) Up to 280/280 ipm in duplex (mono/color)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me), Scan-to-SMB (Scan-to- Home), Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan- to-WebDAV, Scan-to-DPWS, Scan-to-URL, TWAIN scan
File formats	JPEG, TIFF, PDF, Compact PDF, Encrypted PDF, XPS, Compact XPS, PPTX Optional: Searchable PDF, PDF/A 1a and 1b, Searchable DOCX/PPTX/XLSX
Scan destinations	2,000 destinations + 100 groups, LDAP support

COPIER SPECIFICATIONS

	* **
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-9,999
Original format	Max. 11" x 17"
Magnification	25–400% in 0.1% steps, Auto zoom

FAX SPECIFICATIONS

Fax standard	Super G3 (optional)
Fax transmission	Analog, i-Fax, Color i-Fax, IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH, MR, MMR, JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,000 single + 100 groups

USER BOX SPECIFICATIONS

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public, Personal (with password or authentication), Group (with authentication)
Type of system boxes	Secure print, Encrypted PDF print, Fax receipt, Fax polling

SYSTEM FEATURES	
Security	ISO 15408 HCD-PP Common Criteria (in evaluation), IP filtering and port blocking, SSL3 and TLS1.0/1.1/1.2 network communication, IPsec support, IEEE 802.1x support, User authentication, Authentication log, Secure print, Kerberos, Hard drive data encryption (AES 256), Confidential fax, Print user data encryption Optional: Antivirus scanning (Bitdefender®), Copy protection (Copy Guard, Password Copy)
Accounting	Up to 1,000 user accounts, Active Directory support (user name + password + e-mail + smb folder), User function access definition, Authentication by mobile device (Android) Optional: Biometric authentication (finger vein scanner) ID card authentication (ID card reader), Authentication by mobile device (iOS)
Software	Net Care Device Manager, Data Administrator, Box Operator, Web Connection, Print Status Notifier, Driver Packaging Utility, Log Management Utility

- $^{\rm 1}$ Warm-up time may vary depending on the operating environment and usage.
- ² Maximum monthly copy/print volume supported under standard vendor-supplied service defines the upper end of expected customer volume for the device. Customers should consider multiple machines if average $monthly\ volume\ approaches\ duty\ cycle\ on\ a\ continual\ basis.$
- All specifications refer to 8.5" x 11" paper of 80 g/m² weight.
- The support and availability of the listed specifications and functionalities vary depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of 8.5" x 11"). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.

















described here may not be available on some products. Design & specifications are subject to change without notice.







For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2020 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo and bizhub are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com









TECHNOLOGY



COLOR HIGH-VOLUME MULTIFUNCTION PRINTER

Up to 65 ppm print/copy output to keep pace with rising demands
Standard dual scanning handles up to 240 originals per minute
High capacity 300-sheet document feeder
Large 10.1" color display with quick tablet-like touchscreen interface
Scan-to-email and FTP, scan-to-me, scan-to-home convenience
Built-in Emperon® print system, universal printer drivers
Simitri® HD polymerized toner for high-resolution imaging
Standard 250 GB HDD for on-board document storage
Web browser with 4 GB of memory
ISO 15408 and IEEE 2600.1 security standards

Power-saving design with quick recovery from sleep mode
6,650-Sheet maximum capacity, tab printing support, carbon-copy printing
Advanced authentication, secure print release, remote firmware updates
Multiple bypass tray and detachable paper feed trays improve paper handling
Finishing options for 80-page booklet-making, up to 100-sheet stapling
Options for 2/3-hole punch, tri-fold, z-fold, post-insertion and more
Downloadable apps to help you work faster and smarter
Multiple i-Options to suit the needs of your workflow
EPEAT Gold-certified, low power consumption to cut costs
Mobile printing support (AirPrint, Google Cloud Print Classic, NFC)

bizhub C659

COLOR HIGH-VOLUME MULTIFUNCTION PRINTER

Superior color, spectacular speed and simple touch-and-swipe operation make the bizhub C659 an ideal document solution for high-volume applications. Output speeds of 65 ppm plus duplex scanning at up to 240 opm keep work flowing — and you'll have powerful, scalable options to increase your productivity and help control your costs.

SYSTEM OVERVIEW

STOTEM STERVICE	
System memory	4 GB
System hard disk	250 GB Standard
Interface	10-BASE-T / 100-BASE-TX / 1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB v2, LPD, IPP, SNMP, HTTP
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Dual scan	Up to 300 originals / 5.5" x 8.5" to 11" x 17" / 35-210 gsm
document feeder	
Printable paper size	Scanning/Copying: up to 11" x 17"
	Printing: up to 11" x 17" full bleed on 12" x 18" paper
	Custom paper sizes
	Banner paper max.: 11.75" x 47.25"
Printable paper weight	52-300 gsm
Paper input capacity	Standard: 3,650 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 3	1,500 sheets / 5.5" x 8.5", 4" x 6" / 52-256 gsm
Tray 4	1,000 sheets / 5.5" x 8.5", 4" x 6" / 52-256 gsm
Large capacity tray	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm
LU-205 (optional)	
Large capacity tray	3,000 sheets / 8.5" x 11" / 52-256 gsm
LU-303 (optional)	
Manual bypass	150 sheets / 4" x 6" to 12" x 18" /
	custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, sort, staple, punch, half-fold, z-fold, tri-fold,
27	post-insertion, booklet
Output capacity	Max. with finisher: 3,300 sheets
19 10 10 19	Max. without finisher: 250 sheets
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheets (up to 209 gsm)
Stapling output capacity	Max.: 1,000 sheets
Tri-fold (optional)	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray)
Copy/print volume	Max.: 300,000 pages / month ¹
Toner lifetime	Black: 48,900 pages / CMY: 33,200 pages
Imaging unit lifetime	Black: 300,000 pages / 1,200,000 pages (Drum/Developer)
illiaging unit metime	
illiaging unit metime	CMY: 200,000 pages
Power consumption	
	CMY: 200,000 pages

COPIER SPECIFICATIONS

Electrostatic laser copy, tandem, indirect
Simitri® HD Polymerized Toner
B&W / Color: up to 65 / 65 ppm (Portrait)
B&W / Color: up to 33 / 33 ppm (Portrait)
B&W / Color: up to 65 / 65 ppm (Portrait)
B&W: 3.7 sec. / Color: 4.9 sec.
B&W: approx. 22 sec. ² / Color: 35 sec. ²
600 x 600 dpi
256 gradations
1-9,999
Up to 11" x 17"
25-400% in 0.1% steps, auto zooming
Electronic sorting, multi-job, adjustments (contrast, sharpness image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1

PRINTER SPECIFICATIONS (STANDARD)

	SH3 (STANDARD)
Print resolution	1,800 (equivalent) x 600 dpi, 1,200 x 1,200 dpi
PDL	PCL6 (XL 3.0), PCL5e/c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32 / x64): 7 / 8 / 10
	Windows Server (x32 / x64): 2008 / 2008 R23 / 20123 / 20163
	Macintosh OS X 10.8 or later
	Linux / Unix / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and
	OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy
	Set" job programming, overlay, watermark, copy protection,
	carbon copy print

PRINTER SPECIFICATIONS (OPTIONAL)

Print controller	Embedded Fiery IC-418 (VI-510 required)	
Memory/HDD	4 GB / 250 GB	
PDL	PostScript 3 (ver. 3019)	
	PCL 6/5c	
Operating systems	Windows (x32 / x64): 7 / 8 / 10	
	Macintosh OS X 10.7 or later	

SCANNER SPECIFICATION


Scan speed	B&W / Color: up to 240 ipm
Scan resolution	Max.: 600 x 600 dpi
Scan modes Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan- to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/ XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, real-time scan preview

FAX SPECIFICATIONS

Fax	Super G3 (optional)
Transmission	Analog, Internet fax, Color i-Fax, IP-Fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to Email/FTP/SMB, up to 400 job programs

USER BOX SPECIFICATIONS

Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public
	Personal (with password or authentication)
	Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation
User box functionality	Reprint, combination, download, sending (Email/FTP/SMB and
	fax), copy box-to-box



PARTNERSHIP

Konica Minolta can help give shape to your ideas and partner with you to achieve your corporate objectives. Contact us to realize opportunities in:

INFORMATION MANAGEMENT	IT SERVICES	TECHNOLOGY
Enterprise Content Management (ECM)	Application Services	Office Multifunction Business Solutions
Document Management	Cloud Services	Commercial and Production Printers
Automated Workflow Solutions	IT Security	3D Printers
Business Process Automation	Managed IT Services	Wide Format Printers
Security and Compliance	IT Consulting & Projects	Laptops, Desktops and
Mobility	Business Consulting Services	Computer Hardware
eDiscovery Services		Servers and Networking Equipment
,		Managed Print Services (MPS)
		Managed Enterprise Services







For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2017 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo and bizhub are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com







CVCTEM	FEATURES
SISIFIAI	LEWINKER

Security	ISO 15408 EAL34
occurre,	IEEE 2600 14
	IP filtering and port blocking
	SSL2, SSL3 and TSL1.0 network communication
	IPsec support
	IEEE 802.1x support
	FIPS 140-2
	User authentication
	Authentication log
	Secure print
	Hard disk overwrite (8 standard types)
	Hard disk data encryption (AES 128)
	Memory data auto deletion
	Confidential fax receipt
	Print user data encryption
	Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts
	Active Directory support
	(user name + password + Email + SMB folder)
	User function access definition
	Optional Biometric authentication (finger vein scanner)
	Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager
	PageScope Data Administrator
	PageScope Box Operator
	PageScope Direct Print
	Print Status Notifier
	Driver Packaging Utility
	Log Management Utility

Log Management Utility

Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.

Warm-up time may vary depending on the operating environment and usage.

Supports x64 orly.

4 Certification pending.

COMPONENTS AND OPTIONS

COMPONENTS AND OPT	IONS
AU-102 Biometric authentication	Finger vein scanner
AU-205H Universal ID card reader	Various ID card technologies
AU-211	Requires WT-506 Working Table
CAC/PIV solution*	
EK-610 USB I/F kit	USB keyboard connection
EK-611 USB I/F kit	USB keyboard connection, Bluetooth
FK-516 Fax board	Super G3 fax, digital fax functionality
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support (requires MK-742)
FS-536 Staple finisher	50-sheet stapling, 3,200 sheets max. output
FS-536SD	50-sheet staple finisher, 20-sheet booklet finisher,
Booklet finisher	2,500 sheets max. output
FS-537 Staple finisher	100-sheet stapling, 3,200 sheets max. output
FS-537SD	100-sheet stapling, 20-sheet booklet finisher,
Booklet finisher	2,500 sheets max. output
HD-524 Hard disk	Backup HDD
IC-418 Fiery image controller	Embedded image controller for graphics-intensive applications
JS-602 Job separator for FS-537	Separation for fax output, etc.
Keyboard	External keyboard (requires KH-102)
KH-102	To place USB keyboard
Keyboard holder	
KP-101 10-Key pad	For use instead of touchscreen
LK-102 v3	PDF/A, PDF encryption, digital signature
LK-104 v3	Provides voice guidance functions
LK-105 v4	Searchable PDF
LK-106	Supports native barcode printing

COMPONENTS AND OPTIONS (CONTINUED)

LK-107	Supports native Unicode printing
LK-108	Supports native OCR A and B font printing
LK-110 v2	Generates various file formats incl. DOCX, XLSX and
	combines LK-102 (encrypted PDF) + LK-105 (searchable PDF,
	OCR functionality)
LK-111	ThinPrint® Client data compression for
	reduced network impact
LU-205	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm
Large capacity unit	
LU-303	3,000 sheets / 8.5" x 11" / 52-256 gsm
Large capacity unit	
MK-715 Mount kit	Banner paper guide
MK-735 Mount kit	Installation kit for ID card reader
MK-742 Mount kit	Installation kit for FK-515 fax board
OT-508 Output tray	Output tray used instead of finisher
PI-507 Post inserter	Cover insertion, post finishing
for FS-537	
PK-520 Punch kit	2/3-hole punching, autoswitching
for FS-536	
PK-523 Punch kit	2/3-hole punching, autoswitching
for FS-537	
RU-515 Relay unit	Required for FS-537/FS-537SD and FS-536/FS-536SD
SC-508 Security kit	Copy Guard function (2x required)
SK-602 Staple kit	Added stapling functionality kit
SP-501 Stamp unit	Added fax stamp capability kit
UK-212 Wireless LAN	Wireless LAN to network connector
UK-501 Multi-feed	Detects multi-feeding in the document feeder
detection kit	Striptings outside and security of purpose and to the open or entitle and of the option because it
VI-510 Interface kit	Fiery controller interface card
for IC-418	
WT-506 Working table	Authentication device placement
WT-513 Upright	Required to mount the control panel in an upright position,
working table	can also be used to hold authentication devices
ZU-609 Z-fold unit	Z-fold for 11" x 17" prints
for FS-537	

for FS-537
* May not be available at time of launch.





bizhub c7501 Color A3 multifunctional









CUSTOMER BENEFITS



Intuitive operability
Operate the bizhub like a
smartphone or tablet with fully
customizable user interface



Mobile connectivity
Print anytime from anywhere
with Konica Minolta´s innovative mobile technologies



Security
Secure network integration,
data encryption, and advanced
user authentication



Application ecosystem Enhanced efficiency thanks to Konica Minolta's extensive applications portfolio



ProductivityReliability, high-speed scanning and printing, combined with powerful finishing functions



Sustainability Numerous eco features reduce energy consumption and costs

OPTIONS



PDF enhancements LK-102v3

OCR text recognition LK-105v4

Barcode fonts LK-106

Unicode fonts LK-107 OCR A and B fonts

LK-108

Document converter pack LK-110v2

ThinPrint® client LK-111 Antivirus LK-116

FOIP IP-Fax (T.38 Fax)*





3 OTHERS

Working table WT-506 Upright panel WT-519

10-Key pad KP-102

Security kit SC-509

1 TB SSD EM-908

Keyboard holder KH-102 External Keyboard

LEGEND

Mandatory option

Option

This option can only be installed with the respective option

above it

4 MEDIA INPUT

Large capacity tray LU-303

Large capacity tray LU-205

Banner tray MK-730

5 MEDIA OUTPUT

Output tray OT-514

Staple finisher
FS-539
Relay unit
RU-519
Booklet finisher
FS-539SD
Relay unit
RU-519

Punch kit for FS-539/SD PK-524 **Staple finisher** FS-540

Relay unit RU-519

Booklet finisher FS-540SD

FS-540SD Relay unit

Punch kit for FS-540/SD PK-526

Post inserter for FS-540/SD PI-507

Job separator for FS-540/SD JS-602 Z-fold unit for FS-540/SD ZU-609

*Not available at time of launch

FINISHING FUNCTIONALITIES































Corner stapling

Two-point stapling

Two-hole punching

Three-hole punching

Duplex

Combined mixplex/ mixmedia Half-fold

Sheet insertion

Tri-fold

Booklet

t Offset sorting

Offset Z-

Z-fold

Banner printing

ner Corner ting Stapling (offline)

DESCRIPTION

ENHANCED FEATURES	
LK-102v3 PDF enhancements	PDF/A(1b), PDF encryption, digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A $$
LK-111 ThinPrint® client	Print data compression for reduced network impact
LK-116 Antivirus	Bitdefender® antivirus provides real time scanning of all incom-
	ing and outgoing data
LK-117 FOIP activation	Fax over IP networks (T.38), requires fax kit
CONNECTIVITY	
FK-514 Fax board	Super G3 fax, digital fax functioality
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection; Bluetooth
IC-420 Fiery controller	Professional color print controller
VI-516 Interface kit for IC-420	Fiery controller interface card
AU-102 Biometric authentication	Finger vein scanner
AU-205H ID card reader	Various ID card technologies
MK-735 Mount kit	Installation kit for ID card reader
WIN-755 WOUTH KIL	ilistaliation kit for iD card reader

OTHERS	
WT-506 Working table	Authentication device placement
WT-519 Working table	Working table for upright panel
KP-102 10-Key pad	For numeric entry instead of touchscreen
SC-509 Security kit	Copy guard function
EM-908 1 TB SSD	1 TB SSD to increase storage space
KH-102 Keyboard holder	To place USB keyboard
External Keyboard	Keyboard for alpha numeric data entry
MEDIA INPUT	
LU-303 Large capacity tray	3,000 sheets, A4, 52–256 g/m ²
LU-205 Large capacity tray	2,500 sheets, A4–SRA3, 52–256 g/m ²
MK-730 Banner tray	Multipage banner feeding
	3
MEDIA QUITDUT	
MEDIA OUTPUT	
OT-514 Output tray	Output tray used instead of finisher
FS-539 Staple finisher	50-sheet stapling; 3,200 sheets max. output
FS-539SD Booklet finisher	50-sheet stapling; 20-sheet booklet finisher;
	2,200 sheets max. output
PK-524 Punch kit for FS-539/SD	2/3 hole punching; autoswitching
FS-540 Staple finisher	100-sheet stapling; 3,200 sheets max. output
FS-540SD Booklet finisher	100-sheet stapling; 20-sheet booklet finisher;
	2,700 sheets max. output
PK-526 Punch kit for FS-540/SD	2/3 hole punching; auto switching
RU-519 Relay unit	For FS-539/SD or FS-540/SD installation
PI-507 Post inserter for FS-540/SD	Cover insertion; post finishing
JS-602 Job separator for FS-540/SD	Separation of fax output; etc.

Z-fold for A3 prints

TECHNICAL SPECIFICATIONS

System speed letter	
System speed 11" x 17"	
Auto duplex speed letter	
1st page out time letter	

SYSTEM SPECIFICATIONS

System speed 11" x 17"	Up to 37/35 ppm (mono/color)
Auto duplex speed letter	Up to 75/70 ppm (mono/color)
1st page out time letter	2.8/3.8 sec. (mono/color)
Warm-up time	Approx. 17/18 sec. (mono/color) ¹
Imaging technology	Laser
Toner technology	Simitri® HD polymerized toner
Panel size/resolution	10.1" / 1024 x 600
System memory	8,192 MB (standard/max)
Solid state drive	256 GB SSD (standard) / 1 TB SSD (optional)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11 b/g/n/ac (optional)
Network protocols	TCP/IP (IPv4 / IPv6); SMB; LPD; IPP; SNMP; HTTP(S); Bonjour
Automatic document feeder	Up to 300 originals; A6–A3; 35–210 g/m²; Dualscan ADF
ADF double feed detection	Standard
Printable paper size	3.5" x 5.5" – 12" x 18"; custom paper sizes,
	banner paper max. 47.2" x 11.7"
Printable paper weight	52–300 g/m ²
Paper input capacity	3,650 sheets / 6,650 sheets (standard/max)
Paper tray input (standard)	1x 500; 3.5" x 5.5" – 11" x 17"; custom sizes; 52–256 g/m²
	1x 500; 5.5" x 8.5" – 12" x 18"; custom sizes; 52–256 g/m²
	1x 1,500; 5.5" x 8.5" – 11" x 17"; 52–256 g/m ²
	1x 1,000; 5.5" x 8.5" - 11" x 17"; 52-256 g/m ²
Large capacity tray (optional)	1x 3,000;5.5" x 8.5" – 11" x 17"; 52–256 g/m²
	1x 2,500; 8.5" x 11" – 12" x 18"; custom sizes; 52–256 g/m²
Manual bypass	150 sheets; 3.5" x 5.5" – 12" x 18"; custom sizes; banner; 60–300
	g/m²
Finishing modes (optional)	Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold;

Letter-fold; Booklet; Post insertion; Z-fold

Up to 75/70 ppm (mono/color)

SYSTEM SPECIFICATIONS

ZU-609 Z-fold unit for FS-540/SD

Automatic duplexing	3.5" x 5.5" – 12" x 18"; 52–256 g/m ²
Output capacity	Up to 200 sheets / up to 3,300 sheets (standard/max)
Stapling	Max. 100 sheets or 98 sheets + 2 cover sheets (up to 300 g/m²)
Stapling output capacity	Max. 200 sets
Letter fold	Max. 3 sheets
Letter fold capacity	Max. 50 sets; unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet (up to 300 g/m²)
Booklet output capacity	Max. 35 booklets; unlimited (without tray)
Duty cycle (monthly)	Max. ² 300,000 pages
Toner lifetime	Black up to 45,000 pages
	CMY up to 45,000 pages
Imaging unit lifetime	Black up to 240,000/1,000,000 pages (drum/developer)
	CMY up to 165,000/1,000,000 pages (drum/developer)
Power consumption	110-120V/ 50/60 Hz; Less than 2.10 kW
System dimension (W x D x H)	24.2" x 27.1" x 47.5" (without options)
System weight	Approx. 353 lbs. (without options)

PRINTER SPECIFICATIONS	
Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Page description language	PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
Operating systems	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64);
	Windows Server 2008 (32/64); Windows Server 2008 R2;
	Windows Server 2012; Windows Server 2012 R2;
	Windows Server 2016; Windows Server 2019; Macintosh OS X
	10.11 or later; Unix; Linux; Citrix
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin

bizhub C750i Datasheet

PRINTER SPECIFICATIONS

Mobile printing	AirPrint (iOS); Mopria (Android);	
	Konica Minolta Print Service (Android);	
	Konica Minolta Mobile Print (iOS/Android)	
	Optional: WiFi Direct	

PRINTER SPECIFICATIONS (OPTIONAL)

Print controller	Embedded Fiery IC-420	
Controller CPU	AMD GX-424CC @ 2.4 GHz	
Memory/HDD	4,096 MB / 500 GB	
Page description language	Adobe PostScript 3 (CPSI 3020); PCL 6; PCL 5c	
Operating systems	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64);	
	Windows Server 2008 (32/64); Windows Server 2008 R2;	
	Windows Server 2012; Windows Server 2012 R2;	
	Windows Server 2016; Windows Server 2019;	
	Macintosh OS X 10.11 or later; Linux	

SCANNER SPECIFICATIONS

SCAINTER ST ECH TCATTO	113
Scan speed	Up to 140/140 ipm in simplex (mono/color)
	Up to 280/280 ipm in duplex (mono/color)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);
	Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV;
	Scan-to-DPWS; Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF,Compact PDF; Encrypted PDF; XPS;
	Compact XPS; PPTX
	optional: Searchable PDF; PDF/A 1a and 1b;
	Searchable DOCX/PPTX/XLSX
Scan destinations	2,000 destinations + 100 groups; LDAP support

COPIER SPECIFICATIONS

Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1–9,999
Original format	Max. 11" x 17"
Magnification	25-400% in 0.1% steps; Auto-zoom

FAX SPECIFCIATION

THE ST EST SHATIST	
Fax standard	Super G3 (optional)
Fax transmission	Analog; i-Fax; Color i-Fax; IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2.000 single + 100 groups























For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

USER BOX SPECIFICATIONS

Storable documents

User boxes	Public; Personal (with password or authentication);	
	Group (with authentication)	
System boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling	
SYSTEM FEATURES		
Security	ISO 15408 HCD-PP Common Criteria (in evalutation);	
	IP filtering and port blocking;	
	SSL3 and TLS1.0/1.1/1.2 network communication; IPsec support;	
	IEEE 802.1x support; User authentication; Authentication log;	
	Secure print; Kerberos;	
	Data encryption (AES 256); Confidential fax;	
	Print user data encryption	
	Optional: Antivirus realtime scanning (Bitdefender®);	
	Copy protection (Copy Guard; Password Copy)	
Accounting	Up to 1,000 user accounts;	
	Active Directory support (user name + password + e-mail + smb folder);	
	User function access definition;	
	Authentication by mobile device (Android)	
	optional: Biometric authentication (finger vein scanner);	
	ID card authentication (ID card reader);	
	Authentication by mobile device (iOS)	
Software	Net Care Device Manager; Data Administrator; Box Operator;	
	Web Connection; Print Status Notifier; Driver Packaging Utility;	
	Log Management Utility	

Up to 3,000 documents or 10,000 pages

- All specifications refer to 8.5" x 11"-size paper of 80 g/m 2 quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a
 particular page size (5% coverage of 8.5" x 11"). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change
- Konica Minolta does not warrant that any specifications mentioned will be error-free.

 All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com









¹ Warm-up time may vary depending on the operating environment and usage

² If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed



Production Print Black & White Multifunction Devices



Giving Shape to Ideas



100 ppm print/copy output – up to 6,000 impressions per hour

2,250,000-Page monthly duty cycle meets high-volume demands

 1200×1200 dpi resolution with advanced LED technology for smooth halftones and sharp text Standard color dual scanning at up to 180 originals per minute

Built-in print controller, flexible scanning to Email, FTP, SMB, HDD, USB and TWAIN scanning Job ticket and page editing from 15" touch-screen display for easy on-board press control

Job Centro and Hot Folder capabilities for job management and workflow

9,000-Sheet maximum paper capacity for long unattended runs

Media sizes up to 12" x 18" and weights up to 350 gsm, duplex capability up to 300 gsm Reliable air-assisted paper-feeding for worry-free printing

All-in-one staple finisher with kits for saddle-stitching, hole-punching and post-insertion Simitri® HD toner with Biomass fuses at lower temperatures

Optional bypass tray and output tray

EPEAT Gold-certified

bizhub PRO 1100

MONOCHROME DIGITAL PRODUCTION PRINTER / COPIER / SCANNER

press





Des		

bizhub PRO 1100	The bizhub PRO 1100 delivers real value to any print production
Overview	environment - with high-speed 100 ppm B&W output, high paper and
	toner capacity, standard built-in print controller and compact footprint
	to save space on your production floor. Dedicated to central in-house
	printing facilities and external print-for-pay services - this device
	provides sturdy construction, high performance and numerous inline
	finishing options teamed up with advanced technology for enhanced
	B&W print quality. Be more productive with high-performance color
	scanning capability with dual scanning ADF in combination with the
	powerful print engine.

System specifications

Oyotom opoomounono	
Туре	Console
Resolution	1,200 x 1,200 dpi / 8-bit 256
Original type	Sheets, Books, Objects
Max. Original size	11" x 17"
Memory capacity	DIMM: 8 GB / HDD: 1TB
Paper size	Standard: 12" x 18", 11" x 17", 8.5" x 11", 8.5" x 14", 9" x 11",
	8" x 13", 5.5" x 8.5"
	Custom: 7.17" x 5.5" to 12.76 x 18.23", 8.5" x 11" tab paper
Image loss	Top edge: Max. 3 mm or less
	Right / Left / Bottom edge: Max. 2 mm or less
Warm-up time	390 sec. or less
First copy out time	3.4 sec. or less
Copy / print speed (Letter)	100 ppm
Copy magnification	Fixed same magnification: 1:1 ± 0.5% or less Scaling up: 1:1.154 / 1.224 / 1.414 / 2.000 Scaling down: 1:0.866 / 0.816 / 0.707 / 0.500 Preset: 3 types Zoom: 25 to 400% (in 0.1% increments)
Paper capacity	Standard: 1,500 sheets x 2 (80 gsm)
Paper weight	Standard: 40 to 300 gsm (Limitations to paper types apply) Option: 40 to 350 gsm (Only available for middle tray of PF-709)
Multiple copy	1 to 9,999 sheets
Power requirements	208 to 240 V, 60Hz, 16 A, Dedicated line
Max. Power	3.6 kW or less (Main unit + PF-709 + FS-532)
consumption	
Dimensions	Main unit + ADF: 39" x 35.75" x 45.75"
$(W) \times (D) \times (H)$	Including operation panel: 47.75" x 35.75" x 57.25"
Weight	749.5 lb (Main unit)
Space requirements $(W) \times (D)$	Main unit + FS-532 + LU-411: 103-3/4" x 81-1/4"

Printer specifications

Туре	Embedded
CPU	Pentium G3420 3.2 GHz
Memory	2 GB
HDD	1 TB 3.5 inch SATA
Print speed	100 ppm
Print resolution	1,200 x 1,200dpi, 600 x 600dpi
PDL	PCL5e/6, PostScript3 (3020), PDF Ver1.7, TIFF Ver. 6 Emulation, PPML (Ver2.2)
Protocol	TCP/IP (LPR, RAW socket), IPX/SPX (NDS, Bindery), NetBEUI, IPP, AppleTalk, WSD, Bonjour, SMB
Compatibility	PCL: Windows Vista* / 7* / 8* / 8.1* / Windows Server 2008* / 2008 R2 2012 / 2012 R2 PS: Windows Vista* / 7* / 8* / 8.1* Windows Server 2008* / 2008 R2 2012 / 2012 R2 / Mac 0S X: 10.6 / 10.7 / 10.8 / 10.9 / 10.10
Fonts	PCL: 80 fonts / PS: 136 fonts
Interface	10Base-T/100Base-TX/1000Base-T. USB 3.0 host. USB 2.0 device
IIIteriace	*Curports 20 bit (v2C) or C4 bit (vC4) on vironment

*Supports 32-bit (x86) or 64-bit (x64) environment.

Scanning specifications

Type	Full-Color Scanner
Scanning speed	Simplex: 90 opm (Color/B&W / Letter @ 400 dpi) Duplex: 180 opm
Scanning size	11" x 17"
Scanning resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi
Protocol	TCP/IP (FTP, SMB, SMTP, WebDAV) (IPv4/IPv6)
Compatibility	Windows Vista* / 7* / 8* / 8.1*
Interface	Ethernet 10Base-T/100Base-TX/1000Base-T
Output format	PDF, TIFF, Encrypted PDF, XPS, Compact PDF, JPEG

*Supports 32-bit (x86) or 64-bit (x64) environment.

Dual scan document feeder (standard)

Туре	Single pass simultaneous duplex system
Original size	11" x 17"
Paper weight	Simplex 35 to 210 gsm / Duplex 50 to 210 gsm
Paper capacity (80 gsm)	Max. 150 sheets
	24-1/4" x 22-3/4" x 5-1/2"
Weight	Approx. 39.75 lb


Options

Various IC card certification device
All-in-One 100-sheet staple finisher / 4,200 sheets max. output
8.5" x 11" GBC Multi-puncher (7 optional user replaceable dies)
8.5" x 11" In-line GBC ring binding unit
Up to 4,500 sheets / 8.5" x 11" / 40-300 gsm
Up to 4,000 sheets / 8.5" x 11" to 12" x 18" / 40-300 gsm
Up to 250 sheets / 5.5" x 8.5" to 12" x 18" / 40-300 gsm
Up to 150 sheets / 5.5" x 8.5" to 12" x 18" / 62-300 gsm
Up to 6,000-sheets total / 5.5" x 8.5" to 12" x 18" / 40-350 gsm
Cover insertion, post finishing for FS-532
2/3-hole punching, autoswitching for FS-532
Removable HDD Kit
Saddle-stitch/folding kit for FS-532 / 25-sheet booklets
with Half-fold and Tri-fold
Z-fold unit for for FS-532 / 11"x17" prints / 2/3-hole punching















TECHNOLOGY



AccurioPress 6136

MONOCHROME DIGITAL PRODUCTION PRESS / COPIER / SCANNER

136 ppm output for high-volume monochrome print production

Inline, closed loop quality management system

High-speed dual color scanning at 240 ipm

Job ticket and page editing from 15" touch-screen display for easy on-board press control Color Centro and Hot Folder capabilities for job management and workflow

True 1,200 x 1,200 dpi resolution with enhanced screening technologies for sharpness

Duty cycle 3,240,000 — accepts media up to 350 gsm

Reliable air-suction paper feed option for smooth paper feeding

Professional feeding of coated media and envelopes

18,000-sheet maximum paper capacity with options

Humidifier option removes static, reduces paper curl

Saddle-stitched booklets with three-side trim and square-fold

Produce 600-page perfect bound books and up to 100-sheet stapling

Envelope print support with optional fuser

Innovative GBC punch unit with interchangeable die sets

Built-in print controller with PCL, PostScript, TIFF and PDF

 $\mathsf{Simitri}^{\circ}\,\mathsf{HD}$ toner with $\mathsf{Biomass}$ to protect the environment

EPEAT Gold-certified — U.S. Energy Star compliant

MONOCHROME DIGITAL PRODUCTION PRESS / COPIER / SCANNER

The AccurioPress 6136 redefines the way you think about monochrome printing, delivering high-quality black and white prints in high-volume environments. Exceptional speed and versatility with 136 ppm print/copy output combined with an aggressive monthly duty cycle of over three million impressions, real-time automated density and registration adjustments to produce unmatched print quality.

SYSTEM SDECIEICATIONS

SYSTEM SPECIFICATIONS	·
Resolution	Print: 1,200 x 1,200 dpi
	Scan: 600 x 600 dpi
Paper weight	Standard: 40-300 gsm
	Opt.: PF-710, PF-709 (middle tray) – 40–350 gsm
Auto duplex	40-300 gsm
Paper sizes (max.)	324 x 463 mm (12.76" x 18.23")
	Opt.: PF-709 – 324 x 463 mm (12.76" x 18.23")
	PF-710 – 324 x 483 mm (12.76" x 19.02")
Paper sizes (min.)	182 x 139 mm (7.17" x 5.47")
	Opt.: PF-709 – 95 x 139 mm (3.74" x 5.47")
	PF-710 – 95 x 133 mm (3.74" x 5.24")
Image loss (max.)	3.0 mm or less for top edge
	2.0 mm or less for bottom edge
	2.0 mm or less for right/left edges
Warm-up time	420 seconds or less
Paper input capacity	Standard: 3,000 sheets
	Max.: 18,000 sheets
Main unit dimensions	39" x 35.8" x 57"
(W x D x H)	
Main unit weight	813.5 lbs
Power requirements	208VAC to 240VAC, 20A, 60 Hz

PRODUCTIVITY

8.5" x 11" (max. per minute)	136 ppm
Monthly duty cycle (max.)	3,240,000 pages

CONTROLLER

Туре	Embedded (network standard)
СРИ	Intel i5-4570S 2.9 GHz
Memory	16 GB
HDD/SSD	HDD: 1-TB x2, SSD: 4 GB
Print-description language	PCLSE/XL (PCL6), Adobe PostScript3 (PS3020),
	PDF v1.7, TIFF v6, PPML v2.2, APPE4.2 (with UK-217)
Printing method	TCP/IP (LPR, RAW socket), NetBEUI, IPP, WSD, Bonjour, SMB
Applicable OS	PCL, PS, PS Plug-in:
•	Windows 7*1/8.1*1/10*1
	Windows Server 2008/2008R2/2012/2012R2/2016
	Mac OS X 10.8/10.9/10.10/10.11/10.12
Interface	10/100/1000Base-T, USB3.0 host, USB2.0 device
*1 Including 64-bit versions.	



For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2018 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA and the KONICA MINOLTA logo are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.

SCANNER SPECIFICATIONS

Туре	Full color
Scan speed (8.5" x 11")	Single-sided 120 ipm/duplex 240 ipm
Scan resolution	600 x 600 dpi
Scan modes	Scan-to-HDD; Scan-to-FTP; Scan-to-SMB; Scan-to-Email;
	Scan-to-WebDAV; Scan-to-USB
Scan formats	TIFF, PDF, Encrypted PDF, PDF/A-1a, PDF/A-1b, Compact PDF,
	IPEG, XPS

COPIER SPECIFICATIONS

Gradations	256 gradations
First copy out ¹	2.7 seconds or less
Continuous print speed ²	136 pages/min (letter landscape)
Magnification	25–400% in 0.1% steps

When letter landscape original is scanned on the platen (zoom 100%, Tray-1).

OPTIONS

OF HONS	
CR-101	Creaser unit for SD-513
EF-105	Envelope fuser
FA-503	PFU adjustment kit
FD-503	Multi-fold punch unit
FD-504	Square folding unit
	for SD-513
FS-532	100-sheet staple finisher
FS-532 PK/SD	100-sheet staple finisher
	with PK and SD-510-522
Punch G2	GBC advanced
	multi-punching unit
GP-501	GBC multi-hole punch unit
GP-502	GBC in-line ring
	binding unit
HD-523	Inner HDD kit
HM-103	Humidification unit
	for RU-518
HT-506	Dehumidification heating
	unit for PF-710
IQ-501	Intelligent quality optimizer
LC-501	Cart for LS-506
LS-506	Stacking unit

MK-732	Post-inserter mount kit
	for FS-532
MK-737	Mount kit for
	third-party products
OT-510	Open stacker
PB-503	Perfect binder
PF-709	Friction paper feed unit
	w/air assist
PP-701	Pre-printed paper kit
	for PF-709
PF-710	Vacuum paper feed unit
PI-502	Post inserter for FS-532
PK-522	2/3-hole punch for FS-532
RH-101	Removable HDD kit
RU-510	Relay unit for GP-501
RU-518	Relay unit for de-curling
SD-506	Booklet making unit
SD-510	Saddle stitch kit for FS-532
SD-513	Saddle stitch unit
SD-513/F	Saddle stitcher front
TU-503	Trimmer unit for SD-513



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446





² Print speed may vary depending on paper type.



TECHNOLOGY



AccurioPress 6136P

MONOCHROME DIGITAL PRODUCTION PRESS

136 ppm output for high-volume monochrome print production

Inline, closed loop quality management system

Job ticket and page editing from 15" touch-screen display for easy on-board press control Color Centro and Hot Folder capabilities for job management and workflow

True 1,200 x 1,200 dpi resolution with enhanced screening technologies for sharpness

Duty cycle 3,240,000 — accepts media up to 350 gsm

Reliable air-suction paper feed option for smooth paper feeding

Professional feeding of coated media and envelopes

18,000-sheet maximum paper capacity with options

Humidifier option removes static, reduces paper curl

Saddle-stitched booklets with three-side trim and square-fold

Produce 600-page perfect bound books and up to 100-sheet stapling

Envelope print support with optional fuser

Innovative GBC punch unit with interchangeable die sets

Built-in print controller with PCL, PostScript, TIFF and PDF

Simitri® HD toner with Biomass to protect the environment

EPEAT Gold-certified — U.S. Energy Star compliant

AccurioPress 6136P

MONOCHROME DIGITAL PRODUCTION PRESS

The AccurioPress 6136P means business with up to 136 ppm print output, a monthly duty cycle of over three million impressions and up to 18,000 sheet capacity. With real-time automated density and registration adjustments and powerful multiple inline finishing options, it gives you all the tools you need to grow your business.

SYSTEM SPECIFICATIONS

Resolution	Print : 1,200 x 1,200 dpi
Paper weight	Standard: 40–300 gsm Opt.: PF-710, PF-709 (middle tray) – 40–350 gsm
Auto duplex	40-300 gsm
Paper sizes (max.)	324 x 463 mm (12.76" x 18.23") Opt.: PF-709 – 324 x 463 mm (12.76" x 18.23") PF-710 – 324 x 483 mm (12.76" x 19.02")
Paper sizes (min.)	182 x 139 mm (7.17" x 5.47") Opt.: PF-709 – 95 x 139 mm (3.74" x 5.47") PF-710 – 95 x 133 mm (3.74" x 5.24")
Image loss (max.)	3.0 mm or less for top edge 2.0 mm or less for bottom edge 2.0 mm or less for right/left edges
Warm-up time	420 seconds or less
Paper input capacity	Standard: 3,000 sheets Max.: 18,000 sheets
Main unit dimensions (W x D x H)	39" x 35.8" x 57"
Main unit weight	761 lbs
Power requirements	208VAC to 240VAC, 20A, 60 Hz

PRODUCTIVITY

8.5" x 11" (max. per minute)	136 ppm
Monthly duty cycle (max.)	3,240,000 pages

CONTROLLER

Embedded (network standard)
Intel i5-4570S 2.9 GHz
16 GB
HDD: 1-TB x2, SSD: 4 GB
PCLSE/XL (PCL6), Adobe PostScript3 (PS3020), PDF v1.7, TIFF v6, PPML v2.2, APPE4.2 (with UK-217)
TCP/IP (LPR, RAW socket), NetBEUI, IPP, WSD, Bonjour, SMB
PCL, PS, PS Plug-in: Windows 7*1/8.1*1/10*1 Windows Server 2008/2008R2/2012/2012R2/2016 Mac OS X 10.8 /10.9/10.10/10.11/10.12
10/100/1000Base-T, USB3.0 host, USB2.0 device

^{*1} Including 64-bit versions.



OI HONS	
CR-101	Creaser unit for SD-513
EF-105	Envelope fuser
FA-503	PFU adjustment kit
FD-503	Multi-fold punch unit
FD-504	Square folding unit
	for SD-513
FS-532	100-sheet staple finisher
FS-532 PK/SD	100-sheet staple finisher
	with PK and SD-510-522
Punch G2	GBC advanced
	multi-punching unit
GP-501	GBC multi-hole punch unit
GP-502	GBC in-line ring
	binding unit
HD-523	Inner HDD kit
HM-103	Humidification unit
	for RU-518
HT-506	Dehumidification heating
	unit for PF-710
IQ-501	Intelligent quality optimizer
LC-501	Cart for LS-506
LS-506	Stacking unit

MK-732	Post-inserter mount kit		
	for FS-532		
MK-737	Mount kit for		
	third-party products		
OT-510	Open stacker		
PB-503	Perfect binder		
PF-709	Friction paper feed unit		
	w/air assist		
PP-701	Pre-printed paper kit		
	for PF-709		
PF-710	Vacuum paper feed unit		
PI-502	Post inserter for FS-532		
PK-522	2/3-hole punch for FS-532		
RH-101	Removable HDD kit		
RU-510	Relay unit for GP-501		
RU-518	Relay unit for de-curling		
SD-506	Booklet making unit		
SD-510	Saddle stitch kit for FS-532		
SD-513	Saddle stitch unit		
SD-513/F	Saddle stitcher front		
TU-503	Trimmer unit for SD-513		





For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2018 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA and the KONICA MINOLTA logo are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446











DIZHUD PRESS 2250P MONOCHROME DIGITAL PRODUCTION PRESS



Descri	ntınne

bizhub PRESS 2250P	The bizhub® PRESS 2250P can be a game-changing digital solution
Overview	for high-volume B&W production demands – with dual print engines in
	a single space-saving configuration, duplex output up to 250 ppm, and
	pro-quality inline finishing options that include saddle-stitching, perfect
	binding, GBC binding and more.

System Specifications

Oystein Opcomoduons	
Controller	Embedded Konica Minolta controller
Resolution	1,200 x 1,200 dpi
Paper weight	40-350 gsm
Paper sizes	Min.: 95 x 139 mm Max.: 324 x 483 mm (with PF-703)
Maximum image area	314 x 483 mm (with PF-703)
Paper input capacity	Standard: 3,000 sheets Max.: 18,000 sheets
Paper output capacity	Max.: 15,000 sheets (plus sub trays)

Productivity

8.5" x 11"	Max. per minute 250 ppm duplex	
11" x 17"	Max. per minute 140 ppm duplex	
12" x 18"	Max. per minute 132 ppm duplex	
8.5" x 11"	Max. per hour 15,000 pph duplex	
11" x 17"	Max. per hour 8,400 pph duplex	
12" x 18"	Max. per hour 7,920 pph duplex	

Options

CR-101	Creaser unit for SD-513
FD-503	Folding and punching unit
FD-504	Square folding unit for SD-513
FS-532	100-sheet stapling finisher
GP-501	Multi (GBC) punching unit
GP-502	Auto ring binding unit
HT-505	Heating unit for PF-703
HM-102	Humidification unit for RU-509
LS-505	Stacking unit
PB-503	Perfect binding unit
PF-703	Air suction paper feed unit
PF-706	Air assist paper feed unit
PI-PFU	Post-insertion unit
PK-522	Punch kit for FS-532
PP-701	Pre-printed paper feed kit for PF-706
RH-101 & HD-511	Removable HDD Kit
RU-509	Decurling relay unit
RU-510	Reversing relay unit
SD-506	Saddle stitch unit
SD-513	Saddle stitch unit
TD-501	Tandem unit
TU-503	Trimmer unit for SD-513




KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446













Production Print Color Multifunction Devices







Introducing the AccurioPress C4080 / C4070 – the incredibly versatile digital printer that connects you with success. With enhanced finishing, intelligent automation, flawless quality and advanced capabilities, simply build your perfect configuration from a huge range of innovative possibilities and say yes to more opportunities that will grow your business.

ACCURIOPRESS C4080 / C4070 SPECIFICATIONS

RETHINK OPTIONS

SYSTEM SPECIFICATIONS

Resolution	3,600 (equivalent) x 2,400 dpi x 8 bit
Paper weight	62 – 360 g/m2
Paper sizes	330.2 x 487.7 mm
	330.2 x 862 mm (max.duplex)
	330.2 x 1300 mm (max. simplex)
Paper input	Max.: 15,390 sheets
Dimension (WxDxH)	31.49" x 35.55" x 42.36"
Unit weight	696.66 lb.

PRODUCTIVITY

AccurioPress C4080			
8.5 x 11 – max. per minute	80 ppm		
11 x 17 – max. per minute	44 ppm		
AccurioPress C4070			
8.5 x 11 – max. per minute	70 ppm		
11 x 17 - max, per minute	38 ppm		

KONICA MINOLTA IMAGE CONTROLLER IC-609

Architecture	Internal
OS	Linux
CPU	Intel Core i5 6500
Clock speed	3.2 GHz
RAM std	16 GB
HDD	2 TB (2 x 1TB)
Page-description language	Adobe PostSript 3; PDF v1.7; APPE v4.6 (with UK-220); TIFF (v6); PPML v2.2
Applicable OS	Windows 8.1/10; Windows Server 2012/R2/2016/2019; Mac OS X 10.11–14

FIERY IMAGE CONTROLLER IC-317

Architecture	External
OS	Windows 10
CPU	Intel® CoreTM I5-6500 processor
Clock speed	3.2 GHz up to 3.6 GHz Turbo
RAM std	8 GB
HDD	1TB
Page-description language	Adobe® PostScript® Levels 1, 2, 3, APPE 5, PDF/X-1a, 3, and 4, EPS, Microsoft
	Office document formats: doc, docx, xls, xlsx, ppt, pptx, pub (via Hot Folders),
	JPEG, 1-bit TIFF, TIFF (optional via Graphic Arts Pro Package), Fiery FreeForm™
	Plus, PPML v3.0, PDF/VT 1 & 2, Creo VPS
Applicable OS	Windows 8.1/10; Windows Server 2012/R2/2016/2019; Mac OS X 10.11–14

FIERY IMAGE CONTROLLER IC-419

Architecture	Internal
OS	Linux
СРИ	Intel® Pentium® Processor G4400
Clock speed	3.3 GHz
RAM std	8 GB
HDD	500 GB
Page-description language	Adobe® PostScript® Levels 1, 2, 3, APPE 5, Microsoft Office document formats:
	doc, docx, xls, xlsx, ppt, pptx, pub (via Hot Folders)
Applicable OS	Windows 8.1/10; Windows Server 2012/R2/2016/2019; Mac OS X 10.11–14

OPTIONS

KM Image Controller	IC-609
EFI external Controller	IC-317
EFI internal Controller	IC-419
Paper Feeding Unit	PF-602m
Dehumidifier heater	HT-504
Paper feeding unit	PF-707m
Dehumidifier heater	HT-506
PFU connection Kit	FA-502
Large capacity feeding unit	LU-202m
Dehumidifier heater f. LU	HT-503
Envelop printing guidef. LU	MK-746
Large capacity feeding unit (banner)	LU-202XLm
Multi bypass feeding	MB-508
Banner Paper Feeder kit	MK-760
Multi bypass tray	MB-509
Intelligent Media Sensor	IM-101
Output Tray	OT-511
Relay Unit	RU-518m
Humidifier	HM-103
Intelligent Quality Optimizer	IQ-501
Purge Unit	RU-702
Auto Inspection Unit	UK-301
Envelop Fusing Unit	EF-107
Long Sheet Kit (Output)	MK-761
Trimmer Unit	TU-510
Creasing kit (Downwards)	CR-102
Creasing kit (Upwards)	CR-103
Center Slit kit	TU-504
CD Perforation kit	PE-102
FD Perforation kit	PE-103
Banner paper kit	MK-764
Business Card kit	JS-507
Folding and Punching Unit	FD-503
Stacking Unit	LS-507
Handcart	LC-502
Booklet Making Unit	SD-506
Booklet Making Unit	SD-513
Square Folding Kit	FD-504
Slitter Kit	TU-503
Creaser Kit	CR-101
Perfect Binding Unit	PB-503
Stapling Unit	FS-532m
Saddle Stitcher Kit	SD-510
Punch Kit	PK-525
Post Inserter Kit	PI-502
Output Tray Unit	OT-512
Long Sheet Kit (Output)	MK-761

IC GOO

- -All specifications refer to A4-size paper of 80 gsm quality.
- -The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- $The stated \ life expectancy of each \ consumable \ is \ based \ on \ specific \ operating \ conditions \ such \ as \ page \ coverage \ for \ a \ particular \ page \ coverage \ for \ a \ particular \ page \ coverage \ for \ a \ particular \ page \ coverage \ for \ a \ particular \ page \ coverage \ for \ a \ particular \ page \ coverage \ for \ a \ particular \ page \ coverage \ for \ a \ particular \ page \ coverage \ for \ a \ particular \ page \ coverage \ for \ a \ particular \ page \ coverage \ for \ a \ particular \ page \ coverage \ for \ a \ particular \ page \ coverage \ for \ a \ particular \ page \ coverage \ for \ a \ page \ for$ size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- -Some of the product illustrations contain optional accessories.
- -Specifications and accessories are based on the information available at the time of printing and are subject to change without
- -Konica Minolta does not warrant that any prices or specifications mentioned will be error-free.
- -All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com









COLOR DIGITAL PRODUCTION PRESS

85 ppm output for high-volume color print production

Inline, closed loop quality management system

Printing on media weights up to 400 gsm

Envelope printing

Optimized printing on all types of stocks with hundreds of built-in media catalogs
Powerful finishing

High-speed, double-sided scanning

Duty cycle 1,530,000

U.S. Energy Star compliant

Banner printing up to 47" with new optional bypass tray*

Duplex banner printing up to 29.5"*

*Available 2018.

COLOR DIGITAL PRODUCTION PRESS

AccurioPress series brings it all: 85 ppm print/copy output, advanced processing for resolution equivalent to 3,600 dpi, our exclusive Simitri HD^E toner for offset -quality color at affordable cost, superior stability over long print runs on a variety of substrates — and multiple inline finishing options to handle a broad array of job specs.

SYSTEM SPECIFICATIONS

STSTEWISPECIFICATIONS	
Resolution	1,200 x 1,200 dpi, (3,600 equivalent) 8-bit, 256 gradations
Paper weight (Plain, Fine,	52-400 gsm
Color Specific) (Coated)	81–400 gsm
Duplex unit	52–400 gsm
Paper sizes (max.)	330 x 487 mm (13" x 19.2") 330 x 1200 mm (13" x 47" banners*)
Paper sizes (min.)	100 x 139 mm (3.94" x 5.47")
Image loss (max.)	4 mm or less for lead and trail edge, 3.0 mm or less for right/left edges
Warm-up time	480 seconds or less
Paper input capacity (max.)	13,890 sheets
Paper output capacity	LS-506 Stacker – 5,000 FS-532 Finisher – 4,500
Main unit dimensions (W x D x H)	37.37" x 37.37" x 52"
Main unit weight	970 lb
Power requirements	208-240V, 60Hz
-	

PRODUCTIVITY

8.5" x 11" (max. per minute)	85 ppm
Monthly duty cycle	1,530,000 pages

CONTROLLER

CONTROLLER	
IC-604 Internal Konica	Available
Minolta controller	
IC-313 External EFI	Available
Fiery controller	
IC-314 External Creo controller	Available
IC-315 External EFI	Available
Fiery controller	

SCANNER SPECIFICATIONS (PF-711 only)

Scan speed (8.5" x 11")	Single-sided 120 ipm / duplex 240 ipm
Scan resolution	600 x 600 dpi
Scan modes	TWAIN scan; Scan-to-HDD; Scan-to-FTP;
	Scan-to-SMB; Scan-to-Email; Scan to USB
Scan formats	PDF, TIFF, JPEG (all controllers), Secured PDF,
	Compact PDF, XPS, PDF/A (with IC-604)

COPIER SPECIFICATIONS (PF-711 only)

Gradations	256 gradations
Magnification	25–400%, in 0.1% steps

FIERY IMAGE CONTROLLER IC-313

Туре	Server
CPU	Intel® Core™ i5-4570S Processor (6M cache, up to 3.60 GHz)
Memory	4 GB
HDD	1 TB
Page-description	Adobe PostScript 3 (3020), PDF 1.7, PPML v3.0GA,
language	APPE 3.0, PCL 5/6 emulation
Printing method	TCP/IP, SNMP, SMB, FTP, LPR, IPP, Bonjour
Applicable OS	Windows Vista / 7 / 8.1 / 10 / Windows Server 2008 / 2012*1
	Mac OS X v10.8 / v10.9 / v10.10
Interface	10Base-T / 100Base-TX / 1000Base-T
*1	

^{*1} Including 64-bit versions.



Туре	Server
CPU	Intel Core i7-4790S 3.2 GHz
Memory	12 GB (7 GB: system memory, 5 GB: image memory)
HDD	3 x 1 TB (1 TB system disk, 2 x 1 TB image disks)
Page-description	Adobe PostScript 3 (PS3020), PDF v1.7, APPE v3.4, PDF/X-1a/3/4,
language	PDF/VT-2, TIFF v6.0, TIFF/IT, PPML v2.2, VPS, PPML/VDX, XPS
Printing method	TCP/IP, SMB, LPR, Bonjour
Applicable OS	Windows 7 / 8.1 / 10 / Windows Server 2008 / 2012*1
	Mac OS X v10.7 / v10.8 / v10.9 / v10.10 / v10.11
Interface	Ethernet (1000BASE-T / 100BASE-TX / 10BASE-T) with IPv6, USB 2.0 / 3.0
14	

^{*1} Including 64-bit versions.

KONICA MINOITA IMAGE CONTROLLED IC-604

KONICA MINOLIA IMAGE CON I ROLLER IC-604	
Туре	AIO to the engine (option)
CPU	Conforms with main unit specification
Memory	20 GB (details: 8 GB (standard of the main body) + 12 GB (IC-604))
HDD	4 TB (details: 1 TB x 4)
Page-description	Adobe PostScript3 (PS3020), PDF v1.7, APPE v4.2, PDF/VT-2,
language	TIFF v6, PPML v2.2, PCL-5c, PCL6 v3
Printing method	TCP/IP(LPR/LPD, Raw Port, socket), IPX/SPX(NDS, Bindery),
	NetBEUI, IPP, Apple Talk, WSD, Bonjour, SMB
Applicable OS	PS Plug-in: Windows 7 / 8.1 / 10, Windows Server 2008 / 2008R2 /
	2012*1 / 2016*1, Mac OS X 10.8 / 10.9 / 10.10 / 10.11 / 10.12
	PS PPD*2: Windows 7 / 8.1 / 10, Windows Server 2008 / 2008R2 /
	2012*1 / 2016*1, Linux CUPS
Interface	Ethernet (1000BASE-T / 100BASE-TX / 10BASE-T) with IPv6, USB 2.0
Scanner resolution	200 / 300 / 400 / 600 dpi
Data format	PDF, TIFF, JPEG, XPS
Driver	HDD Twain Driver, Real Time Mode Twain Driver
.1 .2	-

^{*1} Including 64-bit versions. *2 WHQL is not obtained for the PS PPD driver.

FIERY IMAGE CONTROLLER IC-315

FIERT IMAGE CONTROLLER IC-3 IS	
Туре	Server
CPU	Xeon E5-2637 3.5GHz
Memory	14 GB
HDD	500 GB + 2 x 2 TB
Page-description	Adobe PostScript 3 (PS3020), PDF v1.7, APPE 3.0, PDF/VT-2,
language	PPML v3.0, PCL 5/6 emulation
Printing method	TCP/IP, SNMP, SMB, FTP, IPP, Bonjour
Applicable OS	Windows 7*1 / 8.1*1 / 10*1, Windows Server 2008*1 / 2008R2*1 /
	2012*1, Mac OS X v10.8 / v10.9 / v10.10 / v10.11
Interface	Ethernet (1000BASE-T / 100BASE-TX / 10BASE-T) with IPv6, USB 2.0 / 3.0

^{*1} Including 64-bit versions.

OPTIONS

CR-101	Creaser unit for SD-513
EF-104	Envelope fuser
FA-502	PFU adjustment kit
FD-503	Multi-fold punch unit
FD-504	Square folding unit for SD-513
FS-532	100-sheet staple finisher
FS-532	100-sheet staple finisher
PK/SD	with PK and SD-510-522
GP-501	GBC multi-hole punch unit
GP-502	GBC inline ring binding unit
HM-101	Humidification unit
HT-506	Dehumidification heating
	unit for PF-707
IQ-501	Intelligent quality optimizer
LC-501	Cart for LS-506
LS-506	Stacking unit
LU-	2,500-sheet extra long paper
202XLm	feed unit*
MB-508	Multi-bypass tray*

MK-732	Post-inserter mount kit for FS-532
MK-737	Mount kit for third party products
MK-740	Banner tray unit*
OR-102	ORU enablement kit
OT-510	Open stacker
PB-503	Perfect binder
PF-707m	Vacuum paper feed unit
PF-711	Vacuum paper feed unit
	with scanner
PI-502	Post inserter for FS-532
PK-522	2/3-hole punch for FS-532
RU-510	Relay unit for GP-501
RU-511	Relay unit
SD-506	Booklet making unit
SD-510	Saddle stitch kit for FS-532
SD-513	Saddle stitch unit
TU-503	Trimmer unit for SD-513
WT-512	Working table
*Available 2019	

^{*}Available 2018.



KONICA MINOLTA

KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com











© 2017 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product $and \ brand \ names \ are \ trademarks \ or \ registered \ trademarks \ of \ their \ respective \ companies \ or \ organizations. \ All \ features \ and \ functions \ described \ here$ $may \ not \ be \ available \ on \ some \ products. \ Design \ \& \ specifications \ are \ subject \ to \ change \ without \ notice.$





COLOR DIGITAL PRODUCTION PRESS

100 ppm output for high-volume color print production

Inline, closed loop quality management system

Printing on media weights up to 400 gsm

Envelope printing

Optimized printing on all types of stocks with hundreds of built-in media catalogs
Powerful finishing

High-speed, double-sided scanning

Duty cycle 1,800,000

U.S. Energy Star compliant

Banner printing up to 47" with new optional bypass tray*

Duplex banner printing up to 29.5"*

*Available 2018.

COLOR DIGITAL PRODUCTION PRESS

AccurioPress series brings it all: 100 ppm print/copy output, advanced processing for resolution equivalent to 3,600 dpi, our exclusive Simitri HD^E toner for offset -quality color at affordable cost, superior stability over long print runs on a variety of substrates — and multiple inline finishing options to handle a broad array of job specs.

SYSTEM SPECIFICATIONS

STSTEWISPECIFICATIONS			
Resolution	1,200 x 1,200 dpi, (3,600 equivalent) 8-bit, 256 gradations		
Paper weight (Plain, Fine,	52-400 gsm		
Color Specific) (Coated)	81–400 gsm		
Duplex unit	52–400 gsm		
Paper sizes (max.)	330 x 487 mm (13" x 19.2") 330 x 1200 mm (13" x 47" banners*)		
Paper sizes (min.)	100 x 139 mm (3.94" x 5.47")		
Image loss (max.)	4 mm or less for lead and trail edge, 3.0 mm or less for right/left edges		
Warm-up time	480 seconds or less		
Paper input capacity (max.)	13,890 sheets		
Paper output capacity	LS-506 Stacker – 5,000 FS-532 Finisher – 4,500		
Main unit dimensions (W x D x H)	37.37" x 37.37" x 52"		
Main unit weight	970 lb		
Power requirements	208-240V, 60Hz		
-			

PRODUCTIVITY

8.5" x 11" (max. per minute)	100 ppm
Monthly duty cycle	1,800,000 pages

CONTROLLER

CONTROLLER	
IC-604 Internal Konica	Available
Minolta controller	
IC-313 External EFI	Available
Fiery controller	
IC-314 External Creo controller	Available
IC-315 External EFI	Available
Fiery controller	

SCANNER SPECIFICATIONS (PF-711 only)

Scan speed (8.5" x 11")	Single-sided 120 ipm / duplex 240 ipm		
Scan resolution	600 x 600 dpi		
Scan modes	TWAIN scan; Scan-to-HDD; Scan-to-FTP;		
	Scan-to-SMB; Scan-to-Email; Scan to USB		
Scan formats	PDF, TIFF, JPEG (all controllers), Secured PDF,		
	Compact PDF, XPS, PDF/A (with IC-604)		

COPIER SPECIFICATIONS (PF-711 only)

Gradations	256 gradations
Magnification	25–400%, in 0.1% steps

FIERY IMAGE CONTROLLER IC-313

Туре	Server		
CPU	Intel® Core™ i5-4570S Processor (6M cache, up to 3.60 GHz)		
Memory	4 GB		
HDD	1 TB		
Page-description	Adobe PostScript 3 (3020), PDF 1.7, PPML v3.0GA,		
language	APPE 3.0, PCL 5/6 emulation		
Printing method	TCP/IP, SNMP, SMB, FTP, LPR, IPP, Bonjour		
Applicable OS	Windows Vista / 7 / 8.1 / 10 / Windows Server 2008 / 2012*1		
	Mac OS X v10.8 / v10.9 / v10.10		
Interface	10Base-T / 100Base-TX / 1000Base-T		
*1			

*1 Including 64-bit versions.



Туре	Server			
CPU	Intel Core i7-4790S 3.2 GHz			
Memory	12 GB (7 GB: system memory, 5 GB: image memory)			
HDD	3 x 1 TB (1 TB system disk, 2 x 1 TB image disks)			
Page-description	Adobe PostScript 3 (PS3020), PDF v1.7, APPE v3.4, PDF/X-1a/3/4,			
language	PDF/VT-2, TIFF v6.0, TIFF/IT, PPML v2.2, VPS, PPML/VDX, XPS			
Printing method	TCP/IP, SMB, LPR, Bonjour			
Applicable OS	Windows 7 / 8.1 / 10 / Windows Server 2008 / 2012*1			
	Mac OS X v10.7 / v10.8 / v10.9 / v10.10 / v10.11			
Interface	Ethernet (1000BASE-T / 100BASE-TX / 10BASE-T) with IPv6, USB 2.0 / 3.0			
e1				

^{*1} Including 64-bit versions.

KONICA MINOLTA IMAGE CONTROLLER IC-604

KUNICA MINULIA IMAGI	E CONTROLLER IC-604		
Туре	AIO to the engine (option)		
CPU	Conforms with main unit specification		
Memory	20 GB (details: 8 GB (standard of the main body) + 12 GB (IC-604))		
HDD	4 TB (details: 1 TB x 4)		
Page-description	Adobe PostScript3 (PS3020), PDF v1.7, APPE v4.2, PDF/VT-2,		
language	TIFF v6, PPML v2.2, PCL-5c, PCL6 v3		
Printing method	TCP/IP(LPR/LPD, Raw Port, socket), IPX/SPX(NDS, Bindery),		
	NetBEUI, IPP, Apple Talk, WSD, Bonjour, SMB		
Applicable OS	PS Plug-in: Windows 7 / 8.1 / 10, Windows Server 2008 / 2008R2 / 2012*1 / 2016*1, Mac OS X 10.8 / 10.9 / 10.10 / 10.11 / 10.12		
	PS PPD*2: Windows 7 / 8.1 / 10, Windows Server 2008 / 2008R2 /		
	2012*1 / 2016*1, Linux CUPS		
Interface	Ethernet (1000BASE-T / 100BASE-TX / 10BASE-T) with IPv6, USB 2.0		
Scanner resolution	200 / 300 / 400 / 600 dpi		
Data format	PDF, TIFF, JPEG, XPS		
Driver	HDD Twain Driver, Real Time Mode Twain Driver		
+1			

^{*1}Including 64-bit versions. *2WHQL is not obtained for the PS PPD driver.

FIERY IMAGE CONTROLLER IC-315

Туре	Server		
СРИ	Xeon E5-2637 3.5GHz		
Memory	14 GB		
HDD	500 GB + 2 x 2 TB		
Page-description	Adobe PostScript 3 (PS3020), PDF v1.7, APPE 3.0, PDF/VT-2,		
language	PPML v3.0, PCL 5/6 emulation		
Printing method	TCP/IP, SNMP, SMB, FTP, IPP, Bonjour		
Applicable OS	Windows 7*1 / 8.1*1 / 10*1, Windows Server 2008*1 / 2008R2*1 /		
	2012*1, Mac OS X v10.8 / v10.9 / v10.10 / v10.11		
Interface	Ethernet (1000BASE-T / 100BASE-TX / 10BASE-T) with IPv6, USB 2.0 / 3		
-	· · · · · · · · · · · · · · · · · · ·		

^{*1} Including 64-bit versions.

OPTIONS

CR-101	Creaser unit for SD-513			
EF-104	Envelope fuser			
FA-502	PFU adjustment kit			
FD-503	Multi-fold punch unit			
FD-504	Square folding unit for SD-513			
FS-532	100-sheet staple finisher			
FS-532	100-sheet staple finisher			
PK/SD	with PK and SD-510-522			
GP-501	GBC multi-hole punch unit			
GP-502	GBC inline ring binding unit			
HM-101	Humidification unit			
HT-506	Dehumidification heating			
	unit for PF-707			
IQ-501	Intelligent quality optimizer			
LC-501	Cart for LS-506			
LS-506	Stacking unit			
LU-	2,500-sheet extra long paper			
202XLm	feed unit*			
MB-508	Multi-bypass tray*			

MK-732	Post-inserter mount kit for FS-532		
MK-737	Mount kit for third party products		
MK-740	Banner tray unit*		
OR-102	ORU enablement kit		
OT-510	Open stacker		
PB-503	Perfect binder		
PF-707m	Vacuum paper feed unit		
PF-711	Vacuum paper feed unit		
	with scanner		
PI-502	Post inserter for FS-532		
PK-522	2/3-hole punch for FS-532		
RU-510	Relay unit for GP-501		
RU-511	Relay unit		
SD-506	Booklet making unit		
SD-510	Saddle stitch kit for FS-532		
SD-513	Saddle stitch unit		
TU-503	Trimmer unit for SD-513		
WT-512	Working table		
*Available 2018.	·		



KONICA MINOLTA

KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com











For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2017 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product $and \ brand \ names \ are \ trademarks \ or \ registered \ trademarks \ of \ their \ respective \ companies \ or \ organizations. \ All \ features \ and \ functions \ described \ here$ may not be available on some products. Design & specifications are subject to change without notice.



Compact Multifunction Printers













CUSTOMER BENEFITS



Intuitive operability Operate the bizhub like a

smartphone or tablet with fully customized user interface



Mobile connectivityPrint anytime from anywhere with Konica Minolta's innovative mobile technologies



Security

Secure network integration, data encryption, HDD overwrite, and advanced user authentication



Application ecosystem Enhanced efficiency thanks to Konica Minolta's extensive $applications \ port folio$



Services

Efficient printer fleet management, including automatic consumables delivery, pro-active maintenance, and remote setup

OPTIONS



PDF enhancements LK-102v3

OCR text recognition LK-105v4 Barcode fonts

Unicode fonts LK-107

OCR A and B fonts LK-108

Document converter pack LK-110v2

ThinPrint® client LK-111





LEGEND Mandatory option Option This option can only be installed with the respective option above it







FINISHING FUNCTIONALITIES





Duplex

Corner stapling (offline)

bizhub C3350i Datasheet

DESCRIPTIONS

ENHA	NCFD	FFΔT	IIRFS

LK-102v3 PDF Enhancements	PDF/A (1b); PDF encryption; digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A
LK-111 ThinPrint client	Print data compression for reduced network impact
LK-116 Antivirus	Bitdefender ® antivirus provides real time scanning
	of all in-/outcoming data

CONNECTIVITY

FK-517 Fax board	Super G3 fax, digital fax functionality
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection; Bluetooth
AU-102 Biometric authenticaton	Finger vein scanner
AU-205H	Various ID card technologies
MK-P08 Mount kit	Installation kit for AU-205H

OTHERS

WT-P03 Working table	Authentication device placement	
KP-102 10-Key pad	For use instead of touchscreen	
KH-P02 Keyboard holder	To place USB keyboard	
External Keyboard	Keyboard for alpha numeric data entry	
MEDIA INPUT		
PF-P21 Paper tray	500 sheets, 8.5" x 11" or 8.5" x 14", 60-90 gsm	

To achieve comfortable height for operation $% \label{eq:comfortable} % \label{eq:comfortable}$

Provides storage space for print media and other materials

DK-P05 Copier desk MEDIA OUTPUT

PF-P25 Height adjustment unit

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS

Panel size/resolution	10.1" / 1024 x 600
System memory (standard/max)	5 GB
Solid State Drive	256 GB (standard)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11 b/g/n
Network protocols	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP;
	HTTP(S); AppleTalk; Bonjour
Automatic document feeder (standard)	Up to 80 originals; 5.8" x 8.3" to 8.5" x 14"; 50–128 gsm;
	Dualscan ADF
Paper input capacity (standard/max)	600 sheets / 1,600 sheets
Paper tray input (standard)	1x 500 sheets; 3.9" x 5.8" to 8.5" x 11.7";
	custom sizes; 60–210 gsm
Paper tray input (optional)	2x 500 sheets; 8.5" x 11" or 8.5" x 14"; custom sizes; 60–90 gsm
Manual bypass	100 sheets; 3.5" x 8.8" to 8.5" x 14"; Custom sizes; 60–210 gsm
Automatic duplexing	5.8" x 8.3" to 8.5" x 14"; 60–210 gsm
Finishing modes (optional)	Group; Sort; Staple (offline)
Output capacity (standard)	Max. 250 sheets
Copy/print volume (monthly)	Max. ¹ 96,000 pages
Toner lifetime	Black up to 13,000 pages
	CMY up to 9,000 pages
Imaging unit lifetime	Black up to 200,000 pages (imaging unit)
	CMY up to 100,000 pages (imaging unit)
Power consumption	110–120 V / 60 Hz; Less than 1.45 kW
System dimension (W x D x H)	18.5" x 20.8" x 22.5" (without options)
System weight	Approx. 86 lb. (without options)

PRINTER SPECIFICATIONS

Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Print Speed letter (mono/color)	Up to 35/35 ppm
Page description language	PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
Operating System	Windows 7 (32/64); Windows 8/8.1 (32/64); Windows 10
	(32/64);
	Windows Server 2008 (32/64); Windows Server 2008 R2;
	Windows Server 2012; Windows Server 2012 R2;
	Windows Server 2016; Windows Server 2019;
	Macintosh OS X 10.10 or later; Unix; Linux; Citrix
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	AirPrint (iOS); Mopria (Android);
	Konica Minolta Mobile Print (iOS/Android/Windows 10 Mobile);
	Mobile Authentication and Pairing (iOS/Android);
	WiFi Direct

SCANNER SPECIFICATIONS

Scan speed (mono/color)	Up to 45/45 ipm in simplex
	Up to 90/90 ipm in duplex
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);
	Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV;
	Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF;
	XPS; Compact XPS; PPTX
	Optional: Searchable PDF; PDF/A 1a and 1b;
	Searchable DOCX/PPTX/XLSX
Scan destinations	2,100 (single + group); LDAP support

COPIER SPECIFICATIONS

Imaging technology	Laser
Toner technology	Simitri® HD polymerised toner
Copy/print speed letter (mono/color)	Up to 35/35 ppm
Autoduplex Speed letter (mono/color)	Up to 35/35 ppm
1st copy out time letter	5.6/6.3 sec.
Warm-up time	Approx. 13 sec. in mono; 15 sec. in color ²
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-9,999
Original format	3.9" x 8.8" to 8.5" x 14"; Custom sizes
Magnification	25–400% in 0.1% steps; Auto-zooming

FAX SPECIFICATIONS		
Fax standard	Super G3	
Fax transmission	Analog; i-Fax; Color i-Fax; IP-Fax	
Fax resolution	Up to 600 x 600 dpi	
Fax compression	MH; MR; MMR; JBIG	
Fax modem	Up to 33.6 Kbps	
Fax destinations	2 100 (single + group)	

USER BOX SPECIFICATIONS

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication);
	Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling
SYSTEM FEATURES	
Security Functions (standard)	ISO 15408 HCD-PP Common Criteria (in evalutation); IP filtering
	and port blocking; SSL2; SSL3 and TLS1.0/1.1/1.2 network
	communication; IPsec support; IEEE 802.1x support;
	User authentication; Authentication log; Secure print; Kerberos;
	Hard disk overwrite (8 standard types); Hard disk data encryption
	(AES 256); Memory data auto deletion; Confidential fax receipt;
	Print user data encryption
Security Functions (optional)	Antivirus realtime scanning (Bitdefender®)
Accounting (standard)	Up to 1,000 user accounts; Active Directory support (user name +
	password + e-mail + smb folder); User function access definition
Accounting Functions (optional)	Biometric authentication (finger vein scanner);
	ID card authentication (ID card reader);
	Authentication by mobile device (Android/iOS)
Software	PageScope Net Care Device Manager; PageScope Data Admin-
	istrator; PageScope Box Operator; PageScope Web Connection;
	Print Status Notifier; Driver Packaging Utility; Log Management
	Utility

¹ Maximum monthly copy/print volume supported under standard vendor supplied service. Defines the upper end of the expected customer volume for the device. Customers should consider multiple machines if average monthly volume approaches duty cycle on a continual basis.

- All specifications refer to letter-size paper of 80 gsm weight.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.

 The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a
- particular page size (6% coverage of letter). The actual life of each consumable will vary depending on use and other $printing\ variables\ including\ page\ coverage,\ page\ size,\ media\ type,\ continuous\ or\ intermittent\ printing,\ ambient$ temperature and humidity.
- Some of the product illustrations contain optional accessories.
- $Specifications \ and \ accessories \ are \ based \ on \ the \ information \ available \ at \ the \ time \ of \ printing \ and \ are \ subject \ to \ change$ without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

PARTNERSHIP.

INFORMATION MANAGEMENT

Konica Minolta can help give shape to your ideas and partner with you to achieve your corporate objectives. Contact us to realize opportunities in:

IT SERVICES

Technology Implementation

and Deployment

Enterprise Content Management (ECM) **Application Services** Document Management **Cloud Services Automated Workflow Solutions** IT Security **Business Process Automation** Managed IT Services Security and Compliance IT Consulting & Projects Apple Managed Services Mobility eDiscovery Services Managed Voice Services

For complete information on Konica Minolta products and solutions,

TECHNOLOGY

Office Multifunction Business Solutions Commercial and Production Printers **Industrial Printers** Wide Format Printers 3D Printers Scanners Security Surveillance Systems

Laptops, Desktops and Computer Hardware Servers and Networking Equipment

Managed Print Services (MPS) Managed Enterprise Services















Wi/Fi







KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com









please visit: CountOnKonicaMinolta.com

² Warm-up time may vary depending on the operating environment and usage



TECHNOLOGY



MONOCHROME ALL-IN-ONE PRINTER

High-resolution B&W print/copy output at up to 46 ppm

All-in-one functionality, including Super G3 fax

100,000 page monthly volume for large workloads

Standard PCL and PostScript functionality to fit all environments

Scanning in both B&W and color with reversing auto document feeder

2,000 sheet maximum paper capacity in small footprint

Mobile printing support

Standard wireless connectivity

bizhub 4422

MONOCHROME ALL-IN-ONE PRINTER

The bizhub 4422 packs high-speed productivity into space-saving dimensions, delivering up to 46 ppm high-resolution B&W print/copy output with network integration, including wireless connectivity, built-in fax capability and support for the convenience software and mobile printing functions that help grow your business.

SYSTEM OVERVIEW

System memory	1 GB (standard/max)
Interface	10-Base-T/100-Base-TX/1,000-Base-T Ethernet, USB 2.0,
	802.11x wireless
Network protocols	TCP/IP (IPv4 / IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS, IPX/SPX
Reversing automatic	Up to 50 originals / 4" x 6" to 8.5" x 14" / 52–120 gsm
document feeder	
Printable paper size	4" x 6" to 8.5" x 14" / custom paper sizes
Printable paper weight	60-216 gsm
Paper input capacity	Standard: 350 sheets Max.: 2,000 sheets
Tray 1	250 sheets / 4" x 6" to 8.5" x 11" / 60-120 gsm
Trays 2, 3 & 4 (optional)	250 or 550 sheets each / 8.5" x 11" to 8.5" x 14" / 60–120 gsm
Manual bypass	100 sheets / 4" x 6" to 8.5" x 14"
	custom paper sizes / 60-216 gsm
Automatic duplexing	8.5" x 11" to 8.5" x 14" / 60-90 gsm
Output capacity	Max.: 150 sheets
Copy/print volume	Max.: 100,000 pages / month ¹
Toner lifetime	25,000 pages ²
Imaging unit lifetime	60,000 pages
Power consumption	110 V / 60 Hz, less than 630 W (system)
System dimensions	19.3" x 16.9" x 18.8" (H x W x D)
System weight	Approx. 46 lb

COPIER SPECIFICATIONS

COPIER SPECIFICATIONS	
Copying process	Electrostatic laser copy, tandem, indirect
Print speed	Up to 46 ppm (letter)
Autoduplex speed	Up to 23 ppm (letter)
1st copy out time	6.5 sec.
Warm-up time	Approx. 90 sec. ³
Copy resolution	600 x 600 dpi
Multi-copy	1-999
Original format	4" x 6" to 8.5" x 14"
Magnification	25-400% in 1% steps; auto zooming
Copy functions	Duplex copy, 2-in-1, 4-in-1, poster, density adjustments

PRINTER SPECIFICATIONS

Print resolution	1,200 x 1,200 dpi, 600 x 600 dpi
PDL	PCL5e, PostScript
Operating systems	Windows (x32/x64): 7 / 8 / 8.1 / 10
	Windows Server (x32/x64): 2008 / 2008R2 / 20124 / 2012R2 / 2016
	Macintosh OS X 10.9 or later
	Linux
Printer fonts	89 PCL Latin, 158 PostScript
Print functions	Confidential print, combination, n-up, overlay, watermark

SCANNER SPECIFICATIONS

Scan speed	Up to 45 opm (mono)
Scan resolution	600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-USB Network TWAIN
File formats	TIFF, PDF, JPEG, XPS
Scan destinations	500 (shared with fax), LDAP support

FAX SPECIFICATIONS

Fax	Super G3
Transmission	Analog, PC-fax
Resolution	Max.: 600 x 600 dpi
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	500 (shared with scan), LDAP support
Functions	Polling, time shift, PC-fax

OPTIONS	
PF-15 Paper tray	8.5" x 11" to 8.5" x 14" / 250 sheets / up to 120 gsm
PF-16 Paper tray	8.5" x 11" to 8.5" x 14" / 550 sheets / up to 120 gsm
DK-P02 Copier desk	Ensures ergonomic height and provides storage space
	for print media, etc.
HD-P07	500 GB hard disk to collate large jobs and enable proof copy,
	scan preview and booklet creation in copy mode
UK-P12 Flash memory	256 MB User flash card for font downloading and
	saving job account log
UK-P13 Barcode card	Provides barcode fonts
UK-P14 IPDS card	Provides compatibility for AFP/IPDS printing
CS-1 Convenience stapler	Convenient stapling of up to 50 prints per set

SYSTEM FEATURES	
Security	IP filtering and port blocking, IPsec support,
	IEEE 802.1x support, user authentication, secure print
Software	Net Care Device Manager
	WebConnection
	Data Administrator
	Direct Print
	Konica Minolta Mobile

 $^{^{\}rm I}$ Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guidline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.

⁴ Supports x64 only.









For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2018 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo and bizhub are registered trademarks or trademarks of KONICA MINOLTA, INC. All other $product \ and \ brand \ names \ are \ trademarks \ or \ registered \ trademarks \ of \ their \ respective \ companies \ or \ or \ ganizations. \ All \ features \ and \ functions \ described$ here may not be available on some products. Design & specifications are subject to change without notice.



KONICA MINOLTA

KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com







² The bizhub 4422 ships with a starter toner cartridge (6,000 yield).

³ Warm-up time may vary depending on the operating environment and usage.



Black & White multi-function printer









Table of Contents	
Specifications	3
Duty Cycle	5
Environmental Requirements	6
Basic Configuration	6
Space Requirements	7
Accessories	8
Mixed Original Support	14
Standard Paper Tray Support	14
Print Controller (Standard)	15
Network Functions	15
Print Drivers	15
Scanning Function	17
Software Tools	17
Security	18
Paper Considerations	19
Paper Weight Conversion Chart	19
Paper Type Specifications	20
Recommended Paper Stocks	20
How to Build a System	22
Accessory Options	23



BIZHUB 4750I/4050I SPECIFICATIONS

TYPE	PRINTER
Туре	Digital Printer/Copier/Scanner
Document Holder	Stationary (mirror scanning)
Photoconductor	OPC
Luminous Source	LED light-source illumination
Copying System	Laser electrostatic copy method
Developing System	Dry-2 component developing method
Resolution	Scanning: 600 x 600 dpi
	Printing: 1200 x 1200 dpi
Document Holder	Types: Sheets, books (2-page spreads), three-dimensional objects
	Size: Maximum 8.5" x 14"
Paper	Plain Paper (16 lb to 24 lb)
	Plain Paper+ (24.75 lb to 28 lb)
	Thick Paper 1 (24.25 lb to 32 lb)
	Thick Paper 1+ (32.25 lb to 41.75 lb)
	Thick Paper 2 (42 lb to 55.5 lb)
	Coated Paper 1 (24 lb to 32 lb)
	Coated Paper 1+ (32.25 lb to 41.75 lb)
	Coated Paper 2 (42 lb)
	Recycled Paper (16 lb to 24 lb)
	Special Paper (16 lb to 24 lb)
	Letterhead (16 lb to 24 lb)
	Color Paper (16 lb to 24 lb)
	1-Sided Special Paper (16 lb to 24 lb)
	Envelopes, Label Sheets, Tabs, Postcards
Copy Sizes	1st Tray:
Copy Sizes	3.9" x 5.8" to 8.5" x 11"
	Bypass Tray: 3.5" x 8.8" to 8.5" x 14"
Danas Tray Canasity	1st Tray:
Paper Tray Capacity	<i>,</i>
	Thin Paper/Plain Paper/Recycled Paper/Special Paper/Color Paper/ 1-Sided Special Paper: 500 sheets
	·
	Thick Paper 1/1+/2/Coated Paper 1/1+/2/Postcards: 20 sheets
	Envelopes: 30
	Postcards/Label Sheets: 20 sheets
	Bypass Tray:
	Plain Paper/Recycled Paper/Special Paper/Letterhead/Color Paper/
	1-Sided Special Paper: 100 sheets
	Thick Paper 1/1+/2/Coated Paper 1/1+/2/Postcards/Tabs: 20 sheets
	Envelopes: 10
	Banner Paper/Label Sheets: 10 sheets
Warm-Up Time	Less than 15 seconds (at room temperature/73° F)

BIZHUB 4750I/4050I SPECIFICATIONS

TYPE	DESCRIPTION
Image Loss Width	Leading edge: 0.116" ± 0.079"
	Trailing edge: 0.116" ± 0.079"
	Rear edge: 0.116" ± 0.079"
	Front edge: 0.116" ± 0.079"
First Copy	4750i: 4.3 sec. or less
	4050i: 4.8 sec. or less
Print Speed*	4750i: Plain paper: 50 sheets/min.
(Full Color/B&W)	Thick 1/Thick1+/Thick 2: 21 sheets/min.
(Simplex/Duplex)	4050i: Plain paper: 42 sheets/min.
	Thick 1/Thick 1+/Thick 2: 21 sheets/min.
Magnification Ratios (Preset)	1.0 (full size: 1.00 ± 0.5% or less)
	Enlarge: 129.4%, 154.5%, 200%
	Reduce: 78.5%, 64.7%, 60.7%, 50.0%
	Stored Zoom Ratios: 3
Multiple Copies	1 to 9,999 sheets
Density Control	Copy Density: Manual Density Adjustment (9 Levels)
	Background Density: Automatic and Manual Density Adjustments (9 levels)

BIZHUB 4750I/4050I SPECIFICATIONS

TYPE	DESCRIPTION
Power Requirements	120V, 12 A, 60 Hz
Power Consumption	1.45 kW or less
TEC Value	4750i: 0.77 kWh
	4050i: 0.64 kWh
Dimensions	18.5" (W) x 20.8" (D) x 22.5" (H)
(with control panel)	
Space Requirements*	30.8" (W) x 37.6" (D) x 31.2" (H)
Memory	5 GB (Std.)
Solid State Drive	256 GB (Std.)
Weight	Approx. 78 lb
* The indicated space requiremen	its represent the space required to pull out the paper tray and the tray extension of the bypass tray and with the ADF open.

DUTY CYCLE

bizhub 4750i/4050i	Up to 120,000 Maximum monthly copy/print volume supported under standard vendor supplied service. Defines the upper end of the
	expected customer volume for the device. Customers should consider multiple machines if average monthly volume approaches duty cycle on continual basis.



ENVIRONMENTAL REQUIREMENTS

TYPE	DESCRIPTION
Temperature	50° F to 86° F
Humidity	15% to 85%
Noise During Operation	4750i: 73.3 dB or less
	4050i: 72.5 or less
Noise During Standby	43.5 dB or less
Ozone Emission	0.25 mg/h or less

ELECTRICAL REQUIREMENTS


TYPE	DESCRIPTION	
Line Options	Dedicated	NEMA Diagram for 5-15R
Voltage	110 V/120V	
Amperage	12A	
Cycles	60 Hz	
NEMA Part No.	5-15R	
Cord Length	6.6 ft.	
Note: The main electrical outlet	must be located within 6.6 feet from the right rea	r corner of the bizhub 4750i/4050i main unit.

SAMPLE CONFIGURATION






SPACE REQUIREMENTS



bizhub 4750i/4050i



bizhub 4750i/4050i + PF-P21 + PF-P25 + DK-P05

AUTOMATIC DUPLEX UNIT (STANDARD)

Supported Paper Type	Plain Paper (16 lb to 24 lb)	
	Thick Paper 1 (24.25 lb to 32 lb)	
	Thick Paper 1+ (32.25 lb to 41.75 lb)	
	Thick Paper 2 (42 lb to 55.5 lb)	
	Recycled Paper (16 lb to 24 lb)	
	Special Paper (16 lb to 24 lb)	
	Color Paper (16 lb to 24 lb)	
Supported Paper Size	4.7" x 8.8" to 8.5" x 14"	
Power Requirements	Supplied from main unit	

DUAL SCANNER DOCUMENT FEEDER (STANDARD)

Туре	Single Pass Duplex Document Feeder
Supported Paper Types	1-Sided/2-Sided Originals/Mixed Originals: 8.5" x 14"L to 5.5" x 8.5"
Supported Paper Size	Single-Sided/Double-Sided: 13.5 lb bond to 34 lb bond
	Mixed Original: 13.5 lb bond to 34 lb bond
	1-Sided Plain Paper (13.25 lb to 34 lb)
	2-Sided Plain Paper (13.25 lb to 34 lb)
	Mixed Original Plain Paper (13.25 lb to 34 lb)
Paper Capacity	Max. 80 sheets (21.25 lb) (Single-Sided/Double-Sided Originals)
Scan Speed	48 images/min (one-sided @ 200 dpi) (B&W/Color)
	96 images/min (double-sided @ 200 dpi) (B&W/Color)
Power Requirements	Supplied from main unit.

FK-517 FAX KIT (STANDARD ON 4750I/OPTIONAL ON 4050I)

Number of Stored Pages	10,000 Pages (approx. 700 characters per page when 8.5" x 11" document is stored using fine resolution)
Number of Fax Lines	1 Fax Line (Standard on 4750i; Optional on 4050i)
Communication	ECM/Super G3
Compatible Lines	PSTN, PBX
Scanning Line Density	Ultra Fine: 600 x 600 dpi
,	Super Fine: 16 dot/mm x 15.4 line/mm, 400 x 400 dpi
	Fine: 8 dot/mm x 7.7 line/mm, 200 x 200 dpi
	Normal: 8 dot/mm x 3.85 line/mm
Modem Speed	2.4 kbps-33.6 kbps
Compression	MH/MR/MMR/IBIG
Scanning/(Sending) Paper Size	Original Glass: Max. 11" x 17"
g, (g,	ADF: 11" x 39" (Normal, Fine, Super Fine)
	11" x 17" (Ultra Fine, Manual TX)
Reording Paper Size	8.5" x 14" to 5.5" x 8.5"
Transmission Speed	Approx. 3 sec. (A4, V.34, 33.6 Kbps, JBIG)
Scan Speed	2 sec. (Letter/Fine Mode)
Number of Abbr. Dial	2000
Number of Program Dial	400
Number of Group Dial	100 (Up to 500 destinations per group)
Sequential Multiple	Max. 600
	Station Transmission
Transmitting Function	2-in-1 TX, Mixed Original, F-Code Transmission, Frame Erase Transmission, Sharpness, Header/Footer, Memory Transmission,
	Quick Memory Transmission, Timer Transmission, Incomplete Transmission Hold, Manual Transmission, Confidential Transmission,
	Password Transmission, Polling Transmission, Bulletin Function, Relay Transmission, Fax Forwarding Function, Overseas TX, V.34 OFF
	ECM OFF
Receiving Functions	Duplex Print (RX), Manual Reception, Confidential Reception, Memory Reception, Polling Reception, Bulletin Function, Fax
	Forwarding (to any destination stored in the Address Book), TSI Routing (to any destination stored in the Address Book).

PF-P21 PAPER FEED CABINET (ADD UP TO TWO)

Туре	1 x 500 sheet drawer
Support Paper Types	Plain Paper (16 lb bond to 24 lb bond), Recycled Paper (16 lb to 24 lb), Single Side
	Only Paper (16 lb bond to 24 lb bond), Special Paper (16 lb bond to 24 lb bond),
	Letterhead (16 lb bond to 24 lb bond), Colored Paper (16 lb bond to 24 lb bond)
Supported Paper Size	8.5" x 14" to 7.25" x 10.5"
Paper Capacity	500 sheets (21 lb)
Power Requirements	Supplied from Main Unit
Max. Power Consumption	Less than 15W
Dimensions (W x D x H)	17.7" x 20.8" x 5.7"
Weight Approx.	18.5 lb
PF-P25 HEIGHT ADJUSTMENT UNIT	
Туре	Height Adjustment Unit
Function	Increases working height of the machine. Suggested if the machine is configured with the DK-P05 and fewer than two
	PF-P21 Paper Feeder Cabinets.
DK-P05 COPY DESK	
Туре	Storage drawer only
Function	Stores printing materials such as paper or toner. Recommended when additional paper drawers are installed, to bring the device to
	operational height
Dimensions (W x D x H)	17.7" x 20.8" x 13.8"
Weight Approx.	30 lb
KP-102 10-KEY PAD	
Туре	10-Key Pad
Function	Provides hard keys for entering numerical values and supports Voice Guidance function available with optional LK-104 v3 i-Option
	License Kit. Meets Section 508 Accessibility requirements.
EXTERNAL KEYBOARD	
Туре	QWERTY Keyboard
Function	Computer-type keyboard for alphanumeric data entry. Requires KH-P02 Keyboard Holder and EK-P08 or EK-P09 USB Interface Kit.
Tunction	Computer type regional for appraisance out a entry, requires with 02 regional molder and Ex-F00 of Ex-F00 OSD interface wit.
KH-P02 KEYBOARD HOLDER	
Туре	Mount Kit

AU-102 BIOMETRIC AUTHENTICATION UNIT

Biometric Sensor System	Transmission-type optical system
Verification Time	Approx. 1 sec. or less
Interface	USB 2.0
Dimensions WxDxH	Approx. 2.3" x 3.3" x 2.9"
Weight	Approx. 3 oz. (excluding USB cable)
Max. Power Consumption	DC 5 V, 500 mA
System Conditions	Ambient temperature: 41° to 95° (F) (during operation)
	Humidity: 20% to 80% (No dew condensation)
System Conditions (during non-operation)	Ambient temperature: 32° to 122° (F)
	Humidity: 20% to 80% (No dew condensation)
	NOTE: WT-P03 Working Table is required for AU-102 Biometric Authentication Unit.

AU-204H MAGNETIC STRIPE CARD READER

Dimensions WxDxH	1.3" x 1.2" x 3.9"
Weight	4.5 oz.
Power Supply	Supplied from USB Port
System Conditions (operating mode)	Ambient Temperature: 40° to 158° F
	Humidity: 10% to 90%
Transmit Frequency	3-60 i.p.s.
Certifications	ISO 7810 and ISO 7811/AAMVA
Card Type Compatibility	All magnetic stripe cards
	NOTE: WT-P03 Working Table required for AU-204H Magnetic Stripe Card Reader.

AU-205H IC CARD READER

Dimensions WxDxH	2.8" x 3.7" x 0.6"
Weight	0.25 lb
Power Supply	Supplied from USB Port
System Conditions	Ambient Temperature: 31° to 150° F
	(operating mode)
	Humidity: 5% to 95%
Card/Protocols	HID PROX, HID Indala® Prox, EM Prox
	Low Frequency (125 kHz)
Card/Protocols High Frequency (13.5 MHz)	CCID: MIFARE Classic™ 1K/4K, Ultra Light, Ultra Light C, Plus, MIFARE DESFire™ 0.6,
	MIFARE DESFire™ EV1, IC Card, iClass SE/SR®, MIFARE SE™, DESFire EV1 SE, T=CL,
	ISO 14443 A with up to 848 kbps transmission rate (depending on card*), ISO 15693
	with up to 26 kbps transmission rate (depending on card)
	NOTE: WT-P03 Working Table or MK-P08 Mount Kit (internal mount) required.
	*424 kbps default rate, 848 kbps configurable through web interface.



Type Function

ACCESSORIES

AU-211P CAC/PIV SOLUTION W/CERTIFICATE

Dimensions WxDxH	2.8" x 2.8" x 0.4"
	0.13 lb
Weight	
Power Supply	Supplied from USB Port
System Conditions	0° to 122° F (operating mode)
Interface	Full Speed USB (12 Mbps)
Connector Shape	USB A Type Connector
Compatible Card	PKI-C-Card (PIV, CAC)
	NOTE: WT-P03 Working Table required. Please contact your local Government Account Manager for additional information.
MK-P08 MOUNT KIT	
Туре	Internal Component
Function	Required for internal installation of AU-205H
WT-P03 WORKING TABLE	
Type	External Table
Type Function	External lable Holds AU-102 Biometric Authentication Unit, AU-201H HID Proximity Card Reader, AU-202H HID iClass Reader, AU-204H Magnetic
	Holds AU-102 Biometric Authentication Unit, AU-201H HID Proximity Card Reader, AU-202H HID iClass Reader, AU-204H Magnetic

Required to connect optional External Keyboard or optional i-Option LK-104 v3 Voice Guidance License kit.

USB Interface

EK-DUO LICE	HUCT/IUCVI	INTERFACE WITH BLUETOOTH

EK-P09 USB HOST/LOCAL INTERFACE WITH BI	LUETOOTH
Туре	USB Interface with Bluetooth
Function	Required to connect optional External Keyboard or optional i-Option LK-104 v3 Voice Guidance License Kit.
LK-104 V3 i-OPTION LICENSE KIT	
Туре	License Key
Function	Voice Guidance
LK-105 V4 i-OPTION LICENSE KIT	
Туре	License Key
Function	Provides Searchable PDF function
	Note: The LK-110 v3 supports the same functions as the LK-105 v4, therefore, both license kits cannot be installed on the same device.
LK-106 i-OPTION LICENSE KIT	
Туре	License Key
Function	Supports Bar Code Font Printing
LK-107 i-OPTION LICENSE KIT	
Туре	License Key
Function	Supports Unicode Font Printing
LK-108 i-OPTION LICENSE KIT	
Туре	License Key
Function	Supports OCR Font Printing
LK-110 V3 i-OPTION LICENSE KIT	
Type	License Key
1,500	Electricited
Function	OOXML format file conversion for docx/xlsx, fax to searchable PDF, convert box data to compact PDF, direct print e-mail attached file.
	Combines LK-102 (Encrypted PDF) & LK-105 (Searchable PDF/OCR) functionality.
	Note: If you install the LK-110 v3 on a device, you cannot install the LK-105 v4 on the same device.
LK-111 i-OPTION LICENSE KIT	
Type	License Key
Function	Provides ThinPrint client support
LK-116 i-OPTION LICENSE KIT	
Type Function	License Key Provides BitDefender® antivirus real time scanning of incoming and outgoing data.
runction	Provides bit belender antivirus real time scanning of incoming and outgoing data.
EM-908 EXPANDED MEMORY SSD	1 TD CCD
Type	1 TB SSD
Function	Increases storage space
HV D10 DOUBLE EEED DETECTION VIT	
UK-P19 DOUBLE FEED DETECTION KIT Type	Multi-feed detector
Function	Reduces errors and paper jams.
i uncuoni	neduces citoris and paper jams.

CS-1 CONVENIENCE STAPLER

Туре	Standalone electronic stapler
	·
Stapling Capacity	Up to 50 sheets
Paper Weight	Up to 90 gsm
Durability Cycle	Up to 200,000 stapling operations
Staple Position	Side or corner of document
Type of Clinch	Flat clinch
Dimensions WxDxH	5.3" x 5.7" x 7.5"
Weight	Approx. 4 lb
Power Supply	AC adaptor (supplied). Separate power output required.
Refill Staples	SK-602 (No. 505: 5,000 staples)

FS-P04 OFF-LINE STAPLER

Stapling (off-line)
20 sheets (90 gsm)
From device
SK-501
4.3" x 4.6" x 2.9"
Approx. 2 lb
Provides finishing capabilities. Can be installed on working table WT-P03 or separately.

MIXED ORIGINAL SUPPORT

MAXIMUM DOCUMENT WIDTH1

Document size ²	8.5" x 14" landscape	8.5" x 11" landscape	_
8.5" x 14" (L)	•	•	_
8.5" x 11" (L)	•	•	_

¹ Indicates the width of the widest document size of the mixed originals

STANDARD PAPER TRAY SUPPORT

MAIN UNIT - bizhub 4750i/4050i (PAPER TRAY 1)

Component	Capacity	Size	Weight	
Tray 1	500 sheets	8.5" x 11"	14 lb bond to 24 lb bond	
Bypass	150 sheets	8.5" x 14"	16 lb bond to 79.75 lb bond	

 $^{^{\}rm 2}$ Indicates the document sizes that can be mixed together based on the maximum document width.

[•] Possible x Not Possible

PRINT CONTROLLER (STANDARD)

Туре	Internal Type
CPU	1.6 GHz Quad Core Processor (shared with copier)
Memory	5 GB (shared with copier)
	256 GB Solid State Drive (shared with copier)
Print Speed	4750i: 50 ppm letter
	4050i: 42 ppm letter
Print Resolution	600 x 600 dpi (1800 equivalent x 600 dpi), 1200 x 1200 dpi
PDL	PCL 5e/c emulation, PCL6 (XL version 3.0), PS 3 (Version 3016) Emulation, XPS
Protocol	TCP/IP (IPv4/IPv6), BOOTP, ARP, ICMP, DHCP, DHCPv6, AutoIP, SLP, SNMP, FTP, LPR/LPD, RAW Socket, SMB over TCIP/IP, IPP, HTTP, POP, SMTP, LDAP,
	NTP, SSL, IPX, AppleTalk, Bonjour, NetBEUI, WebDAV, DPWS, S/MIME, IPsec, DNS, Dynamic DNS, LLMNR, LLTD, SSDP, SOAP
Font	PCL Resident Fonts: 80 Roman fonts
	PS3 Emulation Resident Fonts: 137 Roman Type 1 fonts
Interface	Standard Ethernet (10Base-T/100Base-TX/1000Base T); Hi-Speed USB 2.0, USB 1.1, USB Host

NETWORK FUNCTIONS

Sending the Scanned Data in an	Scanned data can be sent to a specified Email address. The destination is specified from the touch panel of this machine and the scanned data is sent as an
Email Message	Email attachment.
Sending Scanned Data as Files	The FTP server address, login password, and other information are entered from the touch panel of this machine. The data files uploaded to the FTP server
(FTP)	can be downloaded from a computer on the network.
Sending Scanned Data to a	Scanned data can be sent to a shared folder on a specified computer. The name of the destination computer, login password, and other information are
Computer on the Network (SMB)	entered from the touch panel of this machine.
Saving Scanned Data in Boxes	Scanned data is uploaded to a specified web server. The host name, file path, user name, and password are entered on the touch panel of the machine. The
	data files uploaded to the server can be downloaded from a computer on the network.
Using the Machine as a Scanner	This machine can be used as a scanner. The scanner can be controlled from a PC connected to the network, and the scanned image can be loaded into an
	application on the PC to be processed.
Web Service (Standard)	This machine can be used to access the Internet.

PRINT DRIVERS

PCL 6 Drivers	Konica Minolta PCL Driver	Windows 7/8.1/10
		Windows 7/8.1/10 64-bit
		Windows Server 2008
		Windows Server 2008/2008 R2/Server 2012/Server 2012 R2/ Server 2016 64-bit
PostScript 3 Emulation	Konica Minolta PostScript 3 Driver	Windows 7/8.1/10
		Windows 7/8.1/10 64-bit
		Windows Server 2008
		Windows Server 2008/2008 R2/Server 2012/Server 2012 R2/ Server 2016 64-bit
		Macintosh OSX
		PPD file for Red Hat Enterprise Linux (CUPS ver. 1.1.22) 10.9/10.10/10.11/10.12/10.13
		PPD+PDE printer driver
(PS Driver Emulation	Konica Minolta XPS Driver	Windows 7/8.1/10
		Windows 7/8.1/10 64-bit
		Windows Server 2008
		Windows Server 2008/2008 R2/Server 2012/Server 2012 R2/ Server 2016 64-bit
ax Driver	Konica Minolta	Windows 7/8.1/10
		Windows 7/8.1/10 64-bit
		Windows Server 2008
		Windows Server 2008/2008 R2/Server 2012/Server 2012 R2/ Server 2016 64-bit

SCANNING FUNCTION

Туре	Full-Color Scanner
Scanning Size	8.5" x 14" to 5.5" x 8.5"
Scanning Resolution	Push Scanning: 600/400/300/200 dpi
	Pull Scanning: 600/400/300/200/100 dpi
Scanning Speed	Duplex: 96 opm (300 dpi)
	Simplex: 48 opm (300 dpi)
Main Function	Scan-to-Email, Scan-to-User Box (HDD), Scan-to-FTP, Scan-to-USB, Scan-to-SMB (Desktop Folder), Scan-to-Me, Scan-to-Home, Scan-to-Scan Server,
	Network Twain (via Ethernet TCP/IP), Scan-to-WebDAV, WS-Scan
Interface	10Base-T/100Base-TX/1000Base-T
Protocol	TCP/IP (FTP, SMB, SMTP)
Supported OS	Windows 7/8.1/10, Windows 7/8.1/10 64-bit
Output Format	Single TIFF, Multi TIFF, JPEG, PDF, Compact PDF, XPS, Compact XPS TIFF (MH, MMR), PDF (MH, MMR, JPEG), JPEG, Outline PDF, PPTX, Searchable PDF,
	PDF/A, Linearized PDF
Driver	Real Time TWAIN Driver, HDD TWAIN Driver
Address Setting	LDAP, Import/Export address from PageScope Web Connection
Authentication	SMTP Authentication, Network User Authentication (Active Directory, Novell, NDS, NTLM ver. 1, NTLM ver. 2, LDAP)
	† Text and image scanning speeds vary depending on the type of document.

SOFTWARE TOOLS

Network & Device Management	Data Administrator
	Driver Packaging Utility
	Log Management Utility
	Net Care Device Manager (Standard)
User Tools	Direct Print
	Box Operator
	Print Status Notifier
	Copy Protection Utility
	Print Utility for Unix
	Web Connection
Management Tools	bizhub vCare

SECURITY

security risks it faces. 4) Protect data from being altered, duplicated or deleted 5) Prevent unauthorized access to data via the Internet 6) Protective Functions 7) Manage log history Protective Functions - lock Job (when printing confidential documents) - lock Job (when printing confidential documents) - Protect data by requiring department name and 8-digit password - Account Track - Prevent Unauthorized Use - Operation log with 2,000-event memory - SDD Encryption - PDF Scan Encryption - PDF Scan Encryption - POF Scan Encryption - Protective Functions - Copy Protection - Network Authentication - Simple Sign- on Authentication - Simple Sign- on Authentication - SMITP Authentication for Email - SSL/TSL Compatibility for PS Web Connection, PS Data Administrator and LDAP Server - Scan Data Encryption - LDAP Authentication - Box Operator Data Encryption - Verification of Box Data Receipt - IP Address Filtering - IP V6 - Encrypted Network Password Printing - Scan-to-USB Memory with User Authentication - Print-from-USB Memory with User Authentication - Print-from-USB Memory with User Authentication - PRINT-Filtering-Incryption - PIPS 140-2 Compliance - IEEE 2600.1 Security Ready - ISD 1504 EAL	Because information assets are	1) Prevent Leaks of proprietary, confidential or personal information	
security risks it faces. 4) Protect data from being altered, duplicated or deleted 5) Prevent unauthorized access to data via the Internet 6) Protect against cyber attacks 7) Manage log history Protective Functions 5) Protect data by requiring department name and 8-digit password Account Track Prevent Unauthorized Use Operation Log with 2,000-event memory SDD Encryption Profective Functions Copy Protection Protective Functions Copy Protection Protective Functions Copy Protection Network Authentication Single Sign-on Authentication Simple Sign-on Authentication SMFP Authentication SMFP Authentication SMFP Authentication Box Operator Data Encryption PDF Scan Encryption (TCP/socket SSL Compatibility) LDAP Authentication Box Operator Data Encryption PDF Scan Encryption PDF Scan Encryption (TCP/socket SSL Compatibility) LDAP Authentication Box Operator Data Encryption PDF Address Filtering PDF Address Filteri	critical, a company needs to		
S) Prevent unauthorized access to data via the Internet 6) Protect against cyber attacks 7) Manage logh history Protective Functions - Job Erase — Deletes Graphic Data (after each job) - Lock Job (when printing confidential documents) - Protect data by requiring department name and 8-digit password - Account Track - Prevent Unauthorized Use - Operation Log with 2,000-event memory - SDD Encryption - PDF Scan Encryption - PDF Scan Encryption - PDF Scan Encryption - Portective Functions - Copy Protection - Network Authentication - SImple Signon Authentication - SImple Signon Authentication - SIMTP Authentication for Email - SSL/TSL Compatibility for PS Web Connection, PS Data Administrator and LDAP Server - Scan Data Encryption (TCP/socket SSL Compatibility) - LDAP Authentication - Box Operator Data Encryption - Verification of Box Data Receipt - IP Address Filtering - IP Ve - Encrypted Network Password Printing - Scan-to-USB Memory with User Authentication - Print-From-USB Memory with User Authentication - S/MIME/Encryption - FIPS 140-2 Compliance - IEEE Zebou Security Ready - ISO 15-40 EAL - Optional Protective Functions - AU-2081 Magnetic Stripe Card Reader - AU-2081 Magnetic Stripe Card Reader	effectively protect against the many	3) Effective data encryption	
6) Protective Functions 7) Manage log history Protective Functions 1 Job Frace Deletes Graphic Data (after each job) 1 Lock job (when printing confidential documents) 1 Protect data by requiring department name and 8-digit password 2 Account Track 2 Prevent Unauthorized Use 2 Operation Log with 2,000-event memory 2 SDD Encryption 3 PDF Scan Encryption 4 PDF Scan Encryption 5 POF Scan Encryption 5 POF Scan Encryption 6 Pof Scan Encryption 7 Single Sign-on Authentication 7 Single Sign-on Authentication 7 SMTP Authentication for Email 7 SSL/TSL Compatibility for PS Web Connection, PS Data Administrator 7 Authority of PS Scan Encryption 8 POF Scan Encryption 8 POF Scan Encryption 9	security risks it faces.	4) Protect data from being altered, duplicated or deleted	
Protective Functions Job Erase — Deltes Graphic Data (after each job) Jock Job (when printing confidential documents) Protect data by requiring department name and 8-digit password Account Track Prevent Unauthorized Use Operation Log with 2,000-event memory SDB Encryption PDF Scan Encryption PDF Scan Encryption POF Scan Encryption Protective Functions Copy Protection Network Authentication Single Sign-on Authentication Single Sign-on Authentication SSIJ TSL Compatibility for PS Web Connection, PS Data Administrator and LDAP Sever Scan Data Encryption (TCP/socket SSL Compatibility) LDAP Authentication Box Operator Data Encryption PW Gerator Data Encryption Verification of Box Data Receipt P Address Filtering P P Gerantor Hate Encryption Possible Scan-to-USB Memory with User Authentication Scan-to-USB Memory with User Authentication SCANIMAC/Encryption FIPS 140-2 Compliance LEEE 2600.1 Security Ready SUS 1540 EAL Optional Protective Functions JU-102 Biometric Authentication JU-104 Biometric Authentication JU-105 Biometric Authentication JU-105 Biometric Authentication JU-106 Biometric Authentication JU-107 Biometric Authentication JU-108 Biometric Authentication		5) Prevent unauthorized access to data via the Internet	
Protective Functions - Job Erase — Deletes Graphic Data (after each job) - Lock Job (when printing confidential documents) - Protect data by requiring department name and 8-digit password - Account Track - Prevent Unauthorized Use - Operation Log with 2,000-event memory - SDD Encryption - PDF Scan Encryption - PP ortective Functions - Copy Protection - Network Authentication - Single Sign-on Authentication - Single Sign-on Authentication - SIMP Authentication Formal - SSL/TSL Compatibility for PS Web Connection, PS Data Administrator and LDAP Server - Scan Data Encryption (TCP/socket SSL Compatibility) - LDAP Authentication - Box Operator Data Encryption - Verification of Box Data Receipt - IP Address Filtering - IP 9 - Encrypted Network Password Printing - Scan-to-USB Memory with User Authentication - SyMIME/Encryption - Print-From-USB Memory with User Authentication - S/MIME/Encryption - IP 1610-2 Compliance - IEEE 2600.1 Security Ready - ISO 15-06 EAL Optional Protective Functions - Lik-Till Situderoler Antivirus - AU-102B inmetric Authentication Unit - AU-205H IC Card Reader - AU-205H IC Card Reader		6) Protect against cyber attacks	
Lock Job (when printing confidential documents) Protect data by requiring department name and 8-digit password Account Track Prevent Unauthorized Use Operation Log with 2,000-event memory SDD Encryption PDF Scan Encryption PDF Scan Encryption Protective Functions Copy Protection Network Authentication Single Sign-on Authentication Single Sign-on Authentication SIMTP Authentication for Email SSL/TSL Compatibility for PS Web Connection, PS Data Administrator and LDAP Server Scan Data Encryption (TCP/socket SSL Compatibility) LDAP Authentication Box Operator Data Encryption Verification of Box Data Receipt PAddress Filtering Protective Functions Concept Server Scan Do-USB Memory with User Authentication Print-from-USB Memory with User Authentication Print-from-USB Memory with User Authentication Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication Scan-to-USB Memory with User Authentication Print-from-USB Memory with USer Aut		7) Manage log history	
Protect data by requiring department name and 8-digit password Account Track Prevent Unauthorized Use Operation Log with 2,000-event memory SDD Encryption PDF Scan Encryption PDF Scan Encryption Protective Functions Copy Protection Network Authentication Single Sign-on Authentication SIMTP Authentication or Email SSL/TSL Compatibility for PS Web Connection, PS Data Administrator and LDAP Server Scan Data Encryption (TCP/socket SSL Compatibility) LDAP Authentication Box Operator Data Encryption Verification of Box Data Receipt PAddress Filtering PAddress Filtering PAddress Filtering Protective Function Scan-to-USB Memory with User Authentication PFInt-from-USB Memory With Us	Protective Functions	• Job Erase — Deletes Graphic Data (after each job)	
Account Track Prevent Unauthorized Use Operation Log with 2,000-event memory SDD Encryption PDF Scan Encryption Protective Functions Copy Protection Network Authentication Single Sign-on Authentication Simple Sign-on Authentication SMFP Authentication for Email SSL/TSL Compatibility for PS Web Connection, PS Data Administrator and LDAP Server Scan Data Encryption (TCP/socket SSL Compatibility) LDAP Authentication Box Operator Data Encryption Verification of Box Data Receipt IP Address Filtering IP v6 Encrypted Network Password Printing Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication FIPS 140-2 Compliance IEEE 2600.1 Security Ready ISO 1540 EAL Optional Protective Functions LK-116 Bitdefender Antivirus AU-205H IC Card Reader AU-205H IC Card Reader		Lock Job (when printing confidential documents)	
Prevent Unauthorized Use Operation Log with 2,000-event memory SDD Encryption PDF Scan Encryption PDF Scan Encryption Protective Functions Copy Protection Network Authentication Single Sign-on Authentication SIMP Authentication for Email SSL/TSL Compatibility for PS Web Connection, PS Data Administrator and LDAF Server Scan Data Encryption (TCP/socket SSL Compatibility) LDAP Authentication Box Operator Data Encryption Verification of Box Data Receipt PAddress Filtering IP V6 Encrypted Network Password Printing Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication S/MIME/Encryption FIPS 140-2 Compliance IEEE Z600.1 Security Ready SQL HOLD Bit Memory SQL HOLD Bit		Protect data by requiring department name and 8-digit password	
Operation Log with 2,000-event memory SDD Encryption PPF Scan Encryption PProtective Functions Copy Protection Network Authentication Single Sign-on Authentication SMTP Authentication for Email SSL/TSL Compatibility for PS Web Connection, PS Data Administrator and LDAP Server Scan Data Encryption (TCP/socket SSL Compatibility) LDAP Authentication Box Operator Data Encryption Verification of Box Data Receipt PP 6 Encrypted Network Password Printing Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication FIPS 140-2 Compliance FIEE 2600.1 Security Ready SD 1504 EAL Optional Protective Functions PLA-102 Biometric Authentication Unit AU-204H Magnetic Stripe Card Reader AU-205H IC Card Reader		Account Track	
SDD Encryption PDF Scan Encryption Protective Functions Copy Protection Network Authentication Single Sign-on Authentication SMTP Authentication for Email SSL/TSL Compatibility for PS Web Connection, PS Data Administrator and LDAP Server Scan Data Encryption (TCP/socket SSL Compatibility) LDAP Authentication Box Operator Data Encryption Protective Function Protective Function Protective Function FIFS 140-2 Compliance FIEEE 2600.1 Security Ready SDI Sol Stade End LK-16 Bitdefender Antivirus AU-102 Binnetric Authentication Unit AU-205H IC Card Reader AU-205H IC Card Reader AU-205H IC Card Reader AU-205H IC Card Reader		Prevent Unauthorized Use	
PDF Scan Encryption Protective Functions Copy Protection Network Authentication Single Sign-on Authentication SIMTP Authentication for Email SSL/TSL Compatibility for PS Web Connection, PS Data Administrator and LDAP Server Scan Data Encryption (TCP/socket SSL Compatibility) LDAP Authentication Box Operator Data Encryption Verification of Box Data Receipt PAddress Filtering Protective Filtering Protective Function Scan-to-USB Memory with User Authentication S/MIME/Encryption FIPS 140-2 Compliance FIEE 2600.1 Security Ready Sionetic Authentication Unit AU-204H Magnetic Stripe Card Reader AU-205H IC Card Reader		Operation Log with 2,000-event memory	
Protective Functions Copy Protection Opty Protection Network Authentication Single Sign-on Authentication SIMTP Authentication for Email SSL/TSL Compatibility for PS Web Connection, PS Data Administrator and LDAP Server Scan Data Encryption (TCP/socket SSL Compatibility) LDAP Authentication Box Operator Data Encryption Verification of Box Data Receipt PAddress Filtering IP V6 Encrypted Network Password Printing Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication Print-from-USB Memory with User Authentication S/MIME/Encryption FIPS 140-2 Compliance IEEE 2600.1 Security Ready ISO 1540 EAL Optional Protective Functions LK-116 Bitdefender Antivirus AU-102 Biometric Authentication Unit AU-204H Magnetic Stripe Card Reader AU-205H IC Card Reader		SDD Encryption	
- Copy Protection - Network Authentication - Single Sign-on Authentication - SMTP Authentication for Email - SSL/TSL Compatibility for PS Web Connection, PS Data Administrator and LDAP Server - Scan Data Encryption (TCP/socket SSL Compatibility) - LDAP Authentication - Box Operator Data Encryption - Verification of Box Data Receipt - IP Address Filtering - IP v6 - Encrypted Network Password Printing - Scan-to-USB Memory with User Authentication - Print-from-USB Memory with User Authentication - Print-from-USB Memory with User Authentication - Print-from-USB Memory with User Authentication - FIPS 140-2 Compliance - IEEE 2600.1 Security Ready - ISO 1540 EAL Optional Protective Functions - LK-116 Bitdefender Antivirus - AU-204H Magnetic Stripe Card Reader - AU-205H IC Card Reader		PDF Scan Encryption	
Network Authentication Single Sign-on Authentication SMTP Authentication for Email SSL/TSL Compatibility for PS Web Connection, PS Data Administrator and LDAP Server Scan Data Encryption (TCP/socket SSL Compatibility) LDAP Authentication Box Operator Data Encryption Verification of Box Data Receipt IP Address Filtering IP V6 Encrypted Network Password Printing Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication Print-from-USB Memory with User Authentication S/MIME/Encryption FIPS 140-2 Compliance IEEE 2600.1 Security Ready ISO 1540 EAL Optional Protective Functions PAU-205H IC Card Reader AU-205H IC Card Reader		Protective Functions	
Single Sign-on Authentication SMTP Authentication for Email SSL/TSL Compatibility for PS Web Connection, PS Data Administrator and LDAP Server Scan Data Encryption (TCP/socket SSL Compatibility) LDAP Authentication Box Operator Data Encryption Verification of Box Data Receipt IP Address Filtering IP v6 Encrypted Network Password Printing Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication FIPS 140-2 Compliance IEEE 2600.1 Security Ready ISO 1540 EAL Optional Protective Functions LLK-116 Bitdefender Antivirus AU-204H Magnetic Stripe Card Reader AU-205H IC Card Reader		Copy Protection	
- SMTP Authentication for Email - SSL/TSL Compatibility for PS Web Connection, PS Data Administrator and LDAP Server - Scan Data Encryption (TCP/socket SSL Compatibility) - LDAP Authentication - Box Operator Data Encryption - Verification of Box Data Receipt - IP Address Filtering - IP v6 - Encrypted Network Password Printing - Scan-to-USB Memory with User Authentication - Print-from-USB Memory with User Authentication - Print-from-USB Memory with User Authentication - S/MIME/Encryption - FIPS 140-2 Compliance - IEEE 2600.1 Security Ready - ISO 1540 EAL Optional Protective Functions Optional Protective Functions - AU-102 Biometric Authentication Unit - AU-205H IC Card Reader - AU-205H IC Card Reader		Network Authentication	
SSL/TSL Compatibility for PS Web Connection, PS Data Administrator and LDAP Server Scan Data Encryption (TCP/socket SSL Compatibility) LDAP Authentication Box Operator Data Encryption Verification of Box Data Receipt IP Address Filtering IP v6 Encrypted Network Password Printing Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication Firth-from-USB Memory with User Authentication S/MIME/Encryption FIPS 140-2 Compliance IEEE 2600.1 Security Ready ISO 1540 EAL Optional Protective Functions AU-102 Biometric Authentication Unit AU-204H Magnetic Stripe Card Reader AU-205H IC Card Reader		Single Sign-on Authentication	
and LDAP Server Scan Data Encryption (TCP/socket SSL Compatibility) LDAP Authentication Box Operator Data Encryption Verification of Box Data Receipt IP Address Filtering IP v6 Encrypted Network Password Printing Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication Print-from-USB Memory with User Authentication FIPS 140-2 Compliance IEEE 2600.1 Security Ready So 1540 EAL Optional Protective Functions AU-102 Biometric Authentication Unit AU-204H Magnetic Stripe Card Reader AU-205H IC Card Reader		SMTP Authentication for Email	
Scan Data Encryption (TCP/socket SSL Compatibility) LDAP Authentication Box Operator Data Encryption Verification of Box Data Receipt IP Address Filtering IP v6 Encrypted Network Password Printing Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication Print-from-USB Memory with User Authentication S/MIME/Encryption FIPS 140-2 Compliance IEEE 2600.1 Security Ready ISO 1540 EAL Optional Protective Functions AU-204H Magnetic Stripe Card Reader AU-205H IC Card Reader		SSL/TSL Compatibility for PS Web Connection, PS Data Administrator	
LDAP Authentication Box Operator Data Encryption Verification of Box Data Receipt IP Address Filtering IP v6 Encrypted Network Password Printing Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication Print-from-USB Memory with User Authentication FIPS 140-2 Compliance IEEE 2600.1 Security Ready ISO 1540 EAL Optional Protective Functions LK-116 Bitdefender Antivirus AU-102 Biometric Authentication Unit AU-204H Magnetic Stripe Card Reader AU-205H IC Card Reader		and LDAP Server	
Box Operator Data Encryption Verification of Box Data Receipt IP Address Filtering IP v6 Encrypted Network Password Printing Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication FIRS 140-2 Compliance IEEE 2600.1 Security Ready ISO 1540 EAL Optional Protective Functions LK-116 Bitdefender Antivirus AU-102 Biometric Authentication Unit AU-204H Magnetic Stripe Card Reader AU-205H IC Card Reader		Scan Data Encryption (TCP/socket SSL Compatibility)	
Verification of Box Data Receipt IP Address Filtering IP v6 Encrypted Network Password Printing Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication S/MIME/Encryption FIPS 140-2 Compliance IEEE 2600.1 Security Ready ISO 1540 EAL Optional Protective Functions LK-116 Bitdefender Antivirus AU-102 Biometric Authentication Unit AU-204H Magnetic Stripe Card Reader AU-205H IC Card Reader		LDAP Authentication	
IP Address Filtering IP v6 Encrypted Network Password Printing Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication S/MIME/Encryption FIPS 140-2 Compliance IEEE 2600.1 Security Ready ISO 1540 EAL Optional Protective Functions LK-116 Bitdefender Antivirus AU-102 Biometric Authentication Unit AU-204H Magnetic Stripe Card Reader AU-205H IC Card Reader		Box Operator Data Encryption	
• IP v6 • Encrypted Network Password Printing • Scan-to-USB Memory with User Authentication • Print-from-USB Memory with User Authentication • S/MIME/Encryption • FIPS 140-2 Compliance • IEEE 2600.1 Security Ready • ISO 1540 EAL Optional Protective Functions • LK-116 Bitdefender Antivirus • AU-102 Biometric Authentication Unit • AU-204H Magnetic Stripe Card Reader • AU-205H IC Card Reader		Verification of Box Data Receipt	
Encrypted Network Password Printing Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication S/MIME/Encryption FIPS 140-2 Compliance IEEE 2600.1 Security Ready ISO 1540 EAL Optional Protective Functions LK-116 Bitdefender Antivirus AU-102 Biometric Authentication Unit AU-204H Magnetic Stripe Card Reader AU-205H IC Card Reader		• IP Address Filtering	
Scan-to-USB Memory with User Authentication Print-from-USB Memory with User Authentication S/MIME/Encryption FIPS 140-2 Compliance IEEE 2600.1 Security Ready ISO 1540 EAL Optional Protective Functions LK-116 Bitdefender Antivirus AU-102 Biometric Authentication Unit AU-204H Magnetic Stripe Card Reader AU-205H IC Card Reader		• IP v6	
Print-from-USB Memory with User Authentication S/MIME/Encryption FIPS 140-2 Compliance IEEE 2600.1 Security Ready ISO 1540 EAL Optional Protective Functions LK-116 Bitdefender Antivirus AU-102 Biometric Authentication Unit AU-204H Magnetic Stripe Card Reader AU-205H IC Card Reader		Encrypted Network Password Printing	
S/MIME/Encryption FIPS 140-2 Compliance IEEE 2600.1 Security Ready ISO 1540 EAL Optional Protective Functions LK-116 Bitdefender Antivirus AU-102 Biometric Authentication Unit AU-204H Magnetic Stripe Card Reader AU-205H IC Card Reader		Scan-to-USB Memory with User Authentication	
FIPS 140-2 Compliance IEEE 2600.1 Security Ready ISO 1540 EAL Optional Protective Functions LK-116 Bitdefender Antivirus AU-102 Biometric Authentication Unit AU-204H Magnetic Stripe Card Reader AU-205H IC Card Reader		Print-from-USB Memory with User Authentication	
IEEE 2600.1 Security Ready ISO 1540 EAL Optional Protective Functions LK-116 Bitdefender Antivirus AU-102 Biometric Authentication Unit AU-204H Magnetic Stripe Card Reader AU-205H IC Card Reader		S/MIME/Encryption	
- ISO 1540 EAL Optional Protective Functions - LK-116 Bitdefender Antivirus - AU-102 Biometric Authentication Unit - AU-204H Magnetic Stripe Card Reader - AU-205H IC Card Reader		• FIPS 140-2 Compliance	
Optional Protective Functions • LK-116 Bitdefender Antivirus • AU-102 Biometric Authentication Unit • AU-204H Magnetic Stripe Card Reader • AU-205H IC Card Reader		• IEEE 2600.1 Security Ready	
• AU-102 Biometric Authentication Unit • AU-204H Magnetic Stripe Card Reader • AU-205H IC Card Reader		• ISO 1540 EAL	
• AU-204H Magnetic Stripe Card Reader • AU-205H IC Card Reader	Optional Protective Functions	LK-116 Bitdefender Antivirus	
• AU-205H IC Card Reader		AU-102 Biometric Authentication Unit	
		AU-204H Magnetic Stripe Card Reader	
• AU-211P CAC/PIV Solution with Certificate		• AU-205H IC Card Reader	
		AU-211P CAC/PIV Solution with Certificate	

PAPER CONSIDERATIONS

PAPER SIZE CONVERSION CHART

Paper	Letter	Letter R	Legal	Tabloid	Statement	Statement R
Measurement	8.5" x 11"	11" x 8.5"	8.5" x 14"	11" x 17"	5.5" x 8.5"	8.5" x 5.5"

PAPER CONSIDERATIONS

PAPER SIZE CONVERSION CHART

Paper	Letter	Letter R	Legal	Statement	Statement R
Measurement	8.5" x 11"	11" x 8.5"	8.5" x 14"	5.5" x 8.5"	8.5" x 5.5"

PAPER WEIGHT CONVERSION CHART

								C	ALIPER
gsm	Bond	Offset	Cover	Tag	Index	Point	Bristol	inches	mm
60.20	16	40	22	37	33	3.2	27.4	0.0032	0.081
67.72	18	45	24	41	37	3.6	30.9	0.0036	0.092
75.20	20	50	28	46	42	3.8	34.3	0.0038	0.097
90.30	24	60	33	56	50	4.8	41.2	0.0048	0.120
105.35	28	70	39	64	58	5.8	48.1	0.0058	0.147
109.11	29	73	40	62	60	6.0	49.8	0.0060	0.152
116.63	31	81	45	73	66	6.1	53.2	0.0061	0.155
131.68	35	90	48	80	74	6.2	60.1	0.0062	0.157
135.45	36	90	50	82	75	6.8	61.8	0.0068	0.173
146.73	39	100	54	90	81	7.2	67.0	0.0072	0.183
150.50	40	100	56	93	83	7.3	68.7	0.0073	0.185
161.78	43	110	60	100	90	7.4	73.8	0.0074	0.188
165.55	44	110	61	02	92	7.6	75.5	0.0076	0.193
176.83	47	120	65	108	97	8.0	80.7	0.0078	0.198
199.41	53	135	74	122	110	9.0	91.0	0.0085	0.216
203.17	54	137	75	125	113	9.0	92.7	0.0090	0.229
218.22	58	146	80	134	120	9.5	99.6	0.0092	0.234
244.56	65	165	90	150	135	10.0	111.6	0.0095	0.241
252.08	67	170	93	156	140	10.5	115.1	0.0100	0.250
270.90	72	183	100	166	150	11.0	123.7	0.0110	0.289
285.95	76	192	105	175	158	13.0	130.5	0.0130	0.330
308.52	82	208	114	189	170	14.0	140.8	0.0140	0.356
312.00	87	220	120	200	180	15.0	142.4	0.0150	0.380
385.06	105	267	146	244	220	18.0	175.8	0.0175	0.445

PAPER TYPE SPECIFICATIONS

Normal (Plain Paper)	The Normal paper is used for copying in general and is called "PPC paper." The normal paper is usually not a recycled paper. Specify [Normal] to the tray to which the normal paper or the recycled paper is loaded for copying.			
Recycled Paper	Recycled Paper is identified as recycled paper along with a designation as to the percentage of the paper that is actually made from recycled materials. Generally speaking, these devices will support recycled paper weighing between 20 lb and 28 lb bond.			
Thick Paper 1	Thick Paper 1 is paper weighing between 28 lb and 32 lb bond lt can be fed via any paper tray.			
Thick Paper 1+	Thick Paper 1+ is paper weighing between 32.25 to 41.75 lb bond. It can be fedvia any paper tray.			
Thick Paper 2	Thick Paper 2 is paper weighing between 32 lb and 53 lb bond. It can be fed via any paper tray.			
Envelopes	Specify (Envelope) for bypass tray.			
Postcards	A Postcard is defined as a rectangular piece of the thick paper or thin cardboard. This product series supports 4" x 6" size postcards. Postcards are fed only via the Bypass Tray.			
Coated Paper	Paper with a coating that makes its surface very smooth. Many coated stocks are shiny or glossy, while others have a dull matte finish. It can be fe from Tray 1 or the Bypass Tray.			

RECOMMENDED PAPER STOCKS

Class.	Weight	Brand of Paper	Size
Plain Paper — Color			
Plain Paper	20 lb. Bond (75 gr)	Domtar Recycled Copy(30% Post Consumer)	8.5" x 11"
Plain Paper	22 lb. Bond(80 gr)	Konica Minolta CF Paper	8.5" X 11"
Plain Paper	22 lb. Bond(80 gr)	Konica Minolta CF Paper	11" X 17"
Plain Paper	22 lb. Bond(80 gr)	Konica Minolta CF Paper	12" X 18"
Plain Paper	24 lb. Bond (89 gr)	SMART Carnival Stellar White	8.5" x 11"
Plain Paper	24 lb. Bond (89 gr)	SMART Carnival White	8.5" x 11"
Plain Paper	24 lb. Bond (90 gr)	SMART Synergy Bond 25% Cotton	8.5" x 11"
Plain Paper	24 lb. Bond (90 gr)	Domtar Microprint Laser	8.5" x 11"
Plain Paper	24 lb. Bond (90 gr)	Mohawk Color Copy 98 Bright White	8.5" x 11"
Thick 1	28 lb. Bond(105 gr)	Konica Minolta CF Paper	8.5" X 11"
Thick 1	28 lb. Bond(105 gr)	Konica Minolta CF Paper	11" X 17"
Thick 1	28 lb. Bond (105 gr)	Konica Minolta CF Paper	12" X 18"
Thick 1	28 lb. Bond (105 gr)	Domtar Microprint Color Copy	8.5" x 11"
Thick 1	32 lb. Bond(120 gr)	Hammermill Color Copy	8.5" X 11"
Thick 1	32 lb. Bond (120 gr)	Hammermill Color Copy Paper – Photo White	8.5" x 11"
Thick 2	60 lb. Cover(163 gr)	Hammermill Color Copy	8.5" X 11"

Plain Paper — B & W			
Plain Paper	20 lb. Bond (75 gr)	Hammermill Tidal MP	8.5" X 11"
Double-Sided Glossy			
Thick 1	32 lb. Bond (120 gr)	Mohawk Color Copy Gloss Pure White	8.5" x 11"
Thick 1	80 lb. Text (118 gr)	Sappi Opus Gloss	8.5" x 11"
Thick 1	90 lb. Text (133 gr)	SMART Kromekote Laser High Gloss Coated Two Sides*	8.5" x 11"
Cover Stock			
Thick 2	60 lb Cover (163 gr)	Domtar Microprint Color Copy Cover	8.5" x 11"
Thick 2	65 lb Cover (176 gr)	Domtar Microprint Color Copy Cover 8.5" x	8.5" x 11"
Labels			
Avery Dennison 5889 Post	tcard		8.5" x 11"
Avery Dennison 6870 (30 I	abels per sheet)		8.5" x 11"
Avery Dennison 6873 (8 la	bels per sheet)		8.5" x 11"
Avery Dennison 6876 (2 la	bels per sheet)		8.5" x 11"
Avery 6878 4-UP labels for	r Color Laser		8.5" x 11"
Envelopes			
Envelope	24 lb.	Preservation Wove 5789 #6 3/4	3.85" x 6.5" (98 x 165 mm)
Tab Dividers			
Avery Dennison 20406 (lo	ng edge only)		8.5" x 11"
Specialty Paper			
Thick 2	_	TECHNI-Print 9721PO* T-shirt Transfer Paper**	8.5" x 11"

^{*} Paper cannot be used in a high humidity environment.

^{**}T-Shirt Transfer Paper: The 4750i/4050i Series should not be used solely for T-shirt transfer applications. T-Shirt transfer paper should be used on a limited basis, not to exceed a 250-sheet per run maximum. If a misfeed should occur, clear it immediately (due to the odor) and then run 15-25 sheets of regular plain paper (20 lb) through the device to clean the fusing rollers.

T-Shirt Transfer paper cannot be used in high humidity environments.

HOW TO BUILD A SYSTEM FOR THE BIZHUB 4750I/4050I DIGITAL PRINTER/ **COPIER/SCANNER/FAX (FROM START TO FINISH)**

STEP 1: BASE UNIT

4750i Digital Printer/Copier/ Scanner/Fax

> Includes PS, PCL & XPS Controller, 5 GB Memory, 250 GB SSD, Standard Wireless Connectivity and Web Browser, Standard Super G3 Fax, Standard Gigabit Ethernet, Duplex Unit, 80-sheet Dual Scan Document Feeder, Standard USB 2.0 (supports local printing), Toner (Yield: 20K) and Imaging Unit.

4050i Digital Printer/Copier/Scanner Includes PS, PCL & XPS Controller, 5 GB Memory, 250 GB SSD, Standard Wireless Connectivity and Web Browser, Standard Gigabit Ethernet, Duplex Unit, 80-sheet Dual Scan Document Feeder, Standard USB 2.0

20K) and Imaging Unit.

(supports local printing), Toner (Yield:

STEP 2: PAPER HANDLING OPTIONS

- PF-P21 Paper Feed Unit (500 sheets, maximum 2)
- PF-P25 Height Adjustment Unit

bizhub 4750i


DK-P05 Copy Desk

STEP 3: FINISHING OPTION:

- CS-1 Convenience Stapler
- FS-P04 Off-line Stapler

STEP 4: ADDITIONAL OPTIONS:

- AU-102 BIOMETRIC AUTHENTICATION*
- AU-205H IC CARD READER**
- MK-P08 MOUNT KIT FOR CARD READER
- **EK-P08 USB CONNECTION KIT**
- EK-P09 USB CONNECTION KIT -BLUETOOTH
- KP-102 10-KEY PAD
- FK-517 FAX KIT (OPTION FOR 4050I ONLY)
- WT-P03 WORKING TABLE
- PDF/A (1A/1B) AND LINEARIZED PDF SUPPORT)
- LK-104 V3 I-OPTION LICENSE KIT (VOICE GUIDANCE)
- LK-105 V4 (SEARCHABLE PDF)
- LK-106 I-OPTION LICENSE KIT (BARCODE FONT PRINTING)
- LK-107 I-OPTION LICENSE KIT (UNICODE FONT PRINTING)
- LK-108 I-OPTION LICENSE KIT (OCR FONT PRINTING)
- LK-110 V2 I-OPTION LICENSE KIT (OOXML FILE CONVERSION,



ACCESSORY OPTIONS FOR BIZHUB 4750I/4050I DIGITAL PRINTER/COPIER/SCANNER/FAX

ACCESSORIES	ITEM NO.	DESCRIPTION	NOTES
BASE UNIT			
4750i	ACT8011	Digital Printer/Copier/Scanner/Fax	Includes PS, PCL & XPS Controller, 5 GB Standard Memory, 250 GB SSD, Standard Wireless Connectivity and Web Browser, Standard Super G3 Fax, Standard Gigabit Ethernet, Duplex Unit, 80-sheet Dual Scan Document Feeder, Standard USB 2.0 (supports local printing), Toner (Yield: 20K) and Imaging Unit.
4050i	ACT9011	Digital Printer/Copier/Scanner/Fax	Includes PS, PCL & XPS Controller, 5 GB Standard Memory, 250 GB SSD, Standard Wireless Connectivity and Web Browser, Standard Gigabit Ethernet, Duplex Unit, 80-sheet Dual Scan Document Feeder, Standard USB 2.0 (supports local printing), Toner (Yield: 20K) and Imaging Unit.
PAPER HANDLING	OPTIONS		Toner (Tield: 2017) and imaging one.
DK-P05	135900	Copy Desk	Adds storage and mobility. Brings MFP up to working height.
PF-P21	ACEVWY1	Paper Feed Unit	Lower feeder unit adds 500 sheets of paper capacity (8.5" x 11" or 8.5" x 14"). Add up to 2. Total paper capacity: 1600 sheets
PF-P25	AAJUW12	Height Adjustment Unit	Increases height of machine.
FINISHING OPTIO	NS		
CS-1	7640013463	Convenience Stapler	Standalone electronic stapler.
FS-P04	ACCGWY1	Stapler	Provides 20-sheet corner stapling off-line finisher.
ADDITIONAL OPT	IONS		
AU-102	A0X9WY1	Biometric Authentication Unit	Scans finger vein patterns to enable users to gain access to the device. Requires WT-P03 Working Table.
AU-204H	7640013468	Magnetic Stripe Card Reader	Allows authorized access to the MFP using Magnetic Stripe Cards.
			Requires WT-P03 Working Table.
AU-205H	R5427000136466	IC Card Reader	Allows access to the MFP via HID Proximity Cards. Working table recommended. Supports IC card types.
AU-211P	_	CAC/PIV Solution with Certificate	Requires WT-P03 Working Table. Contact your local Government Account Manager for information.
EK-P08	ACCTWY1	Local USB Interface Kit	Required to connect optional external keyboard and supports Voice Guidance functions available with optional LK-104 v3.
EK-P09	ACCVWY1	Local USB Interface Kit	Required to connect optional external keyboard, provides bluetooth printing support for mobile phone link and supports Voice Guidance functions available with optional LK-104 v3.
EM-908	ACDJWY1	Expanded Memory SSD	1 TB SSD to increase storage space
External Keyboard	7640006869	External Keyboard	Computer type keyboard for alphanumeric data entry (alternative to the standard QWERTY keyboard available on the MFP's LCD). Requires either EK-P08 or EK-609 and KH-P02.
FK-517	AA1K011	Fax Kit	Adds Super G3 fax functionality for the bizhub 4050i (standard for the bizhub 4750i).
KH-P02	ACCFWY1	Keyboard Holder	Holds the optional QWERTY keyboard in place on the MFP.
KP-102	AACJWY1	10-Key Pad	Optional 10 Key Pad. Supports Voice Guidance function available with optional
	•		LK-104 v3 i-Option License Kit. Affixes to the right-hand side of the control panel.
LK-104 v3	A0PD017	i-Option License Kit	Provides Voice Guidance functionality.
LK-105 v4	A0PD11T	i-Option License Kit	Provides Searchable PDF functionality. Please note that the LK-110 v2 supports the same functions as the LK-105 v4, therefore, both license kits cannot be installed on the same device.
LK-106	A0PD119	i-Option License Kit	Provides Bar Code Font printing support.
LK-107	A0PD11F	i-Option License Kit	Provides Unicode Font printing support.
LK-108	A0PD11G	i-Option License Kit	Provides OCR Font printing support.
LK-110 v2	AOPD11U	i-Option License Kit	Provides DOCX, XLSX format file conversion, Fax to searchable PDF, convert print data in box to compact PDF, combines LK-102 (encrypted PDF) & LK-105 (searchable PDF/OCR) functionality. Please note that if you install the LK-110 V2 on a device, you cannot install the LK-105 v4 on the same device.
LK-111	A0PD11K	i-Option License Kit	Provides ThinPrint client support.
LK-116	A0PDAA1	i-Option License Kit	Bitdefender® antivirus provides real time scanning of all incoming and outgoing data.
MK-P08	ACCKWY1	Mount Kit	Internal mount kit for AU-205H HID Card Authentication Units. Required if card readers are not mounted using the WT-P03 Working Table.
UK-P19	ACCNWY1	Double feed detection kit	Multi-feed detector to reduce errors and paper jams
WT-P03	ACCRWY1	Working Table	Recommended for use with FS-P04, CS-1 or Authentication Units.

CONSUMABLE YIELDS

*Based on 5% total converage

CONSUMABLE	ITEM NO.	YIELD
Toner - Black	ACTD030	20,000
IU-P35K Drum Imaging Unit – Black	AAJV01D	200,000
Waste Toner Box	ACDN0Y1	32,000
Fusing Unit	AAJRR70300	400,000
		* Based on 5% total coverage.





Single Function Printers



bizhub 4000i Black and white A4 printer











CUSTOMER BENEFITS



Mobile connectivityPrint anytime from anywhere with Konica Minolta's innovative mobile technologies



Sustainability
Eco-friendly performance
thanks to the integrated Eco mode which lowers energy consumption, thus saving costs



Small Footprint
Its small footprint and compact
design make it perfectly suitable
even for the smallest office as
well as desktop use

OPTIONS







FINISHING FUNCTIONALITIES





Duplex

Corner stapling (offline)

DESCRIPTIONS

MEDIA INPUT

PF-P23 Paper tray	250 sheets; Ltr, LgI; 60–120 gsm
PF-P24 Paper tray	520 sheets; Ltr, Lgl; 60–120 gsm

MEDIA OUTPUT

CS-1 Convenience stapler 50-sheet off-line stapling

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS

0.0.120.1201000	
Panel size/resolution	1 line LCD
System memory (standard/max)	256 MB (standard/max)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0; Wi-Fi 802.11 b/g/n
Network protocols	TCP/IP (IPv4 / IPv6); LPD; IPP; SNMP; HTTP; HTTP(S)
Paper input capacity (standard/max)	570 sheets / 1,610 sheets (standard/max)
Paper Tray 1	1x 520 sheets; 4.1"x5.8" to 8.5"x14"; 60–120 gsm
Paper Tray 2 & 3 (option)	250 or 500 sheets each; 5.8"x8.25" to 8.5"x14"; 60–120 gsm
Manual bypass	50 sheets; 4.1"x5.8" to 8.5"x14"; custom sizes; 60–200 gsm
Automatic duplexing	8.5"x14"; 60–105 gsm
Output Capacity (standard)	Max. 150 sheets
Print volume (monthly)	Rec. 5,000 pages; Max. 100,000 pages
Toner lifetime	Black up to 12,000 pages
Imaging unit lifetime	50,000
Power consumption	110-120 V / 50/60 Hz; Less than 620 W
System dimension (W x D x H)	14.7"x15.3"x11.3" (without options)
System weight	Approx. 27lbs (without options)

PRINTER SPECIFICATIONS

Imaging technology	Laser
Toner technology	Polymerized Toner
Print resolution	1,200 x 1,200 dpi
Print Speed Ltr (mono)	Up to 42 ppm
1st print out time Ltr (mono)	7.2 sec.
Warm-up time	Approx. 27 sec.
Page description language	PCL 6 (XL3.0); PostScript 3; XPS
Operating Systems	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64);
	Windows Server 2008 (32/64); Windows Server 2008 R2;
	Windows Server 2012; Windows Server 2012 R2;
	Windows Server 2016; Windows Server 2019;
	Macintosh OS X 10.10 or later; Linux
Printer fonts	85 PCL Latin; 66 PostScript 3 Emulation Latin
Mobile Printing	Mopria (Android);
	Konica Minolta Print Service (Android);
	Konica Minolta Mobile Print (iOS/Android/Windows 10 Mobile);
	Google Cloud Print; WiFi Direct

SYSTEM FEATURES

SSL2; SSL3 and TLS1.0/1.1/1.2 network communication;	
IPsec support; IEEE 802.1x support; Secure print; Kerberos	
Active Directory support	
(user name + password + e-mail + smb folder)	
Net Care Device Manager; Web Connection;	
Driver Packaging Utility	

PARTNERSHIP.

eDiscovery Services

Konica Minolta can help give shape to your ideas and partner with you to achieve your corporate objectives. Contact us to realize opportunities in:

INFORMATION MANAGEMENT Enterprise Content Management (ECM) Document Management **Automated Workflow Solutions Business Process Automation** Security and Compliance Mobility

IT SERVICES

TECHNOLOGY Application Services Office Multifunction Business Solutions Commercial and Production Printers Cloud Services IT Security Industrial Printers Managed IT Services Wide Format Printers IT Consulting & Projects 3D Printers Apple Managed Services Scanners Managed Voice Services Security Surveillance Systems Technology Implementation Laptops, Desktops and Computer Hardware and Deployment Servers and Networking Equipment

> Managed Print Services (MPS) Managed Enterprise Services

For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com























KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com













Color printer











CUSTOMER BENEFITS



Intuitive operabilityOperate the bizhub like a smartphone or tablet with fully customized user interface



Mobile connectivityPrint anytime from anywhere with Konica Minolta's innovative mobile technologies



Services


Efficient printer fleet management, including automatic consumables delivery, pro-active maintenance and remote setup



Sustainability

Numerous eco features reduce energy consumption and costs

OPTIONS













FINISHING FUNCTIONALITIES





Duplex

stapling (offline)

bizhub C3300i Datasheet

DESCRIPTIONS

CONNECTIVITY

UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
EK-P08 USB I/F kit	USB keyboard connection
EK-P09 USB I/F kit	USB keyboard connection; Bluetooth
EK-P10 NFC interface	To connect with Android mobile devices
AU-102 Biometric authenticaton	Finger vein scanner
AU-205H ID card reader	Various ID card technologies
MK-P08 Mount kit	Installation kit for ID card reader
OTHERS	

MEDIA OUTPUT

PF-P21 Paper tray	500 sheets, A4, 60-90 gsm (Max. 1)
PF-P25 Height adjustment unit To achieve comfortable height for operation	
DK-P05 Copier desk	Provides storage space for print media and other materials
MEDIA OUTPUT	
FS-P04 Off-line stapler	20-sheet off-line stapling

WT-P03 Working table	Authentication device placement
KP-P03 10-Key pad	For use instead of touchscreen
KH-P02 Keyboard holder	To place USB keyboard
Keyboard	Keyboard for alphanumeric data entry

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS

Panel size/resolution	7" / 800 x 480
System memory (standard/max)	3 GB
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11 b/g/n (optional)
Paper input capacity (standard/max)	600 sheets/1,100 sheets
Paper tray input (standard)	1x 500 sheets; 3.9" x 5.8" to 8.5" x 11"; 60–210 gsm
Paper tray input (optional)	1x 500 sheets; letter/legal; 60–90 gsm
Manual bypass	100 sheets; 3.5" x 8.8" to 8.5" x 14"; Custom sizes; 60–210 gsm
Automatic duplexing	4.7" x 8.8" to 8.5" x 14"; 60–210 gsm
Finishing modes (optional)	Group; Sort; Staple (offline)
Output capacity (standard)	Max. 250 sheets
Print volume (monthly)	Rec. 6,500 pages; Max. 176,000 pages
Toner lifetime	Black up to 13,000 pages
	CMY up to 9,000 pages
Imaging unit lifetime	Black up to 200,000 pages
	CMY up to 100,000 pages
Power consumption	110-120 V / 50/60 Hz; Less than 1.45 kW
System dimension (W x D x H)	16.5" x 20.8" x 18.6" (without options)
System weight	Approx. 73 lb (without options)

PRINTER SPECIFICATIONS

Imaging technology	Laser
Toner technology	Simitri® HD polymerized toner
Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Print Speed letter (mono/color)	Up to 35/35 ppm
1st print out time letter (mono/color)	8.0/8.7 sec.
	Warm-up time Approx. 13 sec. in mono; 15 sec. in color ²
Page description language	PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
Operating System	Windows 7 (32/64); Windows 8/8.1 (32/64); Windows 10 (32/64);
	Windows Server 2008 (32/64); Windows Server 2008 R2;
	Windows Server 2012; Windows Server 2012 R2;
	Windows Server 2016; Windows Server 2019;
	Macintosh OS X 10.10 or later; Unix; Linux; Citrix
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	AirPrint (iOS); Mopria (Android);
	Konica Minolta Mobile Print (iOS/Android/Windows 10 Mobile);
	Mobile Authentication and Pairing (iOS/Android)
	Optional: WiFi Direct

SYS		

SISIEMITEATORES	
Security Functions (standard)	ISO 15408 HCD-PP Common Criteria (in evalutation); IP filtering
	and port blocking; SSL2; SSL3 and TLS1.0/1.1/1.2 network
	communication; IPsec support; IEEE 802.1x support;
	User authentication; Authentication log; Secure print; Kerberos;
	Print user data encryption
Accounting (standard)	Up to 100 user accounts; Active Directory support
	(user name + password)
Accounting Functions (optional)	Biometric authentication (finger vein scanner);
	ID card authentication (ID card reader);
	Authentication by mobile device (Android/iOS)
Software	Net Care Device Manager; Data Administrator; Web Connection;
	Print Status Notifier; Driver Packaging Utility; Log Management
	Utility

- ¹ Maximum monthly copy/print volume supported under standard vendor supplied service. Defines the upper end of the expected customer volume for the device. Customers should consider multiple machines if average monthly volume approaches duty cycle on a continual basis.
- ² Warm-up time may vary depending on the operating environment and usage
- All specifications refer to letter-size paper of 80 gsm.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a
 particular page size (5% coverage of letter). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
 Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby

PARTNERSHIP.

Konica Minolta can help give shape to your ideas and partner with you to achieve your corporate objectives. Contact us to realize opportunities in:

INFORMATION MANAGEMENT	IT SERVICES	TECHNOLOGY
Enterprise Content Management (ECM)	Application Services	Office Multifunction Business Solutions
Document Management	Cloud Services	Commercial and Production Printers
Automated Workflow Solutions	IT Security	Industrial Printers
Business Process Automation	Managed IT Services	Wide Format Printers
Security and Compliance	IT Consulting & Projects	3D Printers
Mobility	Apple Managed Services	Scanners
eDiscovery Services	Managed Voice Services	Security Surveillance Systems
	Technology Implementation and Deployment	Laptops, Desktops and Computer Hardware
		Servers and Networking Equipment
		Managed Print Services (MPS)
		Managed Enterprise Services

For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com























KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com











Black & White single function printer









Table of Contents	
Specifications	3
Duty Cycle	5
Environmental Requirements	6
Basic Configuration	6
Space Requirements	7
Accessories	8
Print Controller (Standard)	13
Print Drivers	13
Security	14
Software Tools	14
Paper Considerations	15
Paper Weight Conversion Chart	15
Paper Type Specifications	16
How to Build a System	18
Accessory Options	19



BIZHUB 4700I SPECIFICATIONS

TYPE	PRINTER
Photoconductor	OPC
Developing System	Dry-type dual-component HMT developing
Resolution	1200 x 1200 dpi, 600 x 600 dpi
Paper	Thin Paper (16 lb to 20 lb)
	Plain Paper (20 lb to 28 lb)
	Plain Paper + (24.75 lb to 28 lb)
	Thick Paper 1 (24.25 lb to 32 lb)
	Thick Paper 2 (32 lb to 53 lb)
	Recycled Paper (20 lb to 28 lb)
	Special Paper (20 lb to 28 lb)
	Letterhead (20 lb to 28 lb)
	Color Paper (20 lb to 28 lb)
	Envelopes, label sheets, postcards
Print Sizes	1st Tray:
	3.9" x 5.8" to 8.5" x 11.7"
	Bypass Tray:
	3.5" x 5.8" to 8.5" x 14"
Paper Tray Capacity	1st Tray:
	Thin Paper/Plain Paper/Recycled Paper/Special Paper/Color Paper/1-Sided Special Paper: 500 sheets
	Thick Paper 1/12: 20 sheets
	Envelopes: 30 sheets
	Label sheets: 20 sheets
	Postcards: 20 sheets
	Bypass Tray:
	Plain Paper/Recycled Paper/Special Paper/Letterhead/Color Paper/
	1-Sided Special Paper: 100 sheets
	Thick Paper 1/2/Postcards: 20 sheets
	Envelopes: 10
	Label Sheets: 20 sheets
	Postcards: 20 sheets
Warm-Up Time	Less than 18 seconds (at room temperature/73° F)

BIZHUB 4700I SPECIFICATIONS


DESCRIPTION	DESCRIPTION
Image Loss Width	Leading edge: 0.17"
	Trailing edge: 0.17"
	Rear edge: 0.17"
	Front edge: 0.17"
First Print	7.4 sec. or less
Print Speed*	Plain paper: 50 pages/min
(Simplex/Duplex)	Thick 1/Thick 2: 20 sheets/min.

BIZHUB 4700I SPECIFICATIONS

TYPE	DIGITAL PRINTER	
Power Requirements	110V, 60 Hz.	
Power Consumption	1450 W or less	
TEC Value	.81 kWh	
Dimensions (with control panel)	16.5" (W) x 20.8" (D) x 18.6" (H)	
Space requirements*	33.6" (W) x 35.4" (D) x 18.6" (H)	
Memory	4 GB; 8 GB Micro SD	
Weight	Approx. 64 lb.	
* The indicated space requirements represent the space required to pull out the paper tray and the tray extension of the bypass tray and with the ADF open.		

DUTY CYCLE

bizhub 4700i	Up to 120,000
	Maximum monthly copy/print volume supported under standard vendor supplied service. Defines the upper end of the expected customer volume for the device. Customers should consider multiple machines if average monthly volume approaches duty cycle on continual basis.



ENVIRONMENTAL REQUIREMENTS

TYPE	DESCRIPTION
Temperature	50° F to 90° F
Humidity	15% to 85%
Noise During Operation	73.3 dB or less
Noise During Standby	32 dB or less

ELECTRICAL REQUIREMENTS


TYPE	DESCRIPTION	
Line Options	Dedicated	NEMA Diagram for 5-15R
Voltage	110 V/120 to 127V	
Amperage	12A	
Cycles	60	(_)
NEMA Part No.	5-15R	
Cord Length	6.6 ft.	
Note: The main electrical outlet	must be located within 6.6 feet from the right rear o	corner of the bizhub 4700i main unit.

SAMPLE CONFIGURATION




SPACE REQUIREMENTS

bizhub 4700i



bizhub 4700i with options



AUTOMATIC DUPLEX UNIT (STANDARD)

Supported Paper Type	Thin Paper (14 lb to 15.5 lb)
	Plain Paper (16 lb to 24 lb)
	Thick Paper 1 (24.25 lb to 32 lb)
	Thick Paper 1+ (32.25 to 41.75 lb)
	Thick Paper 2 (42 lb to 55.5 lb)
	Recycled Paper (16 lb to 24 lb)
Supported Paper Size	4.7" x 8.8" to 8.5" x 14"
Power Requirements	Supplied from main unit
	*There are six Foolscap sizes: 220 x 330 mm (L), 8.5" x 13.5", 8.5" x 13" (L), 8.25" x 13 (L), 8.12" x 13.25" (L) and 8" x 13" (L).
	Any one of these sizes can be selected. For details, please consult with your authorized Konica Minolta Service representative

PF-P21 PAPER FEED CABINET

Туре	1 x 500 sheet drawer
Supported Paper Types	Thin Paper (16 lb bond to 20 lb bond), Plain Paper (20 lb bond to 28 lb bond), Recycled Paper (20 lb to 28 lb),
	Letterhead (16 lb bond to 24 lb bond), Colored Paper (16 lb bond to 24 lb bond)
Supported Paper Size	8.5" x 14" to 5.8" x 8.25", letter and legal only
Paper Capacity	500 sheets (21 lb)
Power Requirements	Supplied from main unit.
Weight	Approximately 17.4 lb

PF-P25 HEIGHT ADJUSTMENT UNIT

Туре	Base (without storage), Increases height of the machine. Suggested if the machine is configured with the DK-P05 and fewer than two		
	PF-P21 Paper Feeder Cabinets.		
Dimensions (W x D x H)	14.3" x 15.1" x 5.8"		
Weight (Approx.)	8.6 lb		

DK-P05 COPY DESK

Туре	Storage drawer only	
Function	Storage of accessories, paper, supplies, etc. Brings machine to working height.	
UK-221 WIRELESS NETWORK ADAPTER		
Tuno	Miscellaneous Option	
Type Function	Provides wireless connectivity	
Tunction	1 Tovides will cless conflictivity	
EK-P08 USB HOST/LOCAL INTERFACE		
Туре	Internal Component	
Function	Provides Type A USB port. Required for installation of an authentication unit or	
	external keyboard.	
EK-P09 USB HOST/LOCAL INTERFACE		
Туре	Internal Component	
Function	Provides Type A USB port and Bluetooth connectivity. Required for installation of an	
	authentication unit or external keyboard.	
EK-P10 NFC KIT		
Туре	Internal Component	
Function	Provides Near Field Communications capabilities.	
AU-205H IC CARD READER		
Dimensions (W x H x D)	2.8" x 3.7" x 0.6"	
Host Interface	USB 2.0 (also compliant with USB 1.1)	
Power Supply	Supplied from USB Port	
Card Protocols	HID PROX, HID Indaia, EM ProxLow Frequency (125 kHz)	
Card Protocols	CCID: MIFARE Classic™ 1K/4K, Ultra Light, Ultra Light C, Plus, High Frequency	
	(13.5 MHz) MIFARE DESFire™ 0.6, MIFARE DESFire™ EV1, IC Card, iCLASS SE/SR®,	
	MIFARE SE™, DESFire EV1 SE, T=CL, ISO 14443 A with up to 848 kbps transmission	
	rate (depending on card1), ISO 15693 with up to 26 kbps transmission rate	
	(depending on card)	
	Keyboard Wedge: MIFARE™ Classic 1K/4K, Ultra Light, Ultra Light C, Plus (Security	
	Level 1), MIFARE DESFire™ 0.6, MIFARE DESFire™ EV1 (MAC/DES/3DES/3K3DES/	
	AES), IC Card, iCLASS SE/SR®, MIFARE SE™, DESFire EV1 SE	
	AL3), IO Calu, IOLA33 3E/3N ⁻² , MIFANE 3E ⁻² , DESFIRE EV I 3E	_

MK-	P08	MOUN	IT KIT

Туре	Internal Component
Function	Required for internal installation of AU-205H

FS-P04 OFF-LINE STAPLER

Туре	Stapling (off-line)	
Staple Capacity	20 sheets (90 gsm)	
Power Supply	From device	
Staples	SK-501	
Dimensions (W x H x D)	4.3" x 4.6" x 2.9"	
Weight	Approx. 2 lb	
Function	Provides finishing capabilities. Can be installed on working table WT-P03 or separately.	
runction	Frovides infishing Capabilities. Can be installed on working table w 1-F03 of Separately.	

KP-P03 KEYPAD

Туре	10-key Pad
Function	Provides hard keys for entering numeric values
EVERNIAL KEVDOARD	

EXTERNAL KEYBOARD

Function

Туре	QWERTY Keyboard	
Function	Computer-type keyboard for alphanumeric data entry. Requires KH-P02 Keyboard Holder	
KH-P02 KEYPAD HOLDER		
Type	Mount Kit	

Required for installation of External Keyboard



PRINT CONTROLLER (STANDARD)

Туре	Internal Type				
CPU	SoC S800 (1.6 GHz)				
Memory	4 GB				
Print Speed (BW)	50 ppm Letter				
Print Resolution	600 x 600 dpi, 1200 x 1200 dpi				
PDL	PCL6, PS 3 Emulation, XPS 1.0 Emulation, PDF 1.7 Emulation, Epson FX-850 Emulation				
Font	PCL Resident Fonts: 80 Scalable Fonts plus 12 Bitmapped Fonts				
	PS3 Emulation Resident Fonts: 137 Scalable Fonts				
Interface	Standard Ethernet (10Base-T/100Base-TX/1000Base T), Hi-Speed USB, 1.1 2.0, 3.0; USB Host, Interface Support for Ethernet SNAP, Ethernet II,				
	Ethernet 802.3, or 802.2				

PRINT DRIVERS

PCL 6	Windows 7/8.1/10 (32-bit and 64-bit)		
PostScript 3 Emulation	Windows Server 2008 (32-bit and 64-bit)		
	Windows Server 2008 R2/2012/2012 R2/2016/2019 (64-bit)		
	Mac OSX 10.10/10.11/10.12/10.13/10.14 (PostScript only)		
	Red Hat Enterprise Linux 5 or later		
XPS	Windows 7/8.1/10		
	Windows Server 2008/2008 R2/2012/2012 R2/2016 x64		

SOFTWARE TOOLS

Management Tools	bizhub vCare				
	Dispatcher Suite				
	Konica Minolta Mobile Print for iOS, Konica Minolta Mobile Print for Android, Konica Minolta Mobile Print for Windows				
	Konica Minolta Print Service, Konica Minolta Print Service				
	PageScope My Print Manager				
	PageScope Net Care Device Manager, PageScope Account Managerm, PageScope Authentication Manager, PageScope My Panel Manager				
	vCare, bizhub Remote Panel, Device Plug-in for PageScope Enterprise Suite				
	HDD BackUp Utility, Log Management Utility, Font Management Utility, Panel Customize Tool, License Install Utility				
	Web Connection, Mopria for Android, Download Manager, Data Administrator, Remote Deployment Tools, Box Operator, Print Status Notifier				
User Tools	Direct Print, Konica Minolta Mobile Print for iPhone/iPad, Konica Minolta Mobile Print for Android, Konica Minolta Mobile Print for Windows				
	WLAN Setup Wizard				
	Remote Deployment Tools				
	Net Care Device Manager				
Network & Device Management	Driver Packaging Utility				

SECURITY

Because information assets are	1) Prevent Leaks of proprietary, confidential or personal information			
critical, a company needs to	mpany needs to 2) Prevent unauthorized use of equipment			
effectively protect against the many 3) Effective data encryption				
security risks it faces.	4) Protect data from being altered, duplicated or deleted			
	5) Prevent unauthorized access to data via the Internet			
	6) Protect against cyber attacks			
	7) Manage log history			
Protective Functions	Active Directory			
	Enterprise Security (802.1x)			
	Secure Print			
	• LDAP			
	• SSL/TLS			
	• IPSec			

SOFTWARE TOOLS

Network, Device Management and User Tools

Data Administrator Download Manager Print Status Notifier Driver Packaging utility

Mobile Print

Net Care Device Manager
Web Connection
Enterprise Suite Plug-in
Account Manager
Authentication Manager
My Print Manager
Box Operator
Driver Packaging Utility

Lock Job (when printing confidential documents)

Protect data by requiring department name and 8-digit password

Account Track • HDD Lock • Prevent Unauthorized Use

Operation Log with 2,000-event memory

PDF Scan Encryption Protective Functions Network Authentication

PAPER CONSIDERATIONS

PAPER SIZE CONVERSION CHART

Paper	Letter	Letter R	Legal	Statement	Statement R	
Measurement	8.5" x 11"	11" x 8.5"	8.5" x 14"	5.5" x 8.5"	8.5" x 5.5"	

PAPER WEIGHT CONVERSION CHART

								C	ALIPER
gsm	Bond	Offset	Cover	Tag	Index	Point	Bristol	inches	mm
60.20	16	40	22	37	33	3.2	27.4	0.0032	0.081
67.72	18	45	24	41	37	3.6	30.9	0.0036	0.092
75.20	20	50	28	46	42	3.8	34.3	0.0038	0.097
90.30	24	60	33	56	50	4.8	41.2	0.0048	0.120
105.35	28	70	39	64	58	5.8	48.1	0.0058	0.147
109.11	29	73	40	62	60	6.0	49.8	0.0060	0.152
116.63	31	81	45	73	66	6.1	53.2	0.0061	0.155
131.68	35	90	48	80	74	6.2	60.1	0.0062	0.157
135.45	36	90	50	82	75	6.8	61.8	0.0068	0.173
146.73	39	100	54	90	81	7.2	67.0	0.0072	0.183
150.50	40	100	56	93	83	7.3	68.7	0.0073	0.185
161.78	43	110	60	100	90	7.4	73.8	0.0074	0.188
165.55	44	110	61	02	92	7.6	75.5	0.0076	0.193
176.83	47	120	65	108	97	8.0	80.7	0.0078	0.198
199.41	53	135	74	122	110	9.0	91.0	0.0085	0.216
203.17	54	137	75	125	113	9.0	92.7	0.0090	0.229
218.22	58	146	80	134	120	9.5	99.6	0.0092	0.234
244.56	65	165	90	150	135	10.0	111.6	0.0095	0.241
252.08	67	170	93	156	140	10.5	115.1	0.0100	0.250
270.90	72	183	100	166	150	11.0	123.7	0.0110	0.289
285.95	76	192	105	175	158	13.0	130.5	0.0130	0.330
308.52	82	208	114	189	170	14.0	140.8	0.0140	0.356
312.00	87	220	120	200	180	15.0	142.4	0.0150	0.380
385.06	105	267	146	244	220	18.0	175.8	0.0175	0.445

PAPER TYPE SPECIFICATIONS

Paper weighing between 16 lb. to 20 lb. bond. It can be fed via any paper tray, except the bypass tray.			
aper meighning between 10 ibi to 20 ibi bondi it our be rou mu any paper truy, encept the bypass truy.			
Normal paper is used for copying in general and is called "PPC paper." The normal paper is usually not a recycled paper. Specify [Normal] to the tray to			
which the normal paper or the recycled paper is loaded for copying.			
Recycled Paper is identified as recycled paper along with a designation as to the percentage of the paper that is actually made from recycled materials			
Generally speaking, these devices will support recycled paper weighing between 20 lb and 28 lb bond.			
Thick Paper 1 is paper weighing between 28 lb and 32 lb bond lt can be fed via any paper tray.			
Thick Paper 2 is paper weighing between 32 lb and 53 lb bond. It can be fed via any paper tray.			
A thin or other specialty type paper that falls within the paper weight specification and appears on the Recommended Paper Stock List.			
Specify (Envelope) for bypass tray.			
A Postcard is defined as a rectangular piece of the thick paper or thin cardboard. This product series supports 4" x 6" size postcards. Postcards are fed only via the Bypass Tray.			

PAPER TYPE SPECIFICATIONS CON'T

Class.	Weight	Brand of Paper	Size
Plain Paper — Color			
Plain Paper	20 lb. Bond (75 gr)	Domtar Recycled Copy(30% Post Consumer)	8.5" x 11"
Plain Paper	22 lb. Bond(80 gr)	Konica Minolta CF Paper	8.5" X 11"
Plain Paper	22 lb. Bond(80 gr)	Konica Minolta CF Paper	11" X 17"
Plain Paper	22 lb. Bond(80 gr)	Konica Minolta CF Paper	12" X 18"
Plain Paper	24 lb. Bond (89 gr)	SMART Carnival Stellar White	8.5" x 11"
Plain Paper	24 lb. Bond (89 gr)	SMART Carnival White	8.5" x 11"
Plain Paper	24 lb. Bond (90 gr)	SMART Synergy Bond 25% Cotton	8.5" x 11"
Plain Paper	24 lb. Bond (90 gr)	Domtar Microprint Laser	8.5" x 11"
Plain Paper	24 lb. Bond (90 gr)	Mohawk Color Copy 98 Bright White	8.5" x 11"
Thick 1	28 lb. Bond(105 gr)	Konica Minolta CF Paper	8.5" X 11"
Thick 1	28 lb. Bond(105 gr)	Konica Minolta CF Paper	11" X 17"
Thick 1	28 lb. Bond (105 gr)	Konica Minolta CF Paper	12" X 18"
Thick 1	28 lb. Bond (105 gr)	Domtar Microprint Color Copy	8.5" x 11"
Thick 1	32 lb. Bond(120 gr)	Hammermill Color Copy	8.5" X 11"
Thick 1	32 lb. Bond (120 gr)	Hammermill Color Copy Paper – Photo White	8.5" x 11"
Thick 2	60 lb. Cover(163 gr)	Hammermill Color Copy	8.5" X 11"
Plain Paper — B & W			
Plain Paper	20 lb. Bond (75 gr)	Hammermill Tidal MP	8.5" X 11"
Double-Sided Glossy			
Thick 1	32 lb. Bond (120 gr)	Mohawk Color Copy Gloss Pure White	8.5" x 11"
Thick 1	80 lb. Text (118 gr)	Sappi Opus Gloss	8.5" x 11"
Thick 1	90 lb. Text (133 gr)	SMART Kromekote Laser High Gloss Coated Two Sides*	8.5" x 11"
Envelopes			
Envelope	24 lb.	Preservation Wove 5789 #6 3/4	3.85" x 6.5" (98 x 165 mm)
* Paper cannot be used in a h	nigh humidity environment.		

HOW TO BUILD A SYSTEM FOR THE BIZHUB 47001 DIGITAL PRINTER (FROM START TO FINISH)

STEP 1: BASE UNIT

Includes PS, PCL & XPS Controller, Automatic Duplex Unit, 500-sheet Paper Cassette, 4 GB Standard Memory, Fast Ethernet, High-speed USB 2.0 Host, 20K Toner Cartridge, and 200K Imaging Unit

STEP 2: PAPER HANCLING OPTIONS

- PF-P21 Paper Feed Unit (500 sheets, maximum 2)
- PF-P25 Height Adjustment Unit

STEP 3: FINISHING OPTION:

- CS-1 Convenience Stapler
- FS-P04 Off-line Stapler



ACCESSORY OPTIONS FOR BIZHUB 4700I DIGITAL PRINTER

ACCESSORIES	ITEM NO.	DESCRIPTION	NOTES
BASE UNIT			
4700i	ACTA011	4700i Printer	Includes PS, PCL & XPS Controller, Automatic Duplex Unit, 500-sheet Paper Cassette, 512 MB Standard Memory, Fast Ethernet, High-speed USB 2.0 Host, 20K Toner Yield, and 200K Imaging Unit
PAPER HANDLING	OPTIONS		
DK-P05	135900	Copy Desk	Adds storage and mobility. Brings printer to operational height.
PF-P21	AAJUW1	Paper Feed Unit	Lower feeder unit adds 500 sheets of paper capacity (8.5" x 11" or 8.5" x 14"). Add up to
			2. Total paper capacity: 1600 sheets
PF-P25	AAJUW12	Height Adjustment Unit	Increases height of machine.
FINISHING OPTIO	NS		
CS-1	7640013463	Convenience Stapler	Standalone electronic stapler.
FS-P04	AACCGWY1	Off-line Electronic Stapler	Off-line Electronic Stapler
ADDITIONAL OPTI	ONS		
AU-205H	R5427000136466	HID Multi-Card Reader	Allows access to SFP via HiD proximity cards.
EK-P08	ACCTWY1	Local Interface Kit	Provides Type A USB port. Required for installation of an authentication unit or external keyboard.
EK-P09	ACCVWY1	Local Interface Kit	Provides Type A USB port and Bluetooth connectivity. Required for installation of an
			authentication unit or external keybaord.
EK-P10	ACCHWY1	NFC interface	Provides Near Field Communications capabilities.
External	7640006869	QWERTY Keyboard	QWERTY keyboard for alphanumeric data entry.
Keyboard			
KH-P02	ACCFWY1	Keyboard Holder	Keyboard holder required for installation of external keyboard.
KP-P03	ACCEWY1	Keypad	Provides hard keys for entering numeric values.
MK-P08	ACCKWY1	Mount Kit	Mount kit for internal installation of AU-205H.
UK-221	ACDMWY1	Wireless LAN	Provides wireless connectivity.

CONSUMABLE YIELDS

*Based on 5% total converage

CONSUMABLE	ITEM NO.	YIELD
TNP91 Toner – Black	ACTD031	20,000
Waste Toner Box	ACDN0Y1	32,000
IUP36K Drum Imaging Unit	AAJV01E	200,000
SK-501 Staples for FS-P04	A6Y8WY1	_
SK-602 Staples	14YK	_