

Leading the way in Business Products, Services, and Solutions



# State of North Carolina Term Contract 204D

Contract Number ITS#400096 Contract Period February 01, 2017 - January 31, 2017 with 2 one year renewals

### Konica Minolta

High Capacity Printer / Multifunction Device Equipment Purchase, Lease, Supplies & Maintenance

www.SystelStateContracts.com





### **General Ordering Information**

#### 1. ORDERING ADDRESS AND PROCEDURES

Orders will be accepted for State of North Carolina agencies located within the State of North Carolina. All orders must be placed as follows:

Systel Business Equipment Co., Inc.

2604 Fort Bragg Road Fayetteville, NC 28303 ATTN. Order Processing Phone: 1-800-849-5900

Email: support@systeloa.com

Fax: 1-910-483-2529

Information on orders, invoices, etc. should be directed to the number indicated above. Facsimile purchase orders are acceptable at the number above.

#### 2. ORDERING PROCEDURES/PURCHASE ORDERS

All purchase orders for photocopiers/ service/supplies are to be issued only to the contracting vendor. Please include the following information with your purchase order:

- The Contract Number:
   204D ITS #400096
- Tax Exempt Certificate- Please be sure to send your tax exempt certificate with your purchase order. This will prevent delays in your order being processed. If one is not sent in with the PO we will contact you by phone to request a copy.
- Product Number
- Quantity of items being ordered
- Description of Item
- Acquisition Plan with unit prices extended & PO Totaled
- Overage of cost for copies, (if applicable)
- Delivery address, contact name and phone number
- Any additional items to be delivered with the copier
- Accessories and appropriate prices, (if applicable)

#### 3. **REMIT TO ADDRESS**

Systel Business Equipment, Inc. will provide invoices under this contract.

Systel Business Equipment, Inc. P.O. Box 35870 Fayetteville, NC 28303

#### 4. PAYMENT TERMS

Net thirty (30) days

#### 5. **DELIVERY**

Thirty (30) days after receipt of order

#### 6. CUSTOMER SUPPORT CENTER

For service, please call our toll free support services number 1-800-849-1500 or locally 910-483-5293.

#### 7. HARD DRIVE SANITATION SERVICE

Please refer to page of this catalog for information and pricing for Hard Drive Sanitation and Removal Service.

#### 8. AUTHORIZED SALES LOCATIONS

For Sales and Service please contact your local Systel Branch Location. Please see page for a list of servicing branch locations.

#### 9. ADDITIONAL RESOURCES

For current pricing, promotions, and models as well as additional models available, please visit Systel's NC State Contract Website: www.SystelStateContracts.com

#### STATE OF NORTH CAROLINA WEBSITE

Please use this website address to confirm the proper procedures and guidelines in using this award.

Click the link to search Systel products: https://it.nc.gov/contract-204d-printers-andperipherals


## **Konica Minolta Model Specifications**





## **Black & White Multifunction Devices**





Up to 22 ppm print/copy output to keep pace with rising demands

Color display with quick tablet-like interface

Touchscreen for simple control and 3rd-party software integration

Standard web browser to support web-based apps

Built-in Emperon® print system, universal printer drivers

Simitri® HD polymerized toner for high-resolution imaging

Standard 250 GB HDD for on-board document storage

Meets ISO 15408 and IEEE 2600.1 Security standards

Power-saving design with quick recovery from sleep mode

3,600-sheet maximum capacity, tab printing support, carbon-copy printing

Advanced authentication, secure print release, remote firmware updates

Options for booklet-making, stapling, hole punch and more

Downloadable apps to help you work faster and smarter

i-Options to add functions for working more efficiently

Low power consumption to cut costs

Mobile printing support (AirPrint, Google Cloud Print, NFC)

## bizhub 227

MONOCHROME MID-VOLUME MULTIFUNCTION PRINTER







#### bizhub 227

As easy as a familiar tablet, the enhanced touch-and-swipe interface of the bizhub 227 helps make you more productive — with 22 ppm output in high-resolution B&W, scanning in color or B&W at up to 45 originals per minute, 3,600-sheet maximum paper capacity and economical, high-value performance.

#### System Overview

System Overview	
System memory	4 GB
System hard disk	250 GB
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Reversing automatic document feeder (optional)	Up to 100 originals / 5.5" x 8.5" to 11" x 17" / 50-128 gsm
Printable paper size	Scanning/Copying: up to 11" x 17" Printing: up to 11" x 17" Custom paper sizes
Printable paper weight	60-220 gsm
Paper input capacity	Standard: 1,100 sheets / Max.: 3,600 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 8.5" x 14" / 60-220 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 11" x 17" / 60-220 gsm
Tray 3 (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 60-220 gsm
Tray 4 (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 60-220 gsm
Large capacity tray PC-413 (optional)	2,500 sheets / 8.5" x 11" / 60-220 gsm
Manual bypass	100 sheets / 4" x 6" to 11" x 17" / custom paper sizes / 60-220 gsm
Automatic duplexing	5.5" x 8.5" to 11" x 17" / 60-220 gsm
Finishing modes	Offset, group, sort, punch, half-fold, tri-fold, booklet
Output capacity	Max. with finisher: 3,300 sheets Max. without finisher: 250 sheets
Stapling (optional)	Max.: 50 sheets or 48 sheets + 1 cover sheet (up to 209 gsm)
Stapling output capacity	Max.: 1,000 sheets
Tri-fold (optional)	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray)
Copy/print volume	Max.: 100,000 pages/month <sup>1</sup>
Toner lifetime	23,000 pages
Imaging unit lifetime	85,000 pages / 590,000 pages (Drum / Developer)
Power consumption	120 V / 50/60 Hz, less than 1.5 kW (system)
System dimensions	23.0" x 26.0" x 28.9" (W x D x H)
System weight	Approx. 124.6 lb

	-							
'n	nic	ar (	С'n	20	ifi	ביי	Hin	ns

Copying process	Electrostatic laser copy, tandem
Toner system	Simitri® HD Polymerized Toner
Print speed (8.5" x 11")	Up to 22 ppm (Portrait)
Print speed (11" x 17")	Up to 14 ppm
Auto-duplex speed	Up to 22 ppm (Portrait)
(8.5" x 11")	
1st copy out time	5.3 sec.
Warm-up time	Approx. 15 sec. <sup>2</sup>
Copy resolution	600 x 600 dpi
Gradations	256 gradations
Multi-copy	1-9,999
Original format	Up to 11" x 17"
Magnification	25-400% in 0.1% steps, auto zooming
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1

#### **Printer Specifications**

Print resolution	1,800 (equivalent) x 600 dpi			
PDL PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS				
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2³ / 2012³ Macintosh OS X 10.2.8 or later UNIX / Linux / Citrix			
Printer fonts	80 PCL Latin, 137 PostScript 3			
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print			

#### **Scanner Specifications**

Scan speed	B&W / Color: up to 45 ipm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview

#### **Fax Specifications**

Fax	Super G3 (optional)
Transmission	Analog, i-Fax, Color i-Fax, IP-Fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to Email/ETP/SMB, up to 400 job programs

#### **User Box Specifications**

occ. Describence	
Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public
	Personal (with password or authentication)
	Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation
User box functionality	Reprint, combination, download, sending (Email/FTP/SMB and fax),
	copy box-to-box

ISO 15408 EAL
IEEE 2600.1
IP filtering and port blocking
SSL2, SSL3 and TSL1.0 network communication
IPsec support
IEEE 802.1x support
User authentication
Authentication log
Secure print
Hard disk overwrite (8 standard types)
Hard disk data encryption (AES 128)
Memory data auto deletion
Confidential fax reception
Print user data encryption
Copy protection (Copy Guard, Password Copy) optional
Up to 1,000 user accounts
Active Directory support
(user name + password + Email + SMB folder)
User function access definition
Optional Biometric authentication (finger vein scanner)
Optional ID card authentication (ID card reader)
PageScope Net Care Device Manager
PageScope Data Administrator
PageScope Box Operator
Print Status Notifier
Driver Packaging Utility
Log Management Utility

<sup>Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis.
This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs 2 Warm-up time may vary depending on the operating environment and usage
3 Supports x64 only</sup> 

<b>Components and Options</b>	8
AU-102 Biometric	Finger vein scanner
authentication	
AU-205H Universal	Various ID card technologies
ID card reader	
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection, Bluetooth
DF-628	Reversing automatic document feeder, capacity 100 originals
Document feeder	
DK-513 Copier desk	Provides storage space for print media and other materials
FK-513 Fax board	Super G3 fax, digital fax functionality
FS-533 Staple finisher	50-sheet stapling, 500 sheets max. output (requires MK-602)
FS-534 Staple finisher	50-sheet stapling, 3,300 sheets max. output (requires RU-514)
FS-534 + SD-511	50-sheet staple finisher, 20-sheet booklet finisher,
Booklet finisher	3,300 sheets max. output (requires RU-514)
JS-506 Job separator	Separation for fax output, etc.
KH-102	To place USB keyboard
Keyboard holder	TO PILCO GOD ROJDOUTU
KP-101 10-Key pad	For use instead of touchscreen
LK-102 v3	PDF/A, PDF encryption, digital signature
PDF enhancements	T DI /A, T DI GIG Sphort, digital signature
LK-104 v3	Provides voice guidance functions
Voice guidance	Trovides voice guidance functions
LK-105 v4	Searchable PDF
OCR text recognition	odd on abio 1 bi
LK-106	Supports native barcode printing
Barcode fonts	2
LK-107	Supports native Unicode printing
Unicode fonts	
LK-108	Supports native OCR A and B font printing
OCR A and B fonts	
LK-110 v2 Enhanced	Generates various file formats incl. DOCX, XLSX and combines
image support	LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
LK-111	Print data compression for reduced network impact
ThinPrint® Client	
LK-114 Universal	Supports server-less ubiquitous printing
print function	
MK-602 Mount kit	Installation kit required for FS-533
MK-735 Mount kit	Installation kit for ID card reader
OC-514 Original cover	Cover instead of auto document feeder
PC-113	5.5" x 8.5" to 11" x 17", 500 sheets, 60-220 gsm
Universal tray (x1)	
PC-213	5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 60-220 gsm
Universal tray (x2)	
PC-413	8.5" x 11", 2,500 sheets, 60-220 gsm
Large capacity tray	
PK-519 Punch kit for FS-533	2/3-hole punching, autoswitching
PK-520 Punch kit	2/3-hole punching, autoswitching
for FS-534	
RU-514 Relay unit	Required for installation of FS-534
UK-212 Wireless LAN	Wireless LAN to network connector
WT-506 Working table	Authentication device placement
Note: Not all antions may be aug	ilable at time of launch

Note: Not all options may be available at time of launch.









#### bizhub 364e

Growing workloads demand higher productivity – and the bizhub 364e delivers 36 ppm output in crisp B&W, with color scanning and scalable options that include dual scanning, Super G3 fax, auto-finishing and more – in compact design with enhanced touch-and-swipe interface that's as easy as a familiar tablet.

System Overview	
System memory	2,048 MB
System hard disk	250 GB
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T ETHERNET, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Dual scan document	Up to 100 originals / 5.5" x 8.5" to 11" x 17" / 35-163 gsm
feeder (optional)	Reversing automatic document feeder or dual scan document feeder available
Printable paper size	Scanning/Copying: up to 11" x 17"
	Printing: up to 11" x 17" full bleed on 12" x 18" paper Custom paper sizes
	Banner paper max.: 11.75" x 47.25"
Printable paper weight	52-300 gsm
Paper input capacity	Standard: 1,150 sheets / Max.: 3,650 sheets
Trav 1	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 3 (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 4 (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 52-256 gsm
Large capacity tray	2,500 sheets / 8.5" x 11" / 52-256 gsm
PC-410 (optional)	,
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, sort, punch, half-fold, tri-fold, booklet
Output capacity	Max. with finisher: 3,300 sheets
	Max. without finisher: 250 sheets
Stapling (optional)	Max.: 50 sheets or 48 sheets + 1 cover sheet (up to 209 gsm)
Stapling output capacity	Max.: 1,000 sheets
Tri-fold	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output	Max.: 100 sheets (tray)
capacity	
Copy/print volume	Max.: 150,000 pages/month <sup>1</sup>
Toner lifetime	24,000 pages
Imaging unit lifetime	120,000 pages / 590,000 pages (Drum / Developer)
Power consumption	120 V / 50/60 Hz, less than 1.5 kW (system)
System dimensions	24.2" x 27" x 36.3" (W x D x H)
System weight	Approx. 168.7 lb

٠.,	nior	Cno	aifia	ation	
וטכ	nei	SUC	CHIC	auvi	15

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD Polymerized Toner
Print speed (8.5" x 11")	Up to 36 ppm (Portrait)
Print speed (11" x 17")	Up to 18 ppm (Portrait)
Autoduplex speed	Up to 36 ppm (Portrait)
(8.5" x 11")	
1st copy out time	5.3 sec.
Warm-up time	Approx. 20 sec. <sup>2</sup>
Copy resolution	600 x 600 dpi
Gradations	256 gradations
Multi-copy	1-9,999
Original format	Up to 11" x 17"
Magnification	25-400% in 0.1% steps, auto zooming
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness, image
	density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1

#### **Printer Specifications**

i ilittoi opooliioutiono	
Print resolution	1,800 x 600 dpi, 1,200 x 1,200 dpi
PDL	PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 <sup>3</sup> / 2012 <sup>3</sup> Macintosh OS X 10.2.8 or later UNIX / Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

### Scanner Specifications

B&W / Color: up to 160 ipm with optional DF-/01
Max.: 600 x 600 dpi
Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
2,100 (shared with fax), LDAP support
Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview

#### **Fax Specifications**

Fax	Super G3 (optional)
Transmission	Analog, i-Fax, Color i-Fax, IP-fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to Fmail/FTP/SMB. up to 400 job programs

#### **User Box Specifications**

occ. Describence	
Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public
	Personal (with password or authentication)
	Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation
User box functionality	Reprint, combination, download, sending (Email/FTP/SMB and fax),
	copy box-to-box

Security	ISO 15408 EAL
	IEEE 2600.1
	IP filtering and port blocking
	SSL2, SSL3 and TSL1.0 network communication
	IPsec support
	IEEE 802.1x support
	User authentication
	Authentication log
	Secure print
	Hard disk overwrite (8 standard types)
	Hard disk data encryption (AES 128)
	Memory data auto deletion
	Confidential fax receipt,
	Print user data encryption
	Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts
	Active Directory support
	(user name + password + Email + SMB folder)
	User function access definition
	Optional Biometric authentication (finger vein scanner)
	Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager
	PageScope Data Administrator
	PageScope Box Operator
	PageScope Direct Print
	Print Status Notifier
	Driver Packaging Utility
	Log Management Utility

<sup>1</sup> Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis.
1 This specification is a guidline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs
2 Warm-up time may vary depending on the operating environment and usage
3 Supports x64 only

<b>Components and Options</b>	8
AU-102 Biometric	Finger vein scanner
authentication	
EK-606 USB I/F kit	USB keyboard connection
EK-607 USB I/F kit	USB keyboard connection, Bluetooth
DF-624	Reversing automatic document feeder, capacity 100 originals
Document feeder	
DF-701	Dual scan automatic document feeder, capacity 100 originals
Document feeder	
DK-510 Copier desk	Provides storage space for print media and other materials
FK-508 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support
FK-511 Fax board	Super G3 fax, digital fax functionality
FS-533 Staple finisher	50-sheet stapling stapling, 500 sheets max. output
FS-534 Staple finisher	50-sheet stapling, 3,300 sheets max. output
FS-534 + SD-511	50-sheet staple finisher, 20-sheet booklet finisher,
Booklet finisher	3,300 sheets max. output
ID card reader	Various ID card technologies
JS-506 Job separator	Separation for fax output, etc.
KH-102	To place USB keyboard
Keyboard holder	Facility in the second of the selection
KP-101 10-Key pad	For use instead of touchscreen
LK-101 v3	Web browser
Web browser	DDE/A DDEtitititititi
LK-102 v3 PDF enhancements	PDF/A, PDF encryption, digital signature
LK-104 v3	Provides voice guidance functions
Voice guidance	Flovides voice guidance functions
LK-105 v3	Searchable PDF
OCR text recognition	odd orlabio i Bi
LK-106	Supports native barcode printing
Barcode fonts	
LK-107	Supports native Unicode printing
Unicode fonts	
LK-108	Supports native OCR A and B font printing
OCR A and B fonts	
LK-110 Enhanced	Generates various file formats incl. DOCX, XLSX and combines
image support	LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
LK-111	Print data compression for reduced network impact
ThinPrint® Client	lastallation lift for EV FOO for bound
MK-728 Mount kit	Installation kit for FK-508 fax board
MK-735 Mount kit	Installation kit for ID card reader
OC-511 Original cover	Cover instead of auto document feeder
PC-110 Universal tray (x1)	5.5" x 8.5" to 11" x 17", 500 sheets, 52-256 gsm
PC-210	5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52-256 gsm
Universal tray (x2)	3.3 x 0.3 to 11 x 17 , 2 x 300 sheets, 32-230 yshi
PC-410	8.5" x 11", 2,500 sheets, 52-256 gsm
Large capacity tray	0.0 X 11 , 2,000 shotts, 02 200 gsiii
PK-519 Punch kit	2/3-hole punching, autoswitching
for FS-533	3,
PK-520 Punch kit	2/3-hole punching, autoswitching
for FS-534	
SC-508 Security kit	Copy Guard function (2x required when DF-701 is installed)
UK-204	Memory extension for i-Options
i-Option memory	
UK-208 Wireless LAN	Wireless LAN to network connector
UK-209 DS board for	bizhub RA when machine is equipped with DF-624
bizhub RA	
WT-506 Working table	Authentication device placement



### MFP bizhub 368/308

MONOCHROME MID-VOLUME MULTIFUNCTION PRINTER

**System Overview** System memory 2,048 MB (standard) System hard disk 250 GB (standard) 10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0 Interface Wi-Fi 802.11a/b/g/n/ac (optional) TCP/IP (IPv4/IPv6), NetBEUI, SMB, LPD, IPP, SNMP, HTTP Network protocols Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP Frame types Automatic document Up to 100 originals, A6-A3, 35-163 gsm feeder (optional) Printable paper size A6-SRA3, customised paper sizes, banner paper max. 1,200 x 297 mm Printable paper weight 52-300 gsm Standard: 1.150 sheets. Max.: 6.650 sheets Paper input capacity Tray 1  $500 \, \text{sheets}, \, A5\text{-}A3, \, 52\text{-}256 \, \text{gsm}$ Tray 2 500 sheets, A5-SRA3, 52-256 gsm Tray 3 PC-110 (optional) 500 sheets, A5-A3, 52-256 gsm Tray 4 PC-210 (optional)  $2 \times 500$  sheets, A5-A3, 52-256 gsm 2,500 sheets, A4, 52-256 gsm Paper feed cabinet PC-410 (optional) Large capacity unit 3,000 sheets, A4/Letter, 52-256 gsm LU-302 (optional) Bypass tray 150 sheets, A5-SRA3, custom sizes, banner, 60-300 gsm Automatic duplexing A5-SRA3, 52-256 gsm Group, sort, staple, punch, output tray, booklet, Finishing modes (optional) centre fold, letter fold, Z-fold Power consumption [220-240 V, 50/60 Hz] less than 1.95 kW (system) [120 V, 60 Hz] less than 1.5 kW (system) [110 V, 50/60 Hz] less than 1.5 kW (system) System dimensions \*1  $[W \times D \times H] 571 \times 660 \times 785.5 \text{ mm} (22.5 \times 26.0 \times 30.9 \text{ inch})$ System weight \*2 Approx. 76 kg (156.5 lb)

<sup>1</sup> Excluding ADF and lower paper tray unit 2 Including Drum/Toner bottle

Copier Specifications	
Copying process	Electrostatic laser copy, intermediate
Toner system	Simitri® HD Polymerized Toner
Copy/print speed A4	368: Up to 36 ppm, 308: Up to 30 ppm
Copy/print speed A3	368: Up to 18 ppm, 308: Up to 15 ppm
1st copy out time	368: 5.0 sec., 308: 5.4 sec.
Warm-up time *3*4	368: 20 sec., 308: 18 sec. or less *3, 20 sec. or less *4
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-9,999
Original format	A5-A3
Magnification	25-400% in 0.1% steps, auto-zooming

<sup>&</sup>lt;sup>3</sup> Time period from when the sub power off mode is released to when this machine is ready for printing while the Main Switch is in the ON state.
<sup>4</sup> Time period from when the Main Power Switch is turned on to when this machine becomes ready for printing.

Printer Specification  Print resolution	1,800 (equivalent) x 600 dpi, 1,200 x 1,200 dpi
Page Description Language	PostScript 3 (3016) Emulation, PCL 6 (XL Version 3.0) Emulation, PCL 5e/c Emulation, XPS
Operating systems	Windows Vista (32/64), Windows 7 (32/64), Windows 8.1 (32/64), Windows 10 (32/64), Windows Server 2008 (32/64), Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Macintosh OS X 10.7 or later, Linux, Unix, Citrix
Printer fonts	80 PCL, 137 PostScript 3 Emulation
Mobile printing	AirPrint (iOS), Mopria (Android), Google Cloud Print (optional), Wi-Fi Direct (optional), Konica Minolta Print Service (Android), PageScope Mobile (iOS, Android, Windows 10 Mobile)

<b>Scanner Specifications</b>	
Scan speed *5 with DF-629	1-sided original: 55 ipm
(optional)	2-sided original: 26 ipm
Scan speed *5 with DF-704	1-sided original: 55 ipm
(optional)	2-sided original: 110 ipm
Resolution	Max.: 600 x 600 dpi
Scan modes	Scan to Email, Scan to PC (SMB), Scan to FTP, Scan to WebDAV, Scar to BOX (HDD), Scan to WSD (Web Service), Scan to DPWS (Device Profile for Web Service), Scan to USB memory, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A-1a (optional), PDF/A 1-b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX, searchable PPTX (optional), searchable DOCX/XLSX (optional)
Destinations	2,100 (single + group), LDAP, PSDA support

<sup>&</sup>quot;5 When copying A4 or Letter (8-1/2 x 11), resolution 600 dpi

A3 multifunctional with 36/30 ppm b/w. Standard Emperon™ print controller with PCL 6, PCL 5, PostScript 3, PDF 1.7, XPS, and OOXML support. Paper capacity of 500 + 500 sheets and 150-sheet manual bypass. Media from A6 to SRA3, 1.2 m banner and 52 - 300 gsm. 2 GB memory, 250 GB hard disk and Gigabit Ethernet standard.

Fax Specifications (optional)	
Fax	Super G3
Transmission	Analog fax, Internet fax, Colour Internet fax, IP address fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression method	MH, MR, MMR, JBIG
Modem speed	Up to 33.6 Kbps
Destinations	2,100 (single + group)

Components and Options DK-510 Copier desk	Provides storage space for print media and other materials
DK-705 Caster table	Used to install this machine on the floor
FS-533 Inner finisher	
PK-519 Punch kit for FS-533	50-sheet stapling, 500 sheets max. output
	2/4 hole punching, autoswitching 50-sheet stapling,
FS-536 Staple finisher	tray1: max. 200-sheet output, tray2: max. 3,000-sheet outpu
FS_536SD Stanle/hooklet finisher	50-sheet staple finisher, 20-sheet booklet finisher,
13-3303D Staple/ Booklet IIIII311CI	tray1: max. 200-sheet output, tray2: max. 2,000-sheet outpu
RU-513 Relay unit for FS-536/SD	For FS-536/SD installation
PK-520 Punch kit for FS-536/SD	2/4 hole punching, Auto switching
S-506 ob separator	Separation for fax output, etc.
CU-101 Air cleaning unit	Improving indoor air quality by reduced emissions
MK-745 Mount kit for CU-101	Installation kit for CU-101
MK-730 Mount kit for bypass tray	
HT-509	Dehumidification heater for Paper feed cabinet,
Dehumidification heater	for PC-110/210/410, DK-510
MK-734 Dehumidification	Dehumidification heater power supply box (Cabinet heater),
heater power supply box	for PC-110/210/410, DK-510
TK-101 Transformer kit	This unit is required to enable the function heater of the Larg
	capacity unit LU-302
KP-101 10-Key pad	10-key
DF-629 Document feeder	Reversing automatic document feeder, capacity 100 original
DF-704 Document feeder	Dualscan automatic document feeder, capacity 100 originals
SP-501 Stamp unit	Stamps a scanned original when sending a fax
OC-511 Original cover	Cover instead of ADF
WT-506 Working table	Authentication device placement
AH-101 Assist handle	Assist handle
FK-514 Fax board	Super G3 fax, fax functionality for 1st and 2nd line
FK-515 Fax board	Super G3 fax, fax functionality for 3rd and 4th line
MK-742 Mount kit for FK-515	Installation kit for FK-515
UK-211 Upgrade kit	2 GB memory extension for upgrades
LK-102 v3 PDF enhancements	PDF/A, PDF encryption, digital signature
LK-104 v3 Voice guidance	Provides voice guidance functions
LK-105 v4 OCR text recognition	Searchable PDF and PPTX, PDF/A-1a
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110 v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A
LK-111 ThinPrint <sup>®</sup> Client	Print data compression for reduced network impact
LK-114 Server-less pull printing	Server-less pull printing system
LK-115 v2 TPM activation	Trusted Platform Module for protection of data encryption and decryption
KH-102 Keyboard holder	To place USB keyboard
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection, Bluetooth LE
SC-508 Security kit	Copy guard function
MK-735 Mount kit	Installation kit for IC card reader
AU-201S IC card authentication	Various IC card technologies
AU-102 Biometric authentication	9
UK-212 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
UK-215 Wireless LAN	Wireless LAN and wireless LAN Simple Access Point Mode
HD-524 Hard disk mirroring kit	Back-up HDD

- All specifications refer to A4-size paper of 80 gsm quality.
- The support and availability of the listed specifications and functionalities vary depending on operating systems applications and network protocols as well as network and system configurations.
- Some of the product illustrations contain optional accessories.
   Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- $\ \, \text{All brand and product names may be registered trademarks or trademarks of their respective holders and are} \,$ hereby acknowledged.



Standard dual scanning at up to 160 originals per minute Large 9" color display with quick tablet-like touchscreen interface 3rd-party software integration with standard web browser Built-in Emperon® print system, universal printer drivers Simitri® HD polymerized toner for high-resolution imaging

Up to 45 ppm print/copy output to keep pace with rising demands

Standard 250 GB HDD for on-board document storage

Meets ISO 15408 and IEEE 2600.1 Security standards\*

Standard web browser, 4 GB of memory

Power-saving design with quick recovery from sleep mode

6,650-sheet maximum capacity, tab printing support, carbon-copy printing

Finishing options for 80-page booklet-making, up to 100-sheet stapling

Option for 2/3-hole punch, tri-fold, z-fold, post-insertion and more

#### \*May not be available at time of launch

## bizhub 458

MONOCHROME MID-VOLUME MULTIFUNCTION PRINTER







#### bizhub 458

Ideal for growing businesses, the bizhub 458 is a powerful, affordable monochrome MFP with superior Simitri HD image quality and fast 45 ppm print/copy output. Standard dual scanning at up to 160 opm brings information into your workflow faster—and enhanced touch screen simplicity never slows you down.

#### **System Overview**

System Over view	
System memory	4 GB
System hard disk	250 GB Standard
Interface	10-BASE-T / 100-BASE-TX / 1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Document feeder	Up to 100 originals / 5.5" x 8.5" to 11" x 17" / 35–163 gsm
Printable paper size	Scanning/Copying: up to 11" x 17"
	Printing: up to 11" x 17" full bleed on 12" x 18" paper
	Custom paper sizes
	Banner paper max.: 11.75" x 47.25"
Printable paper	52–300 gsm
weight	
Paper input capacity	Standard: 1,150 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 11" x 17" / 52–256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 3 (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 4 (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 52-256 gsm
Large capacity tray	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm
LU-207 (optional)	
Large capacity tray	3,000 sheets / 8.5" x 11" / 52-256 gsm
LU-302 (optional)	
Large capacity tray	2,500 sheets / 8.5" x 11" / 52–256 gsm
PC-410 (optional)	
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes /
	50–300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52–256 gsm
Finishing modes	Offset, group, sort, staple, punch, half-fold, z-fold, tri-fold,
	post-insertion, booklet
Output capacity	Max. with finisher: 3,200 sheets
<u> </u>	Max. without finisher: 250 sheets
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheet
Ctauliuu aastaast	(up to 209 gsm)
Stapling output capacity	<b>Max.:</b> 1,000 sheets
Tri-fold (optional)	Up to 3 sheets
Tri-fold (optional)	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output	Max.: 100 sheets (tray)
capacity	widx 100 sileets (tray)
	Max.: 200,000 pages / month <sup>1</sup>
	· -
Copy/print volume	24 400 nages
Toner lifetime	24,400 pages 155,000 pages / 600,000 pages (Drum / Developer)
Toner lifetime Imaging unit lifetime	155,000 pages / 600,000 pages (Drum / Developer)
Toner lifetime Imaging unit lifetime Power consumption	155,000 pages / 600,000 pages (Drum / Developer) 120 V / 60 Hz, less than 0.5 kW (system)
Toner lifetime Imaging unit lifetime	155,000 pages / 600,000 pages (Drum / Developer)

#### **Printer Specifications**

Printer Specifications	
Print resolution	1,800 x 600 dpi, 1,200 x 1,200 dpi
PDL	PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32/x64): Vista / 7 / 8 / 10
	Windows Server (x32/x64): 2003 / 2008 / 2008 R23 / 20123
	Macintosh OS X 10.7 or later
	Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files
	and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex,
	"Easy Set" job programming, overlay, watermark, copy
	protection, carbon copy print

#### **Copier Specifications**

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri HD Polymerized Toner
Print speed	Up to 45 ppm (portrait)
(8.5" x 11")	
Print speed	Up to 22 ppm (portrait)
(11" x 17")	
Autoduplex speed	Up to 45 ppm (portrait)
(8.5" x 11")	
1st copy out time	4.0 sec.
Warm-up time	Approx. 25 sec. <sup>2</sup>
Copy resolution	600 x 600 dpi
Gradations	256 gradations
Multi-copy	1–9,999
Original format	Up to 11" x 17"
Magnification	25-400% in 0.1% steps, auto zooming
Copy functions	Electronic sorting, multi-job, adjustments (contrast,
	sharpness, image density), proof copy, interrupt mode,
	color mode, separate scan, sort/group, combination,
	original selection, ID card copy, 2-in-1, 4-in-1
	·

#### **Scanner Specifications**

Scan speed	B&W / Color: up to 160 ipm
Scan resolution	<b>Max.:</b> 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box,
	Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network
	TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact
	PDF, encrypted PDF and searchable PDF (optional), XPS,
	compact XPS, PPTX and searchable PPTX (optional),
	searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job
	programs, realtime scan preview

#### **Fax Specifications**

Fax	Super G3 (optional)
Transmission	Analog, Internet Fax, Color i-Fax, IP-Fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box,
	receipt to Email/FTP/SMB, up to 400 job programs

#### **User Box Specifications**

Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public
	Personal (with password or authentication)
	Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt,
	fax polling, annotation
User box functionality	Reprint, combination, download, sending
•	(email/FTP/SMB and fax), copy box-to-box

Security	ISO 15408 EAL <sup>4</sup>
-	IEEE 2600.14
	IP filtering and port blocking
	SSL2, SSL3 and TSL1.0 network communication
	IPsec support
	IEEE 802.1x support
	FIPS 140-2
	User authentication
	Authentication log
	Secure print
	Hard disk overwrite (8 standard types)
	Hard disk data encryption (AES 128)
	Memory data auto deletion
	Confidential fax receipt,
	Print user data encryption
	Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts
	Active Directory support
	(user name + password + email + SMB folder)
	User function access definition
	Optional Biometric authentication (finger vein scanner)
	Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager
	PageScope Data Administrator
	PageScope Box Operator
	PageScope Direct Print
	Print Status Notifier
	Driver Packaging Utility
	Log Management Utility

<sup>&</sup>lt;sup>1</sup> Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs

**Components and Options** 

<b>Components and Option</b>	ons
AU-102 Biometric	Finger vein scanner
authentication	
Dynamag magnetic	Requires WT-506 Working Table
stripe card reader	
AU-205H Universal	Various ID card technologies
ID card reader*	
AU-211 CA/PIV solution	Requires WT-506 Working Table
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection, Bluetooth
DK-510 Copier desk	Provides storage space for print media and other materials
FK-514 Fax board	Super G3 fax, digital fax functionality
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support
	(requires MK-742)
FS-533 Staple finisher	50-sheet stapling, 500 sheets max. output
FS-536 Staple finisher	50-sheet stapling, 3,200 sheets max. output (requires RU-513)
FS-536SD Booklet	50-sheet staple finisher, 20-sheet booklet finisher,
finisher	2,200 sheets max. output (requires RU-513)
FS-537 Staple finisher	100-sheet stapling, 3,200 sheets max. output (requires RU-513)
FS-537SD Booklet	100-sheet stapling, 20-sheet booklet finisher,
finisher	2,500 sheets max. output (requires RU-513)
HD-524 Hard disk	Hard disk mirroring, 250 GB
JS-506 Job separator	Separation for fax output, etc.
JS-602 Job separator	Separation for fax output, etc.
for FS-537	
KH-102 Keyboard holder	To place USB keyboard
KP-101 10-Key pad	For use instead of touchscreen
LK-102 v3 PDF	PDF/A, PDF encryption, digital signature
enhancements	TDI/A, TDI encryption, digital signature
LK-104 v3 Voice	Provides voice guidance functions
guidance	Trovides voice guidance functions
LK-105 v4 OCR	Searchable PDF
text recognition	Searchable FDI
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native barcode printing  Supports native Unicode printing
LK-107 Officode forts	
and B fonts	Supports native OCR A and B font printing
LK-110 v2 Enhanced	Generates various file formats incl. DOCX, XLSX and
image support	combines LK-102 (encrypted PDF) + LK-105 (searchable
illage support	PDF/OCR functionality)
LK-111 ThinPrint® Client	Print data compression for reduced network impact
LU-207 Large	8.5" x 11" to 12" x 18", 2,500 sheets / 52–256 gsm
capacity unit	0.5 X 11 to 12 X 10 , 2,500 sheets / 52-250 gsill
LU-302 Large	8.5" x 11", 3,000 sheets / 52–256 gsm
capacity unit	0.5 X 11 , 5,000 sileets / 52-230 gsill
MK-730 Mount kit	Rannor nanor quido
MK-735 Mount kit	Banner paper guide Installation kit for ID card reader
MK-742 Mount kit	Installation kit for FK-515 fax board
OT-506 Output tray	Output tray use instead of finisher
PC-110 Universal	5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm
tray (x1)	5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm
PC-210 Universal	5.5 X 8.5 to 11 X 17 , 2 X 500 sneets, 52–256 gsm
tray (x2) PC-410 Large	0.5111111. 2.500 -h
•	8.5" x 11", 2,500 sheets, 52–256 gsm
capacity tray PI-507 Post inserter	Cover insertion, post finishing
for FS-537	Cover insertion, post imisming
PK-519 Punch kit	2/3-hole punching, autoswitching
for FS-533	2/3-Hole punching, autoswitching
	2/3-hole punching, autoswitching
PK-520 Punch kit for FS-536	2/3-note puncting, autoswitching
PK-523 Punch kit	2/2 hala nunching autoquitahing
for FS-537	2/3-hole punching, autoswitching
	Didfth FC F27 / FC F27CD FC F2C / FC F2CCD
RU-513 Relay unit	Required for the FS-537 / FS-537SD, FS-536 / FS-536SD
SC-508 Security kit	Copy Guard function (2x required)
SP-501 Stamp unit	Added fax stamp capability kit
UK-212 Wireless LAN	Wireless LAN to network connector
UK-501 Multi-feed	Detects multi-feeding in the document feeder
detection kit	A di
WT-506 Working table	Authentication device placement
ZU-609 Z-fold unit	Z-fold for 11" x 17" prints, 2/3-hole punching
for FS-537	
*May not be available at time of launc	II .

<sup>\*</sup>May not be available at time of launch

 $<sup>^{\</sup>rm 2}\,\mbox{Warm-up}$  time may vary depending on the operating environment and usage

<sup>&</sup>lt;sup>3</sup> Supports x64 only

<sup>&</sup>lt;sup>4</sup> Certification pending



Up to 55 ppm print/copy output to keep pace with rising demands Standard dual scanning at up to 160 originals per minute

Large 9" color display with quick tablet-like touchscreen interface
3rd-party software integration with standard web browser

Built-in Emperon® print system, universal printer drivers

Simitri® HD polymerized toner for high-resolution imaging


Standard 250 GB HDD for on-board document storage

Meets ISO 15408 and IEEE 2600.1 Security standards\*

Standard web browser, 4 GB of memory

Power-saving design with quick recovery from sleep mode

6,650-sheet maximum capacity, tab printing support, carbon-copy printing





#### bizhub 558

Ideal for growing businesses, the bizhub 558 is a powerful, affordable monochrome MFP with superior Simitri HD image quality and fast 55 ppm print/copy output. Standard dual scanning at up to 160 opm brings information into your workflow faster—and enhanced touch screen simplicity never slows you down.

#### **System Overview**

System Overview	
System memory	4 GB
System hard disk	250 GB Standard
Interface	10-BASE-T / 100-BASE-TX / 1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Document feeder	Up to 100 originals / 5.5" x 8.5" to 11" x 17" / 35–163 gsm
	Dual scan document feeder
Printable paper size	Scanning/Copying: up to 11" x 17"
	Printing: up to 11" x 17" full bleed on 12" x 18" paper
	Custom paper sizes
	Banner paper max.: 11.75" x 47.25"
Printable paper	52–300 gsm
weight	
Paper input capacity	Standard: 1,150 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 11" x 17" / 52–256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 3 (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 4 (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 52-256 gsm
Large capacity tray	2,500 sheets / 8.5" x 11" to 12" x 18" / 52–256 gsm
LU-207 (optional)	
Large capacity tray	3,000 sheets / 8.5" x 11" / 52-256 gsm
LU-302 (optional)	
Large capacity tray	2,500 sheets / 8.5" x 11" / 52-256 gsm
PC-410 (optional)	
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes /
	50–300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, staple, sort, punch, half-fold, z-fold, tri-fold,
	post-insertion, booklet
Output capacity	Max. with finisher: 3,200 sheets
	Max. without finisher: 250 sheets
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheet
	(up to 209 gsm)
Stapling output	Max.: 1,000 sheets
capacity	
Tri-fold (optional)	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm
Booklet output	Max.: 100 sheets (tray)
capacity	
Copy/print volume	Max.: 250,000 pages / month <sup>1</sup>
Toner lifetime	24,400 pages
Imaging unit lifetime	160,000 pages / 600,000 pages (Drum / Developer)
Power consumption	120 V / 60 Hz, less than 0.5 kW (system)
System dimensions	24.2" x 27" x 31" (W x D x H)
System weight	Approx. 205.03 lb

#### **Printer Specifications**

Print resolution	1,800 x 600 dpi, 1,200 x 1,200 dpi
PDL	PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32/x64): Vista / 7 / 8 / 10
	Windows Server (x32/x64): 2003 / 2008 / 2008 R23 / 20123
	Macintosh OS X 10.7 or later
	Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

#### **Copier Specifications**

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri HD Polymerized Toner
Print speed	Up to 55 ppm (portrait)
(8.5" x 11")	
Print speed	Up to 27 ppm (portrait)
(11" x 17")	
Autoduplex speed	Up to 55 ppm (portrait)
(8.5" x 11")	
1st copy out time	3.5 sec.
Warm-up time	Approx. 22 sec. <sup>2</sup>
Copy resolution	600 x 600 dpi
Gradations	256 gradations
Multi-copy	1–9,999
Original format	Up to 11" x 17"
Magnification	25–400% in 0.1% steps, auto zooming
Copy functions	Electronic sorting, multi-job, adjustments (contrast,
	sharpness, image density), proof copy, interrupt mode,
	color mode, separate scan, sort/group, combination,
	original selection, ID card copy, 2-in-1, 4-in-1
	·

#### **Scanner Specifications**

Scan speed	B&W / Color: up to 160 ipm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP,
	Scan-to-Box, Scan-to-USB, Scan-to-WebDAV,
	Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact
	PDF, encrypted PDF and searchable PDF (optional), XPS,
	compact XPS, PPTX and searchable PPTX (optional),
	searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job
	programs, realtime scan preview

#### **Fax Specifications**

Fax	Super G3 (optional)
Transmission	Analog, Internet Fax, Color i-Fax, IP-Fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to email/FTP/SMB, up to 400 job programs

#### **User Box Specifications**

Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public
	Personal (with password or authentication)
	Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt,
	fax polling, annotation
User box functionality	Reprint, combination, download, sending
	(email/FTP/SMB and fax), copy box-to-box

Security	ISO 15408 EAL <sup>4</sup>
ŕ	IEEE 2600.1 <sup>4</sup>
	IP filtering and port blocking
	SSL2, SSL3 and TSL1.0 network communication
	IPsec support
	IEEE 802.1x support
	FIPS 140-2
	User authentication
	Authentication log
	Secure print
	Hard disk overwrite (8 standard types)
	Hard disk data encryption (AES 128)
	Memory data auto deletion
	Confidential fax receipt,
	Print user data encryption
	Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts
	Active Directory support
	(user name + password + email + SMB folder)
	User function access definition
	Optional Biometric authentication (finger vein scanner)
	Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager
	PageScope Data Administrator
	PageScope Box Operator
	PageScope Direct Print
	Print Status Notifier
	Driver Packaging Utility
	Log Management Utility

Log Management Utility

1 Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs

**Components and Options** 

	ons
AU-102 Biometric	Finger vein scanner
authentication	
Dynamag magnetic	Requires WT-506 Working Table
stripe card reader	
AU-205H Universal	Various ID card technologies
ID card reader*	
AU-211 CA/PIV solution	Requires WT-506 Working Table
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection, Bluetooth
DK-510 Copier desk	Provides storage space for print media and other materials
FK-514 Fax board	Super G3 fax, digital fax functionality
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support
FC F22 Ct . 1. C . 1. L	(requires MK-742)
FS-533 Staple finisher	50-sheet stapling, 500 sheets max. output
FS-536 Staple finisher	50-sheet stapling, 3,200 sheets max. output (requires RU-513)
FS-536SD Booklet	50-sheet staple finisher, 20-sheet booklet finisher,
finisher	2,200 sheets max. output (requires RU-513) 100-sheet stapling, 3,200 sheets max. output (requires RU-513)
FS-537 Staple finisher FS-537SD Booklet	
finisher	100-sheet stapling, 20-sheet booklet finisher,
HD-524 Hard disk	2,500 sheets max. output (requires RU-513)  Hard disk mirroring, 250 GB
JS-506 Job separator	Separation for fax output, etc.
JS-602 Job separator	Separation for fax output, etc.
for FS-537	ocparation for fax output, etc.
KH-102 Keyboard holder	To place USB keyboard
KP-101 10-Key pad	For use instead of touchscreen
LK-102 v3 PDF	PDF/A, PDF encryption, digital signature
enhancements	1 DI /A, 1 DI CHELYPHON, digital signature
LK-104 v3 Voice	Provides voice guidance functions
guidance	·····
LK-105 v4 OCR	Searchable PDF
text recognition	
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A	Supports native OCR A and B font printing
and B fonts	
LK-110 v2 Enhanced	Generates various file formats incl. DOCX, XLSX and
image support	combines LK-102 (encrypted PDF) + LK-105 (searchable
	PDF/OCR functionality)
LK-111 ThinPrint® Client	Print data compression for reduced network impact
LU-207 Large	8.5" x 11" to 12" x 18", 2,500 sheets / 52–256 gsm
LU-207 Large capacity unit	
LU-207 Large capacity unit LU-302 Large	8.5" x 11" to 12" x 18", 2,500 sheets / 52–256 gsm  8.5" x 11", 3,000 sheets / 52–256 gsm
LU-207 Large capacity unit LU-302 Large capacity unit	8.5" x 11", 3,000 sheets / 52–256 gsm
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1)	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2)	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm  5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2) PC-410 Large	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2) PC-410 Large capacity tray	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm  5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm  8.5" x 11", 2,500 sheets, 52–256 gsm
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2) PC-410 Large capacity tray PI-507 Post inserter	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm  5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2) PC-410 Large capacity tray	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm  5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm  8.5" x 11", 2,500 sheets, 52–256 gsm
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2) PC-410 Large capacity tray PI-507 Post inserter for FS-537	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm  5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm  8.5" x 11", 2,500 sheets, 52–256 gsm  Cover insertion, post finishing
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2) PC-410 Large capacity tray PI-507 Post inserter for FS-537 PK-519 Punch kit	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm  5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm  8.5" x 11", 2,500 sheets, 52–256 gsm  Cover insertion, post finishing
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2) PC-410 Large capacity tray PI-507 Post inserter for FS-537 PK-519 Punch kit for FS-533	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm  5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm  8.5" x 11", 2,500 sheets, 52–256 gsm  Cover insertion, post finishing  2/3-hole punching, autoswitching
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2) PC-410 Large capacity tray PI-507 Post inserter for FS-537 PK-519 Punch kit for FS-533 PK-520 Punch kit	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm  5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm  8.5" x 11", 2,500 sheets, 52–256 gsm  Cover insertion, post finishing  2/3-hole punching, autoswitching
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2) PC-410 Large capacity tray PI-507 Post inserter for FS-537 PK-519 Punch kit for FS-533 PK-520 Punch kit for FS-536	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm  5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm  Cover insertion, post finishing  2/3-hole punching, autoswitching
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2) PC-410 Large capacity tray PI-507 Post inserter for FS-537 PK-519 Punch kit for FS-533 PK-520 Punch kit for FS-536 PK-523 Punch kit	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm  5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm  Cover insertion, post finishing  2/3-hole punching, autoswitching
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2) PC-410 Large capacity tray PI-507 Post inserter for FS-537 PK-519 Punch kit for FS-533 PK-520 Punch kit for FS-536 PK-523 Punch kit for FS-537	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm  5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm  8.5" x 11", 2,500 sheets, 52–256 gsm  Cover insertion, post finishing  2/3-hole punching, autoswitching  2/3-hole punching, autoswitching
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2) PC-410 Large capacity tray PI-507 Post inserter for FS-537 PK-519 Punch kit for FS-533 PK-520 Punch kit for FS-536 PK-523 Punch kit for FS-537 RU-513 Relay unit	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm  5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm  8.5" x 11", 2,500 sheets, 52–256 gsm  Cover insertion, post finishing  2/3-hole punching, autoswitching  2/3-hole punching, autoswitching  Required for the FS-537 / FS-537SD, FS-536 / FS-536SD Copy Guard function (2x required)  Added fax stamp capability kit
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2) PC-410 Large capacity tray PI-507 Post inserter for FS-537 PK-519 Punch kit for FS-533 PK-520 Punch kit for FS-536 PK-523 Punch kit for FS-537 RU-513 Relay unit SC-508 Security kit	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm  5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm  8.5" x 11", 2,500 sheets, 52–256 gsm  Cover insertion, post finishing  2/3-hole punching, autoswitching  2/3-hole punching, autoswitching  Required for the FS-537 / FS-537SD, FS-536 / FS-536SD Copy Guard function (2x required)
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2) PC-410 Large capacity tray PI-507 Post inserter for FS-537 PK-519 Punch kit for FS-533 PK-520 Punch kit for FS-536 PK-523 Punch kit for FS-536 PK-523 Punch kit for FS-537 RU-513 Relay unit SC-508 Security kit SP-501 Stamp unit	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm  5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm  8.5" x 11", 2,500 sheets, 52–256 gsm  Cover insertion, post finishing  2/3-hole punching, autoswitching  2/3-hole punching, autoswitching  Required for the FS-537 / FS-537SD, FS-536 / FS-536SD Copy Guard function (2x required)  Added fax stamp capability kit
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2) PC-410 Large capacity tray PI-507 Post inserter for FS-537 PK-519 Punch kit for FS-538 PK-520 Punch kit for FS-537 RU-513 Relay unit SC-508 Security kit SP-501 Stamp unit UK-212 Wireless LAN UK-501 Multi-feed detection kit	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm  5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm  8.5" x 11", 2,500 sheets, 52–256 gsm  Cover insertion, post finishing  2/3-hole punching, autoswitching  2/3-hole punching, autoswitching  Required for the FS-537 / FS-537SD, FS-536 / FS-536SD Copy Guard function (2x required)  Added fax stamp capability kit  Wireless LAN to network connector Detects multi-feeding in the document feeder
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2) PC-410 Large capacity tray PI-507 Post inserter for FS-537 PK-519 Punch kit for FS-538 PK-520 Punch kit for FS-537 RU-513 Relay unit SC-508 Security kit SP-501 Stamp unit UK-212 Wireless LAN UK-501 Multi-feed detection kit	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm  5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm  Cover insertion, post finishing 2/3-hole punching, autoswitching  2/3-hole punching, autoswitching  Required for the FS-537 / FS-537SD, FS-536 / FS-536SD Copy Guard function (2x required) Added fax stamp capability kit Wireless LAN to network connector Detects multi-feeding in the document feeder  Authentication device placement
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2) PC-410 Large capacity tray PI-507 Post inserter for FS-537 PK-519 Punch kit for FS-533 PK-520 Punch kit for FS-537 RU-513 Relay unit SC-508 Security kit SP-501 Stamp unit UK-212 Wireless LAN UK-501 Multi-feed detection kit WT-506 Working table ZU-609 Z-fold unit	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm  5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm  8.5" x 11", 2,500 sheets, 52–256 gsm  Cover insertion, post finishing  2/3-hole punching, autoswitching  2/3-hole punching, autoswitching  Required for the FS-537 / FS-537SD, FS-536 / FS-536SD Copy Guard function (2x required)  Added fax stamp capability kit  Wireless LAN to network connector Detects multi-feeding in the document feeder
LU-207 Large capacity unit LU-302 Large capacity unit MK-730 Mount kit MK-735 Mount kit MK-742 Mount kit OT-506 Output tray PC-110 Universal tray (x1) PC-210 Universal tray (x2) PC-410 Large capacity tray PI-507 Post inserter for FS-537 PK-519 Punch kit for FS-538 PK-520 Punch kit for FS-537 RU-513 Relay unit SC-508 Security kit SP-501 Stamp unit UK-212 Wireless LAN UK-501 Multi-feed detection kit	8.5" x 11", 3,000 sheets / 52–256 gsm  Banner paper guide Installation kit for ID card reader Installation kit for ID card reader Installation kit for FK-515 fax board Output tray use instead of finisher 5.5" x 8.5" to 11" x 17", 500 sheets, 52–256 gsm  5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52–256 gsm  8.5" x 11", 2,500 sheets, 52–256 gsm  Cover insertion, post finishing  2/3-hole punching, autoswitching  2/3-hole punching, autoswitching  Required for the FS-537 / FS-537SD, FS-536 / FS-536SD Copy Guard function (2x required)  Added fax stamp capability kit Wireless LAN to network connector Detects multi-feeding in the document feeder  Authentication device placement Z-fold for 11" x 17" prints, 2/3-hole punching

<sup>\*</sup>May not be available at time of launch

 $<sup>^{\</sup>rm 2}\,\mbox{Warm-up}$  time may vary depending on the operating environment and usage

<sup>&</sup>lt;sup>3</sup> Supports x64 only

<sup>&</sup>lt;sup>4</sup> Certification pending



#### • • • •

High-speed print/copy output of 80 ppm in high-quality B&W Standard dual scanning handles up to 240 originals per minute High capacity 300-sheet document feeder INFO-Palette display for instant access to more information Large 9" color display with quick tablet-like interface Web browser ready with 4 GB memory Downloadable apps to improve your productivity Built-in Emperon® print system, universal printer drivers Simitri® HDE toner guarantees excellent print quality Scan to email and ftp, scan-to-me, scan-to-home convenience 6,650-Sheet capacity, tab printing support, carbon-copy printing Finishing options for 80-page booklet-making, up to 100-sheet stapling Options for 2/3-hole punch, tri-fold, z-fold, post-insertion and more Internal card reader and other advanced security options ISO 15408 and IEEE 2600.1 Security standards Optional voice guidance, PDF/A formatting Multiple i-Options to suit the needs of your workflow Low power consumption, eco-indicator to help cut costs **EPEAT Gold-certified** Mobile printing support (AirPrint, Google Cloud Print, NFC)

## bizhub 808

MONOCHROME HIGH-VOLUME MULTIFUNCTION PRINTER

mfp





#### bizhub 808

With 80 ppm print/copy output in high-resolution B&W, standard dual scanning at up to 240 opm, multiple finishing options and enhanced touch-and-swipe interface, the bizhub 808 brings maximum productivity to high-volume document demands and in-house, on-demand printing applications.

#### **System Overview**

System memory	4 GB
System hard disk	250 GB
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0,
	Wi-Fi 802.11 b/g (opt.)
Network protocols	TCP/IP (IPv4/IPv6), NetBEUI, SMB, LPD, IPP, SNMP, HTTP
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Dual scan	Up to 300 originals / 5.5" x 8.5" to 11" x 17" / 35–210 gsm
document feeder	
Printable paper size	Scanning/Copying: up to 11" x 17"
	Printing: up to 11" x 17" full bleed on 12" x 18" paper
	Custom paper sizes
	Banner paper max.: 11.75" x 47.25"
Printable	52–300 gsm
paper weight	
Paper input capacity	Standard: 3,650 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52–256 gsm
Tray 3	1,500 sheets / 8.5" x 11", 5.5" x 8.5", 4" x 6" / 52-256 gsm
Tray 4	1,000 sheets / 8.5" x 11", 5.5" x 8.5", 4" x 6" / 52-256 gsm
Large capacity tray	3,000 sheets / 8.5" x 11" / 52-256 gsm
LU-303 (optional)	
Large capacity tray	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm
LU-205 (optional)	
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes /
	52–300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52–256 gsm
Finishing modes	Offset, group, sort, staple, punch, post insertion,
	z-fold, half-fold, tri-fold, booklet
Output capacity	Max. with finisher: 3,200 sheets
	Max. without finisher: 250 sheets
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheets
	(up to 209 gsm)
Stapling	Max.: 1000 sheets
output capacity	
Tri-fold	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray), unlimited
Booklet	Max.: 20 sheets or 19 sheets + 1 cover sheet
	(up to 209 gsm)
Booklet output	Max.: 100 sheets (tray), unlimited
capacity	
Copy/print volume	Max.: 300,000 pages/month <sup>1</sup>
Toner lifetime	Black: 40,800 pages
Imaging unit lifetime	400,000 pages / 1,200,000 pages (Developer)
Power consumption	120 V / 50/60 Hz, less than 2.1 kW (system)
System dimensions	26.4" x 32.3" x 48.5" (W x D x H)
System weight	Approx. 441 lb.

### **Printer Specifications**

Printer Specification	ons
Print resolution	1,800 x 600 dpi, 1,200 x 1,200 dpi
PDL	PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32/x64): Vista / 7 / 8
	Windows Server (x32/x64): 2008 / 2008 R2 / 2012 / 2012 R2
	Macintosh OS X 10.6 / 10.7 / 10.8 / 10.9 / 10.10
	UNIX / Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3 emulation
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files
	and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex,
	"Easy Set" job programming, overlay, watermark, copy
	protection, carbon convingint

#### **Copier Specifications**

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri <sup>®</sup> HD <sup>E</sup> Polymerized Toner
Print speed	Up to 80 ppm (Portrait)
(8.5" x 11")	
Autoduplex speed	Up to 80 ppm (Portrait)
(8.5" x 11")	
1st copy out time	3.6 sec.
Warm-up time	Approx. 100 sec. <sup>2</sup>
Copy resolution	600 x 600 dpi
Gradations	256 gradations
Multi-copy	1–9,999
Original format	Up to 11" x 17"
Magnification	25–400% in 0.1% steps, auto zooming
Copy functions	Chapter, cover and page insertion, proof copy (print
	and screen), adjustment test print, digital art functions,
	job setting memory, poster mode, image repeat,
	overlay, stamping, copy protection

#### **Scanner Specifications**

Scan speed	B&W / Color: up to 240 ipm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box,
	Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network
	TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact
	PDF, encrypted PDF and searchable PDF (optional), XPS,
	compact XPS, PPTX and searchable PPTX (optional),
	searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job
	programs, real time scan preview

#### **Fax Specifications**

Fax	Super G3 (optional)
Transmission	Analog, i-Fax, Color i-Fax, IP-fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box,
	receipt to Email/FTP/SMB, up to 400 job programs

#### **User Box Specifications**

	<del></del>
Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public
	Personal (with password or authentication)
	Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling
User box functionality	Reprint, combination, download, sending
	(Email/FTP/SMB and fax), copy box-to-box

Security	ISO 15408 EAL3 <sup>3</sup>	
-	IEEE 2600.1 <sup>3</sup>	
	IP filtering and port blocking	
	SSL2, SSL3 and TSL1.0 network communication	
	IPsec support	
	IEEE 802.1x support	
	User authentication	
	Authentication log	
	Secure print	
	Hard disk overwrite (8 standard types)	
	Hard disk data encryption (AES 256)	
	Hard disk mirroring (opt.) Memory data auto deletion Confidential fax receipt	
		Print user data encryption
		Copy protection (Copy Guard, Password Copy) (opt.)
	Accounting	Up to 1,000 user accounts
		Active Directory support
	(user name + password + Email + SMB folder)	
	User function access definition	
	Optional Biometric authentication (finger vein scanner)	
	Optional ID card authentication (ID card reader)	
Software	PageScope Net Care Device Manager	
	PageScope Data Administrator	
	PageScope Box Operator	
	PageScope Direct Print	
	Print Status Notifier	
	Driver Packaging Utility	
	Log Management Utility	

Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.

**Components and Options** 

Components and Opti	ions
AU-102 Biometric	Finger vein scanner
nuthentication	
AU-205H Universal	Various ID card technologies
D card reader	-
K-610 USB I/F kit	USB keyboard connection
EK-611 USB I/F kit	USB keyboard connection, Bluetooth
K-515 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support
K-516 Fax board	Super G3 fax, digital fax functionality
S-536 Staple finisher	50-sheet stapling, 3,200 sheets max. output
S-536SD	50-sheet staple finisher, 20-sheet booklet finisher,
Booklet finisher	2,200 sheets max. output
S-537 Staple finisher	100-sheet stapling, 3,200 sheets max. output
S-537SD	100-sheet stapling, 20-sheet booklet finisher,
Booklet finisher	2,500 sheets max. output
ID-524 Hard	Back-up HDD
lisk mirroring	васк-ир прр
	Constitution for four surfaces to the
S-602 Job	Separation for fax output, etc.
eparator for FS-537	External leash and (require - 1/11 102)
(eyboard	External keyboard (requires KH-102)
(H-102	To place USB keyboard
Keyboard holder	F 1 1 6 1
(P-101 10-Key pad	For use instead of touchscreen
K-102 v3	PDF/A, PDF encryption, digital signature
DF enhancements	
.K-104 v3	Provides voice guidance functions
/oice guidance	
K-105 v3	Searchable PDF
OCR text recognition	
K-106	Supports native barcode printing
Barcode fonts	
.K-107	Supports native Unicode printing
Jnicode fonts	
K-108	Supports native OCR A and B font printing
OCR A and B fonts	
K-110 Enhanced	Generates various file formats incl. DOCX, XLSX
mage support	and combines LK-102 (encrypted PDF) + LK-105
	(searchable PDF/OCR functionality)
K-111	Print data compression for reduced network impact
hinPrint® Client	
U-205	8.5" x 11" to 12" x 18", 2,500 sheets, 52-256 gsm
arge capacity tray	
U-303	8.5" x 11", 3,000 sheets, 52–256 gsm
arge capacity tray	
/IK-735 Mount kit	Installation kit for ID card reader
/IK-742 Mount kit	Installation kit for FK-515 fax board
T-508 Output tray	Output tray used instead of finisher
PI-507 Post inserter	Cover insertion, post finishing
or FS-537	., 3
K-520 Punch kit	2/3-hole punching, autoswitching
or FS-536	,
PK-523 Punch kit	2/3-hole punching, autoswitching
or FS-537	2, 5 hole punching, autoswitching
U-515 Relay unit	Required for the FS-537/FS-537SD
o Ji J Nelay Ullit	and FS-536/FS-536SD
C-508 Security kit	Copy Guard function (2x required)
JK-212	Wireless LAN to network connector
JK-501 Multi-feed	Detects multi-feeding in the document feeder
letection kit	A. Alexandra da de de de de
VT-506 Working table	Authentication device placement
VT-513 Working table	Used to mount the control panel in an upright position
ZU-609 Z-fold unit for FS-537	Z-fold for 11" x 17" prints, 2/3-hole punching

<sup>&</sup>lt;sup>2</sup> Warm-up time may vary depending on the operating environment and usage

<sup>&</sup>lt;sup>3</sup> Certification pending



## **Color Multifunction Devices**





Up to 22 ppm print/copy output to keep pace with rising demands

Color display with quick tablet-like interface

Touchscreen for simple control and 3rd-party software integration

Standard web browser to support web-based apps

Built-in Emperon® print system, universal printer drivers

Simitri® HD polymerized toner for high-resolution imaging

Standard 250 GB HDD for on-board document storage

Meets ISO 15408 and IEEE 2600.1 Security standards

Power-saving design with quick recovery from sleep mode

3,600-sheet maximum capacity, tab printing support, carbon-copy printing

Advanced authentication, secure print release, remote firmware updates

Options for booklet-making, stapling, hole punch and more

Downloadable apps to help you work faster and smarter

i-Options to add functions for working more efficiently

Low power consumption to cut costs

Mobile printing support (AirPrint, Google Cloud Print, NFC)

## bizhub C227

COLOR MID-VOLUME MULTIFUNCTION PRINTER

mfp





#### bizhub C227

As easy as a familiar tablet, the enhanced touch-and-swipe interface of the bizhub C227 helps make you more productive – with 22 ppm output in high-resolution color, scanning up to 45 originals per minute, 3,600-sheet maximum paper capacity and economical, high-value performance.

System Overview	
System memory	4 GB (when UK-211 is installed)
System hard disk	250 GB
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Reversing automatic document feeder (optional)	Up to 100 originals / 5.5" x 8.5" to 11" x 17" / 50-128 gsm
Printable paper size	Scanning/Copying: up to 11" x 17"  Printing: up to 11" x 17"  Custom paper sizes
Printable paper weight	60-220 gsm
Paper input capacity	Standard: 1,100 sheets / Max.: 3,600 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 8.5" x 14" / 60-220 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 11" x 17" / 60-220 gsm
Tray 3 (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 60-220 gsm
Tray 4 (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 60-220 gsm
Large capacity tray PC-413 (optional)	2,500 sheets / 8.5" x 11" / 60-220 gsm
Manual bypass	100 sheets / 4" x 6" to 11" x 17" / custom paper sizes / 60-220 gsm
Automatic duplexing	5.5" x 8.5" to 11" x 17" / 60-220 gsm
Finishing modes	Offset, group, sort, punch, half-fold, tri-fold, booklet
Output capacity	Max. with finisher: 3,300 sheets Max. without finisher: 250 sheets
Stapling (optional)	Max.: 50 sheets or 48 sheets + 1 cover sheet (up to 209 gsm)
Stapling output capacity	Max.: 1,000 sheets
Tri-fold (optional)	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray)
Copy/print volume	Max.: 100,000 pages/month <sup>1</sup>
Toner lifetime	23,000 pages
Imaging unit lifetime	85,000 pages / 600,000 pages (Drum / Developer)
Power consumption	120 V / 50/60 Hz, less than 1.5 kW (system)
System dimensions	23.0" x 26.0" x 28.9" (W x D x H)
System weight	Approx. 124.6 lb

		_		
,uı	nior	Sno	rifics	itions

Copying process	Electrostatic laser copy, tandem	
Toner system	Simitri® HD Polymerized Toner	
Print speed (8.5" x 11")	Up to 22 ppm (Portrait)	
Print speed (11" x 17")	Up to 14 ppm	
Auto-duplex speed	Up to 22 ppm (Portrait)	
(8.5" x 11")		
1st copy out time	<b>B&amp;W:</b> 6.8 sec. / <b>Color:</b> 8.4 sec.	
Warm-up time	Approx. 20 sec. <sup>2</sup>	
Copy resolution	600 x 600 dpi	
Gradations	256 gradations	
Multi-copy	1-9,999	
Original format	Up to 11" x 17"	
Magnification	25-400% in 0.1% steps, auto zooming	
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1	

#### **Printer Specifications**

Print resolution	1,800 (equivalent) x 600 dpi
PDL PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS	
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 / 10 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 <sup>3</sup> / 2012 <sup>3</sup> Macintosh OS X 10.2.8 or later UNIX / Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

### **Scanner Specifications**

Scan speed	B&W / Color: up to 45 ipm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview

#### **Fax Specifications**

Fax	Super G3 (optional)
Transmission	Analog, i-Fax, Color i-Fax, IP-Fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to Email/ETP/SMB, up to 400 job programs

#### **User Box Specifications**

Max.: 3,000 documents or 10,000 pages
Public
Personal (with password or authentication)
Group (with authentication)
Secure print, encrypted PDF, fax receipt, fax polling, annotation
Reprint, combination, download, sending (Email/FTP/SMB and fax),
copy box-to-box

Security	ISO 15408 EAL
	IEEE 2600.1
	IP filtering and port blocking
	SSL2, SSL3 and TSL1.0 network communication
	IPsec support
	IEEE 802.1x support
	User authentication
	Authentication log
	Secure print
	Hard disk overwrite (8 standard types)
	Hard disk data encryption (AES 128)
	Memory data auto deletion
	Confidential fax reception
	Print user data encryption
	Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts
	Active Directory support
	(user name + password + Email + SMB folder)
	User function access definition
	Optional Biometric authentication (finger vein scanner)
	Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager
	PageScope Data Administrator
	PageScope Box Operator
	Print Status Notifier
	Driver Packaging Utility
	Log Management Utility
	* * *

<sup>Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis.
This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs 2 Warm-up time may vary depending on the operating environment and usage
3 Supports x64 only</sup> 

Components and Options	S
AU-102 Biometric	Finger vein scanner
authentication	
AU-205H Universal	Various ID card technologies
ID card reader	HODI. I
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection, Bluetooth
DF-628	Reversing automatic document feeder, capacity 100 originals
Document feeder	
DK-514 Copier desk	Provides storage space for print media and other materials
FK-513 Fax board	Super G3 fax, digital fax functionality
FS-533 Staple finisher	50-sheet stapling, 500 sheets max. output (requires MK-602+ MK-603)
FS-534 Staple finisher	50-sheet stapling, 3,300 sheets max. output (requires RU-514+ MK-603)
FS-534 + SD-511	50-sheet staple finisher, 20-sheet booklet finisher,
Booklet finisher	3,300 sheets max. output (requires RU-514)
JS-506 Job separator	Separation for fax output, etc.
KH-102	To place USB keyboard
Keyboard holder	
KP-101 10-Key pad	For use instead of touchscreen
LK-102 v3	PDF/A, PDF encryption, digital signature
PDF enhancements	
LK-104 v3	Provides voice guidance functions
Voice guidance	
LK-105 v4	Searchable PDF
OCR text recognition	O controlled to the controlled
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110 v2 Enhanced	Generates various file formats incl. DOCX, XLSX and combines
image support	LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
LK-111	Print data compression for reduced network impact
ThinPrint® Client	
MK-602 Mount kit	Installation kit required for FS-533
MK-603 Mount kit	Installation kit required for FS-533, FS-534, FS-534+SD-511 and JS-506
MK-735 Mount kit	Installation kit for ID card reader
OC-514 Original cover	Cover instead of auto document feeder
PC-114	5.5" x 8.5" to 11" x 17", 500 sheets, 60-220 gsm
Universal tray (x1)	
PC-214	5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 60-220 gsm
Universal tray (x2)	
PC-414	8.5" x 11", 2,500 sheets, 60-220 gsm
Large capacity tray	0/01-1
PK-519 Punch kit for FS-533	2/3-hole punching, autoswitching
PK-520 Punch kit for FS-534	2/3-hole punching, autoswitching
RU-514 Relay unit	Required for installation of FS-534
UK-211	2 GB memory expansion, required for most i-Options, registered
	overlay, and concurrent use of web browser and certain other functions, including stamp print, watermark, date/time print, header/footer, image overlay, and management number
UK-212 Wireless LAN	Wireless LAN to network connector
WT-506 Working table	Authentication device placement
	and the state of t







#### bizhub C368

Ideal for growing businesses, the bizhub C368 is a powerful, affordable color MFP with superior Simitri HD image quality and fast 36 ppm print/copy output. Optional dual scanning at up to 160 opm brings information into your workflow faster— and enhanced touch-screen simplicity never slows you down.

#### System Overview

System Overview	
System memory	4 GB
System hard disk	250 GB Standard
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Document feeder	Up to 100 originals / 5.5" x 8.5" to 11" x 17" / 35-163 gsm
(optional)	Reversing automatic document feeder or dual scan document
	feeder available
Printable paper size	Scanning/Copying: up to 11" x 17"  Printing: up to 11" x 17" full bleed on 12" x 18" paper
	Custom paper sizes
	Banner paper max.: 11.75" x 47.25"
Printable paper weight	52-300 gsm
Paper input capacity	Standard: 1,150 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 3 (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 4 (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 52-256 gsm
Large capacity tray	3,000 sheets / 8.5" x 11" / 52-256 gsm
LU-302 (optional)	·
Large capacity tray	2,500 sheets / 8.5" x 11" / 52-256 gsm
PC-410 (optional)	
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, sort, punch, half-fold, tri-fold, booklet
Output capacity	Max. with finisher: 3,300 sheets
Charling (autional)	Max. without finisher: 250 sheets
Stapling (optional) Stapling output	Max.: 50 sheets or 48 sheets + 2 cover sheet (up to 209 gsm)
capacity	Max.: 1,000 sheets
Tri-fold (optional)	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output	Max.: 100 sheets (tray)
capacity	man 100 chocc (act)
Copy/print volume	Max.: 125,000 pages/month <sup>1</sup>
Toner lifetime	Black: 28,000 pages / CMY: 26,000 pages
Imaging unit lifetime	Black: 120,000 pages / 600,000 pages (Drum / Developer) CMY: 90,000 pages / 600,000 pages (Drum / Developer)
Power consumption	120 V / 60 Hz, less than 1.5 kW (system)
System dimensions	24.2" x 27" x 31" (W x D x H)
System weight	Approx. 187.39 lb

Caniar	Cnor	aifina	tiono
Copier	อมชเ	JIIIGa	นบทร

Copying process	Electrostatic laser copy, tandem, indirect		
ioner system Simitri® HD Polymerized Toner			
Print speed (8.5" x 11")	B&W / Color: up to 36 ppm (Portrait)		
Print speed (11" x 17")	B&W / Color: up to 18 ppm (Portrait)		
Autoduplex speed (8.5" x 11")	B&W / Color: up to 36 ppm (Portrait)		
1st copy out time	<b>B&amp;W:</b> 5.3 sec. / <b>Color:</b> 6.9 sec.		
Warm-up time	Approx. 20 sec. <sup>2</sup>		
Copy resolution	600 x 600 dpi		
Gradations	256 gradations		
Multi-copy	1-9,999		
Original format	Up to 11" x 17"		
Magnification	25-400% in 0.1% steps, auto zooming		
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1		

#### **Printer Specifications**

i illitoi opcomoations	
Print resolution	1,800 x 600 dpi, 1,200 x 1,200 dpi
PDL	PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 <sup>3</sup> / 2012 <sup>3</sup> Macintosh OS X 10.6 or later Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

#### **Printer Specifications (Optional)**

Print controller	Embedded Fiery IC-416	
Memory/HDD	2 GB / 160 GB	
PDL	PostScript 3 (ver. 3019) PCL 6/5c	
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 <sup>3</sup> / 2012 <sup>3</sup> Macintosh OS X 10.8 or later	

#### **Scanner Specifications**

Scan speed	B&W / Color: up to 160 ipm with optional DF-704
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview

#### **Fax Specifications**

Fax	Super G3 (optional)	
Transmission	Analog, Internet fax, Color i-Fax, IP-Fax	
Resolution	Max.: 600 x 600 dpi (ultra-fine)	
Compression	MH, MR, MMR, JBIG	
Modem	Up to 33.6 Kbps	
Destinations	2,100 (single + group)	
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to	
	Email/ETP/SMB, up to 400 job programs	

#### **User Box Specifications**

Storable documents	Max.: 3,000 documents or 10,000 pages	
Type of user boxes	Public	
	Personal (with password or authentication) Group (with authentication)	
	droup (with authentication)	
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation	
User box functionality	Reprint, combination, download, sending (Email/FTP/SMB and fax), copy box-to-box	

Security	ISO 15408 EAL	Π
	IEEE 2600.1	
	IP filtering and port blocking	
	SSL2, SSL3 and TSL1.0 network communication	
	IPsec support	
	IEEE 802.1x support	
	FIPS 140-2	
	User authentication	
	Authentication log	
	Secure print	
	Hard disk overwrite (8 standard types)	
	Hard disk data encryption (AES 128)	
	Memory data auto deletion	
	Confidential fax receipt,	
	Print user data encryption	
	Copy protection (Copy Guard, Password Copy) optional	
Accounting	Up to 1,000 user accounts	
	Active Directory support	
	(user name + password + Email + SMB folder)	
	User function access definition	
	Optional Biometric authentication (finger vein scanner)	
	Optional ID card authentication (ID card reader)	
Software	PageScope Net Care Device Manager	
	PageScope Data Administrator	
	PageScope Box Operator	
	PageScope Direct Print	
	Print Status Notifier	
	Driver Packaging Utility	
	Log Management Utility	

<sup>1</sup> Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis.

This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs

2 Warm-up time may vary depending on the operating environment and usage

3 Supports x64 only

Cam	non	onte	and	Ontions	s

Components and Option	8
AU-102 Biometric authentication	Finger vein scanner
AU-204H Magnetic stripe card reader	Requires WT-506 Working Table
AU-205H Universal	Various ID card technologies
ID card reader	Danisha WT FOO Washing Table
AU-211 CA/PIV solution	Requires WT-506 Working Table
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit DF-629	USB keyboard connection, Bluetooth  Reversing automatic document feeder, capacity 100 originals
Document feeder	neversing automatic document reeder, capacity 100 originals
DF-704	Dual scan automatic document feeder, capacity 100 originals
Document feeder DK-510 Copier desk	Provides storage space for print media and other materials
FK-514 Fax board	Super G3 fax, digital fax functionality
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support
FS-533 Staple finisher	(requires MK-742) 50-sheet stapling, 500 sheets max. output
FS-534 Staple finisher	50-sheet stapling, 3,300 sheets max. output (requires RU-513)
FS-534 + SD-511 Booklet finisher	50-sheet staple finisher, 20-sheet booklet finisher, 3,300 sheets max. output (requires RU-513)
HD-524 Hard disk	Hard disk mirroring, 250 GB
IC-416 Fiery image	Embedded image controller for graphics-intensive applications
JS-506 Job separator	Separation for fax output, etc.
KH-102	To place USB keyboard
Keyboard holder	For the desired of the observer
KP-101 10-Key pad LK-102 v3	For use instead of touchscreen PDF/A, PDF encryption, digital signature
PDF enhancements	
LK-104 v3 Voice guidance	Provides voice guidance functions
LK-105 v4	Searchable PDF
OCR text recognition LK-106	Supports native barcode printing
Barcode fonts	Supports frative barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108	Supports native OCR A and B font printing
OCR A and B fonts LK-110 v2 Enhanced	Generates various file formats incl. DOCX, XLSX and combines
image support	LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
LK-111 ThinPrint® Client	Print data compression for reduced network impact
LU-302	8.5" x 11", 3,000 sheets / 52-256 gsm
Large capacity unit	
MK-730 Mount kit MK-735 Mount kit	Banner paper guide Installation kit for ID card reader
MK-742 Mount kit	Installation kit for FK-515 fax board
OC-511 Original cover	Cover instead of auto document feeder
PC-110 Universal tray (x1)	5.5" x 8.5" to 11" x 17", 500 sheets, 52-256 gsm
PC-210	5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52-256 gsm
Universal tray (x2) PC-410	8.5" x 11", 2,500 sheets, 52-256 gsm
Large capacity tray	
PK-519 Punch kit for FS-533	2/3-hole punching, autoswitching
PK-520 Punch kit for FS-534	2/3-hole punching, autoswitching
RU-513 Relay unit	Required for the FS-534
SC-508 Security kit	Copy Guard function (2x required when DF-701 is installed)
SK-602 Staple kit SP-501 Stamp unit	Added stapling functionality kit  Added fax stamp capability kit
UK-212 Wireless LAN	Wireless LAN to network connector
VI-508 Interface kit for IC-416	Fiery controller interface card
WT-506 Working table	Authentication device placement
	·





Up to 45 ppm print/copy output to keep pace with rising demands Standard dual scanning handles up to 240 originals per minute High capacity 300-sheet document feeder Large 10.1" color display with quick tablet-like touchscreen interface Scan-to-email and FTP, scan-to-me, scan-to-home convenience Built-in Emperon® print system, universal printer drivers Simitri® HD polymerized toner for high-resolution imaging Standard 250 GB HDD for on-board document storage Web browser with 4 GB of memory ISO 15408 and IEEE 2600.1 Security standards Power-saving design with quick recovery from sleep mode 6,650-Sheet maximum capacity, tab printing support, carbon-copy printing Advanced authentication, secure print release, remote firmware updates Multiple bypass tray and detachable paper feed trays improve paper handling Finishing options for 80-page booklet-making, up to 100-sheet stapling Option for 2/3-hole punch, tri-fold, z-fold, post-insertion and more Downloadable apps to help you work faster and smarter Multiple i-Options to suit the needs of your workflow EPEAT Gold-certified, low power consumption to cut costs

### bizhub C458

COLOR MID-VOLUME MULTIFUNCTION PRINTER

Mobile printing support (AirPrint, Google Cloud Print, NFC)

mfp





#### bizhub C458

If your workload is growing, the bizhub C458 is the MFP solution you've been searching for – with 45 ppm print/copy output in superior Simitri HD color or cost-effective B&W. The C458 also offers standard dual scanning at up to 240 opm, 6,650-sheet maximum paper capacity, enhanced touch-and-swipe operation on the large 10.1 inch control panel and full solution integration.

System Overview	
System memory	4 GB
System hard disk	250 GB Standard
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Dual scan	Up to 300 originals / 5.5" x 8.5" to 11" x 17" / 35-210 gsm
document feeder	
Printable paper size	Scanning/Copying: up to 11" x 17"
	Printing: up to 11" x 17" full bleed on 12" x 18" paper Custom paper sizes
	Banner paper max.: 11.75" x 47.25"
Printable paper weight	52-300 gsm
Paper input capacity	Standard: 1,150 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 3 (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 4 (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 52-256 gsm
Large capacity tray LU-207 (optional)	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm
Large capacity tray LU-302 (optional)	3,000 sheets / 8.5" x 11" / 52-256 gsm
Large capacity tray PC-415 (optional)	2,500 sheets / 8.5" x 11" / 52-256 gsm
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, sort, staple, punch, half-fold, z-fold, tri-fold, post-insertion, booklet
Output capacity	Max. with finisher: 3,300 sheets Max. without finisher: 250 sheets
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheet (up to 209 gsm)
Stapling output capacity	Max.: 1,000 sheets
Tri-fold (optional)	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray)
Copy/print volume	Max.: 150,000 pages/month <sup>1</sup>
Toner lifetime	<b>Black:</b> 28,000 pages / <b>CMY:</b> 26,000 pages
Imaging unit lifetime	Black: 145,000 pages / 600,000 pages (Drum / Developer) CMY: 125,000 pages / 600,000 pages (Drum / Developer)
Power consumption	120 V / 60 Hz, less than 0.5 kW (system)
System dimensions	24.2" x 27" x 38" (W x D x H)
System weight	Approx. 242.5 lb

Copier S	pecifications
----------	---------------

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD Polymerized Toner
Print speed (8.5" x 11")	B&W / Color: up to 45 ppm (Portrait)
Print speed (11" x 17")	B&W / Color: up to 22 ppm (Portrait)
Autoduplex speed (8.5" x 11")	B&W / Color: up to 45 ppm (Portrait)
1st copy out time	<b>B&amp;W:</b> 4.0 sec. / <b>Color:</b> 5.1 sec.
Warm-up time	Approx. 25 sec. <sup>2</sup>
Copy resolution	600 x 600 dpi
Gradations	256 gradations
Multi-copy	1-9,999
Original format	Up to 11" x 17"
Magnification	25-400% in 0.1% steps, auto zooming
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1

#### **Printer Specifications**

Print resolution	1,800 x 600 dpi, 1,200 x 1,200 dpi
PDL	PCL6 (XL 3.0), PCL5e/c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 <sup>3</sup> / 2012 <sup>3</sup> Macintosh OS X 10.6 or later Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

#### **Printer Specifications (Optional)**

Print controller	Embedded Fiery IC-416 (VI-510 required)	
Memory/HDD	2 GB / 160 GB	
PDL	PostScript 3 (ver. 3019) PCL 6/5c	
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 <sup>3</sup> / 2012 <sup>3</sup> Macintosh OS X 10.8 or later	

#### Scanner Specifications

Scan speed	B&W / Color: up to 240 ipm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs,

#### **Fax Specifications**

Fax	Super G3 (optional)
Transmission	Analog, Internet fax, Color i-Fax, IP-Fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to Fmail/FTP/SMB, up to 400 job programs

### User Box Specifications

Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public Personal (with password or authentication)

	Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation
User box functionality	Reprint, combination, download, sending (Email/FTP/SMB and fax) copy box-to-box

System	Features
Jocenn	reaction

-,	
Security	ISO 15408 EAL <sup>4</sup> IEEE 2600.1 <sup>4</sup> IP filtering and port blocking SSL2, SSL3 and TSL1.0 network communication IPsec support IEEE 802.1x support FIPS 140-2 User authentication Authentication log Secure print Hard disk overwrite (8 standard types) Hard disk data encryption (AES 128) Memory data auto deletion Confidential fax receipt, Print user data encryption Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts Active Directory support (user name + password + Email + SMB folder) User function access definition Optional Biometric authentication (finger vein scanner) Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager PageScope Data Administrator PageScope Box Operator PageScope Direct Print Print Status Notifier Driver Packaging Utility Log Management Utility
144 1	

Log Management Utility

1 Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs

2 Warm-up time may vary depending on the operating environment and usage

3 Supports x64 only

4 Certification pending

**Components and Options** 

Components and Option	ons
AU-102 Biometric authentication	Finger vein scanner
AU-204H Universal ID card reader*	Magnetic stripe card reader: requires WT-506 Working table
AU-205H Universal ID card reader	Various ID card technologies
AU-211 CAC/PIV solution	Requires WT-506 Working Table
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection, Bluetooth
DK-510 Copier desk	Provides storage space for print media and other materials
FK-514 Fax board	Super G3 fax, digital fax functionality
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support (requires MK-742)
FS-533 Staple finisher	50-sheet stapling, 500 sheets max. output
FS-536 Staple finisher	50-sheet stapling, 3,200 sheets max. output
FS-536SD Booklet finisher	50-sheet staple finisher, 20-sheet booklet finisher, 2,500 sheets max. output
FS-537 Staple finisher	100-sheet stapling, 3,200 sheets max. output
FS-537SD Booklet finisher	100-sheet stapling, 20-sheet booklet finisher, 2,500 sheets max. output
HD-524 Hard disk	Backup HDD
IC-416 Fiery image controller	Embedded image controller for graphics-intensive applications
S-506 Job separator	Separation for fax output, etc.
S-602 Job separator for FS-537	Separation for fax output, etc.
Keyboard	External keyboard (requires KH-102)
KH-102 Keyboard holder	To place USB keyboard
KP-101 10-Key pad	For use instead of touchscreen
LK-102 v3 PDF enhancements	PDF/A, PDF encryption, digital signature
LK-104 v3 Voice guidance	Provides voice guidance functions
LK-105 v4	Searchable PDF
OCR text recognition	Searchable i Di

#### **Components and Options (Continued)**

Components and Option	ons (continueu)
LK-107 Unicode fonts	Supports native Unicode printing
LK-108	Supports native OCR A and B font printing
OCR A and B fonts	
LK-110 v2 Enhanced	Generates various file formats incl. DOCX, XLSX and combines
image support	LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality
LK-111	Print data compression for reduced network impact
ThinPrint® Client	
LU-207	8.5" x 11" to 12" x 18", 2,500 sheets / 52-256 gsm
Large capacity unit	
LU-302	8.5" x 11", 3,000 sheets / 52-256 gsm
Large capacity unit	
MK-730 Mount kit	Banner paper guide
MK-735 Mount kit	Installation kit for ID card reader
MK-742 Mount kit	Installation kit for FK-515 fax board
OT-506 Output tray	Output tray used instead of finisher
PC-115	5.5" x 8.5" to 11" x 17", 500 sheets, 52-256 gsm
Universal tray (x1)	
PC-215	5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52-256 gsm
Universal tray (x2)	
PC-415	8.5" x 11", 2,500 sheets, 52-256 gsm
Large capacity tray	
PI-507 Post inserter	Cover insertion, post finishing
for FS-537	
PK-519 Punch kit	2/3-hole punching, autoswitching
for FS-533	
PK-520 Punch kit	2/3-hole punching, autoswitching
for FS-536	2/21 1 1: 1: 1:
PK-523 Punch kit for FS-537	2/3-hole punching, autoswitching
RU-513 Relay unit	D
	Required for FS-537/FS-537SD and FS-536/FS-536SD
SC-508 Security kit	Copy Guard function (2x required)
SK-602 Staple kit	Added stapling functionality kit
SP-501 Stamp unit	Added fax stamp capability kit
UK-212 Wireless LAN	Wireless LAN to network connector
UK-501 Multi-feed	Detects multi-feeding in the document feeder
detection kit	
VI-510 Interface kit	Fiery controller interface card
for IC-416	
WT-506 Working table	Authentication device placement
ZU-609 Z-fold unit	Z-fold for 11" x 17" prints, 2/3-hole punching
for FS-537	

<sup>\*</sup> May not be available at time of launch.







#### bizhub C558

If your workload is growing, the bizhub C558 is the MFP solution you've been searching for – with 55 ppm print/copy output in superior Simitri HD color or cost-effective B&W. The C558 also offers standard dual scanning at up to 240 opm, 6,650-sheet maximum paper capacity, enhanced touch-and-swipe operation on the large 10.1 inch control panel and full solution integration.

System Overview	
System memory	4 GB
System hard disk	250 GB Standard
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
<b>Dual scan</b>	Up to 300 originals / 5.5" x 8.5" to 11" x 17" / 35-210 gsm
document feeder	
Printable paper size	Scanning/Copying: up to 11" x 17"
	Printing: up to 11" x 17" full bleed on 12" x 18" paper Custom paper sizes
	Banner paper max.: 11.75" x 47.25"
Printable paper weight	52-300 asm
Paper input capacity	Standard: 1,150 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 3 (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 4 (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 52-256 gsm
Large capacity tray LU-207 (optional)	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm
Large capacity tray LU-302 (optional)	3,000 sheets / 8.5" x 11" / 52-256 gsm
Large capacity tray PC-415 (optional)	2,500 sheets / 8.5" x 11" / 52-256 gsm
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, sort, staple, punch, half-fold, z-fold, tri-fold, post-insertion, booklet
Output capacity	Max. with finisher: 3,300 sheets Max. without finisher: 250 sheets
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheet (up to 209 gsm)
Stapling output capacity	Max.: 1,000 sheets
Tri-fold (optional)	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray)
Copy/print volume	<b>Max.:</b> 200,000 pages/month <sup>1</sup>
Toner lifetime	<b>Black:</b> 28,000 pages / <b>CMY:</b> 26,000 pages
Imaging unit lifetime	Black: 145,000 pages / 600,000 pages (Drum / Developer) CMY: 130,000 pages / 600,000 pages (Drum / Developer)
Power consumption	120 V / 60 Hz, less than 0.5 kW (system)
System dimensions	24.2" x 27" x 38" (W x D x H)
System weight	Approx. 242.5 lb

Copier Specifications
-----------------------

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD Polymerized Toner
Print speed (8.5" x 11")	B&W / Color: up to 55 ppm (Portrait)
Print speed (11" x 17")	B&W / Color: up to 27 ppm (Portrait)
Autoduplex speed (8.5" x 11")	B&W / Color: up to 55 ppm (Portrait)
1st copy out time	<b>B&amp;W:</b> 4.4 sec. / <b>Color:</b> 3.5 sec.
Warm-up time	Approx. 22 sec. <sup>2</sup>
Copy resolution	600 x 600 dpi
Gradations	256 gradations
Multi-copy	1-9,999
Original format	Up to 11" x 17"
Magnification	25-400% in 0.1% steps, auto zooming
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1

#### **Printer Specifications**

Print resolution	1,800 x 600 dpi, 1,200 x 1,200 dpi
PDL	PCL6 (XL 3.0), PCL5e/c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 <sup>3</sup> / 2012 <sup>3</sup> Macintosh OS X 10.6 or later Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Printfunctions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

#### **Printer Specifications (Optional)**

Print controller	Embedded Fiery IC-416 (VI-510 required)
Memory/HDD	2 GB / 160 GB
PDL	PostScript 3 (ver. 3019) PCL 6/5c
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 <sup>3</sup> / 2012 <sup>3</sup> Macintosh OS X 10.8 or later

#### Scanner Specifications

Scan speed	B&W / Color: up to 240 ipm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs,

### **Fax Specifications**

Fax	Super G3 (optional)
Transmission	Analog, Internet fax, Color i-Fax, IP-Fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to Email/FTP/SMB. up to 400 job programs

## User Box Specifications

Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public Personal (with password or authentication)

	Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation
User box functionality	Reprint, combination, download, sending (Email/FTP/SMB and fax) copy box-to-box

System reacures	
Security	ISO 15408 EAL <sup>4</sup> IEEE 2600.1 <sup>4</sup> IP filtering and port blocking SSL2, SSL3 and TSL1.0 network communication IPsec support IEEE 802.1x support FIPS 140-2 User authentication Authentication log Secure print Hard disk overwrite (8 standard types) Hard disk data encryption (AES 128) Memory data auto deletion Confidential fax receipt, Print user data encryption Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts Active Directory support (user name + password + Email + SMB folder) User function access definition Optional Biometric authentication (finger vein scanner) Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager PageScope Data Administrator PageScope Box Operator PageScope Direct Print Print Status Notifier Driver Packaging Utility Log Management Utility

<sup>1</sup> Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs

2 Warm-up time may vary depending on the operating environment and usage

3 Supports x64 only

4 Certification pending

Components and Options

Components and Opti	ons
AU-102 Biometric	Finger vein scanner
authentication	
AU-204H Universal ID card reader	Magnetic stripe card reader: requires WT-506 Working table
AU-205H Universal	Various ID card technologies
ID card reader*	various io card tecrinologies
AU-211	Requires WT-506 Working Table
CAC/PIV solution	
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection, Bluetooth
DK-510	Provides storage space for print media and other materials
Copier desk	
FK-514 Fax board	Super G3 fax, digital fax functionality
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support (requires MK-742)
FS-533 Staple finisher	50-sheet stapling, 500 sheets max. output
FS-536 Staple finisher	50-sheet stapling, 3,200 sheets max. output
FS-536SD	50-sheet staple finisher, 20-sheet booklet finisher,
Booklet finisher	2,500 sheets max. output
FS-537 Staple finisher	100-sheet stapling, 3,200 sheets max. output
FS-537SD	100-sheet stapling, 20-sheet booklet finisher,
Booklet finisher	2,500 sheets max. output
HD-524 Hard disk	Backup HDD
IC-416 Fiery image controller	Embedded image controller for graphics-intensive applications
JS-506 Job separator	Separation for fax output, etc.
JS-602 Job separator for FS-537	Separation for fax output, etc.
Keyboard	External keyboard (requires KH-102)
KH-102	To place USB keyboard
Keyboard holder	
KP-101 10-Key pad	For use instead of touchscreen
LK-102 v3	PDF/A, PDF encryption, digital signature
PDF enhancements	
LK-104 v3	Provides voice guidance functions
Voice guidance	
LK-105 v4	Searchable PDF
OCR text recognition	
LK-106 Barcode fonts	Supports native barcode printing

#### **Components and Options (Continued)**

Components and Option	ons (Continued)
LK-107 Unicode fonts	Supports native Unicode printing
LK-108	Supports native OCR A and B font printing
OCR A and B fonts	1 3
LK-110 v2 Enhanced	Generates various file formats incl. DOCX, XLSX and combines
image support	LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
LK-111	Print data compression for reduced network impact
ThinPrint® Client	
LU-207	8.5" x 11" to 12" x 18", 2,500 sheets / 52-256 gsm
Large capacity unit	
LU-302	8.5" x 11", 3,000 sheets / 52-256 gsm
Large capacity unit	
MK-730 Mount kit	Banner paper guide
MK-735 Mount kit	Installation kit for ID card reader
MK-742 Mount kit	Installation kit for FK-515 fax board
OT-506 Output tray	Output tray used instead of finisher
PC-115	5.5" x 8.5" to 11" x 17", 500 sheets, 52-256 gsm
Universal tray (x1)	
PC-215	5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52-256 gsm
Universal tray (x2)	
PC-415	8.5" x 11", 2,500 sheets, 52-256 gsm
Large capacity tray	
PI-507 Post inserter	Cover insertion, post finishing
for FS-537	
PK-519 Punch kit	2/3-hole punching, autoswitching
for FS-533	0/01
PK-520 Punch kit for FS-536	2/3-hole punching, autoswitching
	2/2 hala nunahing autoquitahing
PK-523 Punch kit for FS-537	2/3-hole punching, autoswitching
RU-513 Relay unit	Required for FS-537/FS-537SD and FS-536/FS-536SD
SC-508 Security kit	Copy Guard function (2x required)
SK-602 Staple kit	Added stapling functionality kit
SP-501 Stamp unit	Added fax stamp capability kit
UK-212 Wireless LAN	Wireless LAN to network connector
UK-501 Multi-feed	Detects multi-feeding in the document feeder
detection kit	
VI-510 Interface kit	Fiery controller interface card
for IC-416	A. Alexandra de
WT-506 Working table	Authentication device placement
ZU-609 Z-fold unit for FS-537	Z-fold for 11" x 17" prints, 2/3-hole punching
* May not be available at ti	

<sup>\*</sup> May not be available at time of launch.





#### bizhub C658

If your workload is growing, the bizhub C658 is the MFP solution you've been searching for – with 65 ppm print/copy output in superior Simitri HD color or cost-effective B&W. The C658 also offers standard dual scanning at up to 240 opm, 6,650-sheet maximum paper capacity, enhanced touch-and-swipe operation on the large 10.1 inch control panel and full solution integration.

System Overview	
System memory	4 GB
System hard disk	250 GB Standard
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
<b>Dual scan</b>	Up to 300 originals / 5.5" x 8.5" to 11" x 17" / 35-210 gsm
document feeder	
Printable paper size	Scanning/Copying: up to 11" x 17"
	<b>Printing:</b> up to 11" x 17" full bleed on 12" x 18" paper Custom paper sizes
	Banner paper max.: 11.75" x 47.25"
Printable paper weight	52-300 gsm
Paper input capacity	Standard: 1,150 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 3 (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 4 (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 52-256 gsm
Large capacity tray LU-207 (optional)	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm
Large capacity tray LU-302 (optional)	3,000 sheets / 8.5" x 11" / 52-256 gsm
Large capacity tray PC-415 (optional)	2,500 sheets / 8.5" x 11" / 52-256 gsm
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, sort, staple, punch, half-fold, z-fold, tri-fold, post-insertion, booklet
Output capacity	Max. with finisher: 3,300 sheets
- " ' "	Max. without finisher: 250 sheets
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheet (up to 209 gsm)
Stapling output capacity	Max.: 1,000 sheets
Tri-fold (optional)	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray)
Copy/print volume	Max.: 220,000 pages/month <sup>1</sup>
Toner lifetime	<b>Black:</b> 28,000 pages / <b>CMY:</b> 26,000 pages
Imaging unit lifetime	<b>Black:</b> 155,000 pages / 600,000 pages (Drum / Developer) <b>CMY:</b> 135,000 pages / 600,000 pages (Drum / Developer)
Power consumption	120 V / 60 Hz, less than 0.5 kW (system)
System dimensions	24.2" x 27" x 38" (W x D x H)
System weight	Approx. 242.5 lb

Copier S	pecifications
----------	---------------

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD Polymerized Toner
Print speed (8.5" x 11")	B&W / Color: up to 65 ppm (Portrait)
Print speed (11" x 17")	B&W / Color: up to 33 ppm (Portrait)
Autoduplex speed (8.5" x 11")	B&W / Color: up to 65 ppm (Portrait)
1st copy out time	<b>B&amp;W:</b> 3 sec. / <b>Color:</b> 4 sec.
Warm-up time	Approx. 22 sec. <sup>2</sup>
Copy resolution	600 x 600 dpi
Gradations	256 gradations
Multi-copy	1-9,999
Original format	Up to 11" x 17"
Magnification	25-400% in 0.1% steps, auto zooming
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1

#### **Printer Specifications**

Print resolution	1,800 x 600 dpi, 1,200 x 1,200 dpi
PDL	PCL6 (XL 3.0), PCL5e/c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 <sup>3</sup> / 2012 <sup>3</sup> Macintosh OS X 10.7 or later Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Printfunctions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

#### **Printer Specifications (Optional)**

	( -
Print controller	Embedded Fiery IC-416 (VI-510 required)
Memory/HDD	2 GB / 160 GB
PDL	PostScript 3 (ver. 3019) PCL 6/5c
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 <sup>3</sup> / 2012 <sup>3</sup> Macintosh OS X 10.8 or later

### Specifications

Specifications	
Scan speed	B&W / Color: up to 240 ipm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs,

realtime scan preview

#### **Fax Specifications**

Fax	Super G3 (optional)
Transmission	Analog, Internet fax, Color i-Fax, IP-Fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to Email/FTP/SMB. up to 400 job programs

### **User Box**

Specifications	
Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public Personal (with password or authentication) Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation
User box functionality	Reprint, combination, download, sending (Email/FTP/SMB and fax), copy box-to-box

system reatures	100 15400 5414
Security	ISO 15408 EAL <sup>4</sup> IFFF 2600.1 <sup>4</sup>
	IP filtering and port blocking
	SSL2, SSL3 and TSL1.0 network communication
	IPsec support
	IEEE 802.1x support FIPS 140-2
	User authentication
	Authentication log
	Secure print
	Hard disk overwrite (8 standard types)
	Hard disk data encryption (AES 128)
	Memory data auto deletion
	Confidential fax receipt,
	Print user data encryption
	Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts
	Active Directory support
	(user name + password + Email + SMB folder)
	User function access definition
	Optional Biometric authentication (finger vein scanner)
	Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager
	PageScope Data Administrator
	PageScope Box Operator
	PageScope Direct Print
	Print Status Notifier
	Driver Packaging Utility
	Log Management Utility
1 Mar day on a seathful	distribution of the state of th

<sup>1</sup> Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs

2 Warm-up time may vary depending on the operating environment and usage

3 Supports x64 only

4 Certification pending

**Components and Options** 

Components and Opti	Ulis
AU-102 Biometric authentication	Finger vein scanner
AU-204H Universal ID card reader	Magnetic stripe card reader: requires WT-506 Working table
AU-205H Universal ID card reader*	Various ID card technologies
AU-211 CAC/PIV solution	Requires WT-506 Working Table
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection, Bluetooth
DK-510 Copier desk	Provides storage space for print media and other materials
FK-514 Fax board	Super G3 fax, digital fax functionality
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support (requires MK-742)
FS-536 Staple finisher	50-sheet stapling, 3,200 sheets max. output
FS-536SD Booklet finisher	50-sheet staple finisher, 20-sheet booklet finisher, 2,500 sheets max. output
FS-537 Staple finisher	100-sheet stapling, 3,200 sheets max. output
FS-537SD Booklet finisher	100-sheet stapling, 20-sheet booklet finisher, 2,500 sheets max. output
HD-524 Hard disk	Backup HDD
IC-416 Fiery image controller	Embedded image controller for graphics-intensive applications
JS-602 Job separator for FS-537	Separation for fax output, etc.
Keyboard	External keyboard (requires KH-102)
KH-102 Keyboard holder	To place USB keyboard
KP-101 10-Key pad	For use instead of touchscreen
LK-102 v3 PDF enhancements	PDF/A, PDF encryption, digital signature
LK-104 v3 Voice guidance	Provides voice guidance functions
LK-105 v4 OCR text recognition	Searchable PDF
LK-106 Barcode fonts	Supports native barcode printing

#### **Components and Options (Continued)**

Components and Option	ons (Continued)
LK-107 Unicode fonts	Supports native Unicode printing
LK-108	Supports native OCR A and B font printing
OCR A and B fonts	
LK-110 v2 Enhanced	Generates various file formats incl. DOCX, XLSX and combines
image support	LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
LK-111	Print data compression for reduced network impact
ThinPrint® Client	
LU-207	8.5" x 11" to 12" x 18", 2,500 sheets / 52-256 gsm
Large capacity unit	
LU-302	8.5" x 11", 3,000 sheets / 52-256 gsm
Large capacity unit	D '1
MK-730 Mount kit	Banner paper guide
MK-735 Mount kit	Installation kit for ID card reader
MK-742 Mount kit	Installation kit for FK-515 fax board
OT-506 Output tray	Output tray used instead of finisher
PC-115	5.5" x 8.5" to 11" x 17", 500 sheets, 52-256 gsm
Universal tray (x1)	
PC-215	5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52-256 gsm
Universal tray (x2)	0.511 4411 2.500 1 1 52.250
PC-415 Large capacity tray	8.5" x 11", 2,500 sheets, 52-256 gsm
PI-507 Post inserter	Cover insertion, post finishing
for FS-537	Cover insertion, post imisming
PK-520 Punch kit	2/3-hole punching, autoswitching
for FS-536	2/3 Hole parterning, dateswitching
PK-523 Punch kit	2/3-hole punching, autoswitching
for FS-537	,
RU-513 Relay unit	Required for FS-537/FS-537SD and FS-536/FS-536SD
SC-508 Security kit	Copy Guard function (2x required)
SK-602 Staple kit	Added stapling functionality kit
SP-501 Stamp unit	Added fax stamp capability kit
UK-212 Wireless LAN	Wireless LAN to network connector
UK-501 Multi-feed	Detects multi-feeding in the document feeder
detection kit	
VI-510 Interface kit	Fiery controller interface card
for IC-416	
WT-506 Working table	Authentication device placement
ZU-609 Z-fold unit	Z-fold for 11" x 17" prints, 2/3-hole punching
for FS-537	
* May not be available at t	ma at launah

<sup>\*</sup> May not be available at time of launch.







High-speed print/copy output: 60 ppm color, 75 ppm B&W Standard dual scanning handles up to 180 originals per minute INFO-Palette display for instant access to more information Large 9" color display with quick tablet-like interface Downloadable apps to improve your productivity Built-in Emperon® print system, universal printer drivers Simitri® HD toner guarantees excellent print quality Scan to email and ftp, scan-to-me, scan-to-home convenience 6,650-Sheet capacity, tab printing support, carbon-copy printing Standard 250 GB HDD for on-board document storage Finishing options for 80-page booklet-making, up to 100-sheet stapling Options for 2/3-hole punch, tri-fold, z-fold, post-insertion and more Internal card reader and other advanced security options ISO 15408 and IEEE 2600.1 Security standards PageScope® suite, optional voice guidance, PDF/A formatting Multiple i-Options to suit the needs of your workflow Fiery image control option for graphics-intensive applications Low power consumption, eco-indicator to help cut costs **EPEAT Gold-certified** Mobile printing support (AirPrint, Google Cloud Print, NFC)

## bizhub C754e

COLOR HIGH-VOLUME MULTIFUNCTION PRINTER







### bizhub C754e

Superior color, spectacular speed and simple touch-and-swipe operation make the bizhub C754e an ideal document solution for high-volume applications. Output of 60 ppm in color and 75 ppm in B&W keeps work flowing — and you'll have powerful, scalable options to increase your productivity and help control your costs.

### System Overview

System Overview	
System memory	2,048 MB
System hard disk	250 GB
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Dual scan	Up to 150 originals / 5.5" x 8.5" to 11" x 17" / 35-210 gsm
document feeder	
Printable paper size	Scanning/Copying: up to 11" x 17"
	Printing: up to 11" x 17" full bleed on 12" x 18" paper Custom paper sizes
	Banner paper max: 11.75" x 47.25"
Printable paper weight	52-300 gsm
Paper input capacity	Standard: 3,650 sheets / Max.: 6,650 sheets
Trav 1	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 3	1,500 sheets / 8.5" x 11", 5.5" x 8.5", 4" x 6" / 52-256 gsm
Tray 4	1,000 sheets / 8.5" x 11", 5.5" x 8.5", 4" x 6" / 52-256 gsm
Large capacity tray	3,000 sheets / 8.5" x 11" / 52-256 gsm
LU-301 (optional)	0,000 3110013 / 0.0 X 11 / 02 200 gs111
Large capacity tray	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm
LU-204 (optional)	
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, sort, punch, post insertion, z-fold, half-fold, tri-fold, booklet
Output capacity	Max. with finisher: 3,300 sheets Max. without finisher: 250 sheets
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheets (up to 209 gsm)
Stapling (optional)	Max.: 100 sheets of 94 sheets + 2 cover sheets (up to 209 gsm)
capacity	Widx 1000 Stieets
Tri-fold	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray), unlimited
Booklet	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output	Max.: 100 sheets (tray), unlimited
capacity	man 100 onote (tray); animico
Copy/print volume	Max.: 278,000 pages/month <sup>1</sup>
Toner lifetime	Black: 47,200 pages / CMY: 31,500 pages
Imaging unit lifetime	Black: 300,000 pages / 1,200,000 pages (Drum / Developer)
	CMY: 155,000 pages
Power consumption	120 V / 50/60 Hz, less than 2.1 kW (system)
System dimensions	25.5" x 31.5" x 45.5" (W x D x H)
System weight	Approx. 487.25 lb

		ons

Copying process	Electrostatic laser copy, tandem, indirect	
Toner system	Simitri® HD Polymerized Toner	
Print speed (8.5" x 11")	B&W: Up to 75 ppm (Portrait) / Color: Up to 60 ppm (Portrait)	
Print speed (11" x 17")	B&W: Up to 37 ppm (Portrait) / Color: Up to 30 ppm (Portrait)	
Autoduplex speed	B&W: Up to 75 ppm (Portrait) / Color: Up to 60 ppm (Portrait)	
(8.5" x 11")		
1st copy out time	<b>B&amp;W:</b> 3.6 sec. / <b>Color:</b> 5.3 sec.	
Warm-up time	Approx. 22 sec. <sup>2</sup>	
Copy resolution	600 x 600 dpi	
Gradations	256 gradations	
Multi-copy	1-9,999	
Original format	Up to 11" x 17"	
Magnification	25-400% in 0.1% steps, auto zooming	
Copy functions	Chapter, cover and page insertion, proof copy (print and screen), adjustment test print, digital art functions, job setting memory, poster mode, image repeat, overlay (optional), stamping, copy protection	

### **Printer Specifications**

Print resolution	1,800 x 600 dpi, 1,200 x 1,200 dpi	
PDL	PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS	
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 / 2012 <sup>3</sup> Macintosh OS X 10.2.8 or later UNIX / Linux / Citrix	
Printer fonts	80 PCL Latin, 137 PostScript 3 emulation	
Print functions	ions Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" jol programming, overlay, watermark, copy protection, carbon copy pr	

### **Printer Specifications (Optional)**

Print controller	Embedded Fiery IC-414
Memory / HDD	2 GB / 160 GB
PDL	PostScript 3 (ver. 3019) PCL 6/5c
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 <sup>3</sup> / 2012 <sup>3</sup> Macintosh DS X 10 2 8 or later

### **Scanner Specifications**

Scan speed	B&W / Color: up to 180 ipm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview

### **Fax Specifications**

Fax	Super G3 (optional)
Transmission	Analog, i-Fax, Color i-Fax, IP-fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to

### **User Box Specifications**

Storable documents	Max.: 3,000 documents or 10,000 pages	
Type of user boxes	Public	
	Personal (with password or authentication)	
	Group (with authentication)	
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation	
User box functionality	Reprint, combination, download, sending (Email/FTP/SMB and fax), copy box-to-box	

Features

Security	ISO 15408 EAL3
	IEEE 2600.1
	IP filtering and port blocking
	SSL2, SSL3 and TSL1.0 network communication
	IPsec support
	IEEE 802.1x support
	User authentication
	Authentication log
	Secure print
	Hard disk overwrite (8 standard types)
	Hard disk data encryption (AES 128)
	Memory data auto deletion
	Confidential fax receipt,
	Print user data encryption
	Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts
	Active Directory support
	(user name + password + Email + SMB folder)
	User function access definition
	Optional Biometric authentication (finger vein scanner)
	Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager
	PageScope Data Administrator
	PageScope Box Operator
	PageScope Direct Print
	Print Status Notifier
	Driver Packaging Utility

<sup>1</sup> Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis.
1 This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs
2 Warm-up time may vary depending on the operating environment and usage
3 Supports x64 only

**Components and Options** 

Components and Option	8
AU-102 Biometric	Finger vein scanner
authentication	
EK-604 USB I/F kit	USB keyboard connection
EK-605 USB I/F kit	USB keyboard connection, Bluetooth
FK-508 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support
FK-511 Fax board	Super G3 fax, digital fax functionality
FS-534 Staple finisher	50-sheet stapling, 3,300 sheets max. output
FS-534 + SD-511	50-sheet staple finisher, 20-sheet booklet finisher,
Booklet finisher	3,300 sheets max. output
FS-535 Staple finisher	
<u> </u>	100-sheet stapling, 3,200 sheets max. output
IC-414 Fiery controller	Professional color print controller
ID card reader	Various ID card technologies
JS-602 Job separator	Separation for fax output, etc.
for FS-535	
KH-102	To place USB keyboard
Keyboard holder	
KP-101 10-Key pad	For use instead of touchscreen
LK-101 v3	Web browser
Web browser	
LK-102 v3	PDF/A, PDF encryption, digital signature
PDF enhancements	
LK-104 v3	Provides voice guidance functions
Voice guidance	
LK-105 v3	Searchable PDF
OCR text recognition	
LK-106	Supports native barcode printing
Barcode fonts	
LK-107	Supports native Unicode printing
Unicode fonts	
LK-108	Supports native OCR A and B font printing
OCR A and B fonts	
LK-110 Enhanced	Generates various file formats incl. DOCX, XLSX and combines
image support	LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
LK-111	Print data compression for reduced network impact
ThinPrint® Client	
LU-204	8.5" x 11" to 12" x 18", 2,500 sheets, 52-256 gsm
Large capacity tray	
LU-301	8.5" x 11", 3,000 sheets, 52-256 gsm
Large capacity tray	
MK-728 Mount kit	Installation kit for FK-508 fax board
MK-735 Mount kit	Installation kit for ID card reader
OT-503 Output tray	Output tray used instead of finisher
PI-505 Post inserter	Cover insertion, post finishing
for FS-535	*
PK-520 Punch kit	2/3-hole punching, autoswitching
for FS-534	
PK-521 Punch kit	2/3-hole punching, autoswitching
for FS-535	
SC-508 Security kit	Copy Guard function (2x required)
SD-512 Saddle kit for	Booklet finishing, half-fold, tri-fold
FS-535	
SX-4600WAN	Wireless LAN to network connector
Wireless LAN	
UK-204	Memory extension for i-Options
i-Option memory	mornory extension for a options
VI-506 Interface kit	Fiery controller interface card
for IC-414	rong conductor interface out a
WT-506 Working table	Authentication device placement
ZU-606 Z-fold unit	Z-fold for 11" x 17" prints, 2/3-hole punching
for FS-535	2 1010 101 11 X 17 Printo, 270 note purioning



# **Compact Multifunction Printers**





High-resolution B&W print/copy output at up to 42 ppm

All-in-one functionality, including Super G3 fax 100,000 page monthly volume for large workloads

Standard PCL and Postscript functionality to fit all environments

Scanning in both B&W and color with reversing auto document feeder

2000-sheet maximum paper capacity in small footprint

Mobile printing support (AirPrint, NFC)

MONOCHROME ALL-IN-ONE PRINTER







bizhub 4020	The bizhub 4020 packs high-speed productivity into space-saving
	dimensions, delivering up to 42 ppm high-resolution B&W print/copy
	output with network integration, built-in fax capability and support for
	the convenience coffware and mobile printing functions that help group

vour business.

System Specifications	ıs
-----------------------	----

Oyotom opcomoduono	
System memory	512 MB (standard) / 2.5 GB (maximum)
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4 / IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS, IPX/SPX
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Reversing automatic document feeder	Up to 50 originals, 4" x 6" to 8.5" x 14", 52-120 gsm
Printable paper size	4" x 6" to 8.5" x 14" / custom paper sizes
Printable paper weight	60-163 gsm
Paper input capacity	Standard: 350 sheets / Max.: 2,000 sheets
Tray 1	250 sheets / 4" x 6" to 8.5" x 11" / 60-120 gsm
Trays 2, 3 & 4 (optional)	250 or 550 sheets each / 8.5" x 11" to 8.5" x 14" / 60-120 gsm
Manual bypass	100 sheets / 4" x 6" to 8.5" x 14" / custom paper sizes / 60-163 gsm
Automatic duplexing	8.5" x 11" to 8.5" x 14" / 60-210 gsm
Output capacity	Max.: 150 sheets
Copy/print volume	Max.: 100,000 pages / month <sup>1</sup>
Toner lifetime	20,000 pages
Imaging unit lifetime	60,000 pages
Power consumption	110 V / 60 Hz, Less than 600 W (system)
System dimensions	19.3" x 17.8" x 19.8" (H x W x D)
System weight	Approx. 48 lb

### **Copier Specifications**

Copying process	Electrostatic laser copy, tandem, indirect
Print speed	Up to 42 ppm (Letter)
Autoduplex speed	Up to 19 ppm (Letter)
1st copy out time	6.5 sec.
Warm-up time	Approx. 95 sec. <sup>2</sup>
Copy resolution	600 x 600 dpi
Multi-copy	1-999
Original format	4" x 6" to 8.5" x 14"
Magnification	25-400% in 1% steps; auto zooming
Copy functions	Duplex copy 2-in-1 4-in-1 poster density adjustments

### **Printer Specifications**

Print resolution	1,200 x 1,200 dpi, 600 x 600 dpi
PDL	PCL5e, PostScript
Operating systems	Windows (x32/x64): Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2012 <sup>3</sup> Macintosh OS X 10.x or later Linux
Printer fonts	89 PCL Latin, 91 PostScript
Print functions	Confidential print, combination, n-up, overlay, watermark

### **Scanner Specifications**

Scan speed	Up to 43/20 opm (mono/color)
Scan resolution	600 x 600 dpi
Scan modes	Scan-to-email, Scan-to-SMB, Scan-to-FTP, Scan-to-USB, Network TWAIN
File formats	TIFF, PDF, JPEG, XPS
Scan Destinations	500 (shared with fax), LDAP support

### **Fax Specifications**

Fax	Super G3
Transmission	Analog, PC-fax
Resolution	Max: 600 x 600 dpi
Compression	MH, MR, MMR, JBIG
Modem	up to 33.6 Kbps
Destinations	500 (shared with scan), LDAP support
Functions	Polling, time shift, PC-Fax

Options	
PF-11 Paper tray	8.5" x 11" to 8.5" x 14" / 250 sheets / up to 120 gsm
PF-12 Paper tray	8.5" x 11" to 8.5" x 14" / 550 sheets / up to 120 gsm
DK-P02 Copier desk	Ensures ergonomic height and provides storage space for print media, etc.
EM-P03 Expanded memory	2 GB memory extension for faster processing
NC-P02	Wireless LAN to network connector
UK-P01 Flash memory	256 MB User flash card for font downloading and saving job account log
UK-P10 Barcode card	Provides barcode fonts
UK-P11 IPDS card	Provides compatibility for AFP/IPDS printing
CS-1 Convenience stapler	Convenient stapling of up to 50 prints per set

### **System Features**

Security	IP filtering and port blocking, IPsec support, IEEE 802.1x support, user authentication, secure print
Software	PageScope Net Care Device Manager, PageScope WebConnection, PageScope Data Administrator, PageScope Direct Print, PageScope Mobile

<sup>&</sup>lt;sup>1</sup> Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guidline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs



<sup>&</sup>lt;sup>2</sup> Warm-up time may vary depending on the operating environment and usage

<sup>3</sup> Supports x64 only





bizhub 4050	With 42 ppm print/copy output in high-resolution B&W, the bizhub 4050
	delivers faster, better-looking documents. Compact, networkable and
	cost-efficient, it also lets you scan and share information in color from
	your touch-and-swipe control panel – even add optional high-speed fax
	for all-in-one productivity

System Specifications	
System memory	2 GB (standard)
System hard disk	320 GB (standard)
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4 / IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Reversing automatic document feeder	Up to 50 originals / 5.5" x 8.5" to 8.5" x 14" / 52-120 gsm
Printable paper size	4" x 6" to 8.5" x 14" / custom paper sizes
Printable paper weight	60-163 gsm
Paper input capacity	Standard: 650 sheets / Max.: 2,300 sheets
Tray 1	550 sheets / 4" x 6" to 8.5" x 14" / 60-120 gsm
Tray 2-4 (optional)	250 or 550 sheets / 8.5" x 11 to 8.5 x 14" / 60-120 gsm
Manual bypass	100 sheets / 4" x 6" to 8.5" x 14" / custom paper sizes / 60-163 gsm
Automatic duplexing	Letter, legal / 60-90 gsm
Finishing modes	Group/sort, staple (optional)
Output capacity	Max.: 250 sheets
Stapling (optional)	Max.: 20 sheets
Copy/print volume	Max.: 100,000 pages / month <sup>1</sup>
Toner lifetime	20,000 pages
Imaging unit lifetime	60,000 pages
Power consumption	120 V / 60 Hz, less than 985 W (system)

### **Copier Specifications**

System dimensions

System weight

oopioi opooinioutiono	
Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD Polymerized Toner
Print speed	Up to 42 ppm (Letter)
Autoduplex speed	Up to 20 ppm (Letter)
1st copy out time	8.5 sec.
Warm-up time	Approx. 77 sec. <sup>2</sup>
Copy resolution	600 x 600 dpi
Multi-copy	1-999
Original format	Max: up to 8.5" x 14"
Magnification	25-400% in .1% steps, auto zooming
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness,
	image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1

19.3" x 19" x 22.1" (W x D x H)

Approx. 52 lb

### Drintor Cassifications

Printer Specifications	
Print resolution	600 x 600 dpi, 1,200 x 1,200 dpi (reduced speed)
PDL	PCL5e/c emulation, PCL XL ver. 3.0, PostScript 3 emulation (3016), XPS ver. 1.0, OpenXPS, PDF 1.7
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2003 R2 / 2008 / 2008 R2 <sup>s</sup> / 2012 <sup>s</sup> Macintosh OS X 10.2.8 or later Linux Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3 Latin
Print functions	Direct Print of TIFF, XPS, PDF and OOXML (DOCX, XLSX, PPTX), secure print, combination, n-up, poster, booklet page order, watermark

### **Scanner Specifications**

Scan speed	Up to 48 opm
Scan resolution	600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-USB, Scan-to-HDD, Scan-to-DPWS, Network TWAIN
File formats	JPEG, TIFF, XPS, PDF, PDF/A(1b), Compact PDF
Scan Destinations	2,100 (shared with fax), LDAP support
Scan functions	Up to 400 job programs

### **Fax Specifications (optional)**

Fax	Super G3 (optional)
Transmission	Analog, PC-fax
Resolution	Max: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Time shift, PC-fax, fax forwarding, up to 400 program dials

Uptions	
PF-P11 Paper tray	8.5" x 11" to 8.5" x 14" / 250 sheets / up to 120 gsm
PF-P12 Paper tray	8.5" x 11" to 8.5" x 14" / 550 sheets / up to 120 gsm
DK-P02 Copier desk	Provides storage space for print media, etc.
FS-P02 Inner finisher	20-sheet corner stapling
KP-P01 10-Key pad	For use instead of touchscreen
FK-512 Fax board	Supports G3 fax communication, digital fax functionality
MK-P03 Fax mount kit	Installation kit for fax board
ID Card Reader	Various ID card technologies
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR fonts	Supports native OCR A and B font printing
LK-111	Print data compression for reduced network impact
ThinPrint® Client	
SX-4600WAN	Wireless LAN to network connector
Wireless LAN	

System Features	
Security	ISO 15408 EAL3 (in evaluation), IP filtering and port blocking, SSL2, SSL3 and TSL1.0 network communication, IPsec support, IEEE 802.1x support, user authentication, secure print, HDD overwrite (8 standard types), HDD data encryption, copy protection (print only)
Software	PageScope Net Care Device Manager, PageScope Data Administrator, PageScope Direct Print, PageScope Mobile, Print Status Notifier, Driver Packaging Utility
Software	PageScope Net Care Device Manager, PageScope Data Administrator, PageScope Direct Print, PageScope Mobile, Print Status Notifier, Driver Packaging Utility

<sup>&</sup>lt;sup>1</sup> Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guidline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs



 $<sup>^{\</sup>rm 2}\,\mbox{Warm-up}$  time may vary depending on the operating environment and usage

<sup>&</sup>lt;sup>3</sup> Supports x64 only



# MFP

## bizhub C3851series

COLOUR MID-VOLUME MULTIFUNCTION PRINTER

A4 multifunctional with 38/33 ppm b/w and colour. Standard Emperon  $^{\!\top\!\!}$  print controller with PCL 5e/c, PostScript 3, PDF 1.7, XPS, OpenXPS and OOXML support. Paper capacity of 550 + 2 x 500 sheets and 100-sheet bypass tray. Media from A6 to A4 and 60 – 210 gsm. 2 GB memory, 250 GB hard disk and Ethernet standard.

System Overview	
System memory	2,048 MB (standard), 4,096 MB (optional)
System hard disk	250 GB (standard)
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 1.1, USB 2.0, Wi-Fi 802.11b/g/n/ac (optional)
Network protocols	TCP/IP (IPv4/IPv6), FTP, SMB, SMTP, WebDAV, TCP Socket WSD
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Automatic document feeder	Up to 50 originals (80 gsm), A4, B5, Legal, Letter (short edge feed), 50-128 gsm
Printable paper size	A6-A4, B6, B5, Letter, Legal, customised paper sizes
Printable paper weight	60-210 gsm
Paper input capacity	Standard: 650 sheets, Max.: 1,650 sheets
Tray 1	550 sheets, A6-A4, 60-210 gsm
Tray 2 & 3 PF-P13 (optional)	2 x 500 sheets, B5, A4, Executive, Letter, Legal, 60–90 gsm
Bypass tray	100 sheets, A5-A4, custom sizes, 60-210 gsm
Automatic duplexing	A4/Letter, 60-210 gsm
Finishing modes *1	Group, sort, staple, offset-sort, offset-group
Output capacity	Max.: 250 sheets
Stapling	50 sheets (up to 297mm), 30 sheets (more than 297 mm), 60-90 gsm
Stapling output capacity	Max.: 250 sheets or 25 sets
Power consumption	C3851FS, C3351: [220-240 V, 50/60 Hz] less than 1.7 kW (system) [110-127V, 50/60 Hz] less than 1.55 kW (system) C3851: [220-240 V, 50/60 Hz] less than 1.7 kW (system) [100V, 50/60 Hz] less than 1.45 kW (system)
System dimensions *2	[W x D x H] 555 x 584 x 603 mm (21.9 x 23.0 x 23.7 inch)
System weight *3	C3851FS: Approx. 51.8 kg (114.2 lb) C3851/C3351: Approx. 47.9 kg (105.6 lb)

<sup>&</sup>lt;sup>11</sup> For C3851FS only. <sup>22</sup> Excluding ADF and lower paper feed unit.

		Developer,		

<b>Copier Specifications</b>	
Copying process	Electrostatic laser copy, tandem, intermediate transfer
Toner system	Simitri <sup>®</sup> HD Polymerized Toner
Copy/print speed A4 (mono/colour)	bizhub C3851FS/C3851: Up to 38 ppm, bizhub C3351: Up to 33 ppm
Copy/print speed Letter (mono/colour)	bizhub C3851FS/C3851: Up to 40 ppm, bizhub C3351: Up to 35 ppm
1st copy out time (mono)	bizhub C3851FS: 8.3 sec., bizhub C3851: 6.2 sec., bizhub C3351: 8.1 sec.
1st copy out time (colour)	bizhub C3851FS: 9.2 sec., bizhub C3851: 7.1 sec., bizhub C3351: 9.1 sec.
Warm-up time *4	Approx. 20 sec.
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-999
Original format	A6-A4
Magnification	25-400% in 0.1% steps, auto-zooming

<sup>&</sup>lt;sup>74</sup> Warm-up time may vary depending on the operating environment and usage

Scanner Specifications	
Scan speed (mono)	Up to 35 ipm (A4), Up to 37 ipm (Letter)
Scan speed (colour)	Up to 35 ipm (A4), Up to 37 ipm (Letter)
Resolution	Max.: 600 x 600 dpi
Scan modes	Scan to Email, Scan to PC (SMB), Scan to FTP, Scan to WebDAV, Scan to BOX (HDD), Scan to USB memory, Scan to DPWS (Device Profile for Web Service), Network TWAIN scan
File formats	JPEG, TIFF, PDF, XPS, , PDF/A-1a (optional), PDF/A 1-b (optional) compact PDF

Scanner Specifications (optional)		
Super G3		
Analog fax, Internet fax, Colour Internet fax, IP address fax		
Max.: 600 x 600 dpi (ultra-fine)		
MH, MR, MMR, JBIG		
Up to 33.6 Kbps		

<b>Components and Options</b>	
DK-P03 Copier desk	Provides storage space for print media and other materials
FS-P03 Off-line stapler	20-sheet stapling
SK-602 Staple kit	1 cartrige, 5,000 needles (for C3851FS only)
SK-501 Staple kit (off-line)	1 cartrige, 1,000 needles (FS-P03 is required)
EK-P05 Local interface kit	Local interface kit for USB hub
EK-P06 Local interface kit	Local interface kit for USB hub with Bluetooth LE
UK-216 Wireless LAN kit	Wireless LAN and wireless LAN Access Point Mode
AU-102 Biometric authentication	Finger vein scanner
AU-201S IC card authentication	IC card authentication unit
MK-P02 Mount kit	Installation kit for IC card authentication
WT-P02 Working table	Authentication device placement
FK-517 Fax kit	Super G3 fax, fax functionality, single line
KP-101 10-Key pad	For use instead of touchscreen
KP-H01 Keyboard holder	Keyboard holder
UK-211 Upgrade kit	2 GB memory extension for upgrades
LK-102 v3 PDF enhancements	PDF/A, PDF encryption, digital signature
LK-104 v3 Voice guidance	Provides voice guidance functions
LK-105 v4 OCR text recognition	Searchable PDF and PPTX, PDF/A-1a
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110 v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A
LK-111 ThinPrint <sup>®</sup> Client	Print data compression for reduced network impact
LK-114 Server-less pull printing	Server-less pull printing system
LK-115 v2 TPM activation	Trusted Platform Module for protection of data encryption and decryption
ID card reader	Various ID card technologies
CU-202 Air cleaning unit	Improving indoor air quality by reduced emissions

<b>Printer Specifications</b>	
Print resolution	1,200 x 1,200 dpi, 600 x 600 dpi
Page Description Language	PCL 5e/c Emulation, PCL XL (Version 3.0) Emulation, PostScript 3 (3016) Emulation, XPS Ver.1.0, PPML/GA2.2, PPML VDX, Open XPS, PDF 1.7, OOXML (docx, xlsx, pptx)
Operating systems	Windows Vista (32/64), Windows 7 (32/64), Windows 8.1 (32/64), Windows 10 (32/64), Windows Server 2008 (32/64), Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Macintosh OS X 10.6 or later, Red Hat Enterprise Linux 5 or later
Printer fonts	80 PCL, 137 PostScript 3 Emulation
Mobile printing	AirPrint (iOS), Mopria (Android), Google Cloud Print (optional), Wi-Fi Direct (optional), Konica Minolta Print Service (Android), PageScope Mobile (iOS, Android, Windows 10 Mobile)

<sup>-</sup> All specifications refer to A4-size paper of 80 gsm quality.

The support and availability of the listed specifications and functionalities vary depending on operating systems, applications and network protocols as well as network and system configurations.

Some of the product illustrations contain optional accessories.
 Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.

Konica Minolta does not warrant that any specifications mentioned will be error-free.

All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



# **Single Function Printers**





35 ppm B&W output speed to keep pace with growing document demands 1200 x 1200 dpi resolution for sharp, clear images

Instant-on fuser for fast warm-up and first-copy output times

Accepts 8.5" x 11" or 8.5" x 14" paper in weights from 16 lb bond to 43 lb cover stock

Outstanding envelope printing quality

Standard auto duplexing and auto blank page removal to save paper

Mobile printing support (AirPrint, NFC)

# zhub 3301P

MONOCHROME SINGLE FUNCTION PRINTER

printer





### Overview

Overview	
bizhub 3301P	For small businesses with large workloads, the bizhub 3301P
	outperforms ordinary desktop printers. You'll have 35 ppm B&W output,
	1200 x 1200 dpi resolution, standard auto duplexing and built-in
	connectivity for network integration with office MFPs - a cost-effective
	solution for higher productivity.

	On a street of the second	
svstem	Specifications	

System memory	Standard/Max.: 128 MB
Interface	10-BASE-T/100-BASE-TX ETHERNET, USB 2.0,
	IEEE 1284 Bidiectional Parallel
Network protocols	IPv4, IPv6, IPP, SNMP, HTTP, HTTPS
Printable paper size	4" x 6" to 8.5" x 14" / custom paper sizes
Printable paper weight	60-163 gsm
Paper input capacity	Standard: 300 sheets / Max.: 850 sheets
Tray 1	250 sheets / 4" x 6" to 8.5" x 14" / 60-120 gsm
Tray 2 (optional)	250 or 550 sheets / 5.5" x 8.5" to 8.5" x 14" / 60-120 gsm
Manual bypass	50 sheets / 4" x 6" to 8.5" x 14' / custom paper sizes / 60-163 gsm
Automatic duplexing	8.5" x 11" to 8.5" x 14" / 60-90 gsm
Output capacity	Max.: 150 sheets
Print volume	Max.: 50,000 pages / month <sup>1</sup>
Toner lifetime	Up to 10,000 pages
Imaging unit lifetime	Up to 60,000 pages
Power consumption	100-127 V / 47-63 Hz, less than 900 W (system)
System dimensions	15.7" x 10.3" x 12.1" (W x D x H)
System weight	Approx. 30.9 lb

### **Printer Specifications**

rilliter Specifications	
Printing process	Electrostatic laser
Print speed	Up to 35 ppm (Letter)
Autoduplex speed	Up to 30 ppm (Letter)
1st print out time	6.5 sec.
Print resolution	1200 x 1200 dpi
PDL	PCL5/6 emulation, PostScript 3, XPS
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2² / 2012² Macintosh OS X 10.x or later Linux AS/400 SAP
Printer fonts	89 PCL, 91 PostScript 3 Emulation Latin
Print functions	Duplex, n-up, watermark, electronic sorting

### **Options**

1050 1 1 100 100
s / 250 sheets / 60-120 gsm
s / 550 sheets / 60-120 gsm
/ Adjustable to bring configurations
and macros or to save job
et

### **System Features**

System i catales	
Security	TCP/UDP port disabling, certificate management, SNMPv3, HTTPS
	server, SSL protocol, IEEE 802.1x support, SMTP authentication
Software	PageScope Net Care Device Manager

<sup>1</sup> Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guidline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs
<sup>2</sup> Supports 54-bit version only







One unified experience, thanks to Konica Minolta's Emperon® controller Simitri® HD Polymerized toner, for excellent print quality and low environmental impact PSES support and optional card readers for authentication More flexibility in fulfilling special printing demands with Konica Minolta's i-Options

# bizhub C3100P

COLOR SINGLE FUNCTION PRINTER







### Overview

0.00.000	
bizhub C3100P	For print-only applications, the bizhub® C3100P combines space-
	saving design with Emperon® controller and high-speed output of
	32 color prints per minute – an ideal productivity solution in mixed
	MFP and desktop environments, branch locations and small to
	mid-size businesses with rising document demands.

System Specification	
System memory	1 GB (standard) / 2 GB (optional)
System hard disk	320 GB (optional)
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4 / IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Printable paper size	4" x 6" to 8.5" x 14" / custom paper sizes
Printable paper weight	60-210 gsm
Paper input capacity	Standard: 350 sheets / Max.: 850 sheets
Tray 1	250 sheets / 4" x 6" to 8.5" x 11" / 60-210 gsm
Tray 2 (optional)	500 sheets / 8.5" x 11" to 8.5" / 60-90 gsm
Manual bypass	100 sheets / 4" x 6" to 8.5" x 14" / custom paper sizes / 60-210 gsm
Automatic duplexing	8.5" x 11" / 60-210 gsm
Output capacity	Max.: 200 sheets
Copy/print volume	Max.:120,000 pages / month <sup>4</sup>
Toner lifetime	CMYK: 6,000 pages
Imaging unit lifetime	Black: 30,000 pages / CMY: 30,000 pages
Power consumption	110 V / 60 Hz, less than 1.2 kW (system)
System dimensions	13.8" x 17.6" x 21.4" (H x W x D)
System weight	Approx. 62.4 lb

### Printer Specification

Printer Specification	
Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD Polymerized Toner
Print speed	Up to 32 ppm (Letter, mono/color)
Autoduplex speed	Up to 32 ppm (Letter, mono/color)
1st copy out time	12.9 sec. (mono/color)
Warm-up time	Approx. 36 sec. <sup>2</sup>
Print resolution	1,200 x 1,200 dpi, 600 x 600 dpi
PDL	PCL5e/c, PostScript 3, XPS <sup>1</sup>
Operating systems	Windows (x32/x64): Vista / 7 / 8 Windows Server (x32/x64): 2008 / 2008 R2 / 2012³ / 2012 R2 Macintosh OS X 10.x or later Linux Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3 emulation Latin
Print functions	Direct Print <sup>1</sup> of PDF, JPEG, TIFF, XPS <sup>1</sup> and OOXML (DOCX, XLSX, PPTX), overlay, watermark, n-up

### **Options**

PF-14 Paper tray	8.5" x 11" to 8.5" x 14" / 500 sheets / up to 90 gsm
SCD-25 Copier desk	Ensures ergonomic height and provides storage space for print media, etc.
HD-P06 Hard disk	320 GB HDD <sup>1</sup>
1 GB Expanded	1 GB memory extension for faster processing
memory	
ID Card reader	Various ID card technologies <sup>1</sup>
LK-106 Barcode fonts	Supports native barcode printing <sup>1</sup>
LK-107 Unicode fonts	Supports native Unicode printing <sup>1</sup>
LK-108 OCR	Supports native OCR A and B font printing <sup>1</sup>
A and B fonts	
LK-111	Print data compression for reduced network impact
ThinPrint® client	
MK-P07	Installation required for NC-P03 Wireless network interface
Wireless mount kit	
NC-P03 Wireless	Provides Wireless network connectivity <sup>5</sup>
network interface	
CS-1	Convenient stapling of up to 50 prints per set
Convenience stapler	

System Features	
Security	IP filtering and port blocking SSL21, SSL31 and
-	TSL1.0 network communication <sup>1</sup> , IPsec support <sup>1</sup> ,
	IEEE 802.1x support <sup>1</sup> , user authentication <sup>1</sup> , secure print <sup>1</sup> ,
	HDD overwrite (8 standard types)1, HDD data encryption1
Software	PageScope Net Care Device Manager <sup>1</sup> , PageScope WebConnection <sup>1</sup> ,
	PageScope Data Administrator <sup>1</sup> , PageScope Direct Print <sup>1</sup> ,
	PageScope Mobile

- <sup>1</sup> HD-P06 optional hard disk enables secure printing, proof-then-print, print & hold, job storing, XPS emulation, i-Option support and ID card reader support
- $^{\rm 2}\,\mbox{Warm-up}$  time may vary depending on the operating environment and usage
- 3 Supports x64 only
- <sup>4</sup> Maximum monthly copy/print volume supported under vendor supplied service. Defines the upper end of th expected customer volume for the device. Customers should consider multiple machines if average approaches duty cycle on a continual basis.
- <sup>5</sup> Requires the MK-P07. Compatible with the C3100P item# A6DR012.







50 ppm B&W output speed to keep pace with growing document demands 1200 x 1200 dpi resolution for sharp, clear images

Instant-on fuser for fast warm-up and first-copy output times

Accepts 8.5" x 11" or 8.5" x 14" paper in weights from 16 lb bond to 43 lb cover stock

Outstanding envelope printing quality

Simple print control with easy-to-read display and animated navigation screens

Standard auto duplexing and auto blank page removal to save paper

Direct USB printing

# zhub 4700P

MONOCHROME SINGLE FUNCTION PRINTER







OVCIVICA	
bizhub 4700P	A networkable desktop printer that packs maximum power in minimum space, the bizhub 4700P delivers up to 50 ppm B&W output at
	1200 x 1200 dpi resolution to make documents look more professional
	- with 2,300-sheet maximum paper capacity, standard duplexing and
	easy-to-read LCD display to speed operation.

System Specifications	
System memory	256 MB (standard) / 1.2 GB (maximum with options)
Interface	10-Base-T/100-Base-TX/1,000-Base-T Ethernet, USB 2.0
Network protocols	IPv4, IPv6, IPP, SNMP, HTTP, HTTPS
Printable paper size	4" x 6" to 8.5" x 14" / custom paper sizes
Printable paper weight	60-163 gsm
Paper input capacity	Standard: 650 sheets Max.: 2,300 sheets
Tray 1	550 sheets / 4" x 6" to 8.5" x 14" / 60-120 gsm
Tray 2-4 (optional)	250-550 sheets / 5.5" x 8.5" to 8.5" x 14" / 60-120 gsm
Manual bypass	100 sheets / 4" x 6" to 8.5" x 14' / custom paper sizes / 60-163 gsm
Automatic duplexing	8.5" x 11" to 8.5" x 14" / 60-90 gsm
Output capacity	Max.: 250 sheets
Print volume	Max.:100,000 pages / month <sup>1</sup>
Toner lifetime	Up to 20,000 pages
Imaging unit lifetime	Up to 60,000 pages
Power consumption	100-127 V / 47-63 Hz, Less than 900 W (system)
System dimensions	15.7" x 15" x 12.1" (W x D x H)
System weight	Approx. 34.6 lb

### **Printer Specifications**

Printing process	Electrostatic laser			
Print speed	Up to 50 ppm (Letter)			
Autoduplex speed Up to 42 ppm (Letter)				
1st print out time 6.5 sec.				
Print resolution 1200 x 1200 dpi				
PDL	PCL5/6 emulation, PostScript 3 emulation, XPS			
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2² / 2012² Macintosh OS X 10.x or later Linux AS/400 SAP			
Printer fonts	89 PCL, 91 PostScript 3			
Print functions	Duplex, n-up, watermark, electronic sorting, secure printing, USB direct print			

### **Options**

PF-P11 Paper tray	5.5" x 8.5" to 8.5" x 14" / custom paper sizes / 250 sheets / 60-120 gsm
PF-P12 Paper tray	5.5" x 8.5" to 8.5" x 14" / custom paper sizes / 550 sheets / 60-120 gsm
DK-P02 Copier desk	Provides storage space for print media, etc. / Adjustable to bring machine to working height with a variety of configurations
EM-P01 512 MB DIMM	512 MB memory extension for faster processing
EM-P02 1 GB DIMM	1 GB memory extension for faster processing
UK-P01 User flash	256 MB User flash for storing fonts, forms and macros or to save job
	account log
UK-P02 Barcode card	Barcode engine
UK-P03 IPDS card	Provides compatibility for IPDS printing
NC-P01 Wireless LAN	Provides wireless connectivity
CS-1	Convenient stapling of up to 50 prints per set
Convenience stapler	

### **System Features**

Security	TCP/UDP port disabling, certificate management, SNMPv3, HTTPS server, SSL protocol, IEEE 802.1x support, SMTP authentication, secure print, (print hold/PIN)
Software	PageScope Net Care Device Manager

<sup>1</sup> Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guidline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs <sup>2</sup> Supports 64-bit version only







## **Hard Drive Security**

Systel Business Equipment would like to assure you that we are a leader in the area of MFP security. Our MFP's can ensure documents that are copied, scanned, faxed or otherwise transmitted, do not remain stored on the hard drive or in DRAM memory as a standard feature. Additional standard security capabilities include:

- ISO 15408 EAL Level 3 Certification for the Total System Architecture
- Password Protection
- Hard Drive Encryption
- Hard Drive Reformat
- Data Auto Deletion

We not only conform to current internationally recognized data security standards, but sit on the committees that are developing future information technology security standards. We also offer a wide range of security solutions and services beyond the standard features of our products including integration into corporate IT security and authentication systems and Common Access Card support for DOD and government applications.

For more details on our range of security capabilities and offerings, go to: http://www.systeloa.com/data-security

Hard Drive Sanitation—Where available, a qualified service technician will perform a "data overwrite" of the hard drive using built-in sanitation technology. The drive will be cleared of data and re-initialized in the machine before disposal. Availability of this option depends on model and configuration. Cost - \$195.00 flat charge for labor.

Hard Drive replacement and return—at the time of disposal, the internal hard drive will be removed and sealed in a container that will be returned to the customer. A replacement hard drive will be installed and re-initialized with the generic device control programs. Availability of this opno depends on model and configuration. Cost - \$275.00 flat charge for labor and replacement cost of the hard drive.





## Systel Sales Branches / Service Locations List

Systel Branch	Street Address	City, State	Zip	Phone	Fax	Counties
Fayetteville - HQ	2604 Fort Bragg Rd	Fayeteville, NC	28303	910-321-7700	910-484-5100	N/A
Asheville  SYSTEL	1314A Park Terrace Center Patton Avenue	Asheville, NC	28806	828-254-8000	828-254-8095	Buncombe Cherokee Clay Graham Haywood Henderson Jackson Macon Madison Swain Transylvania
Atlanta	2100 Norcross Parkway, Ste 100	Norcross, GA	30071	770-246-0034	770-246-0427	Yancey Cobb Coweta Dawson Decatur Douglas Effingham Elbert Fannin Fayette Fulton Gordon Gwinnett Habersham Hall Henry
Charlotte	1201 Woodbridge Ctr. Drive, Ste. 120	Charlotte, NC	28217	704-357-3000	704-357-1440	Anson Cabarrus Cleveland Gaston Iredell Mecklenburg Rowan Stanly Union
Fayetteville	831 Tom Starling Road	Fayetteville, NC	28306	910-321-7700	910-484-5100	Bladen Cumberland Harnett Hoke Lee Montgomery Moore Richmond Robeson Sampson Scotland Wayne
Greensboro	3517 West Wendover Avenue	Greensboro, NC	27407	336-808-8000	336-808-8100	Beaufort Bertie Chowan Currituck Dare Gates Greene Halifax Hertford Hyde Jones

						Lenoir Martin Nash Northampton Pasquotank Perquimans Pitt Tyrrell Washington
Hickory	1966 Briarwood Drive	Hickory, NC	28602	828-294-2811	828-294-4081	Alexander Ashe Avery Burke Caldwell Catawba Davie Lincoln McDowell Mitchell Rutherford Watauga Wilkes
Raleigh	2725 E. Millbrook Road, Ste 103	Raleigh, NC	27604	919-876-8522	919-850-9597	Chatham Durham Edgecombe Franklin Granville Johnston Orange Person Vance Wake Warren Wilson
Wilmington	249 South Kerr Avenue	Wilmington, NC	28403	910-791-2266	910-791-8883	Brunswick Carteret Columbus Craven Duplin New Hanover Onslow Pender



## **Guaranteed Maintenance Agreement**

### **REMIT TO:**

Systel Business Equipment Co., Inc. Post Office Box 35870 Fayetteville, NC 28303

Date:
Customer #:
Program Type:
Contract Start Date:
Contract End Date:

Telephone (910) 321-7700 Fax (910) 483-2846 B/W Start Meter Make/Model Serial Number **EQUIP ID# Color Start Meter** Addendum Attached: Single Group Combined LOCATION: BILL TO Key Operator/ Meter POC: Meter Method: Technician Assigned: Fmail address: Phone #: Fax#: @Remote / RDS: Labrador: LEASE/RENTAL CUSTOMERS: If this agreement is being provided at no charge in consideration for a lease/rental agreement on equipment with SYSTEL check here INCLUDES: **COVERAGE TYPE** Appropriate categories must be initialed by Customer in the box to the left of the option (Please check one) COPIES Type S - Includes all parts and labor; Excludes drums, supplies, and networking Type B - Includes all parts, labor, and drums; Excludes supplies and networking Type F - Includes all parts, labor, and supplies; Excludes paper, staples, color toner, and networking DEVELOPMENTS Type C - Includes all parts, labor, and supplies; Excludes paper, staples, and networking **Equipment Type** Base Rate\* Base Allowance Additional Rate over Base Payment Information B/W UNIT Total Payment COLOR UNIT \$ \_ Sales Tax **B/W PRINTER** \$ \$ Payment Due -**COLOR PRINTER** \$ \$ If wide-format, billing is per Square foot / Linear Foot The base rate and allowance are payable in advance. "This transaction shall be governed in all respects by the terms and conditions of contract # NC STC 204D (ITS-400096). COMMENTS:

TERMS AND CONDITIONS				
		Check here if power equipment filter is provided. Customer acknowledges receipt herewith of power filter equipment. Serial Number		
		Any terms and conditions which conflict with, vary from or supplement the Agreement terms shall be deemed null and void".		

- 1. This Agreement is for one year beginning on effective date and will be automatically renewed and billed for one (1) year periods unless either party notifies the other in writing at least thirty (30) days before the annual expiration date of this Agreement.
- 2. This Agreement does not cover physical damage from misuse, abuse, natural disasters, fire, theft, water or spillage of any liquid or from damage of clips, staples or other foreign objects, drum scratches of any kind, malfunctions of associated peripheral equipment, transmission lines, modems, retraining of equipment operators or service calls which result from improper operation, service which should be performed by key operator, major rebuilding, overhauling or operating supplies which include toner, paper, developer, drums, filters or heat roller kits, except as noted. Freight on supplies shipped per the above coverage type is not included.
- or heat roller kits, except as noted. Freight on supplies shipped per the above coverage type is not included.

  3. This Agreement may be canceled by Systel at any time, including but not limited to nonpayment by Customer. If this Agreement is terminated for any reason, including nonpayment, customer agrees to pay regular price for any supplies indicated above as provided at no charge in this Agreement and received within ninety (90) days prior to the effective date of termination. Any change in program type or plan must be made at renewal date and customer must provide Systel with a minimum of thirty (30) days written notice before renewal of any request to change to any other type service plan.
- 4.Customer agrees to pay all invoices when due and keep any open account with Systel current at all times. Service may be suspended or this Agreement may be terminated if customer's account becomes past due.
- customer's account becomes past due.

  5. Should actual usage not be available to Systel, then usage will be estimated based upon previous usage. Further, Customer acknowledges that a certain service discount may have been provided in exchange for providing monthly meters via an @Remote or RDS device. If customer is unwilling or unable to provide monthly meters under such program, additional charges of \$25 per unit may apply under this Agreement.
- 6. The power filter equipment listed above is provided to customer at no charge as long as this agreement is in effect. At termination of this agreement for any reason whatsoever customer agrees to return to Systel, freight or postage prepaid, the power filter equipment named herein. If not received within 10 days of the effective termination date of this agreement, customer agrees to pay to Systel the replacement value of \$159.00 for this equipment and remit this amount within 10 days of receipt of invoice by Systel. Customer shall bear full responsibility for all loss or damage to the power filter equipment provided.

  7. Coverage will be void under this Agreement if equipment is serviced by anyone other than Systel personnel or supplies are used which are purchased from any company other
- 7. Coverage will be void under this Agreement if equipment is serviced by anyone other than Systel personnel or supplies are used which are purchased from any company other than Systel. All supplies must be replaced when needed to continue coverage under this Agreement. A special rate on service has been provided in consideration for supply purchases and use of supplies from any other source could result in higher service rates. Service calls resulting from the use of inferior quality supplies will not be covered under this Agreement and will be billed at standard hourly rates.
- 8. This Agreement is non-transferable and prices are subject to change annually. This Agreement is non-refundable during the contract period. Any training for operator after initial installation is not included in this Agreement and will be billed separately.
- 9. This Agreement will not be effective until approved by Systel Management and upon receipt of initial payment or approved purchase order. All service will be charged at standard hourly rates until approved contract is on file. Agreements may not be back dated to cover prior service. Units out of warranty may require inspection charge and purchase of any worn items that would be covered under any subsequent contract.
- 10. Systel normally provides service response time in four (4) hours or less from the time the call is placed with our Dispatch Department. Emergency service calls where the equipment is totally inoperable are guaranteed to our customers if they notify us at the time of placing the call that emergency service is required and the machine is totally inoperable (will not make a copy). If for any reason Systel fails to respond to emergency service calls within four (4) working hours, then the customer shall be entitled to a twenty-five dollar (\$25.00) credit to their account to be used for the purchase of supplies or other services. The customer must notify the technician upon their arrival to receive credit under this program. No credits will be issued after the date of any call for which credit is claimed.
- 11. Systel provides to its customers a total satisfaction guarantee as long as your machine is continuously under a Systel Guaranteed Maintenance Agreement. At any time the customer is not totally satisfied with their equipment purchased, leased, or rented through Systel, it may be exchanged for similar equipment of equivalent age, condition, and volume. Type of equipment substituted will be at the sole discretion of Systel. The company's normal installation and removal charges shall apply to any substitutions or equipment requested by customer.
- 12. There are no warranties, agreements or representations of any kind, directly or indirectly, expressed or implied, except those specifically stated herein. The warranties provided herein for the equipment shall only be for the use of the equipment in the manner for which it was designed in accordance with all applicable manufacturer and vendor manuals.

By executing this agreement, I acknowledge that I have read and understand this agreement and I certify that I am authorized to execute this agreement on behalf of customer. Authorized signature acknowledges terms / conditions and expiration dates or meter.

CUSTOMER ACCEPTANCE			SYSTEL SALES REPRESENTATIV	SYSTEL SALES REPRESENTATIVE		
Authorized Signature/Date	Print Name	Title	Signature Rep #	Date		
			Manager Approval:			